



# TEST REPORT

**No. I16D00097-EMC**

*For*

**Client : Haier Telecom (Qingdao)Co.,Ltd**

**Production: GSM/WCDMA/LTE handset**

**Model Name : L30**

**Hardware Version: V1.01**

**Software Version: L30-H02-S021-Tigo**

**FCC ID: SG7201605L30**

**Issued date: 2016-06-28**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

**Test Laboratory:**

ECIT Shanghai, East China Institute of Telecommunications

Add: 7F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: [welcme@ecit.org.cn](mailto:welcme@ecit.org.cn)

## Revision Version

Report Number	Revision	Date	Memo
I16D00097-EMC	00	2016-06-28	Initial creation of test report

## CONTENTS

1. TEST LABORATORY .....	4
1.1. TESTING LOCATION .....	4
1.2. TESTING ENVIRONMENT .....	4
1.3. PROJECT DATA .....	4
1.4. SIGNATURE .....	4
2. CLIENT INFORMATION .....	5
2.1. APPLICANT INFORMATION .....	5
2.2. MANUFACTURER INFORMATION .....	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....	6
3.1. ABOUT EUT .....	6
3.2. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	6
4. REFERENCE DOCUMENTS.....	7
4.1. REFERENCE DOCUMENTS FOR TESTING .....	7
5. TEST RESULTS.....	8
5.1. SUMMARY OF TEST RESULTS.....	8
5.2. STATEMENTS.....	8
6. TEST EQUIPMENTS UTILIZED.....	9
6.1 RADIATED EMISSION EQUIPMENTS LIST .....	9
6.1 CE EQUIPMENTS LIST.....	9
7. SYSTEM CONFIGURATION DURING TEST .....	10
7.1 TEST MODE.....	10
7.2 CONNECTION DIAGRAM OF TEST SYSTEM.....	10
8. MEASUREMENT RESULTS .....	11
8.1 RADIATED EMISSION 30MHZ-12.75GHZ .....	11
8.2 CONDUCTED EMISSION.....	15

## 1. Test Laboratory

### 1.1. Testing Location

Company Name: ECIT Shanghai, East China Institute of Telecommunications  
Address: 7F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai,  
P. R. China  
Postal Code: 200001  
Telephone: 86-21-63843300  
Fax: 86-21-63843301  
FCC registration No: 489729


### 1.2. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 30-60%

### 1.3. Project data

Project Leader: Xu Yuting  
Testing Start Date: 27-05, 2016  
Testing End Date: 03-06, 2016

### 1.4. Signature




Wu Jiashen

(Prepared this test report)



You Jinjun

(Reviewed this test report)



Zheng Zhongbin

Director of the laboratory

(Approved this test report)

## 2. Client Information

### 2.1. Applicant Information

Company Name: Haier Telecom (Qingdao)Co.,Ltd  
Address /Post: No1,Haier Road,Hi-tech Zone,Qingdao, China  
Tel: 0532-88937273  
City: Qingdao  
Country: China

### 2.2. Manufacturer Information

Company Name: Haier Telecom (Qingdao)Co.,Ltd  
Address /Post: No1,Haier Road,Hi-tech Zone,Qingdao, China  
Tel: 0532-88937273  
City: Qingdao  
Country: China

### 3. Equipment under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

EUT Description	GSM/WCDMA/LTE handset
Model name	L30
Serial Number or IMEI	861864030000225
GSM Frequency Band	GSM900/GSM1800/GSM850/GSM1900
UMTS Frequency Band	WCDMA Band II/Band V
LTE Frequency Band	FDD 4/5/7,
HW Version	V1.01
SW Version	L30-H02-S021-Tigo

#### 3.2. Internal Identification of AE used during the test

AE ID*	Description	Model	SN
AE1	Adapter	TPA-59A5065UU	NA
AE2	Battery	H15408	EB0D1100000EG610157F
AE3	Earphone	NA	NA
AE4	Data Cable	NA	NA
AE5	Desktop PC	OptiPlex 790 DT	X8RP1 A01 APCC
AE6	Notebook PC	ThinkPad Edge T430I	PBB32WP
AE7	LAN Cable	NA	NA
AE8	VGA Cable	NA	NA
AE9	RS232 Cable	NA	NA
AE10	Keyboard	SK-8120	NA
AE11	Mouse	M032B0B	NA

\*AE ID: is used to identify the test sample in the lab internally.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	10-1-10 Edition
ANSI C63.4	Method of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

## 5. Test Results

### 5.1. Summary of Test Results

Items	Test List	Clause in FCC rules	Verdict
1	Radiated Emission	15.109(a)	Pass
2	Conducted Emission	15.107(a)	Pass

### 5.2. Statements

The L30 supporting GSM/WCDMA/LTE, manufactured by Haier Telecom (Qingdao)Co.,Ltd is a new product for testing. ECIT only performed test cases which identified with Pass/Fail/Inc result in section 5.1.

ECIT has verified that the compliance of the tested device specified in section 3 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 4 of this test report.



## 6. Test Equipments Utilized

### 6.1 Radiated Emission Equipments list

No.	Name	Type	Series Number	Producer	Cal. Date	Cal. interval
1	Universal Radio Communication	CMU200	123126	R&S	2016-05-12	1
2	Test Receiver	ESU40	100307	R&S	2016-05-12	1
3	Trilog Antenna	VULB9163	VULB9163-515	Schwarzbeck	2014-11-05	3
4	Double Ridged Guide	ETS-3117	00135885	ETS	2014-05-06	3
5	EMI Test Software	EMC32 V9.15	NA	R&S	NA	NA

### 6.1 CE Equipments list


No.	Name	Type	Series Number	Producer	Cal. Date	Cal. interval
1	Universal Radio	CMU200	123123	R&S	2016-05-12	1
2	Test Receiver	ESCI	101235	R&S	2016-05-12	1
3	2-Line V-Network	ENV216	101380	R&S	2016-05-12	1
4	EMI Test Software	EMC32 V9.15	NA	R&S	NA	NA

## 7. System Configuration during Test

### 7.1 Test Mode

Test Item	Function Type
AC Conducted Emission	Mode 1: Idle + Camera on + USB cable (Data Link with PC) <Figure 1> Mode 2: Idle + Earphone + MP4 + Adapter charging <Figure 2>
Radiated Emission	Mode 1: Idle + Camera on + USB cable (Data Link with PC) <Figure 1> Mode 2: Idle + Earphone + MP4 + Adapter charging <Figure 2>
Remark: 1. All test modes are performed, only the worst cases test data are recorded in this report. 2. Data Link with PC means data application transferred mode between EUT and PC.	

### 7.2 Connection Diagram of Test System



<Figure 1>



<Figure 2>

## 8. Measurement Results

Only the worst test result was shown in this report.

### 8.1 Radiated Emission 30MHz-12.75GHz

#### Method of Measurement

For 30-1000MHz, the EUT was placed on the top of a rotating 0.8-m table above the ground at a semi-anechoic chamber. The distance between the EUT and the received antenna was 3 meters. The table was rotated 360 degree and the received antenna mounted on a variable-height antenna tower was varied from 1m to 4m to find the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna were set during the measurement. Tested in accordance with the procedures of ANSI C63.4-2014, section 8.3.

For 1000-12750MHz, The maximal emission value was acquired by adjusting the antenna height, The table was rotated 360 degree to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna were set during the measurement.

#### Limits for Radiated Emission at a measuring distance of 3m

Frequency Range (MHz)	Quasi-Peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54

Frequency Range (MHz)	Peak (dBuV/m)	Average (dBuV/m)
Above 1000	74	54

#### Test conditions

Frequency Range (MHz)	RBW/VBW	Sweep Time (s)
30-1000	120KHz/300KHz	Auto
1000-12750	1MHz/1MHz	Auto


#### Uncertainty Measurement

The measurement uncertainty is 5.71dB (k=2).

## Test Results

Mode 1: Idle + Camera on + USB cable (Data Link with PC)

Frequency Range: 30MHz – 1GHz





Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)
33.968280	10.50	40.00	29.50	1000.0	120.000	100.0	V	356.0	-26.1
236.313900	26.96	46.00	19.04	1000.0	120.000	175.0	H	252.0	-23.1
240.008560	37.50	46.00	8.50	1000.0	120.000	100.0	H	246.0	-22.9
314.321792	38.54	46.00	7.46	1000.0	120.000	100.0	V	354.0	-19.9
478.527404	30.84	46.00	15.16	1000.0	120.000	106.0	H	145.0	-15.5
949.988216	35.30	46.00	10.70	1000.0	120.000	106.0	H	319.0	-7.6

Note:

1. Emission level(QP)=Raw value by receiver + Corr(Antenna factor + cable loss - preamplifier gain)
2. The raw value is used to calculate by software which is not shown in the sheet.
3. Margin=limit value – emission level.

Mode 1: Idle + Camera on + USB cable (Data Link with PC)





## Horizontal

### Final Result

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
1329.407133	47.97	---	74.00	26.03	50.0	1000.000	100.0	V	57.0
1329.407133	---	24.45	54.00	29.55	50.0	1000.000	100.0	V	57.0
1495.756600	---	32.24	54.00	21.76	50.0	1000.000	100.0	V	2.0
1495.756600	47.97	---	74.00	26.03	50.0	1000.000	100.0	V	2.0
1911.163466	---	26.16	54.00	27.84	50.0	1000.000	100.0	V	38.0
1911.163466	50.06	---	74.00	23.94	50.0	1000.000	100.0	V	38.0
3319.021533	48.39	---	74.00	25.61	50.0	1000.000	100.0	V	202.0
3319.021533	---	28.09	54.00	25.91	50.0	1000.000	100.0	V	202.0
5985.451800	---	33.77	54.00	20.23	50.0	1000.000	200.0	V	6.0
5985.451800	48.91	---	74.00	25.09	50.0	1000.000	200.0	V	6.0
11623.316200	---	40.95	54.00	13.05	50.0	1000.000	200.0	V	214.0
11623.316200	53.58	---	74.00	20.42	50.0	1000.000	200.0	V	214.0

Note:

1. Emission level(peak or average)=Raw value by receiver + Corr(Antenna factor+ cable loss - preamplifier gain)
  2. The raw value is used to calculate by software which is not shown in the sheet.
- Margin=limit value – emission level.

## 8.2 Conducted Emission

### Method of Measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies with the band 150 kHz to 30MHz shall not exceed the limits. Both lines of the power mains connected to the EUT were checked for maximum conducted interference. Tested in accordance with the procedures of ANSI C63.4-2014, section 7.3

### Limit of Conducted Emission

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency

### Test Condition in Charging Mode

Voltage (V)	Frequency (Hz)	RBW	Sweep Time (s)
120	60	9 KHz	Auto

### Uncertainty Measurement


The measurement uncertainty is 3.55dB (k=2).

### Test Results

Mode 1: Idle + Camera on + USB cable (Data Link with PC)

Frequency Range:

150kHz – 30MHz



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.485812	---	20.73	46.24	25.51	1000.0	9.000	L1	ON	9.6
0.485812	28.41	---	56.24	27.83	1000.0	9.000	L1	ON	9.6
5.739412	---	30.43	50.00	19.57	1000.0	9.000	L1	ON	9.8
5.739412	40.64	---	60.00	19.36	1000.0	9.000	L1	ON	9.8
12.810131	---	42.95	50.00	7.05	1000.0	9.000	L1	ON	9.8
12.810131	44.51	---	60.00	15.49	1000.0	9.000	L1	ON	9.8
13.358625	---	45.30	50.00	4.70	1000.0	9.000	L1	ON	9.8
13.358625	47.01	---	60.00	12.99	1000.0	9.000	L1	ON	9.8
16.063781	---	28.46	50.00	21.54	1000.0	9.000	N	ON	9.9
16.063781	40.67	---	60.00	19.33	1000.0	9.000	N	ON	9.9
17.571206	---	40.11	50.00	9.89	1000.0	9.000	N	ON	9.9
17.571206	43.85	---	60.00	16.15	1000.0	9.000	N	ON	9.9

Note:

1. Emission level(quasi-peak or Average peak)=Raw value by receiver + Corr(Insertion loss+cable loss)
2. The raw value is used to calculate by software which is not shown in the sheet.
3. Margin=limit value – emission level.

\*\*\*\*\*End the Report\*\*\*\*\*