



**SGS-CSTC Standards
Technical Services Ltd.**

1/F., Building No. 1 Building, Agriculture Machinery Materials Co. Wushan
Road, Shipai, Tianhe District, Guangzhou, China
Telephone: +86 (0) 20 3848 1001 Fax: +86 (0) 20 3848 1006
E-Mail: kent.hsu@sgs.com
FEDERAL COMMUNICATIONS COMMISSION
Registration number: 282399

Report No.: GLEMO040801088RFI
Page: 1 of 19
FCC ID: SH7GX300R

FCC TEST REPORT

Application No. : GLEMO040801088RF (SGS SZ NO.:SZTYR040804549/TS)

Applicant: Prism Technology Limited

FCC ID: SH7GX300R

Fundamental Carrier Frequency : 2.441 GHz

Equipment Under Test (EUT):

Name: XBox 2.4G Wireless Gamepad

Model: GX300R

Standards: FCC PART 15, SUBPART C : 2002

Date of Receipt: 06 August 2004

Date of Test: 10 to 20 August 2004

Date of Issue: 12 September 2004

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Kent Hsu
Laboratory Manager
SGS-CSTC Co.,Ltd.

This report refers to the General Conditions for Inspection and Testing Services, printed overleaf

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the SGS PRODUCT CERTIFICATION MARK.. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS.....	2
3 GENERAL INFORMATION.....	3
3.1 CLIENT INFORMATION	3
3.2 GENERAL DESCRIPTION OF E.U.T.....	3
3.3 DESCRIPTION OF SUPPORT UNITS	3
3.4 STANDARDS APPLICABLE FOR TESTING.....	3
3.5 TEST LOCATION.....	3
3.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	3
3.7 TEST FACILITY.....	4
4 TEST RESULTS.....	5
4.1 TEST INSTRUMENTS	5
4.2 E.U.T. OPERATION	5
4.3 TEST PROCEDURE & MEASUREMENT DATA	6
4.3.1 Radiated Emissions	6
4.3.2 Conducted Emissions, 150KHz to 30MHz	11
4.3.3 Occupied Bandwidth	12
5 PHOTOGRAPHS - TEST SETUP.....	13
6 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	15-19

3 General Information

3.1 Client Information

Applicant Name: Prism Technology Limited
Applicant Address: Room 713, 7 Floor, Block A, Hoplite Industrial Centre, 3-5 Wang Tai Road, Kowloon Bay, Hong Kong

3.2 General Description of E.U.T.

Product Name: XBox 2.4G Wireless Gamepad
Model: GX300R
Power Supply: 4.8V DC (4 x 'AAA' Size Rechargeable Batteries) for Transmitter, Receiver powered by host PS2.
Power Cord: N/A-

3.3 Description of Support Units

The EUT was tested as a Microsoft X-Box & TCL 14" TV monitor.

3.4 Standards Applicable for Testing

The customer requested FCC tests for a XBox 2.4G Wireless Gamepad
The standard used was FCC PART 15, SUBPART C (2003) section 15.249.

3.5 Test Location

All tests were performed at:-
SGS-CSTC Standards Technical Services Ltd., Guangzhou Safety & EMC Laboratory, 1/F, Building No. 1, Agriculture Machinery Materials Company Warehouse Ltd., Wushan Road Shipai, Tianhe District, Guangzhou, China. P.C. 510630.
Tel: +86 20 3848 1001
Fax: +86 20 3848 1006

3.6 Other Information Requested by the Customer

None.

3.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP – Lab Code: 200611-0**
SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0. Effective through December 31, 2004.
- **ACA**
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.
- **VCCI**
The 3m Semi-anechoic chamber and Shielded Room (11.5m x 4m x 4m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1599 and C-1706 respectively.
Date of Registration: February 28, 2003. Valid until May 30, 2005
- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**
Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.
- **CNAL – LAB Code: L0141**
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAL/AC01: 2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of Testing Laboratories.
- **FCC – Registration No.: 282399**
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002. With the above and NVLAP's accreditation, SGS-CSTC is an authorised test laboratory for the DoC process.
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAL/AC01: 2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of Testing Laboratories.
- **Industry Canada (IC)**
The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5169.

4 Test Results

4.1 Test Instruments

Test Equipment	Manufacturer	Model	Asset No.	Cal. Due Date
3m Semi- Anechoic Chamber	Frankonia	3m method	EMC0501	15-02-2005
EMI Test Receiver	Rohde & Schwarz	ESCS30	EMC0506	15-02-2005
Bilog Type Antenna	Schaffner Chase	CBL6143	EMC0519	17-01-2005
Coaxial cable	SGS-CSTC	10m	EMC0514	04-11-2004
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 30	EMC0521	01-04-2005
Horn Antenna	ROHDE & SCHWARZ	HF906	EMC0517	01-04-2005
Temperature, Humidity & Barometer	Oregon Scientific	BA-888	EMC0003	24-07-2004
Peramplifier	Agilent	8449B	EMC0520	30-06-2005
Coaxial cable	SGS	N/A	EMC0514	01-06-2005
Shielding Room	Frankonia	12 x 4 x 4 m ³	EMC0103	N/A
LISN	Schaffner Chase	MNZ050D11	1421	04-11-2004
EMI Test Receiver	Rohde& Schwarz	ESCS30	100086	09-12-2004
Coaxial Cable	SGS	2m	EMC0107	01-06-2005

4.2 E.U.T. Operation

Input voltage: 4.8V DC (4 x 'AAA' Size Rechargeable Batteries) for Transmitter.

Operating Environment:

Temperature: 24.0 °C

Humidity: 52 % RH

Atmospheric Pressure: 1012 mbar

EUT Operation: Pre-test in transmitting mode with different channels.
The channels just only a coding changes, not frequency changes.

Compliance test in transmitting mode (the switch at 7 player mode (1,3 on) as the user manual shown) since no worse case be found.

4.3 Test Procedure & Measurement Data

4.3.1 Radiated Emissions

4.3.1.1 Test in transmitting mode

Test Requirement: FCC Part15 C
 Test Method: Based on FCC Part15 C Section 15.249
 Test Date: 18 August 2004
 Measurement Distance: 3m (Semi-Anechoic Chamber)
 Frequency range: 30 MHz – 25GHz for transmitting mode.
 Test instrumentation resolution bandwidth
 120 kHz (30 MHz - 1000 MHz), 1 MHz (1000 M – 25GHz)
 Operation: Receive antenna scan height 1 - 4 m, polarization Vertical/
 Horizontal

Requirements:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dBuV/m @ 3m)	Field Strength of Harmonics and Spurious Emissions (dBuV/m @ 3m)
902 to 928	94.0	54.0
2400 to 2483.5	94.0	54.0
5725 to 5875	94.0	54.0
24000 to 24250	108.0	68.0

The fundamental frequency of the EUT is 2441MHz

The limit for average field strength dBuV/m for the fundamental frequency= 94.0 dBuV/m.

No fundamental is allowed in the restricted bands.

The limit for average field strength dBuV/m for the harmonics and spurious frequencies = 54.0 dBuV/m. Spurious in the restricted bands must be less than 54.0 dBuV/m or 15.209.

Test Procedure: The procedure used was ANSI Standard C63.4-2000. The receiver was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

The field strength is calculated by adding the Antenna Factor, Cable Factor & Peramplifier .
The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Peramlifer Factor

The following test results were performed on the EUT:

1. Fundamental emission

Peak Measurement

Test Frequency (GHz)	Measuring Level (dBuV/m)		Limits (dBuV/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
2.441	89.2	85.4	114.0	24.8	28.6
Average Measurement					
2.441	78.8	76.5	94.0	15.2	17.5

2. Harmonics & Spurious Emissions

Peak Measurement

Test Frequency (GHz)	Measuring Level (dBuV/m)		Limits (dBuV/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
2) 4.882	52.5	54.6	74.0	21.5	19.4
3) 7.323	50.9	53.9	74.0	23.1	20.1
4) 9.764	49.8	52.5	74.0	24.2	21.5
5) 12.205	48.6	50.2	74.0	25.4	23.8
6) 14.646	N/A	N/A	74.0	N/A	N/A
7) 17.087	N/A	N/A	74.0	N/A	N/A
8) 19.528	N/A	N/A	74.0	N/A	N/A
9) 21.969	N/A	N/A	74.0	N/A	N/A
10) 24.410	N/A	N/A	74.0	N/A	N/A
Average Measurement					
2) 4.882	46.0	47.8	54.0	8.0	6.2
3) 7.323	42.3	42.0	54.0	11.7	12.0
4) 9.764	46.2	43.5	54.0	7.8	10.5
5) 12.205	45.1	42.8	54.0	8.9	11.2
6) 14.646	N/A	N/A	54.0	N/A	N/A
7) 17.087	N/A	N/A	54.0	N/A	N/A
8) 19.528	N/A	N/A	54.0	N/A	N/A
9) 21.969	N/A	N/A	54.0	N/A	N/A
10) 24.410	N/A	N/A	54.0	N/A	N/A

N/A: refer to remark 1).



Remark:

- 1). For this intentional radiator operates below 10 GHz, the spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the fifth harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 7th harmonic.
- 2). According to 15.249 (e) As shown in Section 15.35(b), for frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

TEST RESULTS: The unit does meet the FCC requirements.

3. Other Spurious Emissions. (30MHz-1000MHz)

Test Requirement: FCC Part15 Section 15.209
 Test Method: Based on FCC Part15 B
 Measurement Distance: 3m
 Limit:
 40.0 dB μ V/m between 30MHz & 88MHz
 43.5 dB μ V/m between 88MHz & 216MHz
 46.0 dB μ V/m between 216MHz & 960MHz
 54.0 dB μ V/m above 960MHz
 Detector: Peak for pre-scan , 120kHz resolution bandwidth within 1GHz,
 1MHz resolution bandwidth above 1GHz
 Quasi-Peak if maximised peak within 6dB of limit

The following quasi-peak measurements were performed on the EUT:

Frequency (Hz)	Antenna Polarization	Emission Level (dB μ V/m)	Limit dB μ V/m)	Margin (dB)
282.047M	Vertical	32.3	46.0	13.7
479.053M	Vertical	34.2	46.0	11.8
258.041M	Vertical	31.9	46.0	14.1
107.625M	Vertical	32.0	43.5	11.5
165.750M	Vertical	29.6	43.5	13.9
250.022M	Vertical	31.2	43.5	12.3
2.170G	Vertical	47.2	54.0	6.8
5.374G	Vertical	48.6	54.0	5.4
99.937M	Horizontal	31.0	43.5	12.5
62.250M	Horizontal	29.6	40.0	10.4
166.500M	Horizontal	28.9	43.5	14.6
456.750M	Horizontal	29.8	46.0	16.2
729.000M	Horizontal	31.3	46.0	14.7
500.052M	Horizontal	32.5	46.0	13.5
2.170G	Horizontal	49.1	54.0	4.9
5.374G	Horizontal	43.8	54.0	10.2

The field strength is calculated by adding the Antenna Factor, Cable Factor & Peramplifier .
 The basic equation with a sample calculation is as follows:
 Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Peramlifer Factor

TEST RESULTS: The unit does meet the FCC requirements

4.3.1.2 Test in charging mode

Test Requirement: FCC Part15 Section 15.109
 Test Method: Based on FCC Part15 B
 Measurement Distance: 3m
 Limit:
 40.0 dB μ V/m between 30MHz & 88MHz
 43.5 dB μ V/m between 88MHz & 216MHz
 46.0 dB μ V/m between 216MHz & 960MHz
 54.0 dB μ V/m above 960MHz
 Detector: Peak for pre-scan , 120kHz resolution bandwidth within 1GHz,
 1MHz resolution bandwidth above 1GHz
 Quasi-Peak if maximised peak within 6dB of limit

The following quasi-peak measurements were performed on the EUT:

Frequency (MHz)	Antenna Polarization	Emission Level (dB μ V/m)	Limit dB μ V/m)	Margin (dB)
59.145	Vertical	26.0	40.0	14.0
99.938	Vertical	23.9	43.5	19.6
139.063	Vertical	28.5	43.5	15.0
198.750	Vertical	28.2	43.5	15.3
243.000	Vertical	29.5	46.0	16.5
374.563	Vertical	30.6	46.0	15.4
138.000	Horizontal	22.9	43.5	20.6
163.250	Horizontal	20.8	43.5	22.7
182.250	Horizontal	23.0	43.5	20.5
240.048	Horizontal	27.6	46.0	18.4
250.020	Horizontal	26.7	46.0	19.3
364.000	Horizontal	25.9	46.0	20.1

The field strength is calculated by adding the Antenna Factor, Cable Factor & Peramplifier .
 The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Peramlifer Factor

TEST RESULTS: The unit does meet the FCC requirements

4.3.2 Conducted Emissions, 150KHz to 30MHz

Test Requirement: FCC Part15 Section 15.107
 Test Method: ANSI C63.4
 Test Date: 18 August 2004
 Frequency Range: 150KHz to 30MHz
 Class / Severity: Class B
 Detector: Peak for pre-scan (9kHz Resolution Bandwidth)

4.3.2.1 E.U.T. Operation

Operating Environment:
 Temperature: 24.0 °C Humidity: 52 % RH Atmospheric Pressure: 1012 mBar
 EUT Operation: Test in charging mode.
 Quasi-Peak if maximised peak within 6dB of limit

4.3.2.2 Measurement Data


An initial pre-scan was performed on the live and neutral lines with peak detector.
 Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
 The following Quasi-Peak and Average measurements were performed on the EUT.

Freq. MHz	Line	QP Level dBuV	Limit dBuV	Margin dB	AV Level dBuV	Limit dBuV	Margin dB
0.159	Live	10.6	65.5	54.9	-8.5	55.5	64.0
0.169	Live	10.4	65.0	54.6	-8.1	55.0	63.1
0.439	Live	14.6	57.1	42.5	-7.8	47.1	54.9
0.453	Live	16.9	56.8	39.9	-7.5	46.8	54.3
0.464	Live	15.4	56.6	41.2	-7.6	46.6	54.2
0.501	Live	11.5	56.0	44.5	-8.9	46.0	54.9
0.176	Neutral	10.4	64.7	54.3	-8.4	54.7	63.1
0.470	Neutral	15.5	56.5	41.0	-6.2	46.5	52.7
0.479	Neutral	13.4	56.4	43.0	-7.3	46.4	53.7
0.489	Neutral	11.2	56.2	45.0	-8.3	46.2	54.5
0.502	Neutral	8.6	56.0	47.4	-8.6	46.0	54.6
0.513	Neutral	9.6	56.0	46.4	-8.4	46.0	54.4

4.3.3 Occupied Bandwidth

Test Requirement:	FCC Part 15 C
Test Method:	Based on FCC Part15 C Section 15.249: Operation within the band 2400 – 2483.5 MHz
Test Date:	19 August 2004
Requirements:	15.249 (d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.
Method of measurement:	A small sample of the transmitter output was fed into the Spectrum Analyzer and the attached plot was taken. The vertical is set to 10dB per division. The horizontal scale is set to 100KHz per division.

The occupied bandwidth as below:



The test result for the Emissions radiated outside of the specified frequency bands , please refer the section 4.3.1 of this report.

The worst case is 49.1dBuV/m at frequency 2.170GHz, it's below the limits in Section 15.209.

For the field strength of Lower Edges:2400MHz is 32.2dBuV/m.

For the field strength of Upper Edges:2483.5MHz is 32.7dBuV/m.

The results: The unit does meet the FCC requirements.