



RF EXPOSURE REPORT

REPORT NO.: SA960620L06

MODEL NO.: WRT-390U

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: U-MEDIA Communications, Inc.

ADDRESS: 9F, No. 1, Jin-shan 7th St., Hsinchu 300, Taiwan,
R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: 47 14th Lin, Chiapau Tsun, Linko, Taipei, Taiwan,
R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Kueishan, Taoyuan,
Taiwan, R.O.C.



RF EXPOSURE MEASUREMENT (MOBILE DEVICE)

1. INTRODUCTION

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF EXPOSURE LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
(A)LIMITS FOR OCCUPATIONAL / CONTROL EXPOSURES				
300-1500	F/300	6
1500-100,000	5	6
(B)LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz



3. FRIIS FORMULA

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance r .

Ref.: David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,

Page 640, Eq. (11-133).

4. EUT OPERATING CONDITION

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. CLASSIFICATION

The antenna of the product, under normal use condition, is at least 20cm far away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**.



6. TEST RESULTS

6.1 ANTENNA GAIN

The maximum Gain measured in Fully Anechoic Chamber is 4dBi or 2.5119 (numeric).

6.2 OUTPUT POWER INTO ANTENNA & RF EXPOSURE VALUE AT DISTANCE 20cm:

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
1	2412	28.510	14.55	0.014	1.000
6	2437	63.826	18.05	0.032	1.000
11	2462	32.063	15.06	0.016	1.000

802.11g OFDM MODULATION:

CHAN.	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)		PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
1	2412	22.856	22.909	13.59	13.60	45.765	16.61	0.023	1.000
6	2437	32.659	32.734	15.14	15.15	65.393	18.16	0.033	1.000
11	2462	28.907	28.249	14.61	14.51	57.156	17.57	0.029	1.000


DRAFT 802.11n (20MHz) OFDM MODULATION:

CHAN.	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)			PEAK POWER OUTPUT (dBm)			TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN0	CHAIN1	CHAIN2	CHAIN0	CHAIN1	CHAIN2				
1	2412	18.072	17.947	18.113	12.57	12.54	12.58	54.132	17.33	0.027	1.000
6	2437	25.586	25.410	25.468	14.08	14.05	14.06	76.464	18.83	0.038	1.000
11	2462	20.324	20.370	20.324	13.08	13.09	13.08	61.018	17.85	0.030	1.000

DRAFT 802.11n (40MHz) OFDM MODULATION:

CHAN.	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)			PEAK POWER OUTPUT (dBm)			TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN0	CHAIN1	CHAIN2	CHAIN0	CHAIN1	CHAIN2				
1	2422	9.016	9.078	9.057	9.55	9.58	9.57	27.151	14.34	0.014	1.000
4	2437	14.454	14.256	14.421	11.60	11.54	11.59	43.131	16.35	0.022	1.000
7	2452	8.995	9.099	8.913	9.54	9.59	9.50	27.007	14.31	0.013	1.000