

**IEEE C95.1**

**KDB 447498 D03**

**47 C.F.R. Part 1, Subpart I, Section 1.1310**

**47 C.F.R. Part 2, Subpart J, Section 2.1091**

**RF EXPOSURE REPORT**

**For**

**ICG**

**Model: ICG-100-NA-R**

**Trade Name: Intwine connect**

**Issued for**

**Foxconn International Inc**

**NO 2 ZIYOU ST TUCHENG DISTRICT NEW TAIPEI 236**

**Issued by**

**Compliance Certification Services Inc.**

**Hsinchu Lab.**

**NO. 989-1, Wenshan Rd., Shangshan Village,  
Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)**

**<http://www.ccsrf.com>**

**[service@ccsrf.com](mailto:service@ccsrf.com)**

**Issued Date: August 27, 2015**



Testing Laboratory  
0240

## Revision History

<b>Rev.</b>	<b>Issue Date</b>	<b>Revisions</b>	<b>Effect Page</b>	<b>Revised By</b>
00	08/27/2015	Initial Issue	All Page	Vera Hsu

**TABLE OF CONTENTS**

1. **LIMIT** .....4

2. **EUT SPECIFICATION**.....4

3. **TEST RESULTS** .....5

4. **MAXIMUM PERMISSIBLE EXPOSURE**.....6

**1. Limit**

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

**2. EUT Specification**

<b>Product Name</b>	ICG
<b>Model Number</b>	ICG-100-NA-R
<b>Identify Number</b>	T150715D02
<b>Received Date</b>	July 15, 2015
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> Bluetooth 2.1 + EDR / 4.0: 2402 ~ 2480 MHz Zigbee: 2405MHz ~ 2480MHz 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz LTE Band XIII: 779.5MHz ~ 784.5MHz <input type="checkbox"/> Others
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna Specification</b>	WiFi/Bluetooth Antenna Gain :5.00 dBi (Numeric gain: 3.16) Zigbee Antenna Gain :5.00 dBi (Numeric gain: 3.16) LTE (taoglas) Antenna Gain :3.00 dBi (Numeric gain: 2.00) (worst) LTE (FIT) Antenna Gain :1.59 dBi (Numeric gain: 1.44)
<b>Maximum Average output power</b>	Bluetooth 2.1+EDR Mode : 7.22 dBm (5.272 mW) Bluetooth 4.0 Mode : 7.19 dBm (5.236 mW) Zigbee Mode : 14.27 dBm (26.730 mW) IEEE 802.11b Mode: 14.55 dBm (28.510 mW) IEEE 802.11g Mode: 17.81 dBm (60.395 mW) IEEE 802.11n HT 20 Mode: 17.64 dBm (58.076 mW) IEEE 802.11n HT 40 Mode: 17.19 dBm (52.360 mW) LTE Mode: 23.00 dBm (199.526 mW)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A

### 3. Test Results

*No non-compliance noted.*

#### Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

*Where E = Field strength in Volts / meter*

*P = Power in Watts*

*G = Numeric antenna gain*

*d = Distance in meters*

*S = Power density in watts / meter*

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

*Where d = Distance in cm*

*P = Power in mW*

*G = Numeric antenna gain*

*S = Power density in mW / cm<sup>2</sup>*

#### 4. Maximum Permissible Exposure

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where

$P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>

##### Bluetooth 2.1+EDR mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
2480	5.272	3.16	20	0.0033	1

##### Bluetooth 4.0 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
2480	5.236	3.16	20	0.0033	1

##### Zigbee mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
2440	26.73	3.16	20	0.0168	1

##### IEEE 802.11b mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
2437	28.51	3.16	20	0.0179	1

##### IEEE 802.11g mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
2437	60.395	3.16	20	0.0380	1

##### IEEE 802.11n HT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
2462	58.076	3.16	20	0.0365	1

##### IEEE 802.11n HT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)
2437	52.36	3.16	20	0.0329	1

##### LTE Band 13 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
782	199.526	2	20	0.0794	0.521

**Simultaneously MPE**

Simultaneously MPE = MPE 1 / Limit 1 + MPE 2 / Limit2 + MPE 3 / Limit 3

**WiFi + Zigbee + LTE**

Simultaneously MPE = ( 0.0380 mW/cm<sup>2</sup> /1 ) + ( 0.0168 mW/cm<sup>2</sup> /1 ) + ( 0.0794 mW/cm<sup>2</sup>/0.521) = 0.207

**Bluetooth + Zigbee + LTE**

Simultaneously MPE = ( 0.0033 mW/cm<sup>2</sup> /1 ) + ( 0.0168 mW/cm<sup>2</sup> /1 ) + ( 0.0794 mW/cm<sup>2</sup>/0.521) = 0.172