

**IEEE C95.1
KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091**

RF EXPOSURE REPORT

For

ICG

Model: ICG-100-NA-R

Trade Name: Intwine connect

Issued to

**Foxconn International Inc
NO 2 ZIYOU ST TUCHENG DISTRICT
NEW TAIPEI
236**

Issued by

**Compliance Certification Services Inc.
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)
<http://www.ccsrf.com>
service@ccsrf.com
Issued Date: September 18, 2015**



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	September 18, 2015	Initial Issue	ALL	Angel Cheng

TABLE OF CONTENTS

1. LIMIT 4

2. EUT SPECIFICATION..... 4

3. TEST RESULTS 5

4. MAXIMUM PERMISSIBLE EXPOSURE..... 6

1. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT SPECIFICATION

EUT	ICG								
Model	ICG-100-NA-R								
Trade Name	Intwine connect								
Frequency band (Operating)	<input type="checkbox"/> GPRS / EDGE 850MHz: 824.2MHz ~ 848.8MHz <input type="checkbox"/> GPRS / EDGE 1900MHz: 1850.2MHz ~ 1909.8MHz <input type="checkbox"/> WCDMA Band II: 1852.4MHz ~ 1907.6MHz <input type="checkbox"/> WCDMA Band V: 826.4MHz ~ 846.6MHz <input type="checkbox"/> LTE Band IV: 1710.0MHz ~ 1755.0MHz <input checked="" type="checkbox"/> LTE Band XIII: 779.5MHz ~ 784.5MHz <input type="checkbox"/> Others								
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others								
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)								
Antenna Specification	LTE Band XIII: (1) Taoglas / Part No.: TG.30.8113W 3.00 dBi (Numeric gain: 2.00) (2) FIT / Part No.: TG.30.8113W 1.59 dBi (Numeric gain: 1.44) Type: Dipole Antenna								
Measurement Average output power	<table border="1"> <thead> <tr> <th>System</th> <th>Power</th> <th></th> </tr> </thead> <tbody> <tr> <td>LTE Band XIII</td> <td>22.32 dBm</td> <td>(170.61 mW)</td> </tr> </tbody> </table>			System	Power		LTE Band XIII	22.32 dBm	(170.61 mW)
System	Power								
LTE Band XIII	22.32 dBm	(170.61 mW)							
Power Target / Tolerance	<table border="1"> <thead> <tr> <th>System</th> <th>Target Power</th> <th>Tolerance</th> </tr> </thead> <tbody> <tr> <td>LTE Band XIII</td> <td>21.0 dBm</td> <td>± 2 dB</td> </tr> </tbody> </table>			System	Target Power	Tolerance	LTE Band XIII	21.0 dBm	± 2 dB
System	Target Power	Tolerance							
LTE Band XIII	21.0 dBm	± 2 dB							
Max tune up Power / Max time Average Power	<table border="1"> <thead> <tr> <th>System</th> <th>Max Tune up Power</th> <th>Time Average Power</th> </tr> </thead> <tbody> <tr> <td>LTE Band XIII</td> <td>23.0dBm (199.526mW)</td> <td>23.0dBm (199.526mW)</td> </tr> </tbody> </table>			System	Max Tune up Power	Time Average Power	LTE Band XIII	23.0dBm (199.526mW)	23.0dBm (199.526mW)
System	Max Tune up Power	Time Average Power							
LTE Band XIII	23.0dBm (199.526mW)	23.0dBm (199.526mW)							
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A								

3. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where $E =$ Field strength in Volts / meter

$P =$ Power in Watts

$G =$ Numeric antenna gain

$d =$ Distance in meters

$S =$ Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where $d =$ Distance in cm

$P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

4. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where $P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

LTE Band XIII mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
23230	782	199.526	2	20	0.0794	0.521