



# RFID 13.56 MHz Radio Test Report

## FCC ID: SIB-NABIXD-NV10B

This report concerns (check one) :  Original Grant  Class II Change

**Issued Date** : Jun. 11, 2013  
**Project No.** : 1305C141  
**Equipment** : nabi Tablet (nabi XD)  
**Model Name** : NABIXD-NV10C; NABIXD-NV10B  
**Applicant** : Foxconn International Inc.  
**Address** : No.2, Ziyou St., Tucheng Dist., New Taipei City  
236, Taiwan  
**Manufacturer** : FUHU INC  
**Address** : 909 N SEPULVEDA BLVD STE 540 EL  
SEGUNDO, CA 90245-2733

**Tested by:** Neutron Engineering Inc. EMC Laboratory  
**Date of Receipt:** May. 21, 2013  
**Date of Test:**  
May. 21, 2013 ~ Jun. 10, 2013

**Testing Engineer** : David Mao  
(David Mao)

**Technical Manager** : Leo Hung  
(Leo Hung)

**Authorized Signatory** : Steven Lu  
(Steven Lu)

### **Neutron Engineering Inc.**

**No.3, Jinshagang 1st Road, ShiXia, Dalang  
Town, Dong Guan, China.  
TEL : (0769) 8318-3000 FAX : (0769) 8319-6000**



### **Declaration**

**Neutron** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

**Neutron's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

**Neutron's** reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

**Neutron's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



## Table of Contents

1	CERTIFICATION	5
2	SUMMARY OF TEST RESULTS	6
2.1	TEST FACILITY	7
2.2	MEASUREMENT UNCERTAINTY	7
3	GENERAL INFORMATION	8
3.1	GENERAL DESCRIPTION OF EUT	8
3.2	DESCRIPTION OF TEST MODES	9
3.3	BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
3.4	DESCRIPTION OF SUPPORT UNITS	11
4	EMC EMISSION TEST	12
4.1	CONDUCTED EMISSION MEASUREMENT	12
4.1.1	POWER LINE CONDUCTED EMISSION Limits	12
4.1.2	MEASUREMENT INSTRUMENTS LIST AND SETTING	12
4.1.3	TEST PROCEDURE	13
4.1.4	DEVIATION FROM TEST STANDARD	13
4.1.5	TEST SETUP	13
4.1.6	EUT OPERATING CONDITIONS	13
4.1.7	TEST RESULTS	14
4.2	RADIATED EMISSION TEST	17
4.2.1	LIMIT	17
4.2.2	MEASUREMENT INSTRUMENTS LIST	18
4.2.3	TEST PROCEDURE	19
4.2.4	DEVIATION FROM TEST STANDARD	19
4.2.5	TEST SETUP	20
4.2.6	EUT OPERATING CONDITIONS	20
4.2.7	TEST RESULTS (BELOW 30MHZ) - FCC PART 15.209	21
4.2.8	TEST RESULTS - (30-1000MHZ) - FCC PART 15.209	22
4.2.9	TEST RESULTS- FCC PART 15.225	24
4.3	FREQUENCY STABILITY MEASUREMENT	25
4.3.1	LIMIT	25
4.3.2	MEASUREMENT INSTRUMENTS LIST	25
4.3.3	TEST PROCEDURE	25
4.3.4	DEVIATION FROM TEST STANDARD	25
4.3.5	EUT OPERATING CONDITIONS	25
4.3.6	TEST RESULTS	26
5.	20dB SPECTRUM BANDWIDTH MEASUREMENT	27
5.2.	TEST PROCEDURES	27
5.3.	TEST SETUP LAYOUT	27



## Table of Contents

5.4. TEST DEVIATION	27
5.5. EUT OPERATION DURING TEST	27
5.6. TEST RESULT	28
6. EUT TEST PHOTO	29



## 1 CERTIFICATION

Equipment : nabi Tablet (nabi XD)  
Brand Name : nabi  
Model Name : NABIXD-NV10C; NABIXD-NV10B  
Applicant : Foxconn International Inc.  
Factory : Honfujin precision industry(Chongqing) Co.,Ltd.  
Address : No.1,East district 1st Rd.Shapingba District,ChongQing  
Date of Test : May. 21, 2013 ~ Jun. 10, 2013  
Test Item : ENGINEERING SAMPLE  
Standards : FCC Part 15, Subpart C: 15.225  
ANSI C63.4: 2009

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-5-1305C141) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).



**2 SUMMARY OF TEST RESULTS**

Test procedures according to the technical standards:

FCC Part 15, Subpart C: 15.225			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted emission	PASS	
15.35 / 15.205 / 15.209 / 15.225	Radiated emission	PASS	
15.225(e)	Frequency Stability	PASS	
15.203	Antenna Requirement	PASS	
-	20dB Occupied Bandwidth Measurement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report.



**2.1 TEST FACILITY**

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792  
 Neutron's test firm number is 319330

**2.2 MEASUREMENT UNCERTAINTY**

**The measurement uncertainty is not specified by FCC rules and for reference only.**  
 The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95%**.  
 The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
DG-CB03	CISPR	9K~30MHz	V	3.79	
		9K~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	



**3 GENERAL INFORMATION**

**3.1 GENERAL DESCRIPTION OF EUT**

Equipment	nabi Tablet (nabi XD)				
Brand Name	nabi				
Model Name	NABIXD-NV10C; NABIXD-NV10B				
Model Difference	The capacity is different since the manufacturer of chip is different, the NABIXD-NV10C is 32GB, the NABIXD-NV10B is 16GB.				
Product Description	The EUT is a nabi Tablet (nabi XD).				
	<table border="1"> <tr> <td>Operation Frequency:</td> <td>13.56 MHz</td> </tr> <tr> <td>Antenna Designation:</td> <td>Integral Antenna</td> </tr> </table>	Operation Frequency:	13.56 MHz	Antenna Designation:	Integral Antenna
	Operation Frequency:	13.56 MHz			
Antenna Designation:	Integral Antenna				
More details of EUT technical specification, please refer to the User's Manual.					
Power Source	#1 DC voltage supplied from adapter Brand/Model: Chicony/W12-010N3A #2 DC voltage supplied rechargeable Li-Polymer battery. Battery Model: MLP3576113-2P				
Power Rating	#1 I/P: AC 100-240V~ 50/60Hz 0.3A O/P: DC 5.35V 2A #2 DC 3.7V 8000mAh 29.6Wh				
Connecting I/O Port(s)	Please refer to the User's Manual				

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.





**3.2 DESCRIPTION OF TEST MODES**

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Test Mode	Description
Mode 1	TX

<b>Conducted emission test</b>	
Final Test Mode	Description
Mode 1	TX

<b>Radiated emission test</b>	
Final Test Mode	Description
Mode 1	TX

<b>Frequency Stability test</b>	
Final Test Mode	Description
Mode 1	TX


<b>Antenna Requirement test</b>	
Final Test Mode	Description
Mode 1	TX

(1) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.




**3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**

**Conducted:**



C-1: Earphone Cable

**Radiated:**





**3.4 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	nabi Tablet (nabi XD)	nabi	NABIXD-NV10C	SIB-NABIXD-NV10B	N/A	EUT
E-2	Earphone	Apple	N/A	DOC	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	YES	NO	1.1m	

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



**4 EMC EMISSION TEST**

**4.1 CONDUCTED EMISSION MEASUREMENT**

**4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)**

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

**4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Next Calibration
1	LISN	EMCO	3816/2	00052765	May.04.2013	Apr. 25, 2014
2	LISN	R&S	ENV216	100087	Nov.17.2012	Nov.16.2013
3	Test Cable	N/A	C_17	N/A	Mar.28.2013	Mar.15.2014
4	EMI TEST RECEIVER	R&S	ESCS30	826547/02 2	May.04.2013	Apr. 25, 2014
5	50Ω Terminator	SHX	TF2-3G-A	08122902	May.04.2013	Apr. 25, 2014

Remark: " N/A " denotes no model name, serial or calibration specified.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


#### 4.1.3 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT was programmed to be in continuously transmitting mode.




#### 4.1.7 TEST RESULTS

Remark

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform ◦ In this case, a “ \* ” marked in AVG Mode column of Interference Voltage Measured ◦
- (2) Measuring frequency range from 150KHz to 30MHz ◦




E.U.T :	nabi Tablet (nabi XD)	Model Name	NABIXD-NV10C
Temperature :	25 °C	Relative Humidity :	55%
Pressure :	1010hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX	Phase:	Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	38.15	9.72	47.87	66.00	-18.13	peak	
2		0.3810	33.22	9.74	42.96	58.26	-15.30	peak	
3		1.1420	28.13	9.79	37.92	56.00	-18.08	peak	
4	*	4.9531	30.81	9.93	40.74	56.00	-15.26	peak	
5		7.4860	27.13	9.99	37.12	60.00	-22.88	peak	
6		19.8980	23.35	10.23	33.58	60.00	-26.42	peak	



E.U.T :	nabi Tablet (nabi XD)	Model Name	NABIXD-NV10C
Temperature :	25 °C	Relative Humidity :	55%
Pressure :	1010hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX	Phase:	Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1617	31.98	9.72	41.70	65.38	-23.68	peak	
2	*	0.3921	34.54	9.74	44.28	58.02	-13.74	peak	
3		0.9040	28.31	9.80	38.11	56.00	-17.89	peak	
4		1.8410	27.30	9.87	37.17	56.00	-18.83	peak	
5		5.3900	26.33	9.95	36.28	60.00	-23.72	peak	
6		20.1170	22.51	10.25	32.76	60.00	-27.24	peak	





**4.2 RADIATED EMISSION TEST**

**4.2.1 LIMIT**

<b>FCC Part 15.209</b>				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	2400 / F(KHz)	300m	10000 * 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 – 1.705	24000 / F(KHz)	30m	100 * 24000/F(KHz)	20log 24000/F(KHz) + 40
1.705 – 30.00	30	30m	100* 30	20log 30 + 40
30.0 – 88.0	100	3m	100	20log 100
88.0 – 216.0	150	3m	150	20log 150
216.0 – 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500
<b>FCC Part 15.225(a)/(b)/(c)</b>				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
13.553 – 13.567	15,848	30 m	15,848*100	124
13.567 – 13.710	334	30 m	334*100	90.5
13.110 – 13.410	106	30 m	106*100	80.5
13.710 – 14.010				

**Note:**

- (1) The tighter limit shall apply at the boundary between two frequency range.
- (2) Limitation expressed in dBuV/m is calculated by 20log Emission Level (uV/m).
- (3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of  $L_{d1} = L_{d2} * (d_2/d_1)^2$ .  
 Example:  
 F.S Limit at 30m distance is 30uV/m , then F.S Limitation at 3m distance is adjusted as  $L_{d1} = L_1 = 30uV/m * (10)^2 = 100 * 30 uV/m$
- (4) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)  
 Margin Level = Measurement Value – Limit Value



**4.2.2 MEASUREMENT INSTRUMENTS LIST**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Next Calibration
1	Antenna	Schwarzbeck	VULB9160	9160-3232	May.25.2013	Apr. 25, 2014
2	Amplifier	HP	8447D	2944A09673	May.04.2013	Apr. 25, 2014
3	Test Receiver	R&S	ESCI	100382	May.04.2013	Apr. 25, 2014
4	Test Cable	N/A	C-01_CB03	N/A	Jul.01.2012	Jun.30.2013
5	Antenna	ETS	3115	00075789	May.25.2013	Apr. 25, 2014
6	Amplifier	Agilent	8449B	3008A02274	May.04.2013	Apr. 25, 2014
7	Spectrum	Agilent	E4408B	US39240143	Nov.24.2012	Nov. 16.2013
8	Test Cable	HUBER+SUHNER	C-45	N/A	May.02.2013	Apr. 30, 2014
9	Controller	CT	SC100	N/A	N/A	N/A
10	Horn Antenna	EMCO	3115	9605-4803	May.26.2012	May.25.2014
11	Active Loop Antenna	R&S	HFH2-Z2	830749/020	May.04.2013	Apr. 25, 2014
12	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Oct.13.2012	Oct.12.2013

Remark:” N/A” denotes no model name, serial no. or calibration specified.



#### **4.2.3 TEST PROCEDURE**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

**NOTE: (FCC PART 15.209)**

- a. Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode with Detector BW=120 kHz.
- b. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.

**NOTE: (FCC PART 15.225)**


- a. Spectrum Setting:
  - 9 KHz – 150 KHz, RBW= 200Hz, VBW=200Hz, Sweep time = 200 ms.
  - 150 K Hz – 30 MHz, RBW= 10 KHz, VBW=10 KHz, Sweep time = 200 ms.
  - 30 MHz – 1000 MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
- b. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- c. The Log-Bicon Antenna will use to test frequency range from 30MHz to 1000MHz and the Loop Antenna will use to test frequency below 30MHz.

#### **4.2.4 DEVIATION FROM TEST STANDARD**


No deviation

**4.2.5 TEST SETUP**

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) For radiated emissions below 30MHz



**4.2.6 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



**4.2.7 TEST RESULTS (BELOW 30MHZ) - FCC PART 15.209**

EUT :	nabi Tablet (nabi XD)	Model Name	NABIXD-NV10C
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX MODE		

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0312	0°	21.28	23.59	44.87	117.72	-72.85	AVG
0.0312	0°	32.57	23.76	56.33	137.72	-81.39	PK
0.3014	0°	19.14	20.28	39.42	98.02	-58.60	AVG
0.3014	0°	34.25	21.90	56.15	118.02	-61.87	PK
0.4275	0°	20.18	19.97	40.15	94.99	-54.83	AVG
0.4275	0°	33.65	20.14	53.79	114.99	-61.19	PK
3.9241	0°	28.71	18.99	47.70	69.54	-21.84	QP
3.9241	0°	27.58	18.99	46.57	69.54	-22.97	QP
7.1279	0°	29.65	18.03	47.68	69.54	-21.86	QP

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0725	90°	18.56	21.95	40.51	110.40	-69.89	AVG
0.0725	90°	28.68	22.25	50.93	130.40	-79.47	PK
0.3148	90°	20.58	20.24	40.82	97.64	-56.82	AVG
0.3148	90°	33.46	21.19	54.65	117.64	-63.00	PK
2.2447	90°	27.88	19.35	47.23	69.54	-22.31	QP
6.0741	90°	29.16	18.11	47.27	69.54	-22.27	QP
8.7254	90°	26.65	17.90	44.55	69.54	-24.99	QP
10.8214	90°	25.75	17.85	43.60	69.54	-25.94	QP


**Remark**

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported ◦
- (2) Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB); ◦
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor. ◦



**4.2.8 TEST RESULTS - (30-1000MHZ) - FCC PART 15.209**


E.U.T	nabi Tablet (nabi XD)	Model Name	NABIXD-NV10C
Temperature	26 °C	Relative Humidity	60%
Test Voltage	DC 3.7V	Polarization	Vertical
Test Mode	TX		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	46.4900	39.73	-17.20	22.53	40.00	-17.47	peak	
2		152.2200	37.99	-17.86	20.13	43.50	-23.37	peak	
3		236.6100	39.06	-15.82	23.24	46.00	-22.76	peak	
4		408.3000	34.74	-9.67	25.07	46.00	-20.93	peak	
5		600.3600	33.25	-5.49	27.76	46.00	-18.24	peak	
6		741.9800	31.86	-4.31	27.55	46.00	-18.45	peak	



E.U.T	nabi Tablet (nabi XD)	Model Name	NABIXD-NV10C
Temperature	26 °C	Relative Humidity	60%
Test Voltage	DC 3.7V	Polarization	Horizontal
Test Mode	TX		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		199.7500	37.66	-16.93	20.73	43.50	-22.77	peak	
2		280.2600	40.88	-13.16	27.72	46.00	-18.28	peak	
3		359.8000	39.50	-11.19	28.31	46.00	-17.69	peak	
4		612.0000	34.15	-5.29	28.86	46.00	-17.14	peak	
5	*	747.8000	34.27	-4.26	30.01	46.00	-15.99	peak	



**4.2.9 TEST RESULTS- FCC PART 15.225**

E.U.T	nabi Tablet (nabi XD)	Model Name	NABIXD-NV10C
Temperature	26 °C	Relative Humidity	60%
Test Voltage	DC 3.7V		
Test Mode	TX		

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
13.560	0°	50.02	10.99	61.01	124.00	-62.99	
27.020	0°	38.35	9.33	47.68	69.54	-21.86	

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
13.560	90°	51.25	10.99	62.24	124.00	-61.76	
27.020	90°	39.25	9.33	48.58	69.54	-20.96	





**4.3 FREQUENCY STABILITY MEASUREMENT**

**4.3.1 LIMIT**

<b>FCC Part 15.225(e)</b>
The frequency tolerance of the carrier signal shall be maintained within +/-0.01% of the operating frequency over a temperature variation of - 20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

**4.3.2 MEASUREMENT INSTRUMENTS LIST**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Next Calibration
1	Spectrum Analyzer	R&S	FSP_40	100185	Nov. 17.2012	Nov. 16.2013

Remark:” N/A” denotes no model name, serial no. or calibration specified.

**4.3.3 TEST PROCEDURE**

- a. The equipment under test was connected to an external AC power supply and the RF output was connected to a frequency counter via feed through attenuators. The EUT was placed inside the temperature chamber.  
After the temperature stabilized for approximately 20 minutes, the frequency of the output signal was recorded from the counter.
- b. At room temperature (25±5°C), an external variable AC power supply was connected to the EUT. The frequency of the transmitter was measured for 115%, 100% and 85% of the nominal operating input voltage.

**4.3.4 DEVIATION FROM TEST STANDARD**

No deviation

**4.3.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



**4.3.6 TEST RESULTS**

E.U.T	nabi Tablet (nabi XD)	Model Name	NABIXD-NV10C
Temperature	26 °C	Relative Humidity	60%
Test Voltage	DC 3.7V		
Test Mode	TX		

**Frequency Stability Versus Environmental Temperature**

	Temperature (°C)	Voltage (AC)	Frequency (MHz)	Frequency Error (kHz)	Limit (kHz)	Result
	20	120V	13.5600			
0 min	50	120V	13.5601	0.0001	+/- 1.356	PASS
	-20	120V	13.5612	0.0012	+/- 1.356	PASS
2 min	50	120V	13.5623	0.0023	+/- 1.356	PASS
	-20	120V	13.5608	0.0008	+/- 1.356	PASS
5 min	50	120V	13.5606	0.0006	+/- 1.356	PASS
	-20	120V	13.5617	0.0017	+/- 1.356	PASS
10 min	50	120V	13.5613	0.0013	+/- 1.356	PASS
	-20	120V	13.5602	0.0002	+/- 1.356	PASS

**Frequency Stability Versus Input Voltage**

Temperature (°C)	Voltage (AC)		Frequency (MHz)	Frequency Error (kHz)	Limit (kHz)	Result
20	V-nom	120V	13.5600			
20	V-min	118V	13.5612	0.012	+/- 1.356	PASS
20	V-max	132V	13.5623	0.023	+/- 1.356	PASS

## **5. 20dB SPECTRUM BANDWIDTH MEASUREMENT**


### **5.1. LIMIT OF 20dB BANDWIDTH MEASUREMENT**

The 20dB bandwidth shall be specified in operating frequency band.

### **5.2. TEST PROCEDURES**

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 9kHz RBW and 9kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### **5.3. TEST SETUP LAYOUT**



### **5.4. TEST DEVIATION**

There is no deviation with the original standard.

### **5.5. EUT OPERATION DURING TEST**


The EUT was programmed to be in continuously transmitting mode.



**5.6. TEST RESULT**

E.U.T	nabi Tablet (nabi XD)	Model Name	NABIXD-NV10C
Temperature	26 °C	Relative Humidity	60%
Test Voltage	DC 3.7V		
Test Mode	TX		

Frequency (MHz)	20 dBc Bandwidth (KHz)	99% OBW (KHz)	Result
13.56	2.58	2.24	PASS





**6. EUT TEST PHOTO**

**Conducted Measurement Photos**





**Radiated emission test photos**

TX

