



No.198 Kezhu Road, Science Town Economic& Technology  
Development District Guangzhou, China 510663  
Telephone: +86 (0) 20 8215 5555 Fax: +86 (0) 20 8207 5059  
Email: sgs\_internet\_operations@sgs.com

FEDERAL COMMUNICATIONS COMMISSION  
Registration number: 556682

Report No.: SZEMO070200201RFF(I)  
Page : 1 of 8  
FCC ID : SIP-1122-B

## TEST REPORT

**Application No.** : SZEMO070200201RF(SGS SZ NO.: SZTYR070200274/EL)

**Applicant** : MEGA GAIN INTERNATIONAL LTD

**Buyer** : DISNEY

**FCC ID** : SIP-1122-B

**Fundamental Frequency** : 49.860MHz

**Equipment under Test (EUT):**

EUT Name : Cars McQueen/ Mater Full Functional R/C(The Mater only)

Item No. : 0711-TCP143(1122-W)

Labelled Age Grading : 3+ YEARS

Country of Origin : CHINA

Country of Destination : U.S.A

**Standards** : FCC PART 15, SUBPART C : 2006  
Section 15.235

**Date of Receipt** : 06 February 2007

**Date of Test** : 08 February to 19 March 2007

**Date of Issue** : 21 March 2007

<b>Test Result :</b>	<b>PASS *</b>
----------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo  
Laboratory Manager

This report refers to the General Conditions for Inspection and Testing Services, printed overleaf  
This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

All test results in this report can be traceable to National or International Standards.

## 2 Test Summary

Test	Test Requirement	Standard Paragraph	Result
Radiated Emission (30MHz to 1000MHz)	FCC PART 15 :2006	Section 15.235	PASS *
Occupied Bandwidth	FCC PART 15 :2006	Section 15.235	PASS


Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

\* The EUT passed the Radiated Emission test after modification.

1. Added one 5pF capacitance on L4 and the end of antenna to earth.
2. Changed L4 to 4.7 $\mu$  inductance.
3. Changed C1 to 47pF.
4. Changed the C4 to 10000pF.
5. Changed the C5 to 1000pF.
6. Changed the C7 to 47pF.
7. Changed the C8 to 47pF.
8. Changed the L1 to 1.0 $\mu$ .
9. Changed the L2 to 1.2 $\mu$ .
10. Added one 47000pF capacitance on C8 and Q1 to earth.
11. Added one 100000pF capacitance between the supply and earth as below.





### 3 Contents

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 TEST SUMMARY</b> .....	<b>2</b>
<b>3 CONTENTS</b> .....	<b>3</b>
<b>4 GENERAL INFORMATION</b> .....	<b>4</b>
4.1 CLIENT INFORMATION .....	4
4.2 DETAILS OF E.U.T. ....	4
4.3 DESCRIPTION OF SUPPORT UNITS .....	4
4.4 TEST LOCATION .....	4
4.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	4
<b>5 TEST RESULTS</b> .....	<b>5</b>
5.1 TEST INSTRUMENTS.....	5
5.2 E.U.T. OPERATION .....	5
5.3 TEST PROCEDURE & MEASUREMENT DATA .....	5
5.3.1 <i>Radiated Emissions</i> .....	5
5.3.2 <i>Occupied Bandwidth</i> .....	8



## 4 General Information

### 4.1 Client Information

Applicant: MEGA GAIN INTERNATIONAL LTD  
Address of Applicant: RM 1908, GREENFIELD TOWER, CONCORDIA PLAZA, 1, SCIENCE MUSEUM ROAD, T.S.T. EAST. KLN.

### 4.2 Details of E.U.T.

Product Name: Cars McQueen/ Mater Full Functional R/C(The Mater only)  
Item No: 0711-TCP143(1122-W)  
Power Supply: 9V DC (1\*9.0V '6F22' Size Battery) for Tx  
Power Cord: N/A-

### 4.3 Description of Support Units

The EUT was tested as an independent unit: a 49MHz radio transmitter.

### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663

Tel: +86 20 8215 5555 Fax: +86 20 8207 5059

### 4.5 Other Information Requested by the Customer

None.

## 5 Test Results

### 5.1 Test Instruments

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	28-04-2005	27-04-2007
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	100249	22-09-2006	21-09-2007
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0028	20-05-2006	19-05-2007
5	Coaxial cable	SGS	N/A	SEL0027	20-05-2006	19-05-2007
6	BiConiLog Antenna	ETS-LINDGREN	3142C	00042673	03-03-2007	02-03-2008
7	EMI Test Receiver	Rohde & Schwarz	ESCI	100119	12-03-2007	11-03-2008
8	Loop Antenna	Emco	6502	00042963	30-05-2006	29-05-2007

### 5.2 E.U.T. Operation

Input voltage: 9V DC (1\*9.0V '6F22' Size Battery) for the transmitter.

Operating Environment:

Temperature: 23.0 °C

Humidity: 54 % RH

Atmospheric Pressure: 1015 mbar

EUT Operation:

Test the EUT in transmitting mode.

### 5.3 Test Procedure & Measurement Data

#### 5.3.1 Radiated Emissions

Test Requirement: FCC Part15 C Section 15.235

Test Method: ANSI C63.4

Test Date: 08 February 2007 (Initial Test)

19 March 2007 (Test after Modifications)

Measurement Distance: 3m (Semi-Anechoic Chamber)

Requirements: Carrier frequency will not exceed 80dBuV/m AT 3m.

Out of band emissions shall not exceed:

40.0 dB $\mu$ V/m between 30MHz & 88MHz

43.5 dB $\mu$ V/m between 88MHz & 216MHz

46.0 dB $\mu$ V/m between 216MHz & 960MHz

54.0 dB $\mu$ V/m above 960MHz

Detector: Peak Scan (120kHz resolution bandwidth)

Test Procedure: The procedure used was ANSI Standard C63.4-2003. The receiver was scanned from 30MHz to 1000MHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. The worst case emissions were reported.

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. The EUT was measured by Bilog antenna with 2 orthogonal polarities and peak emissions from the EUT were detected within 6dB of the class B limit line.

The following measurements were performed on the modified modified EUT on 21 March 2006:  
 Test the EUT in transmitting mode.

Intentional emission

Test Frequency (MHz)	Peak (dBµV/m)		Limits (dBµV/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
49.860	56.91	44.15	100.0	43.09	55.85

Test Frequency (MHz)	Average (dBµV/m)		Limits (dBµV/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
49.860	52.10	41.23	80.0	27.90	38.77



Other emissions

Test Frequency (MHz)	Quasi-Peak (dBµV/m)	Limits (dBµV/m)	Margin (dB)
	Vertical		Vertical
146.88	36.54	43.50	-6.96
197.58	25.89	43.50	-17.61
297.03	37.57	46.00	-8.43
397.45	35.75	46.00	-10.25
447.18	36.56	46.00	-9.44

Test Frequency (MHz)	Quasi-Peak (dBµV/m)	Limits (dBµV/m)	Margin (dB)
	Horizontal		Horizontal
102.025	27.90	43.50	-15.60
146.875	32.95	43.50	-10.55
346.750	32.81	46.00	-13.19
447.175	32.07	46.00	-13.93
495.925	35.73	46.00	-10.27

Remark:


According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

**Test Results: The unit does meet the FCC Part 15 C Section 15.235 requirements.**

### 5.3.2 Occupied Bandwidth

Test Requirement: FCC Part15 C Section 15.235  
 Test Method: ANSI C63.4  
 Operation within the band 49.82 – 49.90 MHz  
 Test Date: 08 February 2007  
 Requirements: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits in Section 15.209, whichever permits the higher emission levels. The field strength of any emissions removed by more than 10 kHz from the band edges shall not exceed the general radiated emission limits in Section 15.209.  
 Method of measurement: The useful radiated emission from the EUT was detected by the spectrum analyzer with peak detector. The vertical Scale is set to -10dB per division. The horizontal scale is set to 5KHz per division.

The graph as below, represents the emissions take for this device.



N

Date: 9.FEB.2007 09:40:06

**The results: The unit does meet the FCC Part 15 C Section 15.235 requirements.**