

RF Exposure Evaluation

No.: 11021FCE

Applicant	Clarion Co., Ltd.
Address	7-2 Shintoshin Chuo-Ku, Saitama-Shi Saitama-Ken, 330-0081 JAPAN
EUT	Bluetooth module
Model No.	UGZZ8-X02
FCC ID	SJ20608137



Takeshi Matsumura (18 October 2011)



Masashi Tsukui (18 October 2011)

TAIYO YUDEN CO., LTD.

Page: 1 / 2

5607-2, Nakamuroda-machi, Takasaki-shi, Gunma, 370-3347, Japan

Radiofrequency Radiation Exposure Evaluation

- 15.247(i): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission’s guidelines. See § 1.1307(b)(1) of this chapter.
- 1.1307(b)(1): The appropriate exposure limits in § 1.1310 and 2.1093 of this chapter are generally applicable to all facilities, operations and transmitters regulated by the Commission.
- 1.1310: The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b).

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

Limit = 1.0 [mW/cm²] at 2.5GHz

MPE Calculation:

A *	B	C **	D	Limit [mW/cm ²]
Specified Antenna Gain *	Max. RF Output Power at Antenna Terminal [mW]	Distance [cm] **	Power Density. [mW/cm ²]	
1.585	2.951	20	0.000930	1.0

*: Numeric value of antenna gain (2.0dBi).

** : The shortest distance between transmitter’s radiating structure and the body of the user or nearby person. This device should be used in separation distance of at least 20 centimeters maintained between transmitter’s radiating structure and the body of the user or nearby persons. Refer to K30306 user manual.

$$\text{Calculation: } D = (A * B) / (4 * \pi * C^2) \tag{1}$$

For a truly worst-case prediction of power density at or near a surface, such as at groundlevel or on a rooftop, 100% reflection of incoming radiation can be assumed, resulting in a potential doubling of predicted field strength and a four-fold increase in power density. In that case Equations (1) can be modified to:

$$D = (2^2) * (A * B) / (4 * \pi * C^2) \quad (\text{worst-case})$$

$$\text{Power Density} = 0.003722 \text{mW/cm}^2$$

$$\text{MPE Limit} = 1.0 \text{mW/cm}^2 > \text{Power Density in worst-case}$$

This means that according to OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), the equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of 47 CFR Part 15.247(i).