

FCC TEST REPORT

FCC ID : SJ8-CA530
Applicant : RDI Technology (Shenzhen) Co., Ltd.
Address : Building C1 Xintang Industrial Park, East Baishixia, Fuyong, Baoan, Shenzhen, China
Manufacturer : The same as above
Address : The same as above
Equipment Under Test (EUT) :
Product Name : Digital Pan/Tilt Camera
Model No. : CA530
Standards : FCC CFR47 Part 15 Section 15.247:2010
Date of Test : May 11~30, 2013
Date of Issue : June 07, 2013

Test Result : **PASS**

Remark:

* The sample described above has been tested to be in compliance with the requirements of ANSI C63.4:2003. The test results have been reviewed and comply with the rules listed above and found to meet their essential requirements.

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

1/F, Fukangtai Building, West Baima Rd., Songgang Street, Baoan District,
Shenzhen 518105, China


Tel: +86-755-83551033 Fax: +86-755-83552400

Compiled by:



Zero Zhou / Project Engineer

Approved by:



Philo Zhong / Manager

2 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Duty Cycle	15.35	PASS
Band edge	15.247(d) 15.205(a)	PASS
Conduct Emission	15.207	PASS
20dB Bandwidth	15.247(a)(1)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Frequency Separation	15.247(a)(1)	PASS
Number of Hopping Frequency	15.247(a)(1)(iii)	PASS
Dwell time	15.247(a)(1)(iii)	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION	5
4.1 GENERAL DESCRIPTION OF E.U.T.	5
4.2 DETAILS OF E.U.T.	5
4.3 TEST FACILITY	5
4.4 TEST LOCATION	5
4.5 TEST MODE	5
4.6 CHANNEL LIST	6
5 EQUIPMENT USED DURING TEST	7
5.1 EQUIPMENTS LIST	7
5.2 MEASUREMENT UNCERTAINTY	8
5.3 TEST EQUIPMENT CALIBRATION	8
6 CONDUCTED EMISSION	9
6.1 E.U.T. OPERATION	9
6.2 EUT SETUP	9
6.3 CONDUCTED EMISSION TEST RESULT	10
7 RADIATED SPURIOUS EMISSIONS	12
7.1 EUT OPERATION :	12
7.2 TEST SETUP	13
7.3 SPECTRUM ANALYZER SETUP	14
7.4 TEST PROCEDURE	15
7.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	15
7.6 SUMMARY OF TEST RESULTS	16
8 DUTY CYCLE	24
8.1 TEST PROCEDURE	24
8.2 TEST RESULT	24
9 BAND EDGE MEASUREMENT	26
9.1 TEST RESULT:	27
10 20 DB BANDWIDTH MEASUREMENT	35
10.1 TEST PROCEDURE:	35
10.2 TEST RESULT:	35
11 MAXIMUM PEAK OUTPUT POWER	37
11.1 TEST PROCEDURE:	37
11.2 TEST RESULT:	37
12 HOPPING CHANNEL SEPARATION	40
12.1 TEST PROCEDURE:	40
12.2 TEST RESULT:	40
13 NUMBER OF HOPPING FREQUENCY	43
13.1 TEST PROCEDURE:	43
13.2 TEST RESULT:	43
14 DWELL TIME	44

14.1	TEST PROCEDURE:.....	44
14.2	TEST RESULT:.....	44
15	ANTENNA REQUIREMENT.....	48
16	RF EXPOSURE.....	49
16.1	REQUIMENTS:.....	49
16.2	THE PROCEDURES / LIMIT.....	49
16.3	MPE CALCULATION METHOD.....	50
17	PHOTOGRAPHS – TEST SETUP.....	51
17.1	PHOTOGRAPH – RADIATION SPURIOUS EMISSION TEST SETUP.....	51
17.2	PHOTOGRAPH – CONDUCTED EMISSION TEST SETUP.....	52
18	PHOTOGRAPHS - CONSTRUCTIONAL DETAILS.....	53
18.1	EXTERNAL VIEW.....	53
18.2	EUT - INTERNAL VIEW.....	56
19	FCC LABEL.....	62

4 General Information

4.1 General Description of E.U.T.

Product Name	: Digital Pan/Tilt Camera
Model No.	: CA530
Operation Frequency	: 2402MHz ~ 2478MHz, 39 channels in total
Type of Modulation	: GFSK
Oscillator	: Crystal 3.6864MHz,27MHz for CPU,16MHz for RF module
Antenna installation	: Integrated Antenna
Antenna Gain	: 2 dBi

4.2 Details of E.U.T.

Technical Data	: DC 5V 1A powered by adapter (Input: 100-240~50/60Hz, 200mA)
Adapter	: Manufacturer:Csec, M/N:CS6D050100FUF

4.3 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 7760A**

Waltek Services(Shenzhen) Co., Ltd. has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration 7760A, July 12, 2012.

- **FCC – Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, May 26, 2011.

4.4 Test Location

All the tests were performed at:

Waltek Services(Shenzhen) Co., Ltd. at 1/F, Fukangtai Building, West Baima Rd.,Songgang Street, Baoan District, Shenzhen, China

4.5 Test Mode

Test Item	Test Mode
Conducted Emissions	Normal linking(adapter)
Radiated Emissions	Normal linking(adapter)

4.6 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2404	3	2406	4	2408
5	2410	6	2412	7	2414	8	2416
9	2418	10	2420	11	2422	12	2424
13	2426	14	2428	15	2430	16	2432
17	2434	18	2436	19	2438	20	2440
21	2442	22	2444	23	2446	24	2448
25	2450	26	2452	27	2454	28	2456
29	2458	30	2460	31	2462	32	2464
33	2466	34	2468	35	2470	36	2472
37	2474	38	2476	39	2478	40	-

5 Equipment Used during Test

5.1 Equipments List

Conducted Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	Aug. 13,2012	Aug. 12,2013
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Aug. 13,2012	Aug. 12,2013
3.	Cable	LARGE	RF300	EW02014-3	Aug.14,2012	Aug. 13,2013
3m Semi-anechoic Chamber for Radiation Emissions (Test Frequency: 1GHz ~6GHz)						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer	Agilent	E7405A	MY45114943	Aug. 13,2012	Aug. 12,2013
4.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Aug. 13,2012	Aug. 12,2013
5.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	399	Aug. 13,2012	Aug. 12,2013
6.	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Apr.07,2013	Apr.06,2014
7.	Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-148	Aug. 13,2012	Aug. 12,2013
8.	10m Coaxial Cable with N- plug	SCHWARZBECK	AK 9515 H	-	Aug. 13,2012	Aug. 12,2013
3m Semi-anechoic Chamber for Radiation(TDK) (Test Frequency: 32.768kHz ~1GHz)						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	Aug.09,2012	Aug.08,2013
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Aug. 13,2012	Aug. 12,2013
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	Aug.11,2012	Aug.10,2013
4	Amplifier	Compliance pirection systems inc	PAP-0203	22024	Apr.07,2013	Apr.06,2014
5	Cable	HUBER+SUHNE R	CBL2	525178	Sep.15,2012	Sep.14,2013

5.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 4.74 dB (Horn antenna 1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

5.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.4:2003
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth) Quasi-Peak & Average if maximised peak within 6dB of Average Limit

6.1 E.U.T. Operation

Operating Environment:

Temperature: 25.5 °C

Humidity: 51 % RH

Atmospheric Pressure: 1010 mbar

EUT Operation:


The test was performed in normal linking mode, the test data were shown in the report.

The EUT was tested according to ANSI C63.4:2003. The frequency spectrum from 150kHz to 30MHz was investigated.

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.2 EUT Setup

The EUT was placed on the test table in shielding room.




6.3 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.


Test mode: normal linking mode

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1620	32.23	9.81	42.04	65.36	-23.32	QP	
2	0.1620	18.28	9.81	28.09	55.36	-27.27	AVG	
3	0.4340	36.61	9.91	46.52	57.18	-10.66	QP	
4	0.4340	29.88	9.91	39.79	47.18	-7.39	AVG	
5	0.6780	28.80	9.95	38.75	56.00	-17.25	QP	
6	0.6780	22.61	9.95	32.56	46.00	-13.44	AVG	
7	0.8620	28.87	9.98	38.85	56.00	-17.15	QP	
8	0.8620	20.65	9.98	30.63	46.00	-15.37	AVG	
9	1.3180	24.69	10.00	34.69	56.00	-21.31	QP	
10	1.3180	19.01	10.00	29.01	46.00	-16.99	AVG	
11	2.2900	25.05	10.01	35.06	56.00	-20.94	QP	
12	2.2900	18.20	10.01	28.21	46.00	-17.79	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	34.68	9.80	44.48	65.99	-21.51	QP	
2	0.1500	18.13	9.80	27.93	55.99	-28.06	AVG	
3	0.4340	31.18	9.91	41.09	57.18	-16.09	QP	
4	0.4340	22.32	9.91	32.23	47.18	-14.95	AVG	
5	0.5860	23.77	9.94	33.71	56.00	-22.29	QP	
6	0.5860	16.34	9.94	26.28	46.00	-19.72	AVG	
7	0.8620	23.36	9.98	33.34	56.00	-22.66	QP	
8	0.8620	15.50	9.98	25.48	46.00	-20.52	AVG	
9	2.3060	20.35	10.01	30.36	56.00	-25.64	QP	
10	2.3060	13.31	10.01	23.32	46.00	-22.68	AVG	
11	24.0020	11.35	11.52	22.87	60.00	-37.13	QP	
12	24.0020	4.96	11.52	16.48	50.00	-33.52	AVG	

7 Radiated Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: DA 00-705

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

7.1 EUT Operation :

Operating Environment:

Temperature: 25.5 °C


Humidity: 51 % RH

Atmospheric Pressure: 1019 mbar


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

According to FCC Part15 Rules, the system was tested 3MHz to 25000MHz.

Below 30MHz

Sweep SpeedAuto
 IF Bandwidth10KHz
 Video Bandwidth10KHz
 Resolution Bandwidth10KHz

30MHz ~ 1GHz

Sweep SpeedAuto
 IF Bandwidth120 KHz
 Video Bandwidth100KHz
 Quasi-Peak Adapter Bandwidth120 KHz
 Quasi-Peak Adapter ModeNormal
 Resolution Bandwidth100KHz

Above 1GHz

Sweep SpeedAuto
 IF Bandwidth120 KHz
 Video Bandwidth3MHz
 Quasi-Peak Adapter Bandwidth120 KHz
 Quasi-Peak Adapter ModeNormal
 Resolution Bandwidth1MHz

7.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

7.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

7.6 Summary of Test Results

Test Frequency :Below 30MHz


The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 1000MHz

Remark: the EUT was pretested at the high, middle and low channel, and the worse case was the low Channel, so the data show was the low channel only.


Test mode: Normal Link(adapter)

Antenna polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	30.2115	11.32	16.24	27.56	40.00	-12.44	QP	
2	106.2810	12.89	14.17	27.06	43.50	-16.44	QP	
3	259.4433	15.40	15.74	31.14	46.00	-14.86	QP	
4	377.8480	15.60	19.44	35.04	46.00	-10.96	QP	
5	498.7302	15.05	22.94	37.99	46.00	-8.01	QP	
6	932.1403	8.53	31.36	39.89	46.00	-6.11	QP	

Antenna polarization: Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	216.1194	10.24	14.72	24.96	46.00	-21.04	QP	
2	259.4433	15.60	15.74	31.34	46.00	-14.66	QP	
3	319.2071	18.79	17.97	36.76	46.00	-9.24	QP	
4	377.8480	18.67	19.44	38.11	46.00	-7.89	QP	
5	428.7959	17.46	19.91	37.37	46.00	-8.63	QP	
6	932.1403	6.65	31.36	38.01	46.00	-7.99	QP	


Test Frequency: 1GHz ~ 18GHz

Remark: A 2.4GHz High pass filter is used during the test.

AV = Peak +20Log₁₀(duty cycle) =PK+(-36.8)=PK-36.8 [refer to section 8 for more detail]

Test Channel: TX2402MHz


Antenna polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2402.000	45.64	-15.58	30.06	74.00	-43.94	peak	
2	4804.000	53.26	-11.97	41.29	74.00	-32.71	peak	
3	7206.000	57.37	-7.21	50.16	74.00	-23.84	peak	
4	9608.000	55.72	-5.71	50.01	74.00	-23.99	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.

Antenna polarization: Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2402.000	51.14	-15.58	35.56	74.00	-38.44	peak	
2	4804.000	53.99	-11.97	42.02	74.00	-31.98	peak	
3	7206.000	55.25	-7.21	48.04	74.00	-25.96	peak	
4	9608.000	54.23	-5.71	48.52	74.00	-25.48	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 1GHz ~ 18GHz

Test Channel: TX2440MHz


Antenna polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2440.000	45.33	-15.70	29.63	74.00	-44.37	peak	
2	4880.000	53.01	-11.92	41.09	74.00	-32.91	peak	
3	7320.000	62.44	-7.13	55.31	74.00	-18.69	peak	
4	9760.000	56.33	-5.32	51.01	74.00	-22.99	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.

Antenna polarization: Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2440.000	45.38	-15.70	29.68	74.00	-44.32	peak	
2	4880.000	50.84	-11.92	38.92	74.00	-35.08	peak	
3	7320.000	55.51	-7.13	48.38	74.00	-25.62	peak	
4	9760.000	55.16	-5.32	49.84	74.00	-24.16	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.

Test Channel: TX2478MHz


Antenna polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2478.000	45.01	-15.68	29.33	74.00	-44.67	peak	
2	4956.000	54.37	-11.78	42.59	74.00	-31.41	peak	
3	7434.000	61.83	-6.94	54.89	74.00	-19.11	peak	
4	9912.000	53.95	-5.13	48.82	74.00	-25.18	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.

Antenna polarization: Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2478.000	44.32	-15.68	28.64	74.00	-45.36	peak	
2	4961.000	50.57	-11.77	38.80	74.00	-35.20	peak	
3	7443.000	54.25	-6.91	47.34	74.00	-26.66	peak	
4	9908.000	54.48	-5.13	49.35	74.00	-24.65	peak	
5	12390.000	53.77	-4.82	48.95	74.00	-25.05	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.

Test Frequency :Above 18GHz

The measurements were more than 20 dB below the limit and not reported


8 Duty Cycle

Test Requirement: FCC Part 15.35
 Test Method: ANSI C63.4:2003
 Test Status: TX mode.


8.1 Test Procedure

1. The EUT was placed on a turntable which is 0.8m above ground plane
2. Set EUT as normal working mode
3. Set SPA center frequency = fundamental frequency, RBW = 1000 kHz, VBW = 1000 kHz, Span = 0 Hz, Adjacent sweep time.

8.2 Test Result



Date: 20.MAY.2013 23:19:20



The EUT is auto. operation for transmitter, it is declared by the manufacturer as a duty cycle ratio of less than 100%.

The EUT's work time : $T_{on} = \text{pulse time} = 1.444 \text{ ms}$

The EUT's work period : $T = T_{ON} + T_{OFF} = \text{transmission period} = 100 \text{ ms}$

The EUT's duty cycle : $D = T_{on} / T = 1.444 / 100 * 100\% = 1.44\%$

Duty Cycle Correction Factor(dB) = $20 * \text{Log}_{10}(\text{Duty Cycle}) = 20 * \text{Log}_{10}(1.44 \%)$


= -36.8dB

9 Band Edge Measurement

Test Requirement:	Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	DA 00-705
Measurement Distance:	3m
Limit:	40.0 dBuV/m between 30MHz & 88MHz; 43.5 dBuV/m between 88MHz & 216MHz; 46.0 dBuV/m between 216MHz & 960MHz; 54.0 dBuV/m above 960MHz. 74.0 dBuV/m for peak above 1GHz 54.0 dBuV/m for AVG above 1GHz
Detector:	For Peak value: RBW = 1 MHz for $f \geq 1$ GHz VBW \geq RBW; Sweep = auto Detector function = peak Trace = max hold For AVG value: RBW = 1 MHz for $f \geq 1$ GHz VBW = 10Hz; Sweep = auto Detector function d= AVG Trace = max hold
Test Mode:	continuous transmitting

9.1 Test Result:


Lower Channel –Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2400.000	79.94	-15.58	64.36	74.00	-9.64	peak	
2	2402.055	109.65	-15.59	94.06	74.00	20.06	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.


Lower Channel –Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2400.000	78.81	-15.58	63.23	74.00	-10.77	peak	
2	2402.055	106.05	-15.59	90.46	74.00	16.46	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.


Upper Channel – Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2478.660	108.10	-15.68	92.42	74.00	18.42	peak	
2	2483.500	52.90	-15.67	37.23	74.00	-36.77	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.


Upper Channel –Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2478.030	102.16	-15.68	86.48	74.00	12.48	peak	
2	2483.500	54.66	-15.67	38.99	74.00	-35.01	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.


Lower Channel (Hopping on) –Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2400.000	86.46	-15.58	70.88	74.00	-3.12	peak	
2	2404.145	107.94	-15.59	92.35	74.00	18.35	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.


Lower Channel (Hopping on) –Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2400.000	84.32	-15.58	68.74	74.00	-5.26	peak	
2	2401.865	106.79	-15.58	91.21	74.00	17.21	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.


Upper Channel (Hopping on)– Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2476.020	107.39	-15.68	91.71	74.00	17.71	peak	
2	2483.500	54.90	-15.67	39.23	74.00	-34.77	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.

Upper Channel (Hopping on)–Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2475.750	102.61	-15.68	86.93	74.00	12.93	peak	
2	2483.500	52.66	-15.67	36.99	74.00	-37.01	peak	

No.	Freq. (MHz)	Duty Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	-	-	-	-	-	-	The measurements were more than 20 dB below the limit and not reported.

10 20 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247
 Test Method: DA 00-705
 Test Mode: Test in fixing operating frequency at low, Middle, high channel.


10.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 100kHz


10.2 Test Result:

Test Channel	Bandwidth
Low	1.916MHz
Middle	1.756MHz
High	1.756MHz


Test result plot as follows:



Date: 20.MAY.2013 16:57:35



Date: 20.MAY.2013 17:00:37



Date: 20.MAY.2013 17:02:37

11 Maximum Peak Output Power

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	DA 00-705
Test Limit:	Regulation 15.247 (b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. Refer to the result "Number of Hopping Frequency" of this document. The 0.125watts (20.97 dBm) limit applies.
Test mode:	Test in fixing frequency transmitting mode.


11.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.


11.2 Test Result:

Test Channel	Output Power (dBm)	Limit (dBm)
Low	15.50	20.97
Middle	15.29	20.97
High	14.91	20.97

Test result plot as follows:




Date: 20.MAY.2013 17:10:11



Date: 20.MAY.2013 17:11:10

High Channel



Date: 20.MAY.2013 17:13:05

12 Hopping Channel Separation

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: DA 00-705

Test Limit: Regulation 15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 1W.

Test Mode: Test in hopping transmitting operating mode.


12.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1000kHz. VBW = 1000kHz , Span = 4MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section
Submit this plot.


12.2 Test Result:

Test Channel	Separation (MHz)	Result
Low	2.06	PASS
Middle	2.06	PASS
High	2.06	PASS

Test result plot as follows:




Date: 20.MAY.2013 22:05:04



Date: 20.MAY.2013 22:05:41

High Channel



Date: 20.MAY.2013 22:06:18

14 Dwell Time

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	DA 00-705
Test Limit:	Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Mode:	Test in hopping transmitting operating mode.

14.1 Test Procedure:

- 1.Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2.Set spectrum analyzer span = 0. centered on a hopping channel;
- 3.Set RBW = 1MHz and VBW = 1MHz.Sweep = as necessary to capture the entire dwell time per hopping channel.
- 4.Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

14.2 Test Result:

The test period: $T = 0.4(s) * 39 = 15.6 (s)$

So, the Dwell Time can be calculated as follows:

Low channel: Dwell Time = $15(\text{times})/8(s) * 0.212(\text{ms}) * 15.6(s) = 0.0062(s)$


Middle channel: Dwell Time = $15(\text{times})/8(s) * 0.216(\text{ms}) * 15.6(s) = 0.0063(s)$

High channel: Dwell Time = $15(\text{times})/8(s) * 0.244(\text{ms}) * 15.6(s) = 0.0071(s)$


Note : Mkr Delta is once pulse time.

Frequency	Mkr Delta(ms)	Dwell Time(s)	Limits(s)	Result
2402 MHz	0.212	0.0062	0.400	Pass
2440 MHz	0.216	0.0063	0.400	Pass
2478 MHz	0.244	0.0071	0.400	Pass

Low Channel




Date: 20.MAY.2013 23:08:14




Date: 20.MAY.2013 22:29:36

Middle Channel




Date: 20.MAY.2013 23:10:00




Date: 20.MAY.2013 22:30:28

High Channel



Date: 20.MAY.2013 23:17:50



Date: 20.MAY.2013 22:30:55

15 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has a permanent antenna, fulfill the requirement of this section.

16 RF Exposure

Test Requirement: FCC Part 1.1307

Test Mode: The EUT work in test mode(Tx).

16.1 Requirments:

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

16.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

16.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the used antenna, the RF power density can be obtained

Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1.585	15.50	35.481	0.1119	1

17 Photographs – Test Setup

17.1 Photograph – Radiation Spurious Emission Test Setup

Below 30MHz



30MHz-1GHz



Above 1GHz



17.2 Photograph – Conducted Emission Test Setup



18 Photographs - Constructional Details

18.1 External View

















18.2 EUT - Internal View















19 FCC Label

FCC Label Sample for model: CA530

FCC ID: SJ8-CA530

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Label Location for model: CA530

The Label must not be a stick-on paper. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

FCC ID: SJ8-CA530
This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



=End of report=