

TEST REPORT

Reference No...... : WTS15S0628933E
FCC ID : SJ8-M742
Applicant..... : RDI Technology (Shenzhen) Co., Ltd.
Address..... : Building C1, Xintang Industrial Park East Baishixia, Fuyong, Baoan, Shenzhen, PRC.
Manufacturer : The same as above.
Address..... : The same as above.
Product Name..... : Digital Wireless Monitor
Model No...... : M742
Standards : FCC CFR47 Part 15 Section 15.249: 2014
Date of Receipt sample : Jun. 26, 2015
Date of Test : Jun. 29 – Jul. 15, 2015
Date of Issue..... : Jul. 21, 2015
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China
Tel :+86-755-83551033
Fax:+86-755-83552400

Compiled by:



Zero Zhou / Project Engineer

Approved by:



Philo Zhong / Manager

2 Test Summary

Test Items	Test Requirement	Result
Conducted Emissions	15.207	PASS
Radiated Emission	15.249(a) 15.209 15.205(a)	PASS
Periodic Operation	15.35(c)	PASS
Outside of Band Emission	15.249 15.205 15.209	PASS
20dB Bandwidth	15:215(c)	PASS
Antenna Requirement	15.203	PASS

3 Contents

	Page
1 COVER PAGE.....	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF E.U.T.....	4
4.2 DETAILS OF E.U.T.....	4
4.3 TEST FACILITY	4
5 EQUIPMENT USED DURING TEST	5
5.1 EQUIPMENTS LIST	5
5.2 MEASUREMENT UNCERTAINTY.....	5
5.3 TEST EQUIPMENT CALIBRATION.....	5
6 CONDUCTED EMISSION	6
6.1 E.U.T. OPERATION.....	6
6.2 EUT SETUP	6
6.3 MEASUREMENT DESCRIPTION	6
6.4 TEST RESULT	7
7 RADIATION EMISSION TEST	9
7.1 EUT OPERATION.....	9
7.2 TEST SETUP	10
7.3 SPECTRUM ANALYZER SETUP.....	11
7.4 TEST PROCEDURE.....	12
7.5 TEST RESULT	13
8 PERIODIC OPERATION	14
9 OUTSIDE OF BAND EMISSION.....	15
9.1 TEST PROCEDURE.....	15
9.2 TEST RESULT	15
10 20 DB BANDWIDTH MEASUREMENT	16
10.1 TEST PROCEDURE.....	16
10.2 TEST RESULT	16
11 ANTENNA REQUIREMENT	17
12 PHOTOGRAPHS – MODEL M742 TEST SETUP.....	18
12.1 PHOTOGRAPH – CONDUCTED EMISSION TEST SETUP AT TEST SITE 1#.....	18
12.2 PHOTOGRAPH – RADIATION SPURIOUS EMISSION TEST SETUP	18
13 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS.....	20
13.1 MODEL M742 EXTERNAL VIEW.....	20
13.2 MODEL M742 INTERNAL VIEW	25

4 General Information

4.1 General Description of E.U.T.

Product Name	: Digital Wireless Monitor
Model No.	: M742
Model Differences	: N/A
Type of Modulation	: FSK
Frequency Range	: 915MHz
The Lowest Oscillator	: 32.768kHz
Antenna installation	: monopole antenna

4.2 Details of E.U.T.

Technical Data	: DC 5V, 2A powered by adapter (Adapter Input: 100-240V~50/60Hz, 500mA)
----------------	--

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **Industry Canada (IC) Registration No.: 11464A**
The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.
- **FCC – Registration No.: 934118**
Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

4.3.1 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test mode	Lower channel	Middle channel	Upper channel
Transmitting	MHz	915MHz	MHz

5 Equipment Used during Test

5.1 Equipments List

3m Semi-anechoic Chamber for Radiation						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	836079/035	May-07-2015	May-06-2016
2	EMI Test Receiver	R&S	ESVB	825471/005	May-07-2015	May-06-2016
3	Pre-amplifier	Agilent	8447F	3113A06717	May-07-2015	May-06-2016
4	Pre-amplifier	Compliance Direction	PAP-0118	24002	May-07-2015	May-06-2016
5	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	Apr-20-2015	Apr-19-2016
6	Horn Antenna	ETS	3117	00086197	Apr-20-2015	Apr-19-2016
7	Horn Antenna	ETS	3116B	00088203	Apr-20-2015	Apr-19-2016
8	Loop Antenna	SCHWARZECK	HFRA 5165	9365	Apr-20-2015	Apr-19-2016

5.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)

5.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.4:2014
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth)

6.1 E.U.T. Operation

Operating Environment :


Temperature:	25.5 °C
Humidity:	51 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.

6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.4.




6.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


6.4 Test Result

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.3820	34.49	10.17	44.66	58.23	-13.57	QP	
2	0.3820	27.37	10.17	37.54	48.23	-10.69	AVG	
3	0.4340	29.62	10.18	39.80	57.18	-17.38	QP	
4	0.4340	22.69	10.18	32.87	47.18	-14.31	AVG	
5	0.5860	30.44	10.20	40.64	56.00	-15.36	QP	
6	0.5860	22.97	10.20	33.17	46.00	-12.83	AVG	
7	0.7220	29.48	10.21	39.69	56.00	-16.31	QP	
8	0.7220	20.59	10.21	30.80	46.00	-15.20	AVG	
9	0.7980	29.74	10.21	39.95	56.00	-16.05	QP	
10	0.7980	21.48	10.21	31.69	46.00	-14.31	AVG	
11	0.9140	26.73	10.22	36.95	56.00	-19.05	QP	
12	0.9140	18.44	10.22	28.66	46.00	-17.34	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.3780	32.83	10.17	43.00	58.32	-15.32	QP	
2	0.3780	24.36	10.17	34.53	48.32	-13.79	AVG	
3	0.4420	28.87	10.18	39.05	57.02	-17.97	QP	
4	0.4420	20.84	10.18	31.02	47.02	-16.00	AVG	
5	0.5260	26.25	10.19	36.44	56.00	-19.56	QP	
6	0.5260	17.63	10.19	27.82	46.00	-18.18	AVG	
7	0.6580	29.13	10.21	39.34	56.00	-16.66	QP	
8	0.6580	20.40	10.21	30.61	46.00	-15.39	AVG	
9	0.6900	27.53	10.21	37.74	56.00	-18.26	QP	
10	0.6900	18.66	10.21	28.87	46.00	-17.13	AVG	
11	0.8020	27.79	10.21	38.00	56.00	-18.00	QP	
12	0.8020	19.15	10.21	29.36	46.00	-16.64	AVG	

7 Radiation Emission Test

Test Requirement: FCC Part15 Paragraph 15.249

Test Method: ANSI 63.4: 2014

Measurement Distance: 3m

Test Result: PASS

15.249(a)Limit:

Fundamental frequency	Field strength of fundamental		Field strength of harmonics	
	mV/m	dBuV/m	uV/m	dBuV/m
902-928 MHz	50	94	500	54
2400-2483.5 MHz	50	94	500	54
5725-5875 MHz	50	94	500	54
24.0-24.25 GHz	250	108	2500	68

15.209 Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

Note: RF Voltage(dBuV)=20 log₁₀ RF Voltage(uV)

7.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

Sweep SpeedAuto
 IF Bandwidth.....10kHz
 Video Bandwidth10kHz
 Resolution Bandwidth10kHz

30MHz ~ 1GHz

Sweep SpeedAuto
 DetectorPK
 Resolution Bandwidth.....100kHz
 Video Bandwidth300kHz

Above 1GHz

Sweep SpeedAuto
 DetectorPK
 Resolution Bandwidth.....1MHz
 Video Bandwidth3MHz
 DetectorAve.
 Resolution Bandwidth.....1MHz
 Video Bandwidth10Hz

7.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane; For above 1GHz, the EUT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

7.5 Test Result

AV = Peak +20Log10(duty cycle) =PK+XX [refer to section 8 for more detail]

Test Frequency :Below 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 18GHz

channel Transmitting

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.249/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)
302.56	40.17	QP	309	1.7	V	-11.40	28.77	40.00	-11.23
915.00	85.17	PK	64	1.2	H	0.97	86.14	114.00	-27.86
915.00	91.16	PK	220	1.1	V	0.97	92.13	114.00	-21.87
1830.00	72.14	PK	140	1.3	H	-13.21	58.93	74.00	-15.07
1830.00	60.15	PK	107	1.6	V	-13.21	46.94	74.00	-27.06
2745.00	57.65	PK	85	1.2	H	-13.08	44.57	74.00	-29.43
2745.00	56.63	PK	169	1.7	V	-13.08	43.55	74.00	-30.45
3660.00	54.21	PK	350	1.8	H	-9.08	45.13	74.00	-28.87
3660.00	55.66	PK	17	1.2	V	-9.08	46.58	74.00	-27.42

Frequency	PK	Turn table Angle	RX Antenna		Duty cycle Factor	AV	FCC Part 15.249/209/205	
			Height	Polar			Limit	Margin
(MHz)	(dBμV/m)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
915.00	86.14	64	1.2	H	-2.08	84.06	94.00	-9.94
915.00	92.13	220	1.1	V	-2.08	90.05	94.00	-3.95
1830.00	52.93	140	1.3	H	-2.08	50.85	54.00	-3.15
1830.00	46.94	107	1.6	V	-2.08	44.86	54.00	-9.14
2745.00	44.57	85	1.2	H	-2.08	42.49	54.00	-11.51
2745.00	43.55	169	1.7	V	-2.08	41.47	54.00	-12.53
3660.00	45.13	350	1.8	H	-2.08	43.05	54.00	-10.95
3660.00	46.58	17	1.2	V	-2.08	44.50	54.00	-9.50

Test Frequency :From 18GHz to 25GHz

The measurements were more than 20 dB below the limit and not reported.

Waltek Services (Shenzhen) Co.,Ltd.

<http://www.waltek.com.cn>

8 Periodic Operation

The duty cycle was determined by the following equation:

To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

$$\text{Duty Cycle(\%)} = \frac{\text{Total On interval in a complete pulse train}}{\text{Length of a complete pulse train}} * \%$$


$$\text{Duty Cycle Correction Factor(dB)} = 20 * \text{Log}_{10}(\text{Duty Cycle(\%)})$$

Total transmission time(ms)	0.508
Length of a complete transmission period(ms)	0.4
Duty Cycle(%)	78.7
Duty Cycle Correction Factor(dB)	-2.08

Refer to the duty cycle plot (as below), This device meets the FCC requirement.

Length of a complete pulse train:

Remark: FCC part15.35(c) required that a complete pulse train is more than 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.




9 Outside of Band Emission

Test Requirement:	15.249(d):Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.
Test Method:	ANSI C63.10:2013
Test Mode:	Transmitting

9.1 Test Procedure

Refer to section 7.4 of this test report.

9.2 Test Result



10 20 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.215(c)
 Test Method: ANSI C63.10:2013
 Test Mode: Transmitting

10.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

10.2 Test Result

Test Channel	Bandwidth
FSK	541kHz

Test plots

Low Channel



11 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has a Monopole Antenna, fulfil the requirement of this section.

12 Photographs – Model M742 Test Setup

12.1 Photograph – Conducted Emission Test Setup at Test Site 1#




12.2 Photograph – Radiation Spurious Emission Test Setup


Below 30MHz at Test Site



30MHz-1GHz at Test Site



Above 1GHz at Test Site




13 Photographs - Constructional Details

13.1 Model M742 External View




















13.2 Model M742 Internal View











===== End of Report =====