
FCC Test Report

Report No.: AGC01284230402FE10

FCC ID : SK4BP-268V

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : DMR digital and analog VHF portable Radio

BRAND NAME : BridgeCom

MODEL NAME : BP-268V

APPLICANT : BridgeIP, LLC

DATE OF ISSUE : Apr. 18, 2023

STANDARD(S) : FCC Part 90 Rules

REPORT VERSION : V 1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Apr. 18, 2023	Valid	Initial Release

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	7
2.3 RELATED SUBMITTAL(S) / GRANT (S)	8
2.4 TEST METHODOLOGY	8
2.5 CALCULATION OF EMISSION INDICATORS	8
2.6 SPECIAL ACCESSORIES	8
2.7 EQUIPMENT MODIFICATIONS	8
3. TEST ENVIRONMENT	9
3.1 ADDRESS OF THE TEST LABORATORY	9
3.2 TEST FACILITY	9
3.3 ENVIRONMENTAL CONDITIONS	9
3.4 MEASUREMENT UNCERTAINTY	10
3.5 LIST OF EQUIPMENTS USED	11
4.SYSTEM TEST CONFIGURATION	12
4.1 EUT CONFIGURATION	12
4.2 EUT EXERCISE	12
4.3 CONFIGURATION OF TESTED SYSTEM	12
4.4 EQUIPMENT USED IN TESTED SYSTEM	12
4.5 SUMMARY OF TEST RESULTS	13
5.DESCRPTION OF TEST MODES	14
6.FREQUENCY TOLERANCE	15
6.1 PROVISIONS APPLICABLE	15
6.2 MEASUREMENT PROCEDURE	15
6.3 MEASUREMENT SETUP	15
6.4 MEASUREMENT RESULTS	16
7. EMISSION BANDWIDTH	17
7.1 PROVISIONS APPLICABLE	18
7.2 MEASUREMENT PROCEDURE	18
7.3 MEASUREMENT SETUP	18
7.4 MEASUREMENT RESULTS	19
8. SPURIOUS RADIATED EMISSION	22
8.1 PROVISIONS APPLICABLE	22
8.2 MEASUREMENT PROCEDURE	22

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.3 MEASUREMENT SETUP	23
8.4 MEASUREMENT RESULTS.....	23
8.5 EMISSION MASK PLOT	31
9.MODULATION CHARACTERISTICS	34
9.1 PROVISIONS APPLICABLE.....	34
9.2 MEASUREMENT METHOD	34
9.3 MEASUREMENT SETUP	34
9.4 MEASUREMENT RESULTS.....	35
10. MAXIMUM TRANSMITTER POWER	37
10.1 PROVISIONS APPLICABLE.....	37
10.2 MEASUREMENT METHOD	37
10.3 MEASUREMENT METHOD	37
10.4 MEASUREMENT RESULTS	37
11. SPURIOUS EMISSION ON ANTENNA PORT	42
11.1 PROVISIONS APPLICABLE	42
11.2 MEASUREMENT METHOD.....	42
11.3 MEASUREMENT SETUP	42
11.4 MEASUREMENT RESULTS.....	43
12.TRANSMITTER FREQUENCY BEHAVIOR.....	47
12.1 PROVISIONS APPLICABLE.....	47
13.2 MEASUREMENT SETUP.....	47
12.3 MEASUREMENT METHOD	48
12.4 MEASURET RESULTS.....	50
13. AUDIO LOW PASS FILTER RESPONSE	51
13.1 PROVISIONS APPLICABLE.....	51
13.2 MEASUREMENT METHOD	52
13.3 MEASUREMENT SETUP.....	52
13.4 MEASURET RESULTS.....	53
APPENDIX I: PHOTOGRAPHS OF TEST SETUP	54
APPENDIX II: PHOTOGRAPHS OF TEST EUT	54

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


1. GENERAL INFORMATION

Applicant	BridgeIP, LLC
Address	113 S. Bridge St. Smithville, MO 64089, United States
Manufacturer	Qixiang Electron Science & Technology Co., Ltd.
Address	Qixiang Building, Tangxi Industrial Zone, Luojiang District, Quanzhou, Fujian, China
Factory	Qixiang Electron Science & Technology Co., Ltd.
Address	Qixiang Building, Tangxi Industrial Zone, Luojiang District, Quanzhou, Fujian, China
Product Designation	DMR digital and analog VHF portable Radio
Brand Name	BridgeCom
Test Model	BP-268V
Deviation from Standard	None
Date of receipt of test item	Apr. 03, 2023
Date of Test	Apr. 03, 2023~Apr. 18, 2023
Test Result	Pass

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA-603-E-2016. The sample tested as described in this report is in compliance with the FCC Rules Part 90. The test results of this report relate only to the tested sample identified in this report.

Prepared By



Bibo Zhang
(Project Engineer)

Apr. 18, 2023

Reviewed By



Calvin Liu
(Reviewer)

Apr. 18, 2023

Approved By



Max Zhang
Authorized Officer

Apr. 18, 2023

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

2. PRODUCT INFORMATION

2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	VER6.1	
Software Version	V1	
Power Supply	DC 7.4V 2600mAh by battery	
Communication Type	Voice / Data	
Operation Frequency Range	From 136MHz to 174MHz	
Modulation Type	Analog Voice:	FM
	Digital (Voice + Data):	4FSK
Digital Type	DMR	
Channel Separation	Analog Voice:	12.5 kHz
	Digital (Voice + Data):	12.5 kHz
Support Data Rate	9600bps	
Emission Designator	Analog Voice:	11K0F3E
	Digital (Voice + Data):	<input checked="" type="checkbox"/> VHF:7K63F1D-7W-12.5kHz <input checked="" type="checkbox"/> VHF:7K63F1D-1W-12.5kHz <input checked="" type="checkbox"/> VHF:7K63F1W-7W-12.5kHz <input checked="" type="checkbox"/> VHF:7K63F1W-1W-12.5kHz
Rated Output Power	7W/1W (It was fixed by the manufacturer, any individual can't arbitrarily change it.)	
Maximum Transmitter Power	38.10dBm(7W)	29.92dBm(1W)
Antenna Designation	Detachable Antenna	
Antenna Gain	1.8dBi	
Frequency Tolerance	1.094ppm	

Note:

1. The product has the same digital working characters when operating in both two digitized voice/data mode. So only one set of test results for digital modulation modes are provided in this test report.
2. This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth. DMR interphone's bandwidth is 12.5 kHz, and it has a double time slot, one is the speech time slot, one is the data time slot, just language sequence is satisfied with 4800 bps/6.25 kHz BW.
3. The actual working frequency band of the device is VHF: 136-174MHz. According to the frequency division requirements of KDB634817 and the federal frequency allocation requirements, the working frequency band that the device needs to meet is VHF: 136-174MHz

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

2.2 TEST FREQUENCY LIST

Operation mode	Channel Separation	Operation Frequency Range	Test channel	Test Frequency
Analog/ Digital	12.5 kHz	136-174MHz	Bottom	136.025 MHz
	12.5 kHz	136-174MHz	Middle	155.7525 MHz
	12.5 kHz	136-174MHz	Top	173.975 MHz

Note:

In section KDB 634817 D01 Sections II) (f) (1) and (2):

Test at least one frequency in each band for each rule part applied under and ensure the device is capable of operating on the frequency under each rule part. This requirement may result in testing on multiple frequencies. Testing on one frequency may be acceptable if multiple listed bands for a rule part with a continuous frequency range are split to remove a conflict with other rules and the technical requirements in the split bands are the same. Additional requirements for RF exposure may apply.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: **SK4BP-268V**, filing to comply with Part 2, Part 90 of the Federal Communication Commission rules.

2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 90	Private Land Mobile Radio Services
2	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
3	ANSI TIA-102.CAAA-E	Project 25 Digital C4FM/CQPSK Transceiver Measurement Methods
4	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
5	KDB 971168 D01	KDB 971168 D01 Power Meas License Digital Systems v03r01
6	KDB 579009 D03	KDB 579009 D03 Applications Part 90 Refarming Bands v01
7	KDB 634817 D01	KDB 634817 D01 Freq Range Listing for Grants v04r01

2.5 CALCULATION OF EMISSION INDICATORS

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

For FM Mode (ChannelSpacing: 12.5kHz)

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

$$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = 11K0$$

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator 7K60F1D and 7K60F1W

The 99% energy rule was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz.

F1D and F1W portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1W.

2.6 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

2.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

3. TEST ENVIRONMENT

3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS
Temperature range (°C)	15 - 35	-20 - 50
Relative humidity range	20 % - 75 %	20 % - 75 %
Pressure range (kPa)	86 - 106	86 - 106
Power supply	DC 7.4V	LV:DC 6.29V/HV: DC 8.51V

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Test Items	Measurement Uncertainty
Frequency stability	$\pm 0.5\%$
Transmitter power conducted	$\pm 0.8\text{dB}$
Transmitter power Radiated	$\pm 1.3\text{dB}$
Conducted spurious emission 9kHz-40 GHz	$\pm 2.7\text{dB}$
Conducted Emission	$\pm 3.2\text{ dB}$
Radiated Emission below 1GHz	$\pm 3.9\text{ dB}$
Radiated Emission above 1GHz	$\pm 4.8\text{ dB}$
Occupied Channel Bandwidth	$\pm 2\%$
FM deviation	$\pm 2\%$
Audio level	$\pm 0.98\text{dB}$
Low Pass Filter Response	$\pm 0.65\text{dB}$
Modulation Limiting	0.42 %
Transient Frequency Behavior	6.8 %

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
EXA Signal Analyzer	Aglient	N9020A	MY53300860	Jun. 08, 2022	Jun. 07, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
preamplifier	ChengYi	EMC184045SE	980508	Oct. 29, 2021	Oct. 28, 2023
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun. 05, 2022	Jun. 04, 2023
HORN ANTENNA	EM	EM-AH-10180	/	Feb. 22, 2023	Feb. 21, 2024
SIGNAL GENERATOR	AGILENT	E4421B	MY43351603	Mar. 04 2022	Mar. 03, 2023
SIGNAL GENERATOR	R&S	SMT03	A0304261	Jun. 05, 2022	Jun. 04, 2023
ANTENNA	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 08, 2021	Jan. 07, 2023
ANTENNA	SCHWARZBECK	VULB9168	D69250	Apr. 28, 2021	Apr. 27, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	May 22, 2022	May 21, 2024
Modulation Domain Analyzer	HP	53310A	3121A02467	Jun. 08, 2022	Jun. 07, 2024
Small environmental tester	ESPEC	SH-242	93008290	Aug. 03, 2022	Aug. 02, 2024
RF Communication Test Set	HP	8920B	US35010161	Aug. 03, 2022	Aug. 02, 2023
Attenuator	Weinachel Corp	58-30-33	ML030	Oct. 24, 2021	Oct. 23, 2022
RF Cable	R&S	1#	--	Each time	N/A
RF Cable	R&S	2#	--	Each time	N/A
Fliter-VHF	Microwave	N26460M1	498703	May 07, 2022	May 06, 2023

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4.SYSTEM TEST CONFIGURATION

4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

- ☐ Test Accessories Come From The Laboratory
☒ Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	ID or Specification	Remark
1	DMR digital and analog VHF portable Radio	BP-268V	SK4BP-268V	EUT
2	Charger	QBC-55L	Input: DC 12V 0.5A Output: DC 8.4V 0.5A	AE
3	Battery	QB-51HL	DC 7.4V 2600mAh	AE
4	Adapter	SAW06F-120-050 0UD	Input: AC 100-240V 50~60Hz, 0.25A Output: DC 12V 0.5A	AE
5	Antenna	N/A	N/A	AE
6	Back clip	N/A	N/A	AE
7	Lanyard	N/A	N/A	AE

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4.5 SUMMARY OF TEST RESULTS

Item	FCC Rules	Description Of Test	Result
1	FCC PART 90	Antenna Equipment	Pass
2	§90.205& 2.1046	Maximum Transmitter Power	Pass
3	§90.207& 2.1047	Modulation Characteristic	Pass
4	§2.1047	Audio Low Pass Filter Response	Pass
5	§90.209& 2.1049	Occupied Bandwidth	Pass
6	§90.210& 2.1049	Emission Mask	Pass
7	§90.213& 2.1055	Frequency Tolerance	Pass
8	§90.214	Transmitter Frequency Behavior	Pass
9	§90.210& 2.1051	Spurious Emission on Antenna Port	Pass
10	§90.210& 2.1053	Spurious Radiated Emission	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

5.DESCRPTION OF TEST MODES

The EUT (**DMR digital and analog VHF portable Radio**) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation.

NO.	TEST MODE DESCRIPTION	CHANNEL SEPARATION
1	TX Bottom channel-VHF	12.5 kHz
2	TX Middle channel-VHF	12.5 kHz
3	TX Middle channel-VHF	12.5 kHz
4	TX Top channel-VHF	12.5 kHz

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. The battery is full-charged during the test.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
5. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

6.FREQUENCY TOLERANCE

6.1 PROVISIONS APPLICABLE

- According to FCC §2.1055,§90.213, the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$ centigrade.
- According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
- According to FCC Part 90 Section 90.213, the frequency tolerance must be maintained within 0.00025% for 12.5 kHz channel separation and 0.0001% for 6.25 kHz channel separation.

6.2 MEASUREMENT PROCEDURE


6.2.1 Frequency stability versus environmental temperature

- Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
- Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1kHz and Video Resolution Bandwidth to 1kHz and Frequency Span to 50kHz. Record this frequency as reference frequency.
- Set the temperature of chamber to 50°C . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
- Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

- Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15°C to 25°C . Otherwise, an environment chamber set for a temperature of 20°C shall be used. The EUT shall be powered by DC 7.4V.
- Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 kHz and Video Resolution Bandwidth to 1kHz. Record this frequency as reference frequency.
- Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

6.4 MEASUREMENT RESULTS

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For VHF-7W						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		136.025	155.7525	173.975		
7.40	-30	0.676	0.653	0.921	2.5	Pass
	-20	0.710	0.744	0.980		
	-10	0.988	0.715	0.879		
	0	0.796	1.027	1.030		
	10	1.002	0.684	0.802		
	20	0.793	0.781	0.592		
	30	0.618	1.035	0.939		
	40	0.690	0.739	0.682		
	50	1.055	0.840	0.957		
8.51	20	0.582	0.701	0.761		
6.29	20	1.020	0.721	0.727		

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For VHF-1W						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		136.025	155.7525	173.975		
7.40	-30	0.888	0.951	0.792	2.5	Pass
	-20	0.504	0.628	1.043		
	-10	0.726	1.061	0.867		
	0	0.750	1.047	0.844		
	10	0.941	0.919	0.745		
	20	0.997	0.978	0.931		
	30	0.650	0.757	0.783		
	40	0.527	0.947	0.751		
	50	0.744	0.744	1.000		
8.51	20	0.961	0.822	0.612		
6.29	20	1.016	0.828	1.071		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For VHF-7W						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		136.025	155.7525	173.975		
7.40	-30	0.626	1.009	0.664	2.5	Pass
	-20	1.069	0.593	0.706		
	-10	0.914	1.069	0.780		
	0	0.702	0.904	0.892		
	10	0.647	0.964	1.094		
	20	1.055	0.870	0.879		
	30	0.859	0.798	0.598		
	40	0.598	0.786	1.099		
	50	0.701	0.981	0.531		
8.51	20	0.918	0.918	0.903		
6.29	20	0.640	0.849	1.041		

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For VHF-1W						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		136.025	155.7525	173.975		
7.40	-30	0.569	0.915	0.864	2.5	Pass
	-20	0.619	1.085	0.769		
	-10	1.088	0.799	0.788		
	0	0.723	1.033	0.585		
	10	0.907	0.970	0.803		
	20	0.966	0.588	1.050		
	30	0.993	0.713	1.044		
	40	0.856	0.948	0.536		
	50	0.650	0.739	0.537		
8.51	20	0.604	0.512	0.975		
6.29	20	0.562	0.798	0.913		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

7. EMISSION BANDWIDTH

7.1 PROVISIONS APPLICABLE

FCC Part 90.209 & FCC Part 2.1049:

The authorized bandwidth shall be 11.25 kHz for 12.5 kHz channel separation and 6 kHz for 6.25 kHz channel separation.

7.2 MEASUREMENT PROCEDURE

1.The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB greater than that necessary to produce 50% of rated system deviation.

Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).

2.Spectrum set as follow:


Centre frequency = fundamental frequency, span=50kHz for 12.5kHz channel spacing, RBW=100Hz, VBW=300Hz, Sweep = auto,

Detector function = peak, Trace = max hold

3.Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.

4.Measure and record the results in the test report.

7.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

7.4 MEASUREMENT RESULTS

Measurement Result of VHF-Analog Modulation-7W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
136.025 MHz	9.847 kHz	10.14 kHz	11.25 kHz	Pass
155.7525 MHz	9.856 kHz	10.14 kHz	11.25 kHz	Pass
173.975 MHz	9.859 kHz	10.14 kHz	11.25 kHz	Pass


Measurement Result of VHF-Analog Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
136.025 MHz	9.848 kHz	10.14kHz	11.25 kHz	Pass
155.7525 MHz	9.857 kHz	10.14 kHz	11.25 kHz	Pass
173.975 MHz	9.859 kHz	10.14 kHz	11.25 kHz	Pass

Measurement Result of VHF-Digital Modulation-7W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
136.025 MHz	7.322 kHz	9.580 kHz	11.25 kHz	Pass
155.7525 MHz	7.630 kHz	9.797 kHz	11.25 kHz	Pass
173.975 MHz	7.333 kHz	9.386 kHz	11.25 kHz	Pass

Measurement Result of VHF- Digital Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
136.025 MHz	7.312 kHz	9.529 kHz	11.25 kHz	Pass
155.7525 MHz	7.496 kHz	9.745 kHz	11.25 kHz	Pass
173.975 MHz	7.522 kHz	10.170 kHz	11.25 kHz	Pass


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test plot as follows:




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


12.5kHz, 4FSK Modulation:136.025MHz-7W




12.5kHz, 4FSK Modulation:155.7525MHz-7W




12.5kHz, 4FSK Modulation:173.975MHz-7W




12.5kHz, 4FSK Modulation:136.025MHz-1W



12.5kHz, 4FSK Modulation:155.7525MHz-1W



12.5kHz, 4FSK Modulation:173.975MHz-1W



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8. SPURIOUS RADIATED EMISSION

8.1 PROVISIONS APPLICABLE

According to FCC §2.1053 and §90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with each channel separation.

Emission Mask D -for 12.5 kHz Channel Separation:

- (1) On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in kHz) f_0 of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in kHz) f_0 of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is lesser attenuation.


8.2 MEASUREMENT PROCEDURE

- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- (8) The maximum signal level detected by the measuring receiver shall be noted.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization.
- (10) Replace the antenna with a proper Antenna (substitution antenna).
- (11) The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- (12) The substitution antenna shall be connected to a calibrated signal generator.
- (13) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- (14) The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- (15) The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- (16) The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- (17) The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.3 MEASUREMENT SETUP

Radiated Emissions 30MHz to 1GHz Test setup



Radiated Emissions Above 1GHz Test setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.4 MEASUREMENT RESULTS

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10 harmonic.

In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The "Read Value" is the spectrum reading of maximum power value.

The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.


$EIRP = \text{"Read Value"} + \text{Measured substitution value} + 2.15.$

Test limit calculation:

Preliminary calculation	Final Result
At least $50 + 10 \log(P) = 50 + 10 \log(7) = 58.45$ (dB)	Limit=P- Preliminary calculation= $38.45 - 58.45 = -20$ dBm
At least $50 + 10 \log(P) = 50 + 10 \log(1) = 50.00$ (dB)	Limit=P- Preliminary calculation= $30.00 - 50.00 = -20$ dBm


Note: The report only reflects high-power test data as the worst.

Test Mode:	TX:136.025MHz-4FSK	Polarity:	Horizontal
------------	--------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	271.53	-58.88	-25.82	-20.00	5.82	33.06	288	Horizontal
2	408.3	-72.59	-38.01	-20.00	18.01	34.58	84	Horizontal
3	544.1	-79.23	-41.35	-20.00	21.35	37.88	101	Horizontal
4	679.9	-80.33	-40.26	-20.00	20.26	40.07	288	Horizontal
5	816.67	-87.74	-44.40	-20.00	24.40	43.34	351	Horizontal
6	2176.2926	-43.90	-44.06	-20.00	24.06	-0.16	145	Horizontal

Test Mode:	TX:136.025MHz-4FSK	Polarity:	Vertical
------------	--------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	408.3	-72.52	-37.41	-20.00	17.41	35.11	357	Vertical
2	544.1	-76.01	-38.60	-20.00	18.60	37.41	37	Vertical
3	679.9	-76.66	-36.54	-20.00	16.54	40.12	1	Vertical
4	748.77	-78.39	-36.99	-20.00	16.99	41.40	17	Vertical
5	1224.4474	-37.28	-36.95	-20.00	16.95	0.33	192	Vertical
6	1360.7611	-37.25	-36.01	-20.00	16.01	1.24	174	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:155.7525MHz-4FSK	Polarity:	Horizontal
------------	---------------------	-----------	------------


NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	311.3	-68.53	-36.29	-20.00	16.29	32.24	277	Horizontal
2	467.47	-80.77	-45.06	-20.00	25.06	35.71	277	Horizontal
3	623.64	-75.59	-35.68	-20.00	15.68	39.91	351	Horizontal
4	778.84	-84.90	-42.18	-20.00	22.18	42.72	277	Horizontal
5	1401.8902	-37.33	-40.75	-20.00	20.75	-3.42	81	Horizontal
6	1558.1808	-40.62	-43.39	-20.00	23.39	-2.77	9	Horizontal

Test Mode:	TX:155.7525MHz-4FSK	Polarity:	Vertical
------------	---------------------	-----------	----------

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	467.47	-73.80	-37.87	-20.00	17.87	35.93	17	Vertical
2	623.64	-70.16	-31.03	-20.00	11.03	39.13	37	Vertical
3	1090.484	-37.77	-38.33	-20.00	18.33	-0.56	161	Vertical
4	1246.7747	-36.75	-36.27	-20.00	16.27	0.48	189	Vertical
5	1401.8902	-29.79	-28.28	-20.00	8.28	1.51	189	Vertical
6	1557.0057	-38.13	-36.17	-20.00	16.17	1.96	171	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:173.975MHz-4FSK	Polarity:	Horizontal
------------	--------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	348.16	-69.90	-36.76	-20.00	16.76	33.14	351	Horizontal
2	521.79	-72.70	-35.60	-20.00	15.60	37.10	351	Horizontal
3	696.39	-70.89	-30.78	-20.00	10.78	40.11	288	Horizontal
4	870.02	-79.64	-36.56	-20.00	16.56	43.08	252	Horizontal
5	1392.4892	-34.19	-37.63	-20.00	17.63	-3.44	234	Horizontal
6	1566.4066	-35.77	-38.48	-20.00	18.48	-2.71	0	Horizontal


Test Mode:	TX:173.975MHz-4FSK	Polarity:	Vertical
------------	--------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	348.16	-70.56	-37.67	-20.00	17.67	32.89	9	Vertical
2	521.79	-70.96	-34.06	-20.00	14.06	36.90	360	Vertical
3	696.39	-67.77	-27.36	-20.00	7.36	40.41	9	Vertical
4	870.02	-71.79	-28.76	-20.00	8.76	43.03	220	Vertical
5	1392.4892	-34.89	-33.44	-20.00	13.44	1.45	259	Vertical
6	1566.4066	-35.53	-33.60	-20.00	13.60	1.93	9	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:136.025MHz-FM	Polarity:	Horizontal
------------	------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	271.53	-61.54	-28.48	-20.00	8.48	33.06	297	Horizontal
2	408.3	-73.05	-38.47	-20.00	18.47	34.58	83	Horizontal
3	544.1	-78.97	-41.09	-20.00	21.09	37.88	112	Horizontal
4	679.9	-81.04	-40.97	-20.00	20.97	40.07	287	Horizontal
5	816.67	-89.85	-46.51	-20.00	26.51	43.34	351	Horizontal
6	5812.1062	-51.18	-41.09	-20.00	21.09	10.09	324	Horizontal

Test Mode:	TX:136.025MHz-FM	Polarity:	Vertical
------------	------------------	-----------	----------




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	271.53	-65.08	-34.90	-20.00	14.90	30.18	9	Vertical
2	408.3	-72.43	-37.32	-20.00	17.32	35.11	360	Vertical
3	544.1	-75.04	-37.63	-20.00	17.63	37.41	19	Vertical
4	679.9	-76.38	-36.26	-20.00	16.26	40.12	19	Vertical
5	816.67	-85.83	-43.30	-20.00	23.30	42.53	207	Vertical
6	1497.0747	-47.45	-45.31	-20.00	25.31	2.14	9	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:155.7525MHz-FM	Polarity:	Horizontal
------------	-------------------	-----------	------------

FCC Part 90 OPER TX




— Limit ■ Final Test — Horizontal

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	311.3	-69.05	-36.81	-20.00	16.81	32.24	84	Horizontal
2	467.47	-81.12	-45.41	-20.00	25.41	35.71	269	Horizontal
3	623.64	-77.04	-37.13	-20.00	17.13	39.91	351	Horizontal
4	778.84	-86.11	-43.39	-20.00	23.39	42.72	269	Horizontal
5	935.01	-91.44	-47.74	-20.00	27.74	43.70	287	Horizontal
6	1401.8902	-39.32	-42.74	-20.00	22.74	-3.42	74	Horizontal

Test Mode:	TX:155.7525MHz-FM	Polarity:	Vertical
------------	-------------------	-----------	----------

FCC Part 90 OPER TX




— Limit ■ Final Test — Vertical

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	311.3	-78.41	-47.02	-20.00	27.02	31.39	176	Vertical
2	467.47	-75.53	-39.60	-20.00	19.60	35.93	19	Vertical
3	623.64	-71.22	-32.09	-20.00	12.09	39.13	19	Vertical
4	778.84	-82.81	-40.84	-20.00	20.84	41.97	9	Vertical
5	1401.8902	-38.69	-37.18	-20.00	17.18	1.51	96	Vertical
6	1558.1808	-41.51	-39.55	-20.00	19.55	1.96	19	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:173.975MHz-FM	Polarity:	Horizontal
------------	------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	348.16	-65.43	-32.29	-20.00	12.29	33.14	351	Horizontal
2	521.79	-74.10	-37.00	-20.00	17.00	37.10	249	Horizontal
3	696.39	-71.55	-31.44	-20.00	11.44	40.11	285	Horizontal
4	870.02	-80.83	-37.75	-20.00	17.75	43.08	259	Horizontal
5	1392.4892	-33.91	-37.35	-20.00	17.35	-3.44	249	Horizontal
6	1566.4066	-36.59	-39.30	-20.00	19.30	-2.71	6	Horizontal

Test Mode:	TX:173.975MHz-FM	Polarity:	Vertical
------------	------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	521.79	-70.76	-33.86	-20.00	13.86	36.90	19	Vertical
2	696.39	-68.70	-28.29	-20.00	8.29	40.41	19	Vertical
3	870.02	-72.66	-29.63	-20.00	9.63	43.03	214	Vertical
4	1043.4793	-36.69	-37.56	-20.00	17.56	-0.87	168	Vertical
5	1392.4892	-27.99	-26.54	-20.00	6.54	1.45	168	Vertical
6	1566.4066	-34.44	-32.51	-20.00	12.51	1.93	178	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


8.5 EMISSION MASK PLOT

The detailed procedure employed for Emission Mask measurements are specified as following:

-Connect the equipment as illustrated.


-Spectrum set as follow:

1. Centre frequency = fundamental frequency, Span=50kHz for 12.5kHz and 25kHz channel spacing, RBW=100Hz, VBW=300Hz for 12.5kHz, RBW=300Hz, VBW=1000Hz for 25kHz, Sweep = auto, Detector function = peak, Trace = max hold
2. Key the transmitter, and set the level of the unmodulated carrier to a fullscale reference line. This is the 0dB reference for the measurement.
3. Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation (Rated system deviation is 2.5 kHz for 12.5kHz channel spacing). The input level shall be established at the frequency of maximum response of the audio modulating circuit.
4. Transmitters employing digital modulation techniques that bypass the limiter and the audio low-pass filter shall be modulated as specified by the manufacturer.
5. Measure and record the results in the test report.




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test plot as follows:




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Emission Mask D@136.025MHz-7W-4FSK




Emission Mask D@155.7525MHz-7W-4FSK




Emission Mask D@173.975MHz-7W-4FSK




Emission Mask D@136.025MHz-1W-4FSK



Emission Mask D@155.7525MHz-1W-4FSK



Emission Mask D@173.975MHz-1W-4FSK



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9. MODULATION CHARACTERISTICS

9.1 PROVISIONS APPLICABLE

According to FCC§2.1047 and §90.207, for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

9.2 MEASUREMENT METHOD


9.2.1 Modulation Limit

- (1). Configure the EUT as shown in figure 1, adjust the audio input for 60% of rated system deviation at 1kHz using this level as a reference (0dB) and vary the input level from -20 to +20dB. Record the frequency deviation obtained as a function of the input level.
- (2). Repeat step 1 with input frequency changing to 300, 1000, 1500 and 3000Hz in sequence.

9.2.2 Audio Frequency Response

- (1). Configure the EUT as shown in figure 1.
- (2). Adjust the audio input for 20% of rated system deviation at 1 kHz using this level as a reference (0 dB).
- (3). Vary the Audio frequency from 100 Hz to 10 kHz and record the frequency deviation.
- (4). Audio Frequency Response = $20\log_{10} (\text{Deviation of test frequency} / \text{Deviation of 1 kHz reference})$.

9.3 MEASUREMENT SETUP




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9.4 MEASUREMENT RESULTS

(A). MODULATION LIMIT:

12.5kHz, Analog modulation, Assigned Frequency:136.025MHz				
Modulation Level (dB)	Peak Freq. Deviation At 300 Hz (kHz)	Peak Freq. Deviation At 1000 Hz (kHz)	Peak Freq. Deviation At 1500 Hz (kHz)	Peak Freq. Deviation At 3000 Hz (kHz)
-20	0.13	0.32	0.52	0.85
-15	0.26	0.54	0.88	1.12
-10	0.32	0.69	0.93	1.25
-5	0.48	0.71	1.02	1.34
0	0.56	0.82	1.11	1.41
+5	0.68	0.91	1.23	1.52
+10	0.72	1.03	1.25	1.55
+15	0.83	1.05	1.44	1.61
+20	0.79	1.01	1.35	1.58



Note: All the modes had been tested, but only the worst data recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

(B). AUDIO FREQUENCY RESPONSE:

12.5kHz, Analog modulation, Assigned Frequency:136.025MHz		
Frequency (Hz)	Deviation (kHz)	Audio Frequency Response(dB)
100	--	--
200	--	--
300	0.21	-12.54
400	0.29	-9.74
500	0.41	-6.73
600	0.49	-5.18
700	0.58	-3.72
800	0.66	-2.60
900	0.75	-1.49
1000	0.89	0.00
1200	0.91	0.19
1400	1.11	1.92
1600	1.23	2.81
1800	1.35	3.62
2000	1.52	4.65
2400	1.71	5.67
2500	1.82	6.21
2800	1.91	6.63
3000	2.11	7.50



Note: All the modes had been tested, but only the worst data recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

10. MAXIMUM TRANSMITTER POWER

10.1 PROVISIONS APPLICABLE

Per FCC §2.1046. § 90.205: Maximum ERP is dependent upon the station's antenna HAAT and required service area.

10.2 MEASUREMENT METHOD

The RF output of Two-way Radio was conducted to a spectrum analyzer through an appropriate attenuator. In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The "Read Value" is the spectrum reading of maximum power value.


The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum.

So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.

$EIRP = \text{"Read Value"} + \text{Measured substitution value} + 2.15.$

10.3 MEASUREMENT METHOD

☒ Conducted Output Power:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd



Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

☒ Effective Radiated Power:

Radiated Below 1GHz



Radiated Above 1 GHz



Any report having the AGCCert Stamp is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

10.4 MEASUREMENT RESULTS

Conducted Power Measurement Results			
Mode	Channel Separation	Test Channel	Measurement Result (dBm)
			For 38.45dBm(7W)
Analog +Voice	12.5 kHz	Bottom(136.025MHz)	38.10
		Middle(155.7525MHz)	37.95
		Top(173.975MHz)	37.99
Digital (Voice+Data)	12.5 kHz	Bottom(136.025MHz)	29.70
		Middle(155.7525MHz)	29.47
		Top(173.975MHz)	29.75

Conducted Power Measurement Results			
Mode	Channel Separation	Test Channel	Measurement Result (dBm)
			For 30.00dBm(1W)
Analog +Voice	12.5 kHz	Bottom(136.025MHz)	29.83
		Middle(155.7525MHz)	29.47
		Top(173.975MHz)	29.91
Digital (Voice+Data)	12.5 kHz	Bottom(136.025MHz)	29.92
		Middle(155.7525MHz)	29.84
		Top(173.975MHz)	29.85

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Power Measurement Results								
Test Mode	Frequency (MHz)	Reading Level (dBuv/m)	Antenna Polarization	S.G. (dBm)	Cable Loss (dB)	Ant.Gain (dBi)	ERP Results (dBm)	Limit (dBm)
Analog +Voice	136.0250	106.92	V	31.69	0.85	6.9	37.74	38.45
	136.0250	106.84	H	31.61	0.85	6.9	37.66	38.45
	155.7525	107.07	V	31.84	0.85	6.9	37.89	38.45
	155.7525	106.95	H	31.72	0.85	6.9	37.77	38.45
	173.975	106.93	V	31.70	0.85	6.9	37.75	38.45
	173.975	106.89	H	31.66	0.85	6.9	37.71	38.45
Digital (Voice+Data)	136.0250	106.81	V	31.58	0.85	6.9	37.63	38.45
	136.0250	106.76	H	31.53	0.85	6.9	37.58	38.45
	155.7525	106.70	V	31.47	0.85	6.9	37.52	38.45
	155.7525	106.63	H	31.40	0.85	6.9	37.45	38.45
	173.975	106.59	V	31.36	0.85	6.9	37.41	38.45
	173.975	106.46	H	31.23	0.85	6.9	37.28	38.45

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Radiated Power Measurement Results								
Test Mode	Frequency (MHz)	Reading Level (dBuv/m)	Antenna Polarization	S.G. (dBm)	Cable Loss (dB)	Ant.Gain (dBi)	ERP Results (dBm)	Limit (dBm)
Analog +Voice	136.0250	98.70	V	23.47	0.85	6.9	29.52	30.00
	136.0250	104.84	H	29.61	0.85	6.9	29.47	30.00
	155.7525	104.9	V	29.67	0.85	6.9	29.31	30.00
	155.7525	104.85	H	29.62	0.85	6.9	29.22	30.00
	173.975	104.78	V	29.55	0.85	6.9	29.66	30.00
	173.975	104.74	H	29.51	0.85	6.9	29.58	30.00
Digital (Voice+Data)	136.0250	104.97	V	29.74	0.85	6.9	29.51	30.00
	136.0250	104.93	H	29.7	0.85	6.9	29.33	30.00
	155.7525	105.01	V	29.78	0.85	6.9	29.41	30.00
	155.7525	104.97	H	29.74	0.85	6.9	29.32	30.00
	173.975	104.85	V	29.62	0.85	6.9	29.43	30.00
	173.975	104.76	H	29.53	0.85	6.9	29.35	30.00

Note: Calculation Formula: $CP = R + A + L$

- (1) CP: The final Conducted Power
- (2) R: The reading value from spectrum analyzer
- (3) A: The attenuation value of the used attenuator
- (4) L: The loss of all connection cables
- (5) Measurement Result=Peak Power (Max)

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

11. SPURIOUS EMISSION ON ANTENNA PORT

11.1 PROVISIONS APPLICABLE

Please refer to FCC 47 CFR 2.1051, 2.1057 & 90.210 for specification details.

Emissions shall be attenuated below the mean output power of the transmitter as follows:

FCC Rules	Attenuation Limit (dBc)
§ 90.210	At least 50 + 10 log (P) dB

50 +10 log (Pwatts)

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: Limit (dBm) =EL-50-10log10 (TP)

EL is the emission level of the Output Power expressed in dBm,


In this application, the EL is P(dBm)

Limit (dBm) = P(dBm)-50-10 log (Pwatts) = -20dBm

11.2 MEASUREMENT METHOD

1. The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation.
2. The resolution bandwidth of the spectrum analyzer was set to 100 kHz. Sufficient scans were taken to show any out of band emission up to 10th . Harmonic for the lower and the highest frequency range.
3. Set RBW 100 kHz, VBW 300 kHz in the frequency band 30MHz to 1GHz,while set RBW=1MHz.VBW=3MHz from the 1GHz to 10th Harmonic.
4. The audio input was set the unmodulated carrier, the resulting picture is print out for each channel separation.

11.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>