



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Xirrus, Inc.
Applicant Address	2101 Corporate Center Drive, Thousand Oaks, CA 91320 USA
FCC ID	SK6-X2120
Manufacturer's company	Life-On Network Communication (Dongguan) Limited
Manufacturer Address	30#Keji Rd., Yin Hu Industrial Area, Qingxi Town, DongGuan City, Guangdong, China

Product Name	Wireless Access Point
Brand Name	XIRRUS
Model No.	X2120
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5150 ~ 5250 MHz / 5725 ~ 5850 MHz
Received Date	Jul. 29, 2015
Final Test Date	Aug. 22, 2015
Submission Type	Original Equipment

Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart E, KDB789033 D02 v01, KDB662911 D01 v02r01, KDB644545 D03 v01.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. VERIFICATION OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	7
3.6. Table for Testing Locations.....	9
3.7. Table for Supporting Units	9
3.8. Table for Parameters of Test Software Setting	10
3.9. EUT Operation during Test	10
3.10. Duty Cycle.....	10
3.11. Test Configurations	11
4. TEST RESULT	14
4.1. AC Power Line Conducted Emissions Measurement.....	14
4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement.....	18
4.3. 6dB Spectrum Bandwidth Measurement	29
4.4. Maximum Conducted Output Power Measurement.....	34
4.5. Power Spectral Density Measurement	37
4.6. Radiated Emissions Measurement	45
4.7. Band Edge Emissions Measurement	69
4.8. Frequency Stability Measurement	78
4.9. Antenna Requirements	85
5. LIST OF MEASURING EQUIPMENTS	86
6. MEASUREMENT UNCERTAINTY	87
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. RADIATED EMISSION CO-LOCATION REPORT	B1 ~ B3



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR580626AB	Rev. 01	Initial issue of report	Sep. 04, 2015

1. VERIFICATION OF COMPLIANCE

Product Name : Wireless Access Point
Brand Name : XIRRUS
Model No. : X2120
Applicant : Xirrus, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jul. 29, 2015 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	4.38 dB
4.2	15.407(a)	26dB Spectrum Bandwidth and 99% Occupied Bandwidth	Complies	-
4.3	15.407(e)	6dB Spectrum Bandwidth	Complies	-
4.4	15.407(a)	Maximum Conducted Output Power	Complies	4.71 dB
4.5	15.407(a)	Power Spectral Density	Complies	4.06 dB
4.6	15.407(b)	Radiated Emissions	Complies	0.15 dB
4.7	15.407(b)	Band Edge Emissions	Complies	0.04 dB
4.8	15.407(g)	Frequency Stability	Complies	-
4.9	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From PoE
Modulation	IEEE 802.11a: OFDM IEEE 802.11n/ac: see the below table
Data Modulation	IEEE 802.11a/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	IEEE 802.11a: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n/ac: see the below table
Frequency Range	5150 ~ 5250 MHz / 5725 ~ 5850 MHz
Channel Number	9 for 20MHz bandwidth ; 4 for 40MHz bandwidth 2 for 80MHz bandwidth
Channel Band Width (99%)	Band 1: IEEE 802.11a: 29.44 MHz IEEE 802.11ac MCS0/Nss1 (VHT20): 25.53 MHz IEEE 802.11ac MCS0/Nss1 (VHT40): 38.78 MHz IEEE 802.11ac MCS0/Nss1 (VHT80): 76.70 MHz Band 4: IEEE 802.11a: 30.74 MHz IEEE 802.11ac MCS0/Nss1 (VHT20): 27.09 MHz IEEE 802.11ac MCS0/Nss1 (VHT40): 43.70 MHz IEEE 802.11ac MCS0/Nss1 (VHT80): 76.41 MHz
Maximum Conducted Output Power	Band 1: IEEE 802.11a: 25.29 dBm IEEE 802.11ac MCS0/Nss1 (VHT20): 25.04 dBm IEEE 802.11ac MCS0/Nss1 (VHT40): 23.82 dBm IEEE 802.11ac MCS0/Nss1 (VHT80): 16.64 dBm Band 4: IEEE 802.11a: 23.92 dBm IEEE 802.11ac MCS0/Nss1 (VHT20): 23.89 dBm IEEE 802.11ac MCS0/Nss1 (VHT40): 23.16 dBm IEEE 802.11ac MCS0/Nss1 (VHT80): 16.09 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description	
Communication Mode	<input checked="" type="checkbox"/> IP Based (Load Based)	<input type="checkbox"/> Frame Based
Beamforming Function	<input type="checkbox"/> With beamforming	<input checked="" type="checkbox"/> Without beamforming
Operating Mode	<input type="checkbox"/> Outdoor access point	
	<input checked="" type="checkbox"/> Indoor access point	
	<input type="checkbox"/> Fixed point-to-point access points	
	<input type="checkbox"/> Mobile and portable client devices	

Antenna and Bandwidth

Antenna	Two (TX)		
	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	MCS 0-15
802.11n (HT40)	2	MCS 0-15
802.11ac (VHT20)	2	MCS 0-9/Nss1-2
802.11ac (VHT40)	2	MCS 0-9/Nss1-2
802.11ac (VHT80)	2	MCS 0-9/Nss1-2

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).

Then EUT supports HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT supports VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:

HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories

Others
Wall-mounted rack*1

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
					2.4GHz	5GHz
1	-	-	Printed Antenna	N/A	Note 1	Note 2
2	-	-	Printed Antenna	N/A		
3	-	-	Printed Antenna	N/A		
4	-	-	Printed Antenna	N/A		

Note 1:

Antenna \ Frequency	Antenna Gain (dBi)			Directional Gain (dBi)					
	2412 MHz	2437 MHz	2462 MHz	For Output Power Gain			For PSD Gain		
				2412 MHz	2437 MHz	2462 MHz	2412 MHz	2437 MHz	2462 MHz
1	2.63	1.12	2.66	1.72	1.30	1.57	4.56	3.72	4.50
2	4.38	4.05	4.36						

Note 2:

Antenna \ Band	Antenna Gain (dBi)		Directional Gain (dBi)			
	Band 1	Band 4	For Output Power Gain		For PSD Gain	
			Band 1	Band 4	Band 1	Band 4
1	4.55	5.59	4.06	5.03	7.06	8.00
2	4.97	6.05				

Note 3: The EUT has four Antennas.

For 2.4GHz function:

For IEEE 802.11b/g/n mode (2TX/2RX):

Ant.1 and Ant.2 can be used as transmitting/receiving antenna.


Ant.1 and Ant.2 could transmit/receive simultaneously.

For 5GHz function:

For IEEE 802.11a/n/ac mode (2TX/2RX):

Ant.1 and Ant.2 can be used as transmitting/receiving antenna.

Ant.1 and Ant.2 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 36, 40, 44, 48, 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 38, 46, 151, 159.

For 80MHz bandwidth systems, use Channel 42, 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5150~5250 MHz Band 1	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz	-	-
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Ant.
AC Power Conducted Emission	Normal Link		-	-	-
Max. Conducted Output Power	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/1 57/165	1+2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/1 57/165	1+2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	1+2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	1+2
Power Spectral Density	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/1 57/165	1+2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/1 57/165	1+2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	1+2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	1+2
26dB Spectrum Bandwidth & 99% Occupied Bandwidth Measurement	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/1 57/165	1+2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/1 57/165	1+2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	1+2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	1+2
6dB Spectrum Bandwidth Measurement	11a/BPSK	Band 4	6Mbps	149/157/165	1+2
	11ac VHT20	Band 4	MCS0/Nss1	149/157/165	1+2
	11ac VHT40	Band 4	MCS0/Nss1	151/159	1+2
	11ac VHT80	Band 4	MCS0/Nss1	155	1+2
Radiated Emission Below 1GHz	Normal Link		-	-	-
Radiated Emission Above 1GHz	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/1 57/165	1+2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/1 57/165	1+2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	1+2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	1+2

Band Edge Emission	11a/BPSK	Band 1&4	6Mbps	36/40/48/149/1 57/165	1+2
	11ac VHT20	Band 1&4	MCS0/Nss1	36/40/48/149/1 57/165	1+2
	11ac VHT40	Band 1&4	MCS0/Nss1	38/46/151/159	1+2
	11ac VHT80	Band 1&4	MCS0/Nss1	42/155	1+2
Frequency Stability	20 MHz	Band 1&4	-	40/157	1
	40 MHz	Band 1&4	-	38/151	1
	80 MHz	Band 1&4	-	42/155	1

Note: VHT20/VHT40 covers HT20/HT40, due to same modulation. The power setting for 802.11n HT20 and HT40 are the same or lower than 802.11ac VHT20 and VHT40.

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1: Normal Link

For Radiated Emission test (Below 1GHz):

Mode 1: Normal Link - EUT Z axis

Mode 2: Normal Link - EUT Y axis

Mode 2 is the worst case, so it was selected to record in this test report.

For Radiated Emission test (Above 1GHz):

The EUT was performed at Y axis and Z axis position for Radiated emission above 1GHz test, and the worst case was found at Y axis. So the measurement will follow this same test configuration.

Mode 1: CTX - Y axis

For Co-location MPE and Radiated Emission Co-location Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to FA: 580626) and Radiated Emission Co-location (please refer to Appendix B) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

Note: The PoE is for measurement only, would not be marketed.

The PoE information as below:

Power	Brand	Model
PoE	PowerDsine	7001G
PoE	PHIHONG	POE20U-560(G)

3.6. Table for Testing Locations

Test Site Location					
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.				
TEL:	886-3-656-9065				
FAX:	886-3-656-9085				
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: 03CH01-CB (Below 1GHz)

Support Unit	Brand	Model	FCC ID
Notebook*3	DELL	E4300	DoC
PoE	PowerDsine	7001G	N/A

For Test Site No: 03CH01-CB (Above 1GHz) and TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC
PoE	PowerDsine	7001G	N/A

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook*3	DELL	E4300	DoC
PoE	PHIHONG	POE20U-560(G)	N/A

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Test Software Version	ART2-GUI Version 2.3					
Mode	Test Frequency (MHz)					
	NCB: 20MHz					
	5180 MHz	5200 MHz	5240 MHz	5745 MHz	5785 MHz	5825 MHz
802.11a	20	25	22.5	18.5	25	21
802.11ac MCS0/Nss1 VHT20	21	25	23.5	19	25	19.5
Mode	NCB: 40MHz					
802.11ac MCS0/Nss1 VHT40	5190 MHz		5230 MHz		5755 MHz	
	17.5		23		16.5	
Mode	NCB: 80MHz					
802.11ac MCS0/Nss1 VHT80	5210 MHz			5775 MHz		
	15			14		

3.9. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.10. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11a	2.017	2.086	96.69%	0.15	2.017
802.11ac MCS0/Nss1 VHT20	1.620	1.953	82.95%	0.81	1.620
802.11ac MCS0/Nss1 VHT40	0.876	1.005	87.16%	0.60	0.876
802.11ac MCS0/Nss1 VHT80	1.138	1.199	94.91%	0.23	1.138

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	1m
3	RJ-45 cable	No	10m


3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz ~1GHz



Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	RJ-45 cable	No	1.5m
3	Power cable	No	1.8m

Test Configuration: above 1GHz



Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	RJ-45 cable	No	1.5m
3	Power cable	No	1.8m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	50%
Test Engineer	Ryo Fan	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISM Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1500	34.13	-21.87	56.00	24.18	9.93	0.02	LINE	Average
2	0.1500	45.54	-20.46	66.00	35.59	9.93	0.02	LINE	QP
3	0.1874	33.84	-20.31	54.15	23.89	9.93	0.02	LINE	Average
4	0.1874	43.41	-20.74	64.15	33.46	9.93	0.02	LINE	QP
5	0.1934	38.07	-15.82	53.89	28.12	9.93	0.02	LINE	Average
6	0.1934	46.84	-17.05	63.89	36.89	9.93	0.02	LINE	QP
7	0.2863	31.83	-18.80	50.63	21.86	9.93	0.04	LINE	Average
8	0.2863	38.96	-21.67	60.63	28.99	9.93	0.04	LINE	QP
9	9.2532	30.62	-19.38	50.00	20.23	10.17	0.22	LINE	Average
10	9.2532	40.56	-19.44	60.00	30.17	10.17	0.22	LINE	QP
11	10.0186	32.64	-17.36	50.00	22.22	10.18	0.24	LINE	Average
12	10.0186	40.31	-19.69	60.00	29.89	10.18	0.24	LINE	QP
13	16.4636	45.48	-4.52	50.00	34.85	10.37	0.26	LINE	Average
14	16.4636	46.51	-13.49	60.00	35.88	10.37	0.26	LINE	QP

Temperature	24°C	Humidity	50%
Test Engineer	Ryo Fan	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1516	33.21	-22.70	55.91	23.41	9.78	0.02	NEUTRAL	Average
2	0.1516	44.80	-21.11	65.91	35.00	9.78	0.02	NEUTRAL	QP
3	0.1924	40.16	-13.77	53.93	30.35	9.79	0.02	NEUTRAL	Average
4	0.1924	47.87	-16.06	63.93	38.06	9.79	0.02	NEUTRAL	QP
5	6.2852	31.18	-18.82	50.00	21.11	9.94	0.13	NEUTRAL	Average
6	6.2852	34.52	-25.48	60.00	24.45	9.94	0.13	NEUTRAL	QP
7	9.4015	29.42	-20.58	50.00	19.20	10.00	0.22	NEUTRAL	Average
8	9.4015	37.40	-22.60	60.00	27.18	10.00	0.22	NEUTRAL	QP
9	10.0186	30.26	-19.74	50.00	20.01	10.01	0.24	NEUTRAL	Average
10	10.0186	34.21	-25.79	60.00	23.96	10.01	0.24	NEUTRAL	QP
11	16.4637	45.62	-4.38	50.00	35.23	10.13	0.26	NEUTRAL	Average
12	16.4637	46.71	-13.29	60.00	36.32	10.13	0.26	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement

4.2.1. Limit

No restriction limits.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

26dB Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.2.3. Test Procedures

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.2.4. Test Setup Layout

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.6.4.

4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 26dB Bandwidth and 99% Occupied Bandwidth

Temperature	25°C	Humidity	45%
Test Engineer	Roki Li		


Mode	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11a	5180 MHz	22.26	16.24
	5200 MHz	41.30	29.44
	5240 MHz	32.35	19.54
	5745 MHz	22.09	16.15
	5785 MHz	42.17	30.74
	5825 MHz	36.17	20.14
802.11ac MCS0/Nss1 VHT20	5180 MHz	26.96	18.84
	5200 MHz	33.65	25.53
	5240 MHz	28.87	19.10
	5745 MHz	25.39	18.58
	5785 MHz	41.83	27.09
	5825 MHz	26.43	18.58
802.11ac MCS0/Nss1 VHT40	5190 MHz	45.80	37.77
	5230 MHz	65.51	38.78
	5755 MHz	45.36	37.48
	5795 MHz	85.94	43.70
802.11ac MCS0/Nss1 VHT80	5210 MHz	87.83	76.70
	5775 MHz	85.22	76.41

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5180 MHz




Date: 22.AUG.2015 09:13:10

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5200 MHz




Date: 22.AUG.2015 09:14:39

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5240 MHz




Date: 22.AUG.2015 09:36:37

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5745 MHz




Date: 22.AUG.2015 09:23:27

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5785 MHz




Date: 22.AUG.2015 09:24:14

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5825 MHz




Date: 22.AUG.2015 09:25:21

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 / 5180 MHz




Date: 22.AUG.2015 09:27:11

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 / 5200 MHz




Date: 22.AUG.2015 09:28:04

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 / 5240 MHz



Date: 22.AUG.2015 09:33:45

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 / 5745 MHz




Date: 22.AUG.2015 10:00:02

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 / 5785 MHz




Date: 22.AUG.2015 10:02:28

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 / 5825 MHz




Date: 22.AUG.2015 10:06:15

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 / 5190 MHz




Date: 22.AUG.2015 10:10:03

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 / 5230 MHz



Date: 22.AUG.2015 10:11:56

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 / 5755 MHz




Date: 22.AUG.2015 10:19:17

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 / 5795 MHz




Date: 22.AUG.2015 10:20:20

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 / 5210 MHz



Date: 22.AUG.2015 10:40:53

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 / 5775 MHz



Date: 22.AUG.2015 10:46:46

4.3. 6dB Spectrum Bandwidth Measurement

4.3.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.3.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.3.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (C) Emission Bandwidth.
3. Multiple antenna system was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.3.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.6.4.

4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of 6dB Spectrum Bandwidth


Temperature	25°C	Humidity	45%
Test Engineer	Roki Liu		

Mode	Frequency	6dB Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11a	5745 MHz	12.64	500	Complies
	5785 MHz	11.30	500	Complies
	5825 MHz	11.54	500	Complies
802.11ac MCS0/Nss1 VHT20	5745 MHz	17.57	500	Complies
	5785 MHz	15.77	500	Complies
	5825 MHz	17.16	500	Complies
802.11ac MCS0/Nss1 VHT40	5755 MHz	34.09	500	Complies
	5795 MHz	33.86	500	Complies
802.11ac MCS0/Nss1 VHT80	5775 MHz	72.75	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5785 MHz




Date: 22.AUG.2015 10:52:58

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 / 5785 MHz




Date: 22.AUG.2015 10:55:54

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 / 5795MHz



Date: 22.AUG.2015 10:59:01

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 / 5775 MHz



Date: 22.AUG.2015 11:00:01

4.4. Maximum Conducted Output Power Measurement

4.4.1. Limit

Frequency Band	Limit
<input checked="" type="checkbox"/> 5.15~5.25 GHz	
Operating Mode	
<input type="checkbox"/> Outdoor access point	<p>The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm) provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).</p>
<input checked="" type="checkbox"/> Indoor access point	<p>The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm) provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>
<input type="checkbox"/> Fixed point-to-point access points	<p>The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm). Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.</p>
<input type="checkbox"/> Mobile and portable client devices	<p>The maximum conducted output power over the frequency band of operation shall not exceed 250 mW (24dBm) provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>

☒	5.725~5.85 GHz	The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm). If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power.
---	----------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	AVERAGE

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (E) Maximum conducted output power =>3. Measurement using a Power Meter (PM) =>b) Method PM-G (Measurement using a gated RF average power meter).
3. Multiple antenna systems was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	45%
Test Engineer	Roki Liu	Test Date	Aug. 20, 2015 ~ Aug. 22, 2015

Mode	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
802.11a	5180 MHz	19.46	19.21	22.35	30.00	Complies
	5200 MHz	22.26	22.30	25.29	30.00	Complies
	5240 MHz	21.08	20.91	24.01	30.00	Complies
	5745 MHz	18.16	18.63	21.41	30.00	Complies
	5785 MHz	20.72	21.09	23.92	30.00	Complies
	5825 MHz	19.55	20.47	23.04	30.00	Complies
802.11ac MCS0/Nss1 VHT20	5180 MHz	20.19	19.70	22.96	30.00	Complies
	5200 MHz	21.93	22.12	25.04	30.00	Complies
	5240 MHz	21.47	21.67	24.58	30.00	Complies
	5745 MHz	17.94	18.64	21.31	30.00	Complies
	5785 MHz	20.69	21.06	23.89	30.00	Complies
	5825 MHz	18.11	19.41	21.82	30.00	Complies
802.11ac MCS0/Nss1 VHT40	5190 MHz	16.63	16.32	19.49	30.00	Complies
	5230 MHz	21.09	20.51	23.82	30.00	Complies
	5755 MHz	15.56	15.80	18.69	30.00	Complies
	5795 MHz	19.60	20.64	23.16	30.00	Complies
802.11ac MCS0/Nss1 VHT80	5210 MHz	13.75	13.51	16.64	30.00	Complies
	5775 MHz	12.88	13.28	16.09	30.00	Complies

4.5. Power Spectral Density Measurement

4.5.1. Limit

The following table is power spectral density limits and decrease power density limit rule refer to section 4.4.1.

Frequency Band		Limit
<input checked="" type="checkbox"/>	5.15~5.25 GHz	
	Operating Mode	
<input type="checkbox"/>	Outdoor access point	17 dBm/MHz
<input checked="" type="checkbox"/>	Indoor access point	17 dBm/MHz
<input type="checkbox"/>	Fixed point-to-point access points	17 dBm/MHz
<input type="checkbox"/>	Mobile and portable client devices	11 dBm/MHz
<input checked="" type="checkbox"/>	5.725~5.85 GHz	30 dBm/500kHz

4.5.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1000 kHz
VBW	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times
Note: If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas RBW (< 500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.	

4.5.3. Test Procedures

1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (F) Maximum Power Spectral Density (PSD).
3. Multiple antenna systems was performed in accordance KDB662911 D01 v02r01 in-Band Power Spectral Density (PSD) Measurements (a) Measure and sum the spectra across the outputs.
4. When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.
5. For 5.725~5.85 GHz, the measured result of PSD level must add $10\log(500\text{kHz}/\text{RBW})$ and the final result should ≤ 30 dBm.

4.5.4. Test Setup Layout



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	45%
Test Engineer	Roki Li	Test Date	Aug. 20, 2015 ~ Aug. 22, 2015

Configuration IEEE 802.11a / Ant. 1 + Ant. 2

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	9.16	15.94	Complies
40	5200 MHz	11.88	15.94	Complies
48	5240 MHz	10.77	15.94	Complies

Note: Directional gain=7.06 >6dBi, so limit = 17 - (7.06 - 6) = 15.94 dBm/MHz.

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
149	5745 MHz	8.19	-3.01	5.18	28.00	Complies
157	5785 MHz	10.80	-3.01	7.79	28.00	Complies
165	5825 MHz	9.89	-3.01	6.88	28.00	Complies

Note: Directional gain=8.00 >6dBi, so limit = 30 - (8 - 6) = 28.00 dBm/500kHz.

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	9.88	15.94	Complies
40	5200 MHz	11.84	15.94	Complies
48	5240 MHz	11.45	15.94	Complies

Note: Directional gain=7.06 >6dBi, so limit = 17 - (7.06 - 6) = 15.94 dBm/MHz.

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
149	5745 MHz	8.28	-3.01	5.27	28.00	Complies
157	5785 MHz	10.68	-3.01	7.67	28.00	Complies
165	5825 MHz	8.72	-3.01	5.71	28.00	Complies

Note: Directional gain=8.00 >6dBi, so limit = 30 - (8 - 6) = 28.00 dBm/500kHz.

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190 MHz	3.44	15.94	Complies
46	5230 MHz	7.75	15.94	Complies

Note: Directional gain=7.06 >6dBi, so limit = 17 – (7.06 – 6) = 15.94 dBm/MHz.

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
151	5755 MHz	2.62	-3.01	-0.39	28.00	Complies
159	5795 MHz	7.13	-3.01	4.12	28.00	Complies

Note: Directional gain=8.00 >6dBi, so limit = 30 – (8 – 6) = 28.00 dBm/500kHz.

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2

Channel	Frequency	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210 MHz	-2.37	15.94	Complies

Note: Directional gain=7.06 >6dBi, so limit = 17 – (7.06 – 6) = 15.94 dBm/MHz.


Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
155	5775 MHz	-2.96	-3.01	-5.97	28.00	Complies

Note: Directional gain=8.00 >6dBi, so limit = 30 – (8 – 6) = 28.00 dBm/500kHz.


Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


Power Density Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5200 MHz




Power Density Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5785 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 / 5200 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 / 5785 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 / 5230 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 / 5795 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 / 5210 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 / 5775 MHz



4.6. Radiated Emissions Measurement

4.6.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.6.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.6.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	Normal Link / Mode 2
Test Date	Aug. 12, 2015		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.6.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	Normal Link / Mode 2

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	47.46	32.84	40.00	-7.16	54.40	0.70	10.15	32.41	300	32 Peak	HORIZONTAL
2	52.31	29.32	40.00	-10.68	52.52	0.73	8.48	32.41	200	142 Peak	HORIZONTAL
3	200.72	31.00	43.50	-12.50	51.64	1.26	10.43	32.33	400	16 Peak	HORIZONTAL
4	229.82	25.81	46.00	-20.19	45.49	1.33	11.30	32.31	400	114 Peak	HORIZONTAL
5	428.67	29.63	46.00	-16.37	43.34	1.78	16.85	32.34	100	40 Peak	HORIZONTAL
6	460.68	29.44	46.00	-16.56	42.68	1.84	17.26	32.34	100	305 Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	52.31	32.09	40.00	-7.91	55.29	0.73	8.48	32.41	150	188 QP	VERTICAL
2	126.03	39.81	43.50	-3.69	58.40	1.04	12.74	32.37	100	161 Peak	VERTICAL
3	156.10	34.84	43.50	-8.66	55.08	1.15	10.96	32.35	100	161 Peak	VERTICAL
4	198.78	34.33	43.50	-9.17	55.11	1.26	10.29	32.33	300	213 Peak	VERTICAL
5	244.37	35.33	46.00	-10.67	53.78	1.37	12.49	32.31	100	91 Peak	VERTICAL
6	421.88	34.54	46.00	-11.46	48.33	1.77	16.77	32.33	150	1 Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6.9. Results for Radiated Emissions (1GHz~40GHz)

Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11a CH 36 / Ant. 1 + Ant. 2
Test Date	Aug. 05, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	15538.15	48.23	54.00	-5.77	32.32	38.34	12.92	35.35	145	143	HORIZONTAL	Average
2	15538.46	60.72	74.00	-13.28	44.81	38.34	12.92	35.35	145	143	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	15541.01	60.48	74.00	-13.52	44.57	38.34	12.92	35.35	148	219	VERTICAL	Peak
2	15541.51	48.34	54.00	-5.66	32.43	38.34	12.92	35.35	148	219	VERTICAL	Average



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11a CH 40 / Ant. 1 + Ant. 2
Test Date	Aug. 12, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15601.20	46.61	54.00	-7.39	29.78	12.58	38.03	33.78	149	274	Average	HORIZONTAL
2	15617.20	58.84	74.00	-15.16	42.03	12.58	38.01	33.78	149	274	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15612.50	58.74	74.00	-15.26	41.93	12.58	38.01	33.78	157	304	Peak	VERTICAL
2	15622.60	46.42	54.00	-7.58	29.61	12.58	38.01	33.78	157	304	Average	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11a CH 48 / Ant. 1 + Ant. 2
Test Date	Aug. 05, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	15719.61	61.29	74.00	-12.71	45.56	38.08	13.03	35.38	148	107	HORIZONTAL	Peak
2	15720.74	48.40	54.00	-5.60	32.67	38.08	13.03	35.38	148	107	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	15717.91	61.25	74.00	-12.75	45.52	38.08	13.03	35.38	157	186	VERTICAL	Peak
2	15721.37	48.42	54.00	-5.58	32.69	38.08	13.03	35.38	157	186	VERTICAL	Average



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11a CH 149 / Ant. 1 + Ant. 2
Test Date	Aug. 05, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	11491.42	50.84	54.00	-3.16	35.14	39.90	11.03	35.23	146	46	HORIZONTAL	Average
2	11491.59	67.26	74.00	-6.74	51.55	39.90	11.04	35.23	146	46	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	11485.92	61.26	74.00	-12.74	45.56	39.90	11.03	35.23	126	337	VERTICAL	Peak
2	11490.96	47.80	54.00	-6.20	32.10	39.90	11.03	35.23	126	337	VERTICAL	Average

Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11a CH 157 / Ant. 1 + Ant. 2
Test Date	Aug. 12, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11566.30	71.24	74.00	-2.76	54.93	10.75	38.94	33.38	147	33	Peak	HORIZONTAL
2	11571.30	52.81	54.00	-1.19	36.50	10.76	38.94	33.39	147	33	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11571.20	48.83	54.00	-5.17	32.52	10.76	38.94	33.39	138	318	Average	VERTICAL
2	11571.40	64.38	74.00	-9.62	48.07	10.76	38.94	33.39	138	318	Peak	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11a CH 165 / Ant. 1 + Ant. 2
Test Date	Aug. 05, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	11650.26	68.77	74.00	-5.23	53.26	39.63	11.10	35.22	143	49	HORIZONTAL	Peak
2	11650.43	53.85	54.00	-0.15	38.34	39.63	11.10	35.22	143	49	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	11646.27	49.40	54.00	-4.60	33.89	39.63	11.10	35.22	155	343	VERTICAL	Average
2	11647.89	61.78	74.00	-12.22	46.27	39.63	11.10	35.22	155	343	VERTICAL	Peak



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36 / Ant. 1 + Ant. 2
Test Date	Aug. 11, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15527.54	61.83	74.00	-12.17	45.93	12.91	35.35	38.34	HORIZONTAL	209	138	Peak
2	15539.30	48.08	54.00	-5.92	32.17	12.92	35.35	38.34	HORIZONTAL	209	138	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15526.58	61.59	74.00	-12.41	45.69	12.91	35.35	38.34	VERTICAL	221	152	Peak
2	15545.47	48.34	54.00	-5.66	32.43	12.92	35.35	38.34	VERTICAL	221	152	Average



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 40 / Ant. 1 + Ant. 2
Test Date	Aug. 12, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15593.50	59.20	74.00	-14.80	42.31	12.58	38.06	33.75	149	41	Peak	HORIZONTAL
2	15608.10	46.52	54.00	-7.48	29.69	12.58	38.03	33.78	149	41	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	15611.90	46.42	54.00	-7.58	29.61	12.58	38.01	33.78	156	113	Average	VERTICAL
2	15616.80	58.55	74.00	-15.45	41.74	12.58	38.01	33.78	156	113	Peak	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 48 / Ant. 1 + Ant. 2
Test Date	Aug. 07, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15717.58	48.98	54.00	-5.02	32.66	13.03	34.80	38.09	HORIZONTAL	254	135	Average
2	15718.58	61.61	74.00	-12.39	45.29	13.03	34.80	38.09	HORIZONTAL	254	135	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15720.67	48.20	54.00	-5.80	31.89	13.03	34.80	38.08	VERTICAL	289	147	Average
2	15722.07	61.65	74.00	-12.35	45.34	13.03	34.80	38.08	VERTICAL	289	147	Peak

Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 149 / Ant. 1 + Ant. 2
Test Date	Aug. 11, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11482.91	62.16	74.00	-11.84	46.44	11.03	35.23	39.92	HORIZONTAL	352	147	Peak
2	11483.63	48.37	54.00	-5.63	32.67	11.03	35.23	39.90	HORIZONTAL	352	147	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11491.01	49.90	54.00	-4.10	34.20	11.03	35.23	39.90	VERTICAL	324	231	Average
2	11498.25	63.27	74.00	-10.73	47.56	11.04	35.23	39.90	VERTICAL	324	231	Peak



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 157 / Ant. 1 + Ant. 2
Test Date	Aug. 12, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11571.20	48.20	54.00	-5.80	31.89	10.76	38.94	33.39	208	310	Average	HORIZONTAL
2	11571.26	63.57	74.00	-10.43	47.26	10.76	38.94	33.39	208	310	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11574.74	70.28	74.00	-3.72	53.97	10.76	38.94	33.39	202	34	Peak	VERTICAL
2	11576.18	52.56	54.00	-1.44	36.25	10.76	38.94	33.39	202	34	Average	VERTICAL



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 165 / Ant. 1 + Ant. 2
Test Date	Aug. 11, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11650.58	65.23	74.00	-8.77	49.72	11.10	35.22	39.63	HORIZONTAL	48	145	Peak
2	11653.04	52.04	54.00	-1.96	36.59	11.10	35.22	39.57	HORIZONTAL	48	145	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11623.95	59.16	74.00	-14.84	43.66	11.09	35.22	39.63	VERTICAL	236	168	Peak
2	11685.31	46.24	54.00	-7.76	30.84	11.12	35.22	39.50	VERTICAL	236	168	Average



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38 / Ant. 1 + Ant. 2
Test Date	Aug. 11, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15539.75	46.84	54.00	-7.16	30.93	12.92	35.35	38.34	HORIZONTAL	117	210	Average
2	15568.70	60.59	74.00	-13.41	44.74	12.94	35.36	38.27	HORIZONTAL	117	210	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15524.99	47.79	54.00	-6.21	31.89	12.91	35.35	38.34	VERTICAL	182	160	Average
2	15598.22	60.46	74.00	-13.54	44.59	12.96	35.36	38.27	VERTICAL	182	160	Peak



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 46 / Ant. 1 + Ant. 2
Test Date	Aug. 07, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15687.76	48.84	54.00	-5.16	32.48	13.01	34.78	38.13	HORIZONTAL	126	141	Average
2	15687.76	61.45	74.00	-12.55	45.09	13.01	34.78	38.13	HORIZONTAL	126	141	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15689.61	48.24	54.00	-5.76	31.87	13.01	34.79	38.15	VERTICAL	42	138	Average
2	15691.11	61.22	74.00	-12.78	44.92	13.01	34.79	38.08	VERTICAL	42	138	Peak



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 151 / Ant. 1 + Ant. 2
Test Date	Aug. 11, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11478.16	45.52	54.00	-8.48	29.80	11.03	35.23	39.92	HORIZONTAL	257	190	Average
2	11512.89	59.27	74.00	-14.73	43.55	11.05	35.23	39.90	HORIZONTAL	257	190	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11462.39	46.52	54.00	-7.48	30.81	11.02	35.23	39.92	VERTICAL	202	122	Average
2	11546.18	59.56	74.00	-14.44	43.90	11.06	35.23	39.83	VERTICAL	202	122	Peak



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 159 / Ant. 1 + Ant. 2
Test Date	Aug. 11, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11586.24	62.18	74.00	-11.82	46.62	11.08	35.22	39.70	HORIZONTAL	290	127	Peak
2	11590.43	46.95	54.00	-7.05	31.39	11.08	35.22	39.70	HORIZONTAL	290	127	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11593.76	48.71	54.00	-5.29	33.15	11.08	35.22	39.70	VERTICAL	317	179	Average
2	11595.64	61.79	74.00	-12.21	46.23	11.08	35.22	39.70	VERTICAL	317	179	Peak



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Ant. 1 + Ant. 2
Test Date	Aug. 11, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15610.46	46.68	54.00	-7.32	30.87	12.96	35.36	38.21	HORIZONTAL	261	184	Average
2	15654.60	60.40	74.00	-13.60	44.62	12.99	35.36	38.15	HORIZONTAL	261	184	Peak

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	15585.57	47.07	54.00	-6.93	31.21	12.95	35.36	38.27	VERTICAL	210	148	Average
2	15639.99	60.25	74.00	-13.75	44.42	12.98	35.36	38.21	VERTICAL	210	148	Peak



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 155 / Ant. 1 + Ant. 2
Test Date	Aug. 11, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11500.51	58.82	74.00	-15.18	43.11	11.04	35.23	39.90	HORIZONTAL	270	179	Peak
2	11532.92	44.74	54.00	-9.26	29.09	11.05	35.23	39.83	HORIZONTAL	270	179	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11521.92	45.48	54.00	-8.52	29.83	11.05	35.23	39.83	VERTICAL	179	150	Average
2	11530.32	58.95	74.00	-15.05	43.30	11.05	35.23	39.83	VERTICAL	179	150	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.7. Band Edge Emissions Measurement

4.7.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for Peak

4.7.3. Test Procedures

1. The test procedure is the same as section 4.6.3.

4.7.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.6.4.

4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.7.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11a CH 36, 40, 48 / Ant. 1 + Ant. 2
Test Date	Aug. 04, 2015, Aug. 11, 2015		

Channel 36

	Freq	Level	Limit	Over	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	5150.00	71.05	74.00	-2.95	65.14	31.52	7.33	32.94	177	300	HORIZONTAL Peak
2	5150.00	53.74	54.00	-0.26	47.83	31.52	7.33	32.94	177	300	HORIZONTAL Average
3	5175.66	115.59			109.63	31.55	7.35	32.94	177	300	HORIZONTAL Peak
4	5185.50	105.62			99.65	31.55	7.36	32.94	177	300	HORIZONTAL Average

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit	Over	Read	Cable	PreampAntenna	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm	
1	5145.37	68.04	74.00	-5.96	62.14	7.32	32.94	31.52	HORIZONTAL	306	181 Peak
2	5150.00	53.00	54.00	-1.00	47.09	7.33	32.94	31.52	HORIZONTAL	306	181 Average
3	5205.50	119.04			113.03	7.38	32.94	31.57	HORIZONTAL	306	181 Peak
4	5206.08	107.75			101.74	7.38	32.94	31.57	HORIZONTAL	306	181 Average

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit	Over	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	5146.53	57.78	74.00	-16.22	51.87	31.52	7.33	32.94	175	304	HORIZONTAL Peak
2	5150.00	45.79	54.00	-8.21	39.88	31.52	7.33	32.94	175	304	HORIZONTAL Average
3	5243.04	117.60			111.52	31.59	7.42	32.93	175	304	HORIZONTAL Peak
4	5243.04	107.84			101.76	31.59	7.42	32.93	175	304	HORIZONTAL Average
5	5353.91	46.21	54.00	-7.79	39.94	31.68	7.52	32.93	175	304	HORIZONTAL Average
6	5359.12	58.98	74.00	-15.02	52.69	31.69	7.53	32.93	175	304	HORIZONTAL Peak

Item 3, 4 are the fundamental frequency at 5240 MHz.

Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11a CH 149, 157, 165 / Ant. 1 + Ant. 2
Test Date	Aug. 04, 2015, Aug. 11, 2015		

Channel 149

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	5713.41	50.86	54.00	-3.14	44.01	32.06	7.79	33.00	198	306	HORIZONTAL	Average
2	5714.13	66.40	74.00	-7.60	59.55	32.06	7.79	33.00	198	306	HORIZONTAL	Peak
3	5723.99	77.45	78.20	-0.75	70.58	32.08	7.79	33.00	198	306	HORIZONTAL	Peak
4	5738.34	104.64			97.77	32.08	7.80	33.01	198	306	HORIZONTAL	Average
5	5748.76	115.05			108.16	32.10	7.81	33.02	198	306	HORIZONTAL	Peak

Item 3, 4 are the fundamental frequency at 5745 MHz.

Channel 157

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5707.19	60.24	68.20	-7.96	53.40	7.78	33.00	32.06	VERTICAL	0	159	Peak
2	5720.66	64.83	78.20	-13.37	57.98	7.79	33.00	32.06	VERTICAL	0	159	Peak
3	5780.08	104.15			97.21	7.83	33.03	32.14	VERTICAL	0	159	Average
4	5780.66	115.83			108.89	7.83	33.03	32.14	VERTICAL	0	159	Peak
5	5850.00	63.62	78.20	-14.58	56.58	7.87	33.05	32.22	VERTICAL	0	159	Peak
6	5860.00	64.41	68.20	-3.79	57.36	7.87	33.06	32.24	VERTICAL	0	159	Peak

Item 3, 4 are the fundamental frequency at 5785 MHz.

Channel 165

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	5818.34	116.01			109.02	32.18	7.85	33.04	186	309	HORIZONTAL	Peak
2	5818.34	106.00			99.01	32.18	7.85	33.04	186	309	HORIZONTAL	Average
3	5852.75	76.73	78.20	-1.47	69.69	32.22	7.87	33.05	186	309	HORIZONTAL	Peak
4	5863.04	70.56	74.00	-3.44	63.51	32.24	7.87	33.06	186	309	HORIZONTAL	Peak
5	5863.18	53.68	54.00	-0.32	46.63	32.24	7.87	33.06	186	309	HORIZONTAL	Average

Item 1, 2 are the fundamental frequency at 5825 MHz.



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36, 40, 48 / Ant. 1 + Ant. 2
Test Date	Aug. 04, 2015, Aug. 11, 2015		

Channel 36

	Freq	Level	Limit Line	Over Limit	Read Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	5145.37	71.98	74.00	-2.02	66.08	31.52	7.32	32.94	175	301	HORIZONTAL	Peak
2	5146.38	53.65	54.00	-0.35	47.74	31.52	7.33	32.94	175	301	HORIZONTAL	Average
3	5182.03	116.44			110.47	31.55	7.36	32.94	175	301	HORIZONTAL	Peak
4	5182.46	106.09			100.12	31.55	7.36	32.94	175	301	HORIZONTAL	Average

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5141.03	69.02	74.00	-4.98	63.13	7.32	32.94	31.51	HORIZONTAL	309	177	Peak
2	5143.92	51.99	54.00	-2.01	46.09	7.32	32.94	31.52	HORIZONTAL	309	177	Average
3	5204.34	107.38			101.37	7.38	32.94	31.57	HORIZONTAL	309	177	Average
4	5206.37	118.28			112.27	7.38	32.94	31.57	HORIZONTAL	309	177	Peak

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit Line	Over Limit	Read Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	5146.09	60.30	74.00	-13.70	54.39	31.52	7.33	32.94	178	309	HORIZONTAL	Peak
2	5150.00	47.36	54.00	-6.64	41.45	31.52	7.33	32.94	178	309	HORIZONTAL	Average
3	5243.04	116.98			110.90	31.59	7.42	32.93	178	309	HORIZONTAL	Peak
4	5244.34	107.26			101.18	31.59	7.42	32.93	178	309	HORIZONTAL	Average
5	5350.00	48.07	54.00	-5.93	41.80	31.68	7.52	32.93	178	309	HORIZONTAL	Average
6	5354.34	60.51	74.00	-13.49	54.23	31.69	7.52	32.93	178	309	HORIZONTAL	Peak

Item 3, 4 are the fundamental frequency at 5240 MHz.

Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 149, 157, 165 / Ant. 1 + Ant. 2
Test Date	Aug. 05, 2015, Aug. 11, 2015		

Channel 149

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	5712.11	67.86	74.00	-6.14	61.01	32.06	7.79	33.00	178	303	HORIZONTAL	Peak
2	5712.68	51.72	54.00	-2.28	44.87	32.06	7.79	33.00	178	303	HORIZONTAL	Average
3	5725.00	77.49	78.20	-0.71	70.62	32.08	7.79	33.00	178	303	HORIZONTAL	Peak
4	5748.91	105.76			98.87	32.10	7.81	33.02	178	303	HORIZONTAL	Average
5	5751.22	116.20			109.31	32.10	7.81	33.02	178	303	HORIZONTAL	Peak

Item 3, 4 are the fundamental frequency at 5745 MHz.

Channel 157

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5708.63	62.39	68.20	-5.81	55.55	7.78	33.00	32.06	HORIZONTAL	302	143	Peak
2	5724.42	66.15	78.20	-12.05	59.28	7.79	33.00	32.08	HORIZONTAL	302	143	Peak
3	5780.95	117.90			110.96	7.83	33.03	32.14	HORIZONTAL	302	143	Peak
4	5787.89	106.20			99.26	7.83	33.03	32.14	HORIZONTAL	302	143	Average
5	5850.00	64.40	78.20	-13.80	57.36	7.87	33.05	32.22	HORIZONTAL	302	143	Peak
6	5863.47	63.36	68.20	-4.84	56.31	7.87	33.06	32.24	HORIZONTAL	302	143	Peak

Item 3, 4 are the fundamental frequency at 5785 MHz.

Channel 165

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	5828.18	116.18			109.18	32.20	7.85	33.05	173	304	HORIZONTAL	Peak
2	5828.47	105.75			98.75	32.20	7.85	33.05	173	304	HORIZONTAL	Average
3	5850.29	77.72	78.20	-0.48	70.68	32.22	7.87	33.05	173	304	HORIZONTAL	Peak
4	5863.18	64.87	74.00	-9.13	57.82	32.24	7.87	33.06	173	304	HORIZONTAL	Peak
5	5863.47	49.65	54.00	-4.35	42.60	32.24	7.87	33.06	173	304	HORIZONTAL	Average

Item 1, 2 are the fundamental frequency at 5825 MHz.



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38, 46 / Ant. 1 + Ant. 2
Test Date	Aug. 05, 2015		

Channel 38

	Freq	Level	Limit	Over	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	5144.50	53.65	54.00	-0.35	47.75	31.52	7.32	32.94	175	304	HORIZONTAL Average
2	5146.24	67.71	74.00	-6.29	61.80	31.52	7.33	32.94	175	304	HORIZONTAL Peak
3	5201.87	110.74			104.73	31.57	7.38	32.94	175	304	HORIZONTAL Peak
4	5202.45	100.27			94.26	31.57	7.38	32.94	175	304	HORIZONTAL Average

Item 3, 4 are the fundamental frequency at 5190 MHz.

Channel 46

	Freq	Level	Limit	Over	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	5139.29	67.55	74.00	-6.45	61.66	31.51	7.32	32.94	178	309	HORIZONTAL Peak
2	5144.79	52.58	54.00	-1.42	46.68	31.52	7.32	32.94	178	309	HORIZONTAL Average
3	5242.16	114.73			108.65	31.59	7.42	32.93	178	309	HORIZONTAL Peak
4	5242.45	104.54			98.46	31.59	7.42	32.93	178	309	HORIZONTAL Average

Item 3, 4 are the fundamental frequency at 5230 MHz.

Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 151, 159 / Ant. 1 + Ant. 2
Test Date	Aug. 14, 2015		

Channel 151

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5711.24	67.82	68.20	-0.38	60.97	7.79	33.00	32.06	HORIZONTAL	309	182	Peak
2	5725.00	74.70	78.20	-3.50	67.83	7.79	33.00	32.08	HORIZONTAL	309	182	Peak
3	5748.05	100.27			93.38	7.81	33.02	32.10	HORIZONTAL	309	182	Average
4	5748.92	110.37			103.48	7.81	33.02	32.10	HORIZONTAL	309	182	Peak

Item 3, 4 are the fundamental frequency at 5755 MHz.

Channel 159

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Pol/Phase	T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	5708.05	63.75	68.20	-4.45	56.91	7.78	33.00	32.06	HORIZONTAL	300	169	Peak
2	5724.71	68.67	78.20	-9.53	61.80	7.79	33.00	32.08	HORIZONTAL	300	169	Peak
3	5786.61	102.06			95.12	7.83	33.03	32.14	HORIZONTAL	300	169	Average
4	5787.76	113.48			106.54	7.83	33.03	32.14	HORIZONTAL	300	169	Peak
5	5852.60	71.55	78.20	-6.65	64.51	7.87	33.05	32.22	HORIZONTAL	300	169	Peak
6	5866.66	68.16	68.20	-0.04	61.10	7.88	33.06	32.24	HORIZONTAL	300	169	Peak

Item 3, 4 are the fundamental frequency at 5795 MHz.



Temperature	24°C	Humidity	57%
Test Engineer	Alvin Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42, 155 / Ant. 1 + Ant. 2
Test Date	Aug. 05, 2015		

Channel 42

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	5143.49	66.38	74.00	-7.62	60.48	31.52	7.32	32.94	175	308	HORIZONTAL	Peak
2	5144.21	53.60	54.00	-0.40	47.70	31.52	7.32	32.94	175	308	HORIZONTAL	Average
3	5202.76	92.78			86.77	31.57	7.38	32.94	175	308	HORIZONTAL	Average
4	5223.02	103.47			97.43	31.58	7.40	32.94	175	308	HORIZONTAL	Peak
5	5351.45	63.08	74.00	-10.92	56.81	31.68	7.52	32.93	175	308	HORIZONTAL	Peak
6	5351.45	50.78	54.00	-3.22	44.51	31.68	7.52	32.93	175	308	HORIZONTAL	Average

Item 3, 4 are the fundamental frequency at 5210 MHz.

Channel 155

	Freq	Level	Limit Line	Over Limit	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		
1	5704.87	68.66	74.00	-5.34	61.84	32.04	7.78	33.00	176	300	HORIZONTAL	Peak
2	5709.21	53.95	54.00	-0.05	47.11	32.06	7.78	33.00	176	300	HORIZONTAL	Average
3	5724.28	70.75	78.20	-7.45	63.88	32.08	7.79	33.00	176	300	HORIZONTAL	Peak
4	5748.23	94.61			87.72	32.10	7.81	33.02	176	300	HORIZONTAL	Average
5	5763.42	104.13			97.21	32.12	7.82	33.02	176	300	HORIZONTAL	Peak
6	5850.00	64.97	78.20	-13.23	57.93	32.22	7.87	33.05	176	300	HORIZONTAL	Peak
7	5865.79	51.36	54.00	-2.64	44.31	32.24	7.87	33.06	176	300	HORIZONTAL	Average
8	5866.51	63.72	74.00	-10.28	56.66	32.24	7.88	33.06	176	300	HORIZONTAL	Peak

Item 4, 5 are the fundamental frequency at 5775 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.8. Frequency Stability Measurement

4.8.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

4.8.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

4.8.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f) / f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
7. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
8. Extreme temperature is $0^\circ\text{C} \sim 45^\circ\text{C}$.

4.8.4. Test Setup Layout



4.8.5. Test Deviation

There is no deviation with the original standard.

4.8.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.8.7. Test Result of Frequency Stability

Temperature	25°C	Humidity	45%
Test Engineer	Roki Li	Test Date	Aug. 20, 2015 ~ Aug. 22, 2015

Mode: 20 MHz / Ant. 1

Voltage vs. Frequency Stability

Voltage (V)	Measurement Frequency (MHz)			
	5200 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5200.0105	5200.0118	5200.0074	5200.0065
110.00	5200.0102	5200.0114	5200.0072	5200.0060
93.50	5200.0096	5200.0104	5200.0058	5200.0055
Max. Deviation (MHz)	0.0105	0.0118	0.0074	0.0065
Max. Deviation (ppm)	2.02	2.27	1.42	1.25
Result	Complies			

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)			
	5200 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5199.9994	5199.9976	5199.9923	5199.9882
10	5199.9610	5199.9614	5199.9941	5199.9931
20	5199.9556	5199.9562	5199.9880	5199.9935
30	5199.9520	5199.9424	5199.9888	5199.9826
40	5199.9388	5199.9396	5199.9826	5199.9934
45	5199.9854	5199.9854	5199.9854	5199.9956
Max. Deviation (MHz)	0.0612	0.0604	0.0174	0.0174
Max. Deviation (ppm)	11.77	11.62	3.35	3.35
Result	Complies			

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5785 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5785.0022	5784.9979	5784.9974	5784.9968
110.00	5785.0000	5784.9976	5784.9970	5784.9964
93.50	5784.9886	5784.9966	5784.9958	5784.9955
Max. Deviation (MHz)	0.0114	0.0034	0.0042	0.0045
Max. Deviation (ppm)	1.97	0.59	0.73	0.78
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5785 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5784.9854	5784.9882	5784.9854	5784.9882
10	5784.9989	5784.9886	5784.9826	5784.9882
20	5784.9579	5784.9577	5784.9562	5784.9854
30	5784.9588	5784.9587	5784.9504	5784.9882
40	5784.9514	5784.9514	5784.9432	5784.9882
45	5784.9854	5784.9882	5784.9854	5784.9882
Max. Deviation (MHz)	0.0486	0.0486	0.0568	0.0146
Max. Deviation (ppm)	8.41	8.41	9.82	2.52
Result	Complies			

Mode: 40 MHz / Ant. 1

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5190 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5189.9818	5189.9818	5189.9818	5189.9818
110.00	5189.9802	5189.9804	5189.9806	5189.9808
93.50	5189.9814	5189.9816	5189.9816	5189.9816
Max. Deviation (MHz)	0.0198	0.0196	0.0194	0.0192
Max. Deviation (ppm)	3.82	3.78	3.74	3.70
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5190 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5189.9766	5189.9762	5189.9768	5189.9663
10	5189.9766	5189.9763	5189.9766	5189.9766
20	5189.9764	5189.9765	5189.9768	5189.9764
30	5189.9825	5189.9854	5189.9869	5189.9818
40	5189.9829	5189.9818	5189.9854	5189.9867
45	5189.9854	5189.9836	5189.9832	5189.9836
Max. Deviation (MHz)	0.0236	0.0238	0.0234	0.0337
Max. Deviation (ppm)	4.55	4.59	4.51	6.49
Result	Complies			

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5755 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5754.9873	5754.9885	5754.9854	5754.9774
110.00	5754.9854	5754.9861	5754.9658	5754.9656
93.50	5754.9859	5754.9854	5754.9925	5754.9854
Max. Deviation (MHz)	0.0146	0.0146	0.0342	0.0344
Max. Deviation (ppm)	2.54	2.54	5.94	5.98
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5755 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5754.9744	5754.9744	5754.9746	5754.9698
10	5754.9742	5754.9744	5754.9745	5754.9743
20	5754.9743	5754.9746	5754.9744	5754.9742
30	5754.9821	5754.9743	5754.9833	5754.9746
40	5754.9836	5754.9744	5754.9901	5754.9768
45	5754.9862	5754.9879	5754.9902	5754.9826
Max. Deviation (MHz)	0.0258	0.0257	0.0256	0.0302
Max. Deviation (ppm)	4.48	4.47	4.45	5.25
Result	Complies			

Mode: 80 MHz / Ant. 1

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5210 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5209.9896	5209.9926	5209.9986	5210.0016
110.00	5209.9898	5209.9928	5209.9988	5210.0018
93.50	5209.9912	5209.9880	5209.9843	5209.9811
Max. Deviation (MHz)	0.0104	0.0120	0.0157	0.0189
Max. Deviation (ppm)	2.00	2.30	3.01	3.63
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5210 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5209.9896	5209.9926	5209.9986	5210.0016
10	5209.9898	5209.9928	5209.9988	5210.0018
20	5209.9912	5209.9880	5209.9843	5209.9811
30	5209.9963	5209.9993	5210.0053	5210.0083
40	5209.9975	5210.0005	5210.0065	5210.0095
45	5210.0026	5210.0056	5210.0116	5210.0146
Max. Deviation (MHz)	0.0104	0.0120	0.0157	0.0189
Max. Deviation (ppm)	2.00	2.30	3.01	3.63
Result	Complies			

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5775 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5774.9917	5774.9947	5775.0007	5775.0037
110.00	5774.9919	5774.9949	5775.0009	5775.0039
93.50	5774.9933	5774.9901	5774.9864	5774.9832
Max. Deviation (MHz)	0.0083	0.0099	0.0136	0.0168
Max. Deviation (ppm)	1.44	1.71	2.35	2.91
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5775 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5774.9741	5774.9740	5774.9741	5774.9742
10	5774.9742	5774.9743	5774.9745	5774.9743
20	5774.9742	5774.9744	5774.9745	5774.9742
30	5774.9745	5774.9745	5774.9746	5774.9747
40	5774.9744	5774.9745	5774.9746	5774.9746
45	5774.9826	5774.9854	5774.9868	5774.9903
Max. Deviation (MHz)	0.0259	0.0260	0.0259	0.0258
Max. Deviation (ppm)	4.48	4.50	4.48	4.47
Result	Complies			

4.9. Antenna Requirements

4.9.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.9.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 22, 2015	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 02, 2014	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 02, 2014	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	Dec. 03, 2014	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 06, 2015	Radiation (O3CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 12, 2015*	Radiation (O3CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Oct. 28, 2014	Radiation (O3CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jul. 21, 2015	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Feb. 24, 2015	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 12, 2015	Radiation (O3CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov. 25, 2014	Radiation (O3CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Nov. 06, 2014	Radiation (O3CH01-CB)
EMI Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8.4GHz	Jan. 21, 2015	Radiation (O3CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz ~ 1 GHz	Nov. 15, 2014	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-40G-1	N/A	1 GHz ~ 40 GHz	Nov. 15, 2014	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-40G-2	N/A	1 GHz ~ 40 GHz	Nov. 15, 2014	Radiation (O3CH01-CB)
Spectrum analyzer	R&S	FSP40	100979	9kHz~40GHz	Dec. 12, 2014	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-7	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-8	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-9	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-6	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 03, 2014	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%