



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / [www.sporton.com.tw](http://www.sporton.com.tw)

## FCC RADIO TEST REPORT

Applicant's company	Xirrus, Inc.
Applicant Address	2101 Corporate Center Drive, Thousand Oaks, CA 91320 USA
FCC ID	SK6-XD2240B
Manufacturer's company	Lite-On Network Communication (Dongguan) Limited
Manufacturer Address	30#Keji Rd., Yin Hu Industrial Area, Qingxi Town, DongGuan City, Guangdong, China

Product Name	Wireless Access Point
Brand Name	XIRRUS, AVAYA
Model No.	XD2240 -1, WAP9144 -1
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Aug. 17, 2015
Final Test Date	Apr. 07, 2016
Submission Type	Original Equipment

### Statement

**Test result included in this report is for the IEEE 802.11n/ac and IEEE 802.11b/g of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB558074 D01 v03r05, KDB 662911 D01 v02r01, KDB644545 D01 v01r02**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies .....	8
3.5. Table for Test Modes .....	9
3.6. Table for Testing Locations.....	10
3.7. Table for Multiple List.....	10
3.8. Table for Supporting Units .....	11
3.9. Table for Parameters of Test Software Setting .....	11
3.10. EUT Operation during Test .....	11
3.11. Duty Cycle .....	12
3.12. Test Configurations .....	13
<b>4. TEST RESULT .....</b>	<b>16</b>
4.1. AC Power Line Conducted Emissions Measurement.....	16
4.2. Maximum Conducted Output Power Measurement.....	20
4.3. Power Spectral Density Measurement .....	22
4.4. 6dB Spectrum Bandwidth Measurement .....	33
4.5. Radiated Emissions Measurement .....	40
4.6. Emissions Measurement .....	59
4.7. Antenna Requirements .....	77
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>78</b>
<b>6. MEASUREMENT UNCERTAINTY.....</b>	<b>79</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A4</b>

## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR582537-03AA	Rev. 01	Initial issue of report	May 17, 2016



## 1. VERIFICATION OF COMPLIANCE

Product Name : Wireless Access Point  
Brand Name : XIRRUS, AVAYA  
Model No. : XD2240 -1, WAP9144 -1  
Applicant : Xirrus, Inc.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Aug. 17, 2015 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink, reading "Sam Chen", is written over a horizontal line.

Sam Chen

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	11.09 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	5.73 dB
4.3	15.247(e)	Power Spectral Density	Complies	5.63 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	3.26 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.18 dB
4.7	15.203	Antenna Requirements	Complies	-

### 3. GENERAL INFORMATION

#### 3.1. Product Details

Items	Description
Product Type	WLAN (4TX, 4RX)
Radio Type	Intentional Transceiver
Power Type	From PoE
Modulation	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n/ac: see the below table
Data Modulation	IEEE 802.11b: DSSS (BPSK / QPSK / CCK) IEEE 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	IEEE 802.11b: DSSS (1/ 2/ 5.5/11) IEEE 802.11g: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n/ac: see the below table
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	IEEE 802.11b: 12.00 MHz IEEE 802.11g: 16.80 MHz IEEE 802.11ac MCS0/Nss1 (VHT20): 19.32 MHz IEEE 802.11ac MCS0/Nss1 (VHT40): 37.00 MHz
Maximum Conducted Output Power	IEEE 802.11b: 24.27 dBm IEEE 802.11g: 24.02 dBm IEEE 802.11ac MCS0/Nss1 (VHT20): 23.99 dBm IEEE 802.11ac MCS0/Nss1 (VHT40): 20.17 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description
Beamforming Function	<input checked="" type="checkbox"/> With beamforming for 802.11n/ac in 2.4GHz/5GHz <input type="checkbox"/> Without beamforming

### Antenna and Band width

Antenna	Four (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V
IEEE 802.11ac	V	V

### IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	4	MCS 0-31
802.11n (HT40)	4	MCS 0-31
802.11ac (VHT20)	4	MCS0-9/Nss1-4
802.11ac (VHT40)	4	MCS0-9/Nss1-4

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).

Then EUT supports HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT supports VHT20, VHT40 in 2.4GHz.

Note 3: Modulation modes consist of below configuration:

HT20/HT40: IEEE 802.11n, VHT20/VHT40: IEEE 802.11ac

## 3.2. Accessories

Others
Wall-mounted rack*1

### 3.3. Table for Filed Antenna

<For Radio 1 >

Ant.	Brand	Model Name	Antenna Type	Connector
1	Liteon	WP8868-E-XS	PIFA Ant.	I-PEX
3	Liteon	WP8868-E-XS	PIFA Ant.	I-PEX
5	Liteon	WP8868-E-XS	PIFA Ant.	I-PEX
7	Liteon	WP8868-E-XS	PIFA Ant.	I-PEX

Ant.	Frequency (MHz) / Antenna Gain (dBi)		
	2412, 2422	2437	2452, 2462
1	2.07	1.35	1.84
3	4.67	3.82	4.52
5	3.68	3.64	3.04
7	4.23	4.10	3.51

Ant.	5GHz Band / Antenna Gain (dBi)	
	Band 1	Band 4
1	0.23	3.09
3	4.19	4.29
5	4.93	4.86
7	4.65	3.94

Frequency Band (MHz)	Correlated Composite Gain (4TX, 1S)	Uncorrelated Composite Gain (4TX, 4S)
2412, 2422	6.99	1.40
2437	7.02	1.36
2452, 2462	7.22	1.68
5150 ~ 5250 (Band 1)	6.10	0.78
5725 ~ 5850 (Band 4)	7.29	1.56



## &lt;For Radio 2&gt;

Ant.	Brand	Model Name	Antenna Type	Connector
2	Liteon	WP8868-E-XS	PIFA Ant.	I-PEX
4	Liteon	WP8868-E-XS	PIFA Ant.	I-PEX
6	Liteon	WP8868-E-XS	PIFA Ant.	I-PEX
8	Liteon	WP8868-E-XS	PIFA Ant.	I-PEX

Ant.	Frequency (MHz) / Antenna Gain (dBi)		
	2412, 2422	2437	2452, 2462
2	1.79	1.19	1.08
4	3.96	3.51	3.06
6	2.93	2.93	3.38
8	2.10	2.49	1.79

Ant.	5GHz Band / Antenna Gain (dBi)	
	Band 1	Band 4
2	1.64	4.60
4	3.02	3.45
6	3.48	4.78
8	3.93	3.69

Frequency Band (MHz)	Correlated Composite Gain (4TX, 1S)	Uncorrelated Composite Gain (4TX, 4S)
2412, 2422	6.01	0.65
2437	5.86	0.22
2452, 2462	5.33	-0.26
5150 ~ 5250 (Band 1)	4.88	-0.30
5725 ~ 5850 (Band 4)	6.98	1.68

## &lt;For Radio 3&gt;

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
9	Liteon	WP8868-E-XS	PIFA Ant.	N/A	3.20

Note: 1. The EUT has three radios.

Radio 1 and Radio 2 supports 2.4GHz WLAN function and 5GHz WLAN function, Radio 3 supports Bluetooth function only.

For Conducted test:

Radio 1 and Radio 2 are the same radios, radio 2 has been evaluated to be the worst case so it's chosen to conduct tests.

Radio 1 and Radio 2 equipped the same type antennas, radio 1 has the higher gain than radio 2 so it's chosen to conduct the gain test.

For Radiated test:

Radio 1 and Radio 2 are the same radios; radio 2 has been evaluated to be the worst case so it's chosen to radiate tests.

2. The EUT has nine antennas.

**For WLAN function (4TX/4RX):**

For Radio 1:

Chain 5, Chain 6, Chain 7 and Chain 8 could transmit/receive simultaneously.


For Radio 2:

Chain 1, Chain 2, Chain 3 and Chain 4 could transmit/receive simultaneously.

**For Bluetooth function (1TX/1RX):**

For Radio 3:

Only Ant. 9 can be used as transmitting/receiving antenna.



### 3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
Power Spectral Density	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
6dB Spectrum Bandwidth	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4
Band Edge Emissions	11b/CCK	1 Mbps	1/6/11	1+2+3+4
	11g/BPSK	6 Mbps	1/6/11	1+2+3+4
	11ac VHT20	MCS0/Nss1	1/6/11	1+2+3+4
	11ac VHT40	MCS0/Nss1	3/6/9	1+2+3+4

Note: 1. VHT20/VHT40 covers HT20/HT40, due to same modulation. The power setting for 802.11n HT20 and HT40 are the same or lower than 802.11ac VHT20 and VHT40.

2. The PoE below are for measurement only, would not be marketed.

Power	Brand	Model No.	FCC ID
PoE	PowerDsine	PD-9001GR/AC	DoC
PoE	H3C	EWPAM1NPoE	N/A
PoE	PowerDsine	PD-7001G	DoC

3. There are two modes of EUT, one is beamforming function, and the other is non-beamforming function for 802.11n/ac. Test results of non-beamforming function was recorded in this report, test results of beamforming function was recorded in Report No.: FR582537-03AB.

The following test modes were performed for all tests:

**For Radiated Emission test<Below 1GHz>:**

Mode 1. EUT Y axis

Mode 2. EUT Z axis

Mode 1 generated the worst test result, so it was recorded in this report.

**For Radiated Emission test<Above 1GHz>:**

The EUT was performed at Y axis and Z axis position for Radiated emission above 1GHz test, and the worst case was found at Y axis. So the measurement will follow this same test configuration.

### 3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	TW0006	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

### 3.7. Table for Multiple List

The brand name and model numbers in the following table are all refer to the identical product.

Brand Name	Model Name	Description
XIRRUS	XD2240 -1	All the design is the same, just for different marketing use.
AVAYA	WAP9144 -1	

From the above models, model: XD2240 -1 was selected as representative model for the test and its data was recorded in this report.

### 3.8. Table for Supporting Units

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
NB*4	DELL	E6430	DoC
Tablet	Samsung	TAB3	DoC
PoE	PowerDsine	PD-9001GR/AC	DoC

For Test Site No: 03CH01-CB<Below 1GHz>

Support Unit	Brand	Model	FCC ID
NB*4	DELL	E4300	DoC
Tablet	Samsung	TAB3	DoC
PoE	PowerDsine	PD-7001G	DoC

For Test Site No: 03CH01-CB<Above 1GHz> and TH01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E4300	DoC
PoE	H3C	EWPAM1NPOE	N/A

### 3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Test Software Version	XirCon-Setup-1.0.2.25					
Mode	Test Frequency (MHz)					
	NCB: 20MHz			NCB: 40MHz		
	2412 MHz	2437 MHz	2462 MHz	2422 MHz	2437 MHz	2452 MHz
802.11b	80	80	80	-	-	-
802.11g	53	80	66	-	-	-
802.11ac MCS0/Nss1 VHT20	58	80	54	-	-	-
802.11ac MCS0/Nss1 VHT40	-	-	-	49	57	52

### 3.10. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

### 3.11. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11b	1.000	1.000	100.00%	0.00	0.01
802.11g	2.054	2.082	98.66%	0.06	0.01
802.11ac MCS0/Nss1 VHT20	1.913	1.942	98.51%	0.07	0.01
802.11ac MCS0/Nss1 VHT40	0.913	0.960	95.10%	0.22	1.10




### 3.12.1. AC Power Line Conduction Emissions Test Configuration






### 3.12.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.0m
2	RJ-45 cable	No	1.5m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	10m

Test Configuration: above 1GHz



Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	RJ-45 cable	No	1m

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	62%
Test Engineer	Deven Huang	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1516	35.97	-19.94	55.91	25.93	10.02	0.02	LINE	Average
2	0.1516	45.31	-20.60	65.91	35.27	10.02	0.02	LINE	QP
3	0.4083	34.93	-12.75	47.68	24.97	9.92	0.04	LINE	Average
4	0.4083	44.16	-13.52	57.68	34.20	9.92	0.04	LINE	QP
5	0.4374	35.80	-11.31	47.11	25.84	9.92	0.04	LINE	Average
6	0.4374	43.46	-13.65	57.11	33.50	9.92	0.04	LINE	QP
7	0.4612	32.74	-13.93	46.67	22.78	9.92	0.04	LINE	Average
8	0.4612	42.48	-14.19	56.67	32.52	9.92	0.04	LINE	QP
9	0.8618	28.51	-17.49	46.00	18.54	9.93	0.04	LINE	Average
10	0.8618	36.62	-19.38	56.00	26.65	9.93	0.04	LINE	QP
11	13.7680	30.08	-19.92	50.00	19.62	10.21	0.25	LINE	Average
12	13.7680	36.79	-23.21	60.00	26.33	10.21	0.25	LINE	QP

Temperature	24°C	Humidity	62%
Test Engineer	Deven Huang	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1582	39.55	-16.01	55.56	29.51	10.02	0.02	NEUTRAL	Average
2	0.1582	47.93	-17.63	65.56	37.89	10.02	0.02	NEUTRAL	QP
3	0.1884	32.99	-21.12	54.11	23.05	9.92	0.02	NEUTRAL	Average
4	0.1884	40.96	-23.15	64.11	31.02	9.92	0.02	NEUTRAL	QP
5	0.4061	36.35	-11.38	47.73	26.39	9.92	0.04	NEUTRAL	Average
6	0.4061	45.12	-12.61	57.73	35.16	9.92	0.04	NEUTRAL	QP
7	0.4444	35.89	-11.09	46.98	25.93	9.92	0.04	NEUTRAL	Average
8	0.4444	44.10	-12.88	56.98	34.14	9.92	0.04	NEUTRAL	QP
9	0.4612	33.52	-13.15	46.67	23.56	9.92	0.04	NEUTRAL	Average
10	0.4612	43.44	-13.23	56.67	33.48	9.92	0.04	NEUTRAL	QP
11	13.6952	30.34	-19.66	50.00	19.88	10.21	0.25	NEUTRAL	Average
12	13.6952	37.48	-22.52	60.00	27.02	10.21	0.25	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

The limit for output power is 30dBm.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

### 4.2.3. Test Procedures

1. Test procedures refer KDB558074 D01 v03r05 section 9.2.3.2 Measurement using a power meter (PM).
2. Multiple antenna systems was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	54%
Test Engineer	Serway Li	Test Date	Oct. 01, 2015

Mode	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
802.11b	2412 MHz	17.77	18.92	17.89	18.06	24.20	30.00	Complies
	2437 MHz	17.74	18.99	17.86	17.94	24.18	30.00	Complies
	2462 MHz	17.87	19.18	17.91	17.88	24.27	30.00	Complies
802.11g	2412 MHz	12.78	14.49	12.85	12.47	19.24	30.00	Complies
	2437 MHz	17.69	19.02	17.58	17.52	24.02	30.00	Complies
	2462 MHz	15.81	17.27	15.96	16.05	22.33	30.00	Complies
802.11ac MCS0/Nss1 VVHT20	2412 MHz	13.67	14.99	13.77	13.84	20.12	30.00	Complies
	2437 MHz	17.49	19.06	17.44	17.66	23.99	30.00	Complies
	2462 MHz	12.85	14.28	12.86	12.77	19.26	30.00	Complies
802.11ac MCS0/Nss1 VHT40	2422 MHz	11.98	12.87	11.89	11.71	18.16	30.00	Complies
	2437 MHz	14.17	14.77	13.81	13.79	20.17	30.00	Complies
	2452 MHz	12.72	13.45	12.92	12.35	18.90	30.00	Complies



### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

#### 4.3.3. Test Procedures

1. Test was performed in accordance with KDB558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .

#### 4.3.4. Test Setup Layout



#### **4.3.5. Test Deviation**

There is no deviation with the original standard.

#### **4.3.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	54%
Test Engineer	Serway Li		

Mode	Frequency	Power Density (dBm/3kHz)					Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3	Chain 4	Total		
802.11b	2412 MHz	-5.25	-4.98	-5.52	-5.50	0.71	7.01	Complies
	2437 MHz	-5.80	-4.28	-4.58	-5.40	1.05	6.98	Complies
	2462 MHz	-4.03	-4.91	-4.98	-5.75	1.15	6.78	Complies
802.11g	2412 MHz	-12.81	-10.91	-13.15	-13.68	-6.48	7.01	Complies
	2437 MHz	-8.38	-7.47	-9.07	-8.16	-2.21	6.98	Complies
	2462 MHz	-10.57	-8.00	-8.71	-8.89	-2.93	6.78	Complies
802.11ac MCS0/Nss1 VHT20	2412 MHz	-11.98	-10.55	-12.11	-11.93	-5.57	7.01	Complies
	2437 MHz	-7.85	-7.96	-8.93	-6.83	-1.81	6.98	Complies
	2462 MHz	-12.73	-11.89	-13.18	-13.71	-6.80	6.78	Complies
802.11ac MCS0/Nss1 VHT40	2422 MHz	-16.49	-16.43	-17.00	-17.57	-10.83	7.01	Complies
	2437 MHz	-15.45	-13.16	-16.08	-15.01	-8.76	6.98	Complies
	2452 MHz	-15.96	-16.46	-16.82	-16.68	-10.45	6.78	Complies

Note: 2412 MHz and 2422 MHz:  $Directional\ Gain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.99\text{dBi}$ , so limit=8-(6.99-6)=7.01 dBm/3kHz.


Note: 2437 MHz:  $Directional\ Gain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 7.02\text{dBi}$ , so limit=8-(7.02-6)=6.98 dBm/3kHz.

Note: 2452 MHz and 2462 MHz:  $Directional\ Gain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 7.22\text{dBi}$ , so limit=8-(7.22-6)=6.78 dBm/3kHz.

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

### Power Density Plot on Configuration IEEE 802.11b / 2412 MHz / Chain 1




Date: 2.OCT.2015 10:31:18

### Power Density Plot on Configuration IEEE 802.11b / 2412 MHz / Chain 2




Date: 2.OCT.2015 10:30:12

### Power Density Plot on Configuration IEEE 802.11b / 2412 MHz / Chain 3




Date: 2.OCT.2015 10:29:21

### Power Density Plot on Configuration IEEE 802.11b / 2412 MHz / Chain 4




Date: 2.OCT.2015 10:28:13

### Power Density Plot on Configuration IEEE 802.11g / 2412 MHz / Chain 1




Date: 2.OCT.2015 10:52:04

### Power Density Plot on Configuration IEEE 802.11g / 2412 MHz / Chain 2




Date: 2.OCT.2015 11:03:31

### Power Density Plot on Configuration IEEE 802.11g / 2412 MHz / Chain 3




Date: 2.OCT.2015 11:04:18

### Power Density Plot on Configuration IEEE 802.11g / 2412 MHz / Chain 4




Date: 2.OCT.2015 11:04:56

### Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 1



Date: 2.OCT.2015 11:48:50


### Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 2



Date: 2.OCT.2015 11:47:44




### Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 3




Date: 2.OCT.2015 11:47:02

### Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 4




Date: 2.OCT.2015 11:45:02

### Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz / Chain 1




Date: 2.OCT.2015 13:33:15

### Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz / Chain 2




Date: 2.OCT.2015 13:33:48

### Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz / Chain 3



Date: 2.OCT.2015 13:34:32

### Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz / Chain 4



Date: 2.OCT.2015 13:35:10

#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

##### 4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth= > 8.1 Option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

#### **4.4.5. Test Deviation**

There is no deviation with the original standard.

#### **4.4.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth


Temperature	23°C	Humidity	54%
Test Engineer	Serway Li		

Mode	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11b	2412 MHz	8.56	12.00	500	Complies
	2437 MHz	8.56	12.00	500	Complies
	2462 MHz	8.08	12.00	500	Complies
802.11g	2412 MHz	6.40	16.08	500	Complies
	2437 MHz	5.04	16.80	500	Complies
	2462 MHz	5.60	16.44	500	Complies
802.11ac MCS0/Nss1 VHT20	2412 MHz	11.04	17.04	500	Complies
	2437 MHz	11.12	19.32	500	Complies
	2462 MHz	11.36	17.16	500	Complies
802.11ac MCS0/Nss1 VHT40	2422 MHz	35.20	36.80	500	Complies
	2437 MHz	35.68	37.00	500	Complies
	2452 MHz	35.20	37.00	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4




Date: 2.OCT.2015 01:53:37

### 99% Occupied Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4




Date: 2.OCT.2015 02:36:02

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4



Date: 2.OCT.2015 01:58:22


### 99% Occupied Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4



Date: 2.OCT.2015 02:32:31



### 6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4




Date: 2.OCT.2015 02:06:57

### 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4




Date: 2.OCT.2015 02:41:16

### 6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4



Date: 2.OCT.2015 02:12:19

### 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 1 + Chain 2 + Chain 3 + Chain 4



Date: 2.OCT.2015 02:47:01

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1 000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



#### **4.5.5. Test Deviation**

There is no deviation with the original standard.

#### **4.5.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25°C	Humidity	56%
Test Engineer	Gino Huang	Configurations	Normal Link
Test Date	Apr. 02, 2016	Test Mode	Mode 1

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.5.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	25℃	Humidity	56%
Test Engineer	Gino Huang	Configurations	Normal Link
Test Mode	Mode 1		


##### Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	30.97	29.06	40.00	-10.94	31.42	1.22	24.91	28.49	203	188 Peak	HORIZONTAL
2	44.55	25.58	40.00	-14.42	35.61	1.30	17.15	28.48	213	223 Peak	HORIZONTAL
3	72.68	25.40	40.00	-14.60	39.80	1.46	12.51	28.37	221	246 Peak	HORIZONTAL
4	154.16	26.04	43.50	-17.46	35.71	1.69	16.57	27.93	241	213 Peak	HORIZONTAL
5	256.98	26.62	46.00	-19.38	32.67	1.99	19.53	27.57	241	247 Peak	HORIZONTAL
6	918.52	35.23	46.00	-10.77	31.62	3.51	27.86	27.76	211	206 Peak	HORIZONTAL



### Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	33.88	36.47	40.00	-3.53	40.53	1.24	23.19	28.49	123	244 Peak	VERTICAL
2	44.55	36.74	40.00	-3.26	46.77	1.30	17.15	28.48	128	222 Peak	VERTICAL
3	72.68	34.29	40.00	-5.71	48.69	1.46	12.51	28.37	143	302 Peak	VERTICAL
4	152.22	39.22	43.50	-4.28	48.84	1.69	16.63	27.94	113	224 Peak	VERTICAL
5	268.62	33.55	46.00	-12.45	39.68	2.03	19.39	27.55	134	234 Peak	VERTICAL
6	800.18	36.32	46.00	-9.68	34.68	3.28	26.70	28.34	118	204 Peak	VERTICAL

### Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 14, 2015		

##### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4824.01	39.46	54.00	-14.54	35.92	5.38	32.55	34.39	145	14	HORIZONTAL Average
2	4824.16	48.39	74.00	-25.61	44.85	5.38	32.55	34.39	145	14	HORIZONTAL Peak

##### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4823.99	35.44	54.00	-18.56	31.90	5.38	32.55	34.39	100	42	VERTICAL Average
2	4824.02	47.50	74.00	-26.50	43.96	5.38	32.55	34.39	100	42	VERTICAL Peak

Temperature	25°C	Humidity	62%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 14, 2015		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4873.96	39.19	54.00	-14.81	35.51	5.40	32.66	34.38	134	5	HORIZONTAL	Average
2	4874.04	48.16	74.00	-25.84	44.48	5.40	32.66	34.38	134	5	HORIZONTAL	Peak

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4873.96	35.24	54.00	-18.76	31.56	5.40	32.66	34.38	144	7	VERTICAL	Average
2	4874.02	47.36	74.00	-26.64	43.68	5.40	32.66	34.38	144	7	VERTICAL	Peak

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 14, 2015		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.02	40.03	54.00	-13.97	36.22	5.42	32.76	34.37	174	5 HORIZONTAL	Average
2	4924.17	48.26	74.00	-25.74	44.45	5.42	32.76	34.37	174	5 HORIZONTAL	Peak

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.88	46.22	74.00	-27.78	42.41	5.42	32.76	34.37	148	5 VERTICAL	Peak
2	4924.04	35.83	54.00	-18.17	32.02	5.42	32.76	34.37	148	5 VERTICAL	Average

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4821.79	33.09	54.00	-20.91	29.55	5.38	32.55	34.39	163	263	HORIZONTAL	Average
2	4824.55	47.69	74.00	-26.31	44.15	5.38	32.55	34.39	163	263	HORIZONTAL	Peak

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4821.68	33.25	54.00	-20.75	29.71	5.38	32.55	34.39	139	204	VERTICAL	Average
2	4823.18	46.13	74.00	-27.87	42.59	5.38	32.55	34.39	139	204	VERTICAL	Peak

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4872.10	33.61	54.00	-20.39	29.93	5.40	32.66	34.38	180	236	HORIZONTAL Average
2	4872.84	46.40	74.00	-27.60	42.72	5.40	32.66	34.38	180	236	HORIZONTAL Peak

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4872.10	33.76	54.00	-20.24	30.08	5.40	32.66	34.38	164	318	VERTICAL Average
2	4873.02	46.85	74.00	-27.15	43.17	5.40	32.66	34.38	164	318	VERTICAL Peak

Temperature	25°C	Humidity	62%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4921.67	46.55	74.00	-27.45	42.76	5.42	32.74	34.37	179	300	HORIZONTAL Peak
2	4922.12	33.62	54.00	-20.38	29.83	5.42	32.74	34.37	179	300	HORIZONTAL Average

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4921.61	33.42	54.00	-20.58	29.63	5.42	32.74	34.37	152	148	VERTICAL Average
2	4924.61	46.18	74.00	-27.82	42.37	5.42	32.76	34.37	152	148	VERTICAL Peak

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.31	33.33	54.00	-20.67	29.79	5.38	32.55	34.39	182	194	HORIZONTAL	Average
2	4823.38	45.83	74.00	-28.17	42.29	5.38	32.55	34.39	182	194	HORIZONTAL	Peak

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.86	34.37	54.00	-19.63	30.83	5.38	32.55	34.39	166	82	VERTICAL	Average
2	4824.61	47.65	74.00	-26.35	44.11	5.38	32.55	34.39	166	82	VERTICAL	Peak



Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.83	34.08	54.00	-19.92	30.40	5.40	32.66	34.38	161	51 HORIZONTAL	Average
2	4874.02	46.06	74.00	-27.94	42.38	5.40	32.66	34.38	161	51 HORIZONTAL	Peak

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.27	46.02	74.00	-27.98	42.34	5.40	32.66	34.38	135	103 VERTICAL	Peak
2	4873.38	33.12	54.00	-20.88	29.44	5.40	32.66	34.38	135	103 VERTICAL	Average

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.06	32.81	54.00	-21.19	29.02	5.42	32.74	34.37	196	250	HORIZONTAL Average
2	4923.19	45.70	74.00	-28.30	41.91	5.42	32.74	34.37	196	250	HORIZONTAL Peak

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.66	32.95	54.00	-21.05	29.14	5.42	32.76	34.37	159	321	VERTICAL Average
2	4924.66	46.36	74.00	-27.64	42.55	5.42	32.76	34.37	159	321	VERTICAL Peak

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4844.43	32.33	54.00	-21.67	28.73	5.39	32.60	34.39	152	190	HORIZONTAL Average
2	4844.66	45.17	74.00	-28.83	41.57	5.39	32.60	34.39	152	190	HORIZONTAL Peak

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4843.11	32.34	54.00	-21.66	28.74	5.39	32.60	34.39	175	151	VERTICAL Average
2	4844.81	45.45	74.00	-28.55	41.85	5.39	32.60	34.39	175	151	VERTICAL Peak

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4873.87	45.90	74.00	-28.10	42.22	5.40	32.66	34.38	176	162	HORIZONTAL	Peak
2	4873.94	33.17	54.00	-20.83	29.49	5.40	32.66	34.38	176	162	HORIZONTAL	Average

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4873.09	33.13	54.00	-20.87	29.45	5.40	32.66	34.38	149	108	VERTICAL	Average
2	4874.83	46.12	74.00	-27.88	42.44	5.40	32.66	34.38	149	108	VERTICAL	Peak

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4903.92	32.71	54.00	-21.29	28.97	5.41	32.71	34.38	152	129	HORIZONTAL	Average
2	4904.90	45.45	74.00	-28.55	41.71	5.41	32.71	34.38	152	129	HORIZONTAL	Peak

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4904.25	32.69	54.00	-21.31	28.95	5.41	32.71	34.38	171	295	VERTICAL	Average
2	4904.70	46.03	74.00	-27.97	42.29	5.41	32.71	34.38	171	295	VERTICAL	Peak

#### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Emissions Measurement

### 4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (30dBc in any 100 kHz bandwidth emission)	100 kHz / 300 kHz for Peak

### 4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.

#### **4.6.4. Test Setup Layout**

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

#### **4.6.5. Test Deviation**

There is no deviation with the original standard.

#### **4.6.6. EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11b CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 14, 2015		

##### Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2387.25	50.81	54.00	-3.19	19.16	3.73	27.92	0.00	224	66	HORIZONTAL	Average
2	2389.13	62.29	74.00	-11.71	30.64	3.73	27.92	0.00	224	66	HORIZONTAL	Peak
3	2413.01	113.54			81.90	3.75	27.89	0.00	224	66	HORIZONTAL	Peak
4	2413.74	110.81			79.17	3.75	27.89	0.00	224	66	HORIZONTAL	Average

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2389.13	47.12	54.00	-6.88	15.47	3.73	27.92	0.00	232	318	HORIZONTAL	Average
2	2390.00	59.60	74.00	-14.40	27.95	3.73	27.92	0.00	232	318	HORIZONTAL	Peak
3	2436.13	111.97			80.33	3.77	27.87	0.00	232	318	HORIZONTAL	Average
4	2436.42	114.66			83.02	3.77	27.87	0.00	232	318	HORIZONTAL	Peak
5	2484.95	47.13	54.00	-6.87	15.49	3.82	27.82	0.00	232	318	HORIZONTAL	Average
6	2499.99	59.81	74.00	-14.19	28.18	3.83	27.80	0.00	232	318	HORIZONTAL	Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

##### Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2461.13	114.89			83.26	3.79	27.84	0.00	249	316	HORIZONTAL	Peak
2	2461.28	112.19			80.56	3.79	27.84	0.00	249	316	HORIZONTAL	Average
3	2487.84	62.86	74.00	-11.14	31.22	3.82	27.82	0.00	249	316	HORIZONTAL	Peak
4	2488.57	50.44	54.00	-3.56	18.80	3.82	27.82	0.00	249	316	HORIZONTAL	Average

Item 1, 2 are the fundamental frequency at 2462 MHz.



Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Sep. 15, 2015		

#### Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2389.42	51.24	54.00	-2.76	19.59	3.73	27.92	0.00	182	305	HORIZONTAL Average
2	2389.86	73.71	74.00	-0.29	42.06	3.73	27.92	0.00	182	305	HORIZONTAL Peak
3	2407.95	112.29			80.64	3.75	27.90	0.00	182	305	HORIZONTAL Peak
4	2409.11	101.98			70.33	3.75	27.90	0.00	182	305	HORIZONTAL Average

Item 3, 4 are the fundamental frequency at 2412 MHz.

#### Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2387.68	48.96	54.00	-5.04	17.31	3.73	27.92	0.00	220	314	HORIZONTAL Average
2	2388.55	65.09	74.00	-8.91	33.44	3.73	27.92	0.00	220	314	HORIZONTAL Peak
3	2434.40	106.23			74.59	3.77	27.87	0.00	220	314	HORIZONTAL Average
4	2434.68	116.36			84.72	3.77	27.87	0.00	220	314	HORIZONTAL Peak
5	2486.39	66.19	74.00	-7.81	34.55	3.82	27.82	0.00	220	314	HORIZONTAL Peak
6	2486.97	47.57	54.00	-6.43	15.93	3.82	27.82	0.00	220	314	HORIZONTAL Average

Item 3, 4 are the fundamental frequency at 2437 MHz.

#### Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2460.84	113.17			81.54	3.79	27.84	0.00	209	65	HORIZONTAL Peak
2	2461.13	102.78			71.15	3.79	27.84	0.00	209	65	HORIZONTAL Average
3	2483.50	53.42	54.00	-0.58	21.78	3.82	27.82	0.00	209	65	HORIZONTAL Average
4	2483.50	72.95	74.00	-1.05	41.31	3.82	27.82	0.00	209	65	HORIZONTAL Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Aug. 17, 2015		

#### Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2389.71	53.82	54.00	-0.18	22.17	3.73	27.92	0.00	122	44	HORIZONTAL Average
2	2389.71	73.34	74.00	-0.66	41.69	3.73	27.92	0.00	122	44	HORIZONTAL Peak
3	2414.89	101.27			69.62	3.76	27.89	0.00	122	44	HORIZONTAL Average
4	2420.10	112.75			81.10	3.76	27.89	0.00	122	44	HORIZONTAL Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

#### Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2389.71	50.15	54.00	-3.85	18.50	3.73	27.92	0.00	102	44	HORIZONTAL Average
2	2390.00	67.89	74.00	-6.11	36.24	3.73	27.92	0.00	102	44	HORIZONTAL Peak
3	2429.76	106.85			75.21	3.76	27.88	0.00	102	44	HORIZONTAL Average
4	2434.68	117.22			85.58	3.77	27.87	0.00	102	44	HORIZONTAL Peak
5	2484.66	66.71	74.00	-7.29	35.07	3.82	27.82	0.00	102	44	HORIZONTAL Peak
6	2484.95	49.87	54.00	-4.13	18.23	3.82	27.82	0.00	102	44	HORIZONTAL Average

Item 3, 4 are the fundamental frequency at 2437 MHz.

#### Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2464.89	102.97			71.33	3.80	27.84	0.00	105	47	HORIZONTAL Average
2	2465.18	113.34			81.70	3.80	27.84	0.00	105	47	HORIZONTAL Peak
3	2484.80	49.92	54.00	-4.08	18.28	3.82	27.82	0.00	105	47	HORIZONTAL Average
4	2485.15	73.60	74.00	-0.40	41.96	3.82	27.82	0.00	105	47	HORIZONTAL Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3, 6, 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Date	Aug. 17, 2015		

### Channel 3

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2389.71	53.81	54.00	-0.19	22.16	3.73	27.92	0.00	103	44	HORIZONTAL Average
2	2390.00	69.42	74.00	-4.58	37.77	3.73	27.92	0.00	103	44	HORIZONTAL Peak
3	2415.05	108.40	74.00	34.40	76.75	3.76	27.89	0.00	103	44	HORIZONTAL Peak
4	2429.53	98.64	54.00	44.64	67.00	3.76	27.88	0.00	103	44	HORIZONTAL Average

Item 3, 4 are the fundamental frequency at 2422 MHz.

### Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2389.42	53.82	54.00	-0.18	22.17	3.73	27.92	0.00	100	48	HORIZONTAL Average
2	2389.42	70.85	74.00	-3.15	39.20	3.73	27.92	0.00	100	48	HORIZONTAL Peak
3	2429.47	110.63			78.99	3.76	27.88	0.00	100	48	HORIZONTAL Peak
4	2429.76	101.03			69.39	3.76	27.88	0.00	100	48	HORIZONTAL Average
5	2484.66	52.71	54.00	-1.29	21.07	3.82	27.82	0.00	100	48	HORIZONTAL Average
6	2484.66	72.66	74.00	-1.34	41.02	3.82	27.82	0.00	100	48	HORIZONTAL Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

### Channel 9

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2385.43	61.37	74.00	-12.63	29.72	3.73	27.92	0.00	101	43	HORIZONTAL Peak
2	2389.77	48.50	54.00	-5.50	16.85	3.73	27.92	0.00	101	43	HORIZONTAL Average
3	2464.74	100.09			68.45	3.80	27.84	0.00	101	43	HORIZONTAL Average
4	2465.02	110.14			78.50	3.80	27.84	0.00	101	43	HORIZONTAL Peak
5	2484.71	51.45	54.00	-2.55	19.81	3.82	27.82	0.00	101	43	HORIZONTAL Average
6	2484.71	73.60	74.00	-0.40	41.96	3.82	27.82	0.00	101	43	HORIZONTAL Peak

Item 3, 4 are the fundamental frequency at 2452 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


# For Emission not in Restricted Band

## Plot on Configuration IEEE 802.11b / Reference Level




Date: 18.SEP.2015 01:10:27

## Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 18.SEP.2015 01:12:43

### Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 18.SEP.2015 01:13:41

### Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 18.SEP.2015 01:15:03

# Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 18.SEP.2015 01:15:38

### Plot on Configuration IEEE 802.11g / Reference Level



Date: 18.SEP.2015 01:18:11


### Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)



Date: 18.SEP.2015 01:21:36




### Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)



Date: 18.SEP.2015 01:22:06


### Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)



Date: 18.SEP.2015 01:23:22




# Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 18.SEP.2015 01:23:54

### Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Reference Level




Date: 18.SEP.2015 01:26:44

### Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 18.SEP.2015 01:28:34

### Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 18.SEP.2015 01:29:16

### Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 18.SEP.2015 01:30:40

# Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 18.SEP.2015 01:31:17

### Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Reference Level




Date: 18.SEP.2015 01:34:08

### Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 18.SEP.2015 01:36:03

### Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 18.SEP.2015 01:36:33

### Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 9 / 30MHz~2400MHz (down 30dBc)



Date: 18.SEP.2015 01:37:50

# Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 9 / 2500MHz~26500MHz (down 30dBc)



Date: 18.SEP.2015 01:38:18

## **4.7. Antenna Requirements**

### **4.7.1. Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### **4.7.2. Antenna Connector Construction**

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.



## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.45GHz	Jan. 27, 2016	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 08, 2015	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 23, 2015	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	May 25, 2015	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	37880	20MHz ~ 2GHz	Sep. 03, 2015	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 16, 2016*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Oct. 28, 2014	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jul. 21, 2015	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Mar. 15, 2016	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 12, 2015	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov. 25, 2014	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Nov. 06, 2014	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Oct. 27, 2015	Radiation (03CH01-CB)
EMI Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8.4GHz	Jan. 27, 2016	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz ~ 1 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-1	N/A	1 GHz ~ 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-2	N/A	1 GHz ~ 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100979	9kHz~40GHz	Dec. 12, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-7	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-8	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-9	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-6	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 03, 2014	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

"\*" Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

## 6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.2 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%