



CM Series mounted on ceiling

New - Ceiling Tile Frame Mount Option!

Ceiling Mount Omni Antenna (Pat.Pnd.)

For 2.4 - 6 GHz

- Antennas provide uniform omni coverage for indoor use
- Models available for WiFi, U-NII, Bluetooth and 802.11 applications
- Mounting kit includes all hardware needed
- Unique design provides high performance at an economical price

Mobile Mark's line of Ceiling Mount omnidirectional antennas are perfect for next generation wireless inbuilding applications including WLAN, Telemetry, and Hotspot. They have features that make them invaluable, solving many of the problems normally associated with these higher frequencies.

These antennas use a design that incorporates a quarter-wave on a groundplane which enhances the peak lobes of these antennas. This unique design provides significant improvements in efficiency while being very economical. These antennas maintain an omni pattern in the horizontal plane while VSWR performance is maintained across the operating bandwidth. A dual band (2.4 & 5.5 GHz) model provides operation on the two popular bands simultaneously (1 coax feed for both bands).

The CM Series antennas have a very low profile that add to their attractive appearance; only 3.5 inches diameter (89 mm), and less than 1 1/2" high (38 mm).

The antennas mount to any ceiling that allows the cable to be routed above; dropped ceilings are perfect for this type of install. The antennas come complete with all the necessary hardware required for installation; including a hole template and 3 each of mounting screws and wall anchors.

The antenna is provided with a white ABS radome and 6 inches (152 mm) of RF-195 cable and SMA-male connector. For ISM, Part 15 compliant connectors are available (reverse polarized), please consult factory.

Model Numbers

Model	Freq.(MHz)	Applications
CM2-2400	2400-2485	802.11b/g, WLAN, ISM
CM2-5500	5000-6000	802.11a, U-NII, ISM
CM2-2400/5500	Both Bands	For dual band radios

For special frequencies or configuration, please consult factory for latest information.

Specifications

Frequency:	See above	Dimensions:	3.5"D x 1.5"H (89 mm x 38 mm)
Gain:		Weight:	1.0 lbs (0.5 kg)
CM2-2400	2.5 dBi	Mounting:	Ceiling Mount; hardware included
CM2-5500	2.5 dBi	Termination:	6" RF-195 (152 mm), male SMA
CM2-2400/5500	2.5 dBi	Options:	Part 15 Reverse Connectors
Bandwidth @2:1 SWR:	See freq range	For special configurations, please consult factory	
Nominal Impedance:	50 ohms		
Max. Power (continuous):	5 watts		
Beamwidth (-3 dB point):	70 degrees		
Radome Material:	ABS		