

## **Certification Exhibit**

**FCC ID: SK9AMI-3  
IC: 864G-AMI3**

**FCC Rule Part: 15.247  
IC Radio Standards Specification: RSS-210**

**ACS Report Number: 08-0028**

**Manufacturer: Itron Electricity Metering, Inc.  
Model: C2SOD**

## **RF Exposure**

**General Information:**

Applicant: Itron Electricity Metering, Inc.  
 ACS Project: 08-0028  
 FCC ID: SK9AMI-3  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure  
 Simultaneous Transmission: Yes

**Technical Information 900 MHz**

Antenna Type: Embedded Quarter Wave Slot  
 Antenna Gain: 0dBi  
 Transmitter Radiated Power: 21.74dBm  
 Maximum System EIRP: 21.74dBm

**Technical Information 2400 MHz**

Antenna Type: Embedded Quarter Wave Slot  
 Antenna Gain: 0dBi  
 Transmitter Radiated Power: 17.25dBm  
 Maximum System EIRP: 17.25dBm

**MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm <sup>2</sup> )	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )
902.25	21.74	0.60	149.28	0	1.000	20	0.030
2405	17.25	1.00	53.09	0	1.000	20	0.011

**Summation of Power Densities – Simultaneous Transmissions**

This device contains multiple transmitters which can operate simultaneously and therefore the maximum RF exposure is determined by the summation of power densities. The 900 MHz LAN and 2.4GHz Zigbee radio can operate simultaneously there it is appropriate to include both of those power density values in the same summation of power densities.

The maximum power density is calculated by a summation of power densities for each simultaneous transmission combination as follows:

900MHz LAN: 0.030 (mW/cm<sup>2</sup>)  
 2.4GHz Zigbee: 0.011 (mW/cm<sup>2</sup>)  
**TOTAL: 0.041 (mW/cm<sup>2</sup>)**

**Installation Guidelines**

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

**RF Exposure**

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

**Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.