

Produkte
Products

Prüfbericht - Nr.: 14032249 001		Seite 1 von 10	
<i>Test Report No.:</i>		<i>Page 1 of 10</i>	
Auftraggeber: <i>Client:</i>	StickNFind LLC 3201 Griffin Road Dania Beach, FL 33312 USA		
Gegenstand der Prüfung: <i>Test Item:</i>	Bluetooth Low Energy Device		
Bezeichnung: <i>Identification:</i>	StickNFind	Serien-Nr.: <i>Serial No.:</i>	Engineering sample
Wareneingangs-Nr.: <i>Receipt No.:</i>	00130215059-001	Eingangsdatum: <i>Date of Receipt:</i>	15.02.2013
Prüfart: <i>Testing Location:</i>	TÜV Rheinland Hong Kong Ltd. 8/F, First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong		
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of test item at delivery:</i>	Test sample(s) is/are not damaged and suitable for testing.		
Prüfgrundlage: <i>Test Specification:</i>	FCC Part 15 Subpart C ANSI C63.4-2003 CISPR 22:1997		
Prüfresultat: <i>Test Results:</i>	Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and passed .		
Prüflaboratorium: <i>Testing Laboratory:</i>	TÜV Rheinland Hong Kong Ltd. 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay Kowloon, Hong Kong		
geprüft/ tested by:		kontrolliert/ reviewed by:	
16.04.2013	Mika Chan Senior Project Engineer	16.04.2013	Sharon Li Section Manager
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>
Sonstiges: Other Aspects		FCCID: SL6-STICKNFIND	
Abkürzungen:	P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet	Abbreviations:	P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i></p>			

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	3
Manufacturers declarations	3
Product function and intended use	4
Submitted documents.....	4
Remark	4
List of Test and Measurement Instruments.....	5
Results FCC Part 15 – Subpart C	6
Subclause 15.203 – Antenna Information	Pass..... 6
Subclause 15.204 – Antenna Information	Pass..... 6
Subclause 15.207 – Disturbance Voltage on AC Mains.....	N/A..... 6
Subclause 15.247 (a)(2) – 6dB Bandwidth Measurement.....	Pass..... 6
Subclause 15.247 (b)(3) – Maximum Peak Output Power	Pass..... 7
Subclause 15.247 (d) – Spurious Conducted Emissions	Pass..... 7
Subclause 15.247 (d) – Spurious Radiated Emissions.....	Pass..... 8
Subclause 15.247 (d) – Band Edge Emissions.....	Pass..... 9
Subclause 15.205 – Band edge compliance of radiated emissions	Pass..... 10
Subclause 15.247 (e) – Power Spectral Density	Pass..... 10
Appendix 1 – Test protocols	18 pages
Appendix 2 – Test setup	2 pages
Appendix 3 – Photo documentation	5 pages
Appendix 4 – Product documentation	8 pages

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	GFSK
Number of channels	40
Channel separation	2 MHz
Type of antenna	Disk Monopole (Buzzer Disk)
Antenna gain (dBi)	-10
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	V _{nom} : 3.0V (CR 2016)
Independent Operation Modes	Transmitting Receiving

Product function and intended use

The test item is a Bluetooth Proximity Tag based on the Bluetooth Low Energy technology.

It offers the following functions:

- Virtual Leash.
- Find It Feature
- Radar Feature

For details, please refer to the user manual.

Submitted documents

Circuit Diagram
Block Diagram
Bill of material
User manual

Remark

Special accessories and auxiliary equipment

-

List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

Equipment	Manufacturer	Type	S/N	Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	25-May-13
Test Receiver	R & S	ESU40	100190	26-May-13
Bi-conical Antenna	R & S	HK116	100242	05-May-13
Log Periodic Antenna	R & S	HL223	841516/020	06-May-13
Coaxial cable 50ohm	Rosenberger	RTK081-05S-05S-10m	LA2-001-10M / 001	15-Nov-13
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	3950M00241	03-Oct-13
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	28-Oct-13
Horn Antenna	EMCO	3115	9002-3351	11-May-13
Double-Ridge Waveguide Horn	EMCO	3116	2616	11-May-13
Active Loop Antenna	EMCO	6502	9107-2651	21-Jun-13
FSP 30 Spectrum Analyser	R & S	FSP 30	100007	17-Sep-13

Results FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information		Pass
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	Permanent attached antenna	
Verdict:	Pass	

Subclause 15.204 – Antenna Information		Pass
Requirement:	Provide information for every antenna proposed for the use with the EUT	
Results:	a) Antenna type: Disk Monopole (Buzzer Disk) b) Manufacturer and model no: N.A. c) Gain with reference to an isotropic radiator: -10 dBi	
Verdict:	Pass	

Subclause 15.207 – Disturbance Voltage on AC Mains		N/A
The EUT is powered by battery.		

Subclause 15.247 (a)(2) – 6dB Bandwidth Measurement		Pass		
Requirement:	Systems using digital modulation techniques may operate in the 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz. There is no requirement for hybrid system to comply with the 500 KHz minimum bandwidth normally associated with a DTS transmission.			
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode, hopping off Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100KHz/ 300KHz Supply voltage : 3.0 VDC from Battery Temperature : 23°C Humidity : 50%				
Results: For test protocols please refer to Appendix 1, page 2-3.				
Channel	Channel frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Verdict
LOW	2402	0.720	0.5	Pass
MID	2440	0.726	0.5	Pass
HIGH	2480	0.702	0.5	Pass

Subclause 15.247 (b)(3) – Maximum Peak Output Power				Pass
Requirement: For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850MHz bands: 1 Watt (30dBm)				
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode, hopping off Port of testing : Temporary antenna port Detector : Peak RBW/VBW : >=DTS BW / >=3xRBW Span : >=RBW Supply voltage : 3.0 VDC from Battery Temperature : 23°C Humidity : 50%				
Results: For test protocols please refer to Appendix 1, page 4-5.				
Channel	Channel frequency (MHz)	Peak Power Output (dBm)	Limit (dBm)	Verdict
LOW	2402	-0.30	30	Pass
MID	2440	0.40	30	Pass
HIGH	2480	0.84	30	Pass

Subclause 15.247 (d) – Spurious Conducted Emissions				Pass	
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2440MHz, 2480MHz), hopping off Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 3.0 VDC from Battery Temperature : 23 °C Humidity : 50 %					
Requirement:		In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.			
Results:		There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(d). For test protocols refer to Appendix 1, page 6-7.			
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	4800	-34.55	-1.09	33.46	Pass
2440	4850	-36.96	0.52	37.48	Pass
2480	4950	-42.22	-0.08	42.14	Pass

Subclause 15.247 (d) – Spurious Radiated Emissions		Pass
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode (2402MHz, 2440MHz, 2480MHz), hopping off Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 1 MHz for f > 1 GHz Supply voltage : 3.0 VDC from Battery Temperature : 23°C Humidity : 50%		
Requirement:	In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in section15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).	
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.	
Tx frequency 2402MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4804.519	52.67	74.0 / P
4804.958	35.39	54.0 / A
Tx frequency 2402MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4804.054	49.94	74.0 / P
4803.878	34.45	54.0 / A
Tx frequency 2440MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4880.416	48.55	74.0 / P
4879.855	33.92	54.0 / A
7321.057	54.98	74.0 / P
7319.775	37.75	54.0 / A
Tx frequency 2440MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No Peak found	-	74.0 / P
No Peak found	-	54.0 / A
Tx frequency 2480MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4959.503	50.52	74.0 / P
4959.919	35.78	54.0 / A

7440.641	61.57	74.0 / P
7439.839	39.77	54.0 / A
Tx frequency 2480MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No Peak found	-	74.0 / P
No Peak found	-	54.0 / A

Subclause 15.247 (d) – Band Edge Emissions		Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 3.0 VDC from Battery Temperature : 23°C Humidity : 50%		
Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Results:	There is no peak found outside any 100 kHz bandwidth of the operating frequency band. For test protocols refer to Appendix 1, page 8.	

Subclause 15.205 – Band edge compliance of radiated emissions		Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 1 MHz Supply voltage : 3.0 VDC from Battery Temperature : 23°C Humidity : 50%		
Requirement:	Radiated emissions which fall in the restricted bands, as defined in 15.205 (a), must also comply with the radiated emission limits specified in 15.209(a).	
Results:	There is no peak found in the restricted bands. For test protocols refer to Appendix 1, page 9-16.	

Subclause 15.247 (e) – Power Spectral Density		Pass	
Requirement:	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.		
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2440MHz, 2480MHz), hopping off Port of testing : Temporary antenna port Detector : Peak RBW/VBW : >=3 KHz / >=>=3xRBW span : >=1.5 x DTS BW Supply voltage : 3.0 VDC from Battery Temperature : 23°C Humidity : 50%			
Results:	For test protocols please refer to Appendix 1, page 17-18.		
Operating frequency (MHz)	Power density (dBm)	Limit (dBm)	Verdict
2402	-11.46	8.0	Pass
2440	-11.75	8.0	Pass
2480	-11.32	8.0	Pass
Verdict:	Pass		