



Certification Exhibit

FCC ID: SL6KEYFOB

FCC Rule Part: 47 CFR Part 2.1093

Project Number: 72153290

Manufacturer: HID Global BluVision, Inc.
Model: BEEKSKF

RF Exposure

General Information:

Applicant: HID Global BluVision, Inc.
Device Category: Portable
Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Printed Inverted F Antenna
Antenna Gain: 0 dBi
Maximum Transmitter Conducted Power: -1.9 dBm, 0.646 mW
Maximum System EIRP: -1.9 dBm, 0.646 mW
Exposure Conditions: Body Worn

Justification for SAR Test Exclusion:

Standalone SAR Test Exclusion:

Per KDB 447498 D01 General RF Exposure Guidance v06, the standalone 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \left[\sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

$$= (0.646 / 5) \cdot (\sqrt{2.480}) = 0.203$$

0.203 < 3.0

Standalone SAR test exclusion is applied.