

VERIFICATION OF COMPLIANCE

- **Equipment** : Industrial Wi-Fi 6 wireless access points /
Industrial Wi-Fi 6 wireless clients
- Model No.** : AWK-1161C-UN, AWK-1165C-UN, AWK-1161C-UN-T,
AWK-1165C-UN-T, AWK-1161C-US, AWK-1165C-US,
AWK-1161C-US-T, AWK-1165C-US-T, AWK-1161A-UN,
AWK-1165A-UN, AWK-1161A-UN-T, AWK-1165A-UN-T,
AWK-1161A-US, AWK-1165A-US, AWK-1161A-US-T,
AWK-1165A-US-T
- Applicant** : Moxa Inc.
No. 1111, Heping Rd., Bade Dist., Taoyuan City 334004, Taiwan

**I HEREBY****DECLARE THAT :**

The equipment was **Passed** the test performed according to
47 CFR FCC Part 2 Subpart J, section 2.1091

The test was carried out on **Jan. 11, 2024** at **SPORTON INTERNATIONAL INC.**
Hsinhua Laboratory.

A handwritten signature in blue ink that reads 'Jackson Tsai'. Below the signature is a horizontal line, and under the line, the name 'Jackson Tsai' is printed in a black, sans-serif font.

Jackson Tsai

Radio Exposure Evaluation Report

FCC ID : SLE-AWK1160

Equipment : Industrial Wi-Fi 6 wireless access points /
Industrial Wi-Fi 6 wireless clients

Brand Name : MOXA

Model Name : AWK-1161C-UN, AWK-1165C-UN,
AWK-1161C-UN-T, AWK-1165C-UN-T,
AWK-1161C-US, AWK-1165C-US,
AWK-1161C-US-T, AWK-1165C-US-T,
AWK-1161A-UN, AWK-1165A-UN,
AWK-1161A-UN-T, AWK-1165A-UN-T,
AWK-1161A-US, AWK-1165A-US,
AWK-1161A-US-T, AWK-1165A-US-T

EUT Rated Voltage Range : DC 9V ~ 30V

Applicant : Moxa Inc.
No. 1111, Heping Rd., Bade Dist., Taoyuan City
334004, Taiwan

Manufacturer : Moxa Inc.
No. 1111, Heping Rd., Bade Dist., Taoyuan City
334004, Taiwan

Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Nov. 23, 2023, and testing was started from Dec. 19, 2023 and completed on Jan. 11, 2024. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION5

1.1 Information.....5

1.2 Applicable Standards8

1.3 Testing Location8

2 MAXIMUM PERMISSIBLE EXPOSURE9

2.1 Limit of Maximum Permissible Exposure9

2.2 RF Exposure Exempt Measurement10

2.3 Multiple RF Sources Exposure11

2.4 MPE Calculation Method12

2.5 Calculated Result and Limit.....13

Photographs of EUT V01



History of this test report

Report No.	Version	Description	Issued Date
FA3N2221	01	Initial issue of report	Feb. 21, 2024



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Ryan Hsiao

Report Producer: Amber Chiu



1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Support
1	MOXA	ANT-WDB-ARM-02	Dipole	Reverse SMA	2.4GHz+5GHz
2	MOXA	ANT-WDB-ARM-0202	Dipole	Reverse SMA	2.4GHz+5GHz
3	MOXA	ANT-WSB-AHRM-05-1.5m	Dipole	Reverse SMA	2.4GHz
4	MOXA	MAT-WDB-CA-RM-2-0205	Dipole	Reverse SMA	2.4GHz+5GHz
5	MOXA	MAT-WDB-DA-RM-2-0203-1m	Dipole	Reverse SMA	2.4GHz+5GHz

Ant.	Gain (dBi)	
	2.4G	5G
1	2	2
2	2	2
3	5	-
4	2	5
5	2	3



Note 1: The EUT has five groups of antenna, each group is 2 antennas.

Note 2: EUT can match with above antennas for using. Higher gain in each group of antenna was used to perform the worst configuration and result of that was recorded as the final test result.

For 2.4GHz function:

For IEEE 802.11 b/g/VHT/ax mode (2TX/2RX)

Ant. 1, Ant 2, Ant 3, Ant 4, Ant 5 could transmit/receive simultaneously.

For 5GHz function:

For IEEE 802.11 a/n/ac/ax mode (2TX/2RX)

Ant. 1, Ant 2, Ant 4, Ant 5 could transmit/receive simultaneously

1.1.3 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model name	Model difference		
	client / AP	10/100/1000 BaseT(X) port	operating temperature
AWK-1161C-US	client	1	-25 to 60°C
AWK-1161C-US-T	client	1	-40 to 75°C
AWK-1161C-UN	client	1	-25 to 60°C
AWK-1161C-UN-T	client	1	-40 to 75°C
AWK-1161A-US	AP	1	-25 to 60°C
AWK-1161A-US-T	AP	1	-40 to 75°C
AWK-1161A-UN	AP	1	-25 to 60°C
AWK-1161A-UN-T	AP	1	-40 to 75°C
AWK-1165C-US	client	5	-25 to 60°C
AWK-1165C-US-T	client	5	-40 to 75°C
AWK-1165C-UN	client	5	-25 to 60°C
AWK-1165C-UN-T	client	5	-40 to 75°C
AWK-1165A-US	AP	5	-25 to 60°C
AWK-1165A-US-T	AP	5	-40 to 75°C
AWK-1165A-UN	AP	5	-25 to 60°C
AWK-1165A-UN-T	AP	5	-40 to 75°C

From the above models, model: AWK-1165C-US-T was selected as representative model for the test and its data was recorded in this report.

Note 1 : Client, AP mode and band: All these features are defined by software, to fulfil different condition of use.

Note 2 : LAN Ports: For different condition of use, product supports 1 LAN port or 5 LAN ports, it depends on product equipped with I/O board or not.

Note 3 : Operating temperature: Model name with -T character, product equipped with heatsink on surface to ensure better cooling capacity.



1.1.4 Accessories

Accessories				
Antenna 1*2	Brand Name	MOXA	Model Name	ANT-WDB-ARM-02
Antenna 2*2	Brand Name	MOXA	Model Name	ANT-WDB-ARM-0202
Antenna 3*2	Brand Name	MOXA	Model Name	ANT-WSB-AHRM-05-1.5m
Antenna 4*2	Brand Name	MOXA	Model Name	MAT-WDB-CA-RM-2-0205
Antenna 5*2	Brand Name	MOXA	Model Name	MAT-WDB-DA-RM-2-0203-1m

Reminder: Regarding to more detail and other information, please refer to user manual.



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

1.3 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory		
<input checked="" type="checkbox"/>	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.) TEL: 886-3-327-3456 FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.		
<input type="checkbox"/>	Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: 886-3-318-0787 FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.		



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040 f (mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060 (mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920 R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450 R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128 R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ <p>f is in MHz; R is in m; $R > \lambda / 2\pi$</p>



2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	<p>The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)</p>
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ <p>a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added.</p> <p>b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.</p> <p>c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.</p> <p>P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).</p> <p>P_{th,i} = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.</p> <p>ERP_j = the ERP of fixed, mobile, or portable RF source j.</p> <p>ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.</p> <p>Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.</p> <p>Evaluated Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.</p>



2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

2.4GHz WLAN

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	5.00	28.91	33.91	0.50	1,683.1003	20	0.54920	1.00000	B	3060	0.5501
2.4G;D1D	5.00	28.85	33.85	0.50	1,660.0073	20	0.54166	1.00000	B	3060	0.5425

5GHz WLAN

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	5.00	23.63	28.63	0.50	499.0109	20	0.16283	1.00000	B	3060	0.1631
5.3G;D1D	5.00	23.74	28.74	0.50	511.8115	20	0.16701	1.00000	B	3060	0.1673
5.6G;D1D	5.00	23.79	28.79	0.50	517.7380	20	0.16894	1.00000	B	3060	0.1692
5.8G;D1D	5.00	29.50	34.50	0.50	1,928.0132	20	0.62912	1.00000	B	3060	0.6301

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

————THE END————