

RF Exposure Evaluation declaration

Product Name	MOXA IEEE 802.11a/b/g/n Wireless
Model No.	WAPN005
FCC ID	SLE-WAPN005L

Applicant	Moxa Inc.
Address	4F,No.135, Lane 235, BAOQIAO Rd. XINDIAN DIST.,NEW TAIPEI CITY, Taiwan

Date of Receipt	Mar. 05, 2014
Date of Declaration	Mar. 14, 2014
Report No.	1430089R-RFUSP09V00

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by TAF any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : MOXA IEEE 802.11a/b/g/n Wireless
 Test Item : RF Exposure Evaluation
 Test Site : No.3 OATS

Operation Frequency	2412~2462, 2422~2452MHz 5180~5320, 5500~5700, 5745~5850MHz, 5190~5310, 5510~5670, 5755~5795MHz
Maximum Conducted output power	25.71dBm
Antenna gain	4.62dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
372.3917	0.214650

Power density is lower than the limit (1 mW/cm²).