



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial
Zone, Gushu 2nd Road, Bao'an District, Shenzhen
518126, P.R. China

TEST REPORT

FCC ID: SLFEF-B205

Applicant : Shenzhen Wanfengda Electronics Co., Ltd.
Address : 2F, Building 1, Hezhou Yuye Industrial Zone, Xixiang, Bao'
an, Shenzhen.

Equipment Under Test (EUT):

Name : Dancing Water Speakers
Model : EF-B205

In Accordance with: FCC PART 15, SUBPART C : 2013 (Section 15.247)

Report No : CST-TCB140325012
Date of Test : March 27, 2014 to April 07, 2014
Date of Issue : April 09, 2014

Test Result: **PASS**

In the configuration tested, the EUT complied with the standards specified above

Authorized Signature

A handwritten signature in black ink, appearing to read "Mark Zhu", is written over a horizontal line.

(Mark Zhu)
General Manager

The manufacture should ensure that all the products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of Shenzhen Certification Technology Service Co., Ltd. Or test done by Shenzhen Certification Technology Service Co., Ltd. Approvals in connection with, distribution or use of the product described in this report must be approved by Shenzhen Certification Technology Service Co., Ltd. Approvals in writing.

Contents

1. General Information.....	4
1.1. Description of Device (EUT).....	4
1.2. Accessories of device (EUT)	4
1.3. Test Lab information	4
2. Summary of test	5
2.1. Summary of test result	5
2.2. Assistant equipment used for test.....	5
2.3. Block Diagram	6
2.4. Test mode	6
2.5. Test Conditions.....	7
2.6. Measurement Uncertainty (95% confidence levels, k=2)	7
2.7. Test Equipment.....	8
3. Maximum Peak Output power	9
3.1. Limit.....	9
3.2. Test Procedure	9
3.3. Test Setup	9
3.4. Test Result.....	9
4. Bandwidth	10
4.1. Limit.....	10
4.2. Test Procedure	10
4.3. Test Result.....	10
5. Carrier Frequency Separation.....	16
5.1. Limit.....	16
5.2. Test Procedure	16
5.3. Test Result.....	16
6. Number Of Hopping Channel	22
6.1. Limit.....	22
6.2. Test Procedure	22
6.3. Test Result.....	22
7. Dwell Time.....	26
7.1. Test limit	26
7.2. Test Procedure.....	26
7.3. Test Results	26
8. Radiated emissions.....	32
8.1. Limit.....	32
8.2. Block Diagram of Test setup.....	33
8.3. Test Procedure	33
8.4. Test Result.....	34
9. Band Edge Compliance	40
9.1. Block Diagram of Test Setup	40
9.2. Limit.....	40
9.3. Test Procedure	40

9.4. Test Result.....	40
10. Power Line Conducted Emissions	65
10.1. Block Diagram of Test Setup	65
10.2. Limit.....	65
10.3. Test Procedure	65
10.4. Test Result.....	65
11. Antenna Requirements.....	68
12. Test setup photo	69
12.1. Photos of Radiated emission	69
12.2. Photos of Conducted Emission test.....	70
13. Photos of EUT	71

1. General Information

1.1. Description of Device (EUT)

EUT : Dancing Water Speakers
Model No. : EF-B205

Trade mark : N/A

Power supply : DC 3.7V Supply by internal Lithium battery
And DC5V from PC for charge

Radio : Bluetooth 2.1+EDR,
Technology
Operation : Bluetooth 2.1+EDR: 2402-2480MHz
frequency
Modulation : Bluetooth 2.1+EDR: GFSK, $\pi/4$ DQPSK, 8-DPSK,

Antenna Type : PCB Antenna, max gain 0 dBi for BT.

Applicant : Shenzhen Wanfengda Electronics Co., Ltd.
Address : 2F, Building 1, Hezhou Yuye Industrial Zone, Xixiang, Bao' an,
Shenzhen.

Manufacturer : Shenzhen Wanfengda Electronics Co., Ltd.
Address : 2F, Building 1, Hezhou Yuye Industrial Zone, Xixiang, Bao' an,
Shenzhen.

1.2. Accessories of device (EUT)

N/A

1.3. Test Lab information

Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
FCC Registered No.:197647
IC Registered No.: 8528B

2. Summary of test

2.1. Summary of test result


Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.4 :2003	PASS
Bandwidth	FCC Part 15: 15.215 ANSI C63.4 :2003	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.4 :2003	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.4 :2003	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.4 :2003	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.4 :2003	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.4 :2003	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.4 :2003	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

2.2. Assistant equipment used for test


Description	:	Notebook
Manufacturer	:	Great Wall
Model No.	:	T80

2.3. Block Diagram

1, For radiated emissions test: EUT was placed on a turn table, which is 0.8 meter high above ground. EUT was be set into BT test mode by “bluetool3” software before test.



2, For Power Line Conducted Emissions Test: EUT was connected to PC by 1m USB line



2.4. Test mode

Keep the EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
BDR:GFSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
EDR: $\pi/4$ DQPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
EDR:8-DPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480

2.5. Test Conditions

Temperature range	22-25°C
Humidity range	40-75%
Pressure range	86-106kPa

2.6. Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for Power point Conducted Emissions Test	2.42dB	
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB	Polarize: V
	2.57dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.54dB	Polarize: V
	4.1dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	2.08dB	Polarize: H
	2.56dB	Polarize: V
Uncertainty for radio frequency	1×10^{-9}	
Uncertainty for conducted RF Power	0.65dB	
Uncertainty for temperature	0.2°C	
Uncertainty for humidity	1%	
Uncertainty for DC and low frequency voltages	0.06%	

2.7. Test Equipment

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
3m Semi-Anechoic	ETS-LINDGREN	N/A	SEL0017	Nov. 16, 13	1 Year
Spectrum analyzer	Agilent	E4407B	MY49510055	Oct. 30, 13	1 Year
Receiver	R&S	ESCI	101165	Oct. 30, 13	1 Year
Receiver	R&S	ESCI	101202	Oct. 30, 13	1 Year
Bilog Antenna	SCHWARZBECK	VULB 9168	9168-438	Mar.11, 14	1 Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	Mar.11, 14	1 Year
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA 9170 D(1432)	Mar.11, 14	1 Year
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	Mar.11, 14	1 Year
L.I.S.N.	SCHWARZBECK	NSLK8126	8126466	Oct. 30, 13	1 Year
Cable	Resenberger	N/A	No.1	Oct. 30, 13	1 Year
Cable	SCHWARZBECK	N/A	No.2	Oct. 30, 13	1 Year
Cable	SCHWARZBECK	N/A	No.3	Oct. 30, 13	1 Year
Power Meter	Anritsu	ML2487A	6K00001491	Oct. 30, 13	1 Year
Power sensor	Anritsu	ML2491A	32516	Oct. 30, 13	1 Year
Pre-amplifier	SCHWARZBECK	BBV9743	9743-019	Oct. 30, 13	1 Year
Pre-amplifier	Quietek	AP-180C	CHM-0602012	Oct. 30, 13	1 Year

3. Maximum Peak Output power

3.1. Limit


Please refer section 15.247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

EUT: Dancing Water Speakers		M/N: EF-B205			
Test date: 2014-03-28		Test site: RF site		Tested by: Joe	
Mode	Freq (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)	Test result
GFSK	2402	2.32	1.71	21.00	PASS
	2441	4.58	2.87	21.00	
	2480	2.58	1.81	21.00	
$\pi/4$ DQPSK	2402	-0.49	0.89	21.00	
	2441	0.05	1.01	21.00	
	2480	2.31	1.70	21.00	
8-DPSK	2402	-0.01	1.00	21.00	
	2441	2.89	1.95	21.00	
	2480	-0.05	0.99	21.00	

4. Bandwidth

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure


The transmitter output was coupled to a spectrum analyzer via a antenna. The bandwidth of the fundamental frequency was measured by spectrum analyzer with $RBW \geq 1\%$ of the 20dB bandwidth and $VBW \geq RBW$. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result


EUT: Dancing Water Speakers		M/N: EF-B205		
Test date: 2014-03-28		Test site: RF site		Tested by: Joe
Mode	Freq (MHz)	20dB Bandwidth (MHz)	Limit (kHz)	Conclusion
GFSK	2402	0.684	N/A	PASS
	2441	0.684		
	2480	0.766		
Pi/4-DQPSK	2402	1.128		
	2441	1.130		
	2480	1.125		
8-DPSK	2402	1.163		
	2441	1.171		
	2480	1.170		

Original Test data For 20dB bandwidth
GFSK


Lowest CH



Middle CH




Highest CH




Pi/4-DQPSK


Lowest CH



Middle CH




Highest CH




8-DPSK


Lowest CH



Middle CH



Highest CH



5. Carrier Frequency Separation

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure

The transmitter output was coupled to a spectrum analyzer via a antenna. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW.

5.3. Test Result

GFSK:

EUT: Dancing Water Speakers		M/N: EF-B205		
Test date: 2014-03-28		Test site: RF site		Tested by: Joe
Mode	Channel separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz)	Conclusion
Lowest	1.005	0.684	2/3 20dB bandwidth or 25kHz	PASS
Middle	1.005	0.684		
Highest	1.000	0.766		

Pi/4DQPSK


EUT: Dancing Water Speakers		M/N: EF-B205		
Test date: 2014-03-28		Test site: RF site		Tested by: Joe
Mode	Channel separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz)	Conclusion
Lowest	1.015	1.128	2/3 20dB bandwidth or 25kHz	PASS
Middle	1.015	1.130		
Highest	1.000	1.125		

8-DPSK


EUT: Dancing Water Speakers		M/N: EF-B205		
Test date: 2014-03-28		Test site: RF site		Tested by: Joe
Mode	Channel separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz) 2/3 20dB bandwidth	Conclusion
Lowest	1.005	1.163	2/3 20dB bandwidth or 25kHz	PASS
Middle	1.000	1.171		
Highest	1.005	1.170		

Original test data for channel separation


GFSK



Lowest




Middle




Highest


Pi/4-DQPSK



Lowest




Middle




Highest


8-DPSK



Lowest



Middle



Highest

6. Number Of Hopping Channel

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels



6.2. Test Procedure

The transmitter output was coupled to a spectrum analyzer via a antenna. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW.



6.3. Test Result

EUT: Dancing Water Speakers		M/N: EF-B205	
Test date: 2014-03-28		Test site: RF site	Tested by: Joe
Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
Pi/4-DQPSK	79		
8-DPSK	79		



Original test data for hopping channel number
GFSK



Pi/4-DQPSK



8-DPSK



7. Dwell Time

7.1. Test limit

Please refer section 15.247

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Results

PASS.

Detailed information please see the following page.

Mode	Packet	Dwell time (second)	Limit (second)	Result
GFSK	DH1	0.166	0.4	Pass
	DH3	0.270		
	DH5	0.325		
Pi/4DQPSK	2-DH1	0.147	0.4	Pass
	2-DH3	0.269		
	2-DH5	0.317		
8DPSK	3-DH1	0.150	0.4	Pass
	3-DH3	0.269		
	3-DH5	0.317		


Note: 1 A period time = 0.4 (s) * 79 = 31.6(s)

2 DH1 time slot = Pulse Duration * (1600/(2*79)) * A period time


DH3 time slot = Pulse Duration * (1600/(4*79)) * A period time

DH5 time slot = Pulse Duration * (1600/(6*79)) * A period time


DH1:




DH3:




DH5:




2DH1:




2DH3:




2DH5:




3DH1:



3DH3:



3DH5:



8. Radiated emissions

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

8.2. Block Diagram of Test setup

8.2.1. In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2. In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator as shown in section 1.4 and 6.1

- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Change power supply range from 85% to 115% of the rated supply voltage for AC power supply.
 - (d) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4 2003 on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result

We have scanned the 10th harmonic from 9KHz to the EUT.
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Remark: All three modulations of EUT have been tested, only show the test data of the worst modulation in this report, and we found the worst modulation is GFSK.

From 30MHz to 1000MHz: Conclusion: PASS

Horizontal:



Shenzhen Certification Technology Service Co., Ltd.
 2F, Building B, East Area of Nanchang Second Industrial Zone,
 Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
 Tel: 4006786199 FAX: +86-755-26736857
 Website: <http://www.cessz.com> Email: Service@cessz.com



Condition : FCC PART 15 B 3m POL: HORIZONTAL
 EUT : Dancing Water speaker
 Model No : EF-B205
 Test Mode : Charging+Transmitting
 Power : DC 3.7V
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%


Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	100.93	54.66	10.35	26.84	0.40	38.57	43.50	-4.93	QP
2	122.40	48.35	12.35	26.88	0.43	34.25	43.50	-9.25	QP
3	146.89	48.34	13.90	26.91	0.37	35.70	43.50	-7.80	QP
4	170.19	50.87	13.18	26.92	0.68	37.81	43.50	-5.69	QP
5	230.10	54.51	11.21	27.08	0.58	39.22	46.00	-6.78	QP
6	238.31	53.38	11.40	27.09	0.54	38.23	46.00	-7.77	QP

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

Vertical:



Shenzhen Certification Technology Service Co., Ltd.
 2F, Building B, East Area of Nanchang Second Industrial Zone,
 Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
 Tel: 4006786199 FAX: +86-755-26736857
 Website: <http://www.cessz.com> Email: Service@cessz.com



Condition : FCC PART 15 B 3m POL: VERTICAL
 EUT : Dancing Water speaker
 Model No : EF-B205
 Test Mode : Charging+Transmitting
 Power : DC 3.7V
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	101.64	48.45	10.35	26.84	0.34	32.30	43.50	-11.20	QP
2	104.17	49.63	10.74	26.85	0.32	33.84	43.50	-9.66	QP
3	170.19	40.08	13.18	26.92	0.68	27.02	43.50	-16.48	QP
4	221.39	50.35	10.75	27.07	0.68	34.71	46.00	-11.29	QP
5	228.49	51.10	11.10	27.08	0.55	35.67	46.00	-10.33	QP
6	237.48	54.04	11.40	27.09	0.50	38.85	46.00	-7.15	QP

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss


1GHz—25GHz Radiated emission Test result									
EUT: Dancing Water Speakers					M/N: EF-B205				
Power: DC 5V From PC									
Test date: 2014-03-29 Test site: 3m Chamber Tested by: Joe									
Test mode: GFSK Tx CH1 2402MHz									
Antenna polarity: Vertical									
No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804	48.62	33.95	10.18	34.26	58.49	74	15.51	PK
2	4804	38.62	33.95	10.18	34.26	48.49	54	5.51	AV
3	7206	/							
4	9608	/							
5	12010	/							
Antenna Polarity: Horizontal									
1	4804	49.62	33.95	10.18	34.26	59.49	74	14.51	PK
2	4804	39.21	33.95	10.18	34.26	49.08	54	4.92	AV
3	7206	/							
4	9608	/							
5	12010	/							
Note:									
1, Measuring frequency from 1GHz to 25GHz									
2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK									
2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK									
3, Result = Read level + Antenna factor + cable loss-Amp factor									
4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

1GHz—25GHz Radiated emission Test result									
EUT: Dancing Water Speakers					M/N: EF-B205				
Power: DC 5V From PC									
Test date: 2014-03-29 Test site: 3m Chamber Tested by: Joe									
Test mode: GFSK Tx CH40 2441MHz									
Antenna polarity: Vertical									
No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4882	48.36	33.93	10.2	34.29	58.2	74	15.8	PK
2	4882	38.25	33.93	10.2	34.29	48.09	54	5.91	AV
3	7323	/							
4	9764	/							
5	12205	/							
Antenna Polarity: Horizontal									
1	4882	47.85	33.93	10.2	34.29	57.69	74	16.31	PK
2	4882	36.38	33.93	10.2	34.29	46.22	54	7.78	AV
3	7323	/							
4	9764	/							
5	12205	/							
Note:									
1, Measuring frequency from 1GHz to 25GHz									
2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK									
2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK									
3, Result = Read level + Antenna factor + cable loss-Amp factor									
4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

1GHz—25GHz Radiated emission Test result									
EUT: Dancing Water Speakers					M/N: EF-B205				
Power: DC 5V From PC									
Test date: 2014-03-29 Test site: 3m Chamber Tested by: Joe									
Test mode: GFSK Tx CH79 2480MHz									
Antenna polarity: Vertical									
No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960	49.32	33.98	10.22	34.25	59.27	74	14.73	PK
2	4960	35.62	33.98	10.22	34.25	45.57	54	8.43	AV
3	7440	/							
4	9920	/							
5	12400	/							
Antenna Polarity: Horizontal									
1	4960	48.68	33.98	10.22	34.25	58.63	74	15.37	PK
2	4960	36.25	33.98	10.22	34.25	46.2	54	7.8	AV
3	7440	/							
4	9920	/							
5	12400	/							
Note:									
1, Measuring frequency from 1GHz to 25GHz									
2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK									
2, Spectrum Set for AV measure: RBW=1MHz, VBW=10Hz, Sweep time=Auto, Detector: PK									
3, Result = Read level + Antenna factor + cable loss-Amp factor									
4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

9. Band Edge Compliance

9.1. Block Diagram of Test Setup



9.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz and 5725MHz to 5850MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.3. Test Procedure


Same with clause 6.3 except change investigated frequency range from 2310MHz to 2405MHz, 2475MHz to 2510MHz.

9.4. Test Result

NOTE : The Band Edge is showed the maximum power data of all mode(GFSK, $\Pi/4$ DQPSK, 8-DPSK)

PASS. (See below detailed test data)


GFSK
CH LOW :



Condition : FCC PART 15_18G PEAK 3m POL: HORIZONTAL
 EUT : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : GFSK L CH
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2390.12	42.12	27.62	34.97	3.92	38.69	74.00	-35.31	Peak
2	2400.00	55.02	27.62	34.97	3.94	51.61	54.00	-2.39	Average
3	2400.00	73.07	27.62	34.97	3.94	69.66	74.00	-4.34	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss




Condition : FCC PART 15_18G PEAK 3m POL: VERTICAL
 EUI : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : GFSK L CH
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2390.00	41.32	27.62	34.97	3.92	37.89	74.00	-36.11	Peak
2	2400.00	55.24	27.62	34.97	3.94	51.83	54.00	-2.17	Average
3	2400.00	72.94	27.62	34.97	3.94	69.53	74.00	-4.47	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss


CH High :



Condition : FCC PART 15_18G PEAK 3m POL: VERTICAL
 EUT : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : GFSK H CH
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2483.50	51.31	27.59	34.97	4.00	47.93	54.00	-6.07	Average
2	2483.50	60.56	27.59	34.97	4.00	57.18	74.00	-16.82	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss




Condition : FCC PART 15_18G PEAK 3m POL: HORIZONTAL
 EUT : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : GFSK H CH
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2483.50	46.31	27.59	34.97	4.00	42.93	54.00	-11.07	Average
2	2483.50	57.21	27.59	34.97	4.00	53.83	74.00	-20.17	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

Hopping


Lowest CH:



Condition : FCC PART 15_18G PEAK 3m POL: VERTICAL
 EUI : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : GFSK Hopping mode
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2390.00	41.99	27.62	34.97	3.92	38.56	74.00	-35.44	Peak
2	2400.00	54.38	27.62	34.97	3.94	50.97	54.00	-3.03	Average
3	2400.00	71.04	27.62	34.97	3.94	67.63	74.00	-6.37	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss




Condition : FCC PART 15_18G PEAK 3m POL: HORIZONTAL
 EUT : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : GFSK Hopping mode
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2390.00	43.45	27.62	34.97	3.92	40.02	74.00	-33.98	Peak
2	2400.00	55.36	27.62	34.97	3.94	51.95	54.00	-2.05	Average
3	2400.00	71.87	27.62	34.97	3.94	68.46	74.00	-5.54	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss


Highest CH:



Condition : FCC PART 15_18G PEAK 3m POL: VERTICAL
 EUT : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : GFSK Hopping mode
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2483.50	51.31	27.59	34.97	4.00	47.93	54.00	-6.07	Average
2	2483.50	61.50	27.59	34.97	4.00	58.12	74.00	-15.88	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss




Condition : FCC PART 15_18G PEAK 3m POL: HORIZONTAL
 EUI : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : GFSK Hopping mode
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2483.50	46.49	27.59	34.97	4.00	43.11	54.00	-10.89	Average
2	2483.50	55.50	27.59	34.97	4.00	52.12	74.00	-21.88	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss


Pi/4-DQPSK
Lowest CH :



Condition : FCC PART 15_18G PEAK 3m POL: VERTICAL
 EUT : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : Pi/4DQPSK L CH
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2390.00	40.45	27.62	34.97	3.92	37.02	74.00	-36.98	Peak
2	2400.00	56.21	27.62	34.97	3.94	52.80	54.00	-1.20	Average
3	2400.00	73.27	27.62	34.97	3.94	69.86	74.00	-4.14	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss



Condition : FCC PART 15_18G PEAK 3m POL: HORIZONTAL
 EUT : Portable Mini Bluetooth Speaker
 Model No : Mini Bass
 Test Mode : Pi/4DQPSK L CH
 Power : DC 5V from PC
 Test Engineer : Joe
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	2390.00	40.45	27.62	34.97	3.92	37.02	74.00	-36.98	
2	2400.00	52.32	27.62	34.97	3.94	48.91	54.00	-5.09	Average
3	2400.00	66.90	27.62	34.97	3.94	63.49	74.00	-10.51	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss