



**SGS-CSTC Standards Technical Services
(Shanghai) Co., Ltd.**

588 West Jindu Road, Songjiang District, Shanghai, China
 Telephone: +86 (0) 21 6191 5666
 Fax: +86 (0) 21 6191 5678
 ee.shanghai@sgs.com

Report No.: SHEM141000268802
 Page: 1 of 94

1 Cover Page

RF TEST REPORT

Application No.:	SHEM1410002688RF
Applicant:	iHealth Lab Inc.
FCC ID:	SLRHS6
IC:	10913A-HS6
Equipment Under Test (EUT):	
NOTE: The following sample(s) submitted was/were identified on behalf of the client as	
Product Name:	Core
Model No.(EUT):	HS6
Standards:	FCC PART 15 Subpart C: 2013 RSS-210 Issue 8 (December 2010) RSS-Gen Issue 3 (December 2010)
Date of Receipt:	October 24, 2014
Date of Test:	November 03, 2014 to November 13, 2014
Date of Issue:	November 27, 2014
Test Result:	Pass*

*In the configuration tested, the EUT detailed in this report complied with the standards specified above.



Tony Wu
E&E Section Manager

SGS-CSTC (Shanghai) Co., Ltd.




The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00	/	November 27, 2014	/	Original

Authorized for issue by:				
Engineer		Eddy Zong		
		Print Name		
Clerk		Susie Liu		
		Print Name		
Reviewer		Keny Xu		
		Print Name		

3 Test Summary

Test Item	FCC Requirement	IC Requirement	Test method	Result
Antenna Requirement	FCC Part 15, Subpart C Section 15.203/15.247 (c)	RSS-Gen 7.1.2	---	PASS
AC Power Line Conducted Emission	FCC Part 15, Subpart C Section 15.207	RSS-Gen Issue 8 Clause 7.2.4	ANSI C63.10 (2009) Section 6.2	N/A
Minimum 6dB Bandwidth	FCC Part 15, Subpart C Section 15.247 (a)(2)	RSS-210 Issue 8 Annex 8	ANSI C63.10 (2009) Section 6.9.1	PASS
Conducted Peak Output Power	FCC Part 15, Subpart C Section 15.247 (b)(3)	RSS-210 Issue 8 Annex 8	ANSI C63.10 (2009) Section 6.10.2	PASS
Power Spectrum Density	FCC Part 15, Subpart C Section 15.247 (e)	RSS-210 Issue 8 Annex 8	ANSI C63.10 (2009) Section 6.11.2	PASS
RF Conducted Spurious Emissions and Band- edge	FCC Part 15, Subpart C Section 15.247(d)	RSS 210 A 8.5	ANSI C63.10 (2009) Section 7.7.9&7.7.10	PASS
Radiated Spurious Emissions and Band- edge	FCC Part 15, Subpart C Section 15.209&15.205	RSS-Gen section 4.9	ANSI C63.10 (2009) Section 6.5&6.6&6.7	PASS
99% Occupied bandwidth	---	RSS-Gen Issue 3 Clause 4.6.1	RSS-Gen Issue 3 Clause 4.6.1	PASS

N/A: Not applicable, please refer to Section 7.3 of this report for details.

4 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENTS.....	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TECHNICAL SPECIFICATIONS.....	5
5.4 TEST MODE.....	5
5.5 DESCRIPTION OF SUPPORT UNITS.....	6
5.6 TEST CHANNEL	6
5.7 TEST LOCATION	7
5.8 TEST FACILITY	7
5.9 MEASUREMENT UNCERTAINTY	8
6 EQUIPMENTS USED DURING TEST.....	9
7 TEST RESULTS	10
7.1 E.U.T. TEST CONDITIONS	10
7.2 ANTENNA REQUIREMENT.....	11
7.3 CONDUCTED EMISSIONS ON MAINS TERMINALS	12
7.4 6dB OCCUPIED BANDWIDTH.....	14
7.5 CONDUCTED PEAK OUTPUT POWER	22
7.6 PEAK POWER SPECTRAL DENSITY.....	28
7.7 CONDUCTED SPURIOUS EMISSIONS AND BAND-EDGE	42
7.7.1 <i>Conducted spurious emission</i>	43
7.7.2 <i>Conducted Band-edge</i>	55
7.8 RADIATED SPURIOUS EMISSIONS AND BAND-EDGE.....	59
7.8.1 <i>Radiated Spurious Emissions</i>	62
7.8.2 <i>Radiated Band edge</i>	72
7.9 99% OCCUPIED BANDWIDTH	87
8 TEST SETUP PHOTOGRAPHS.....	94
9 EUT CONSTRUCTIONAL DETAILS.....	94

5 General Information

5.1 Client Information

Applicant: iHealth Lab Inc.
 Address of Applicant: 719 N.Shoreline Blvd, Mountain View, CA94043
 Manufacturer: Andon Health Co. Ltd
 Address of Manufacturer: No. 3 JinPing Street YaAn Road Nankai District Tianjin, China
 Factory: Andon Health Co. Ltd
 Address of Factory: No. 3 JinPing Street YaAn Road Nankai District Tianjin, China

5.2 General Description of E.U.T.

Brand Name: iHealth
 Product Description: Wireless Body Analysis Scale with WiFi function
 Power Supply: DC 6V 4*AAA Batteries Size
 Remark: Supply the EUT with fully charged battery during the testing.

5.3 Technical Specifications

Operation Frequency: 802.11b/g/n20: 2412MHz~2462MHz
 802.11n40: 2422MHz~2452MHz
 Modulation Technique: 802.11 b DSSS(CCK, DQPSK, DBPSK)
 802.11 g/n20/n40 OFDM(64QAM, 16QAM, QPSK, BPSK)
 Data Rate: 802.11b: 1/2/5.5/11Mbps,
 802.11g: 6/9/12/18/24/36/48/54Mbps
 802.11 n20/n40: MCS0 - MCS7
 Number of Channel: 13 Channels (802.11b,g,n20)
 7 Channels (802.11 n40)
 Antenna Type: Integral

5.4 Test Mode

Test Mode	Description of Test Mode
Engineering mode	Using test software to control EUT working in continuous transmitting, and select channel and modulation type.


5.5 Description of Support Units

The EUT has been tested with support equipments as below.

Description	Manufacturer	Model No.	Supplied By
Laptop	Lenovo	ThinkPad X 100e	SGS

Software name	Manufacturer	Version	Supplied By
sscom3.2	/	1.3.3.0881	Client

Description of connection



5.6 Test Channel

Preliminary tests were performed in all tests in different data rate and antenna configurations at lowest channel, the data rates of worse case as below were chosen for final test.

Modulation Type	Channel	Frequency	Data rate
802.11 b	The lowest channel(CH1)	2412MHz	1Mbps
	The middle channel(CH6)	2437MHz	1Mbps
	The Highest channel(CH11)	2462MHz	1Mbps
802.11 g	The lowest channel(CH1)	2412MHz	6Mbps
	The middle channel(CH6)	2437MHz	6Mbps
	The Highest channel(CH11)	2462MHz	6Mbps
802.11 n20	The lowest channel(CH1)	2412MHz	MCS0
	The middle channel(CH6)	2437MHz	MCS0
	The Highest channel(CH11)	2462MHz	MCS0
802.11 n40	The lowest channel(CH1)	2422MHz	MCS0
	The middle channel(CH6)	2437MHz	MCS0
	The Highest channel(CH11)	2452MHz	MCS0

5.7 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.
No.588 West Jindu Road, Songjiang District, Shanghai, China.201612.
Tel: +86 21 6191 5666
Fax: +86 21 6191 5678

5.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. Date of expiry: 2017-07-14.

- **FCC – Registration No.: 402683**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683, Expiry Date: 2017-09-16.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1. Expiry Date: 2017-06-18.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868 and C-4336 respectively. Date of Registration: 2012-05-29. Date of Expiry: 2015-05-28.

5.9 Measurement Uncertainty

No.	Parameter	Measurement Uncertainty
1	Radio Frequency	$< \pm 1 \times 10^{-5}$
2	Total RF power, conducted	$< \pm 1.5$ dB
3	RF power density, conducted	$< \pm 3$ dB
4	Spurious emissions, conducted	$< \pm 3$ dB
5	All emissions, radiated	$< \pm 6$ dB (30MHz – 1GHz) $< \pm 6$ dB (above 1GHz)
6	Temperature	$< \pm 1^{\circ}\text{C}$
7	Humidity	$< \pm 5$ %
8	DC and low frequency voltages	$< \pm 3$ %

6 Equipments Used during Test

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due date
1	EMI test receiver	Rohde & Schwarz	ESCS30	100086	2014-02-13	2015-02-12
2	Line impedance stabilization network	SCHWARZBECK	NSLK8127	8127490	2014-02-13	2015-02-12
3	Line impedance stabilization network	ETS	3816/2	00034161	2014-02-13	2015-02-12
4	Spectrum Analyzer	Rohde & Schwarz	FSP-30	2705121009	2014-02-13	2015-02-12
5	EMI test receiver	Rohde & Schwarz	ESU40	100109	2014-02-13	2015-02-12
6	Active Loop Antenna (9kHz to 30MHz)	Rohde & Schwarz	FMZB 1519	1519-034	2014-03-19	2015-03-18
7	Broadband UHF-VHF ANTENNA (25MHz to 2GHz)	SCHWARZBECK	VULB9168	9168-313	2014-02-13	2015-02-12
8	Ultra broadband antenna (25MHz to 3GHz)	Rohde & Schwarz	HL562	100227	2014-08-30	2015-08-29
9	Horn Antenna (1GHz to 18GHz)	Rohde & Schwarz	HF906	100284	2014-02-13	2015-02-12
10	Horn Antenna (1GHz to 18GHz)	SCHWARZBECK	BBHA9120D	9120D-679	2014-02-13	2015-02-12
11	Horn Antenna (14GHz to 40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170373	2014-02-13	2015-02-12
12	Pre-amplifier (9KHz – 2GHz)	LNA6900	TESEQ	71033	2014-02-13	2015-02-12
13	Pre-amplifier (1GHz – 26.5GHz)	Rohde & Schwarz	SCU-F0118-G40-BZ4-CSS(F)	10001	2014-02-13	2015-02-12
14	Pre-amplifier (14GHz – 40GHz)	Rohde & Schwarz	SCU-F1840-G35-BZ3-CSS(F)	10001	2014-02-13	2015-02-12
15	Tunable Notch Filter	Wainwright instruments GmbH	WRCT800.0/880.0-0.2/40-5SSK	9170397	2014-06-02	2015-06-01
16	High pass Filter	FSCW	HP 12/2800-5AA2	19A45-02	2014-06-02	2015-06-01
17	High-low temperature cabinet	Suzhou Zhihe	TL-40	50110050	2014-09-11	2015-09-10
18	AC power stabilizer	WOCEN	6100	51122	2014-06-02	2015-06-01
19	DC power	QJE	QJ30003SII	611145	2014-06-02	2015-06-01
20	Signal Generator (Interferer)	Agilent	SMR40	100555	2014-02-14	2015-02-13
21	Signal Generator (Blocker)	Rohde & Schwarz	SMJ100A	02.20.360.142	2014-02-13	2015-02-12
22	Splitter	Anritsu	MA1612A	M12265	/	/
23	Coupler	e-meca	803-S-1	900-M01	/	/

7 Test Results

7.1 E.U.T. test conditions

Test Power: DC 6V

Requirements: 15.31(e) For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

Operating Environment:	Temperature:	20.0 -25.0 °C
	Humidity:	35-75 % RH
	Atmospheric Pressure:	99.2 -102.0 kPa

Test frequencies: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Pursuant to Part 15.31(c) For swept frequency equipment, measurements shall be made with the frequency sweep stopped at those frequencies chosen for the measurements to be reported.

7.2 Antenna Requirement

Standard requirement:

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PCB antenna. The gain of the antenna is less than 0 dBi.



7.3 Conducted Emissions on Mains Terminals

Frequency Range: 150 KHz to 30 MHz

Class/Severity: Class B


Limit:

Frequency range MHz	Class B Limits: dB (µV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Note1: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.
Note2: The lower limit is applicable at the transition frequency.

Test site/setup: Test instrumentation set-up:

Frequency Range	Detector	RBW	VBW
9KHz to 150Hz	Quasi-peak	200Hz	500Hz
150KHz to 30MHz	Quasi-peak	9kHz	30kHz



Test Procedure:

1. The mains terminal disturbance voltage was measured with the EUT in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides 50Ω/50µH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN, which was bonded to the ground reference plane in the same way as the LISN for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.

4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance was between the closest points of the LISN and the EUT. The mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m. All other units of the EUT and associated equipment were at least 0.8 m from the LISN.

Remark: Pre-scan was performed with peak detected on all ports, Quasi-peak & average measurements were performed at the frequencies at which maximum peak emission level were detected. Pretest under all modes; choose the worst case mode (802.11b in Middle channel) record on the report. Please see the attached Quasi-peak and Average test results.


Test Result: N/A

Test Data:

This EUT is powered by battery only; therefore the AC Conducted Emission test is not applicable.

7.4 6dB Occupied Bandwidth

Test Configuration:



Test Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=300KHz, VBW≥3* RBW, Span=30/50MHz, Sweep=auto
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat above procedures until all frequency measured was complete.

Limit: ≥ 500 kHz

Test Result: Pass

Test Data:

Test mode: 802.11b

CH	Frequency (MHz)	Bandwidth (MHz)	Limit Bandwidth (KHz)	Result
Low	2412	10.20	500	PASS
Mid	2437	9.90	500	PASS
High	2462	10.02	500	PASS

Test mode: 802.11g

CH	Frequency (MHz)	Bandwidth (MHz)	Limit Bandwidth (KHz)	Result
Low	2412	16.56	500	PASS
Mid	2437	16.47	500	PASS
High	2462	16.56	500	PASS



Test mode: 802.11n20


CH	Frequency (MHz)	Bandwidth (MHz)	Limit Bandwidth (KHz)	Result
Low	2412	17.52	500	PASS
Mid	2437	17.61	500	PASS
High	2462	17.52	500	PASS

Test mode: 802.11n40


CH	Frequency (MHz)	Bandwidth (MHz)	Limit Bandwidth (KHz)	Result
Low	2422	36.00	500	PASS
Mid	2437	35.96	500	PASS
High	2452	35.80	500	PASS

Test plot as follows:

Test mode:	802.11b	Channel:	Lowest
------------	---------	----------	--------




Test mode:	802.11b	Channel:	Middle
------------	---------	----------	--------






Test mode:	802.11b	Channel:	Highest
------------	---------	----------	---------




Test mode:	802.11g	Channel:	Lowest
------------	---------	----------	--------







Test mode:	802.11g	Channel:	Middle
------------	---------	----------	--------




Test mode:	802.11g	Channel:	Highest
------------	---------	----------	---------




Test mode:	802.11n20	Channel:	Lowest
-------------------	------------------	-----------------	---------------




Test mode:	802.11n20	Channel:	Middle
-------------------	------------------	-----------------	---------------



Test mode:	802.11n20	Channel:	Highest
-------------------	------------------	-----------------	----------------




Test mode:	802.11n40	Channel:	Lowest
-------------------	------------------	-----------------	---------------






Test mode:	802.11n40	Channel:	Middle
------------	-----------	----------	--------




Test mode:	802.11n40	Channel:	Highest
------------	-----------	----------	---------



7.5 Conducted Peak Output Power

Test Configuration:



Test Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.
3. Set the occur band to the entire emission 6dB bandwidth of the signal.
4. Record the max. Power channel reading.
5. Repeat above procedures until all the frequency measured were complete.

Test Limit: 30dBm

Test Result: Pass


Test Data:

Test mode	Test Channel	Reading Power (dBm)	Cable Loss (dB)	Output Power (dBm)	Output Power (mW)	Power Limit (dBm)	Result
802.11b	Lowest	17.03	0.5	17.53	56.62	30	PASS
	Middle	16.91	0.5	17.41	55.08	30	PASS
	Highest	17.13	0.5	17.63	57.94	30	PASS
802.11g	Lowest	16.67	0.5	17.17	52.12	30	PASS
	Middle	16.60	0.5	17.10	51.29	30	PASS
	Highest	16.71	0.5	17.21	52.60	30	PASS
802.11n20	Lowest	16.41	0.5	16.91	49.09	30	PASS
	Middle	16.49	0.5	16.99	50.00	30	PASS
	Highest	16.53	0.5	17.03	50.47	30	PASS
802.11n40	Lowest	16.25	0.5	16.75	47.32	30	PASS
	Middle	16.29	0.5	16.79	47.75	30	PASS
	Highest	16.41	0.5	16.91	49.09	30	PASS


Remark: Output Peak Power = Reading Peak Power + Cable loss

Test result plot as follows:


Test mode:	802.11b	Channel:	Lowest
-------------------	----------------	-----------------	---------------




Test mode:	802.11b	Channel:	Middle
-------------------	----------------	-----------------	---------------




Test mode:	802.11b	Channel:	Highest
-------------------	----------------	-----------------	----------------




Test mode:	802.11g	Channel:	Lowest
-------------------	----------------	-----------------	---------------



Test mode:	802.11g	Channel:	Middle
-------------------	----------------	-----------------	---------------




Test mode:	802.11g	Channel:	Highest
-------------------	----------------	-----------------	----------------




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e_document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only


Test mode:	802.11n20	Channel:	Lowest
-------------------	------------------	-----------------	---------------




Test mode:	802.11n20	Channel:	Middle
-------------------	------------------	-----------------	---------------




Test mode:	802.11n20	Channel:	Highest
-------------------	------------------	-----------------	----------------




Test mode:	802.11n40	Channel:	Lowest
-------------------	------------------	-----------------	---------------



Test mode:	802.11n40	Channel:	Middle
-------------------	------------------	-----------------	---------------




Test mode:	802.11n40	Channel:	Highest
-------------------	------------------	-----------------	----------------



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e_document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

7.6 Peak Power Spectral Density

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: Center Frequency= Channel Frequency, RBW = 3 kHz VBW = 10 kHz. Span= fully encompass the bandwidth, Sweep = auto; Detector Function = Peak Trace mode=max hold,
3. Set MKR=Center Frequency, Trace=Clear Write.
4. Adjust the Span = 300 kHz, Sweep Time=100s, Trace=Max Hold, MKR=Peak Search.
5. Record the marker level for the particular mode.
6. Repeat these steps for other channel and device modes.

Test Limit:

8dBm/3kHz

Test Result:

Pass

Test Data:

Test mode: 802.11b

CH	Frequency (MHz)	Reading (dBm)	Cable Loss (dB)	RF Power Density (dBm)	Limit (dBm)	Result
LOW	2412	-17.27	0.5	-16.77	8	PASS
MID	2437	-17.08	0.5	-16.58	8	PASS
HIGH	2462	-16.23	0.5	-15.73	8	PASS

Test mode: 802.11g

CH	Frequency (MHz)	Reading (dBm)	Cable Loss (dB)	RF Power Density (dBm)	Limit (dBm)	Result
LOW	2412	-18.05	0.5	-17.55	8	PASS
MID	2437	-18.78	0.5	-18.28	8	PASS
HIGH	2462	-17.77	0.5	-17.27	8	PASS

Test mode: 802.11n20

CH	Frequency (MHz)	Reading (dBm)	Cable Loss (dB)	RF Power Density (dBm)	Limit (dBm)	Result
LOW	2412	-17.54	0.5	-17.04	8	PASS
MID	2437	-17.26	0.5	-16.76	8	PASS
HIGH	2462	-18.41	0.5	-17.91	8	PASS



Test mode: 802.11n40

CH	Frequency (MHz)	Reading (dBm)	Cable Loss (dB)	RF Power Density (dBm)	Limit (dBm)	Result
LOW	2422	-22.38	0.5	-21.88	8	PASS
MID	2437	-23.26	0.5	-22.76	8	PASS
HIGH	2452	-21.57	0.5	-21.07	8	PASS

Remark: RF Power Density = Reading + Cable loss + Antenna Gain

Test result plot as follows:


Test mode:	802.11b	Channel:	Lowest
-------------------	----------------	-----------------	---------------




Test mode:	802.11b	Channel:	Middle
-------------------	----------------	-----------------	---------------



*RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz -16.80 dBm
 Ref 20 dBm *Att 30 dB SWT 2.25 s 2.436260000 GHz



*RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz -17.08 dBm
 Ref 20 dBm *Att 30 dB *SWT 100 s 2.436294500 GHz






Test mode:	802.11b	Channel:	Highest
------------	---------	----------	---------




Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] -16.10 dBm
*VBW 10 kHz 2.463120000 GHz
SWT 2.25 s

1 PK
MAXH



Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] -16.23 dBm
*VBW 10 kHz 2.463114600 GHz
*SWT 100 s

1 PK
MAXH




Test mode:	802.11g	Channel:	Lowest
-------------------	----------------	-----------------	---------------



Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -18.92 dBm
 SWT 2.25 s 2.414480000 GHz

1 PK
MAXH




Center 2.412 GHz 2 MHz/ Span 20 MHz



Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -18.05 dBm
 *SWT 100 s 2.414467100 GHz

1 PK
MAXH



Center 2.41448 GHz 30 kHz/ Span 300 kHz




Test mode:	802.11g	Channel:	Middle
------------	---------	----------	--------




Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] -19.12 dBm
VBW 10 kHz 2.438540000 GHz
SWT 2.25 s

1 PK
MAXH



Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] -18.78 dBm
VBW 10 kHz 2.438467700 GHz
*SWT 100 s

1 PK
MAXH




Test mode:	802.11g	Channel:	Highest
-------------------	----------------	-----------------	----------------




*RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -18.57 dBm
 Ref 20 dBm *Att 30 dB SWT 2.25 s 2.462600000 GHz

1 PK
MAXH



*RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -17.77 dBm
 Ref 20 dBm *Att 30 dB *SWT 100 s 2.462592200 GHz


1 PK
MAXH




Test mode:	802.11n20	Channel:	Lowest
-------------------	------------------	-----------------	---------------



Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -19.56 dBm
 SWT 2.25 s 2.410720000 GHz




Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -17.54 dBm
 *SWT 100 s 2.410713700 GHz




Test mode:	802.11n20	Channel:	Middle
-------------------	------------------	-----------------	---------------



Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -19.20 dBm
 SWT 2.25 s 2.435720000 GHz



Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -17.26 dBm
 *SWT 100 s 2.435725100 GHz




Test mode:	802.11n20	Channel:	Highest
-------------------	------------------	-----------------	----------------




*RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -19.40 dBm
 Ref 20 dBm *Att 30 dB SWT 2.25 s 2.463240000 GHz

1 PK
MAXH



*RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -18.41 dBm
 Ref 20 dBm *Att 30 dB *SWT 100 s 2.463212100 GHz

1 PK
MAXH




Test mode:	802.11n40	Channel:	Lowest
-------------------	------------------	-----------------	---------------




*RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -24.41 dBm
 Ref 20 dBm *Att 30 dB SWT 5.6 s 2.416950000 GHz

1 PK
MAXH



*RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -22.38 dBm
 Ref 20 dBm *Att 30 dB *SWT 100 s 2.416965900 GHz

1 PK
MAXH






Test mode:	802.11n40	Channel:	Middle
------------	-----------	----------	--------




Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] -23.26 dBm
VBW 10 kHz 2.431950000 GHz
SWT 5.6 s

1 PK
MAXH



Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] -22.34 dBm
VBW 10 kHz 2.431965000 GHz
*SWT 100 s


1 PK
MAXH




Test mode:	802.11n40	Channel:	Highest
-------------------	------------------	-----------------	----------------



Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -22.54 dBm
 SWT 5.6 s 2.449450000 GHz




Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 VBW 10 kHz -21.57 dBm
 *SWT 100 s 2.449441900 GHz



7.7 Conducted Spurious Emissions and Band-edge

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100KHz. VBW >= RBW. Sweep = auto; Detector Function = Peak (Max. hold).

Limit:

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the Highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Result:


Pass

7.7.1 Conducted spurious emission


Test plot as follows:

Test mode:	802.11b	Channel:	Lowest
-------------------	----------------	-----------------	---------------

30MHz-3GHz:




3GHz-25GHz:




Test mode:	802.11b	Channel:	Middle
-------------------	----------------	-----------------	---------------

30MHz-3GHz:




3GHz-25GHz:




Test mode:	802.11b	Channel:	Highest
-------------------	----------------	-----------------	----------------

30MHz-3GHz:



3GHz-25GHz:




Test mode:	802.11g	Channel:	Lowest
-------------------	----------------	-----------------	---------------

30MHz-3GHz:




Ref 20 dBm * Att 30 dB * RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -3.77 dBm
 SWT 300 ms 2.414910000 GHz



3GHz-25GHz:



Ref 20 dBm * Att 30 dB * RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -37.51 dBm
 SWT 2.2 s 24.494000000 GHz




Test mode:	802.11g	Channel:	Middle
-------------------	----------------	-----------------	---------------

30MHz-3GHz:




Ref 20 dBm *Att 30 dB *RBW 100 kHz Marker 1 [T1] -3.91 dBm
*VBW 300 kHz 2.438670000 GHz
SWT 300 ms



3GHz-25GHz:



Ref 20 dBm *Att 30 dB *RBW 100 kHz Marker 1 [T1] -36.82 dBm
*VBW 300 kHz 24.560000000 GHz
SWT 2.2 s




Test mode:	802.11g	Channel:	Highest
-------------------	----------------	-----------------	----------------

30MHz-3GHz:




1 PK
MAXH



3GHz-25GHz:




1 PK
MAXH




Test mode:	802.11n20	Channel:	Lowest
-------------------	------------------	-----------------	---------------

30MHz-3GHz:



3GHz-25GHz:




Test mode:	802.11n20	Channel:	Middle
-------------------	------------------	-----------------	---------------

30MHz-3GHz:




1 PK
MAXH



3GHz-25GHz:



1 PK
MAXH




Test mode:	802.11n20	Channel:	Highest
-------------------	------------------	-----------------	----------------

30MHz-3GHz:




1 PK
MAXH



3GHz-25GHz:



1 PK
MAXH




Test mode:	802.11n40	Channel:	Lowest
-------------------	------------------	-----------------	---------------

30MHz-3GHz:




1 PK
MAXH



3GHz-25GHz:



1 PK
MAXH




Test mode:	802.11n40	Channel:	Middle
-------------------	------------------	-----------------	---------------

30MHz-3GHz:




1 PK
MAXH



3GHz-25GHz:



1 PK
MAXH




Test mode:	802.11n40	Channel:	Highest
-------------------	------------------	-----------------	----------------

30MHz-3GHz:




Ref 20 dBm *Att 30 dB *RBW 100 kHz Marker 1 [T1] -7.39 dBm
*VBW 300 kHz 2.456490000 GHz
SWT 300 ms



3GHz-25GHz:




Ref 20 dBm *Att 30 dB *RBW 100 kHz Marker 1 [T1] -37.20 dBm
*VBW 300 kHz 24.384000000 GHz
SWT 2.2 s




7.7.2 Conducted Band-edge

Test plot as follows:

Test mode:	802.11b	Channel:	Lowest
-------------------	----------------	-----------------	---------------




Test mode:	802.11b	Channel:	Highest
-------------------	----------------	-----------------	----------------



Test mode:	802.11g	Channel:	Lowest
-------------------	----------------	-----------------	---------------




*RBW 100 kHz Marker 3 [T1]
 *VBW 300 kHz -3.37 dBm
 Ref 20 dBm *Att 30 dB SWT 15 ms 2.413368000 GHz




Test mode:	802.11g	Channel:	Highest
-------------------	----------------	-----------------	----------------




*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -3.21 dBm
 Ref 20 dBm *Att 30 dB SWT 10 ms 2.463200000 GHz



Test mode:	802.11n20	Channel:	Lowest
-------------------	------------------	-----------------	---------------




Test mode:	802.11n20	Channel:	Highest
-------------------	------------------	-----------------	----------------



Test mode:	802.11n40	Channel:	Lowest
-------------------	------------------	-----------------	---------------




*RBW 100 kHz Marker 3 [T1]
 *VBW 300 kHz -7.33 dBm
 Ref 20 dBm *Att 30 dB SWT 15 ms 2.433340000 GHz



Test mode:	802.11n40	Channel:	Highest
-------------------	------------------	-----------------	----------------



*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -7.26 dBm
 Ref 20 dBm *Att 30 dB SWT 15 ms 2.449375000 GHz



7.8 Radiated Spurious Emissions and Band-edge

Frequency Range: 9KHz to 25GHz

Test site/setup: Measurement Distance: 3m (Semi-Anechoic Chamber)
Test instrumentation set-up:

Frequency Range	Detector	RBW	VBW
0.009MHz-0.090MHz	Peak	10kHz	30kHz
0.009MHz-0.090MHz	Average	10kHz	30kHz
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz
0.110MHz-0.490MHz	Peak	10kHz	30kHz
0.110MHz-0.490MHz	Average	10kHz	30kHz
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz
30MHz-1GHz	Quasi-peak	100kHz	300kHz
Above 1GHz	Peak	RBW=1MHz	VBW≥RBW
	Average		VBW=10Hz

Sweep=Auto

15.209 Limit:

Frequency	Limit (dBuV/m)
0.009MHz-0.490MHz	128.5 ~ 93.8
0.490MHz-1.705MHz	73.8 ~63.0
1.705MHz-30MHz	69.5
30MHz-88MHz	40.0
88MHz-216MHz	43.5
216MHz-960MHz	46.0
960MHz-1GHz	54.0
Above 1GHz	54.0

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Configuration:




Figure1. Below 30MHz radiated emissions test configuration




Figure2. 30MHz to 1GHz radiated emissions test configuration




Figure3. Above 1GHz radiated emissions test configuration

- Test Procedure:**
- 1) The procedure used was ANSI Standard C63.10:2009. The receiver was scanned from 9KHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.
 - 2) Low noise amplifier was used below 1GHz, High pass Filter was used above 3GHz.
 - a) Between 1G and 3GHz, we did not use any amplifier or filter.
 - b) Pre-test was performed on Antenna A and Antenna B mode, Compliance test was performed on worse case (Antenna A mode).
 - 3) Test were performed for their spatial orthogonal(X, Y, Z), the worst test data (X orthogonal) was submitted.
 - a) For this intentional radiator operates below 25 GHz. the spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 5rd harmonic.
 - b) As shown in Section, for frequencies above 1000MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
 - 4) Pretest under all modes below 1GHz; choose the worst case mode (802.11b) record on the report.
 - 5) The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test Result: Pass


7.8.1 Radiated Spurious Emissions

30MHz-1GHz:

802.11b

lowest Channel

Vertical




Item	Freq.	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1	41.860	17.87	13.10	23.70	0.29	7.56	40.00	-32.44	QP
2	57.999	20.13	12.10	23.69	0.50	9.04	40.00	-30.96	QP
3	124.133	19.05	11.16	23.65	1.05	7.61	43.50	-35.89	QP
4	317.701	19.41	12.73	23.68	1.93	10.39	46.00	-35.61	QP
5	521.561	19.48	16.95	23.75	2.51	15.19	46.00	-30.81	QP
6	612.657	18.71	19.50	23.82	2.75	17.14	46.00	-28.86	QP

802.11b

lowest Channel

Horizontal




Item	Freq.	Read Level	Antenna Factor	Preamplifier Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1	56.882	19.03	12.10	23.69	0.49	7.93	40.00	-32.07	QP
2	114.917	19.05	10.87	23.65	1.00	7.27	43.50	-36.23	QP
3	164.907	19.26	12.25	23.63	1.25	9.13	43.50	-34.37	QP
4	322.189	20.38	12.95	23.68	1.93	11.58	46.00	-34.42	QP
5	546.169	20.04	17.26	23.77	2.58	16.11	46.00	-29.89	QP
6	717.391	18.75	20.67	23.88	3.01	18.55	46.00	-27.45	QP

802.11b

Middle Channel

Vertical




Item	Freq.	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1	42.900	22.49	13.10	23.70	0.30	12.19	40.00	-27.81	QP
2	46.503	21.12	12.99	23.70	0.36	10.77	40.00	-29.23	QP
3	135.506	22.51	11.43	23.64	1.10	11.40	43.50	-32.10	QP
4	161.474	22.21	12.29	23.63	1.24	12.11	43.50	-31.39	QP
5	239.987	22.74	10.10	23.64	1.53	10.73	46.00	-35.27	QP
6	323.320	22.37	13.03	23.68	1.93	13.65	46.00	-32.35	QP

802.11b

Middle Channel

Horizontal




Item	Freq.	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dB μ V)	(dB/m)	(dB)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)	
1	56.882	19.03	12.10	23.69	0.49	7.93	40.00	-32.07	QP
2	114.917	19.05	10.87	23.65	1.00	7.27	43.50	-36.23	QP
3	164.907	19.26	12.25	23.63	1.25	9.13	43.50	-34.37	QP
4	322.189	20.38	12.95	23.68	1.93	11.58	46.00	-34.42	QP
5	546.169	20.04	17.26	23.77	2.58	16.11	46.00	-29.89	QP
6	717.391	18.75	20.67	23.88	3.01	18.55	46.00	-27.45	QP

802.11b

Highest Channel

Vertical




Item	Freq.	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1	40.417	22.53	13.10	23.70	0.27	12.20	40.00	-27.80	QP
2	53.131	22.07	12.32	23.69	0.45	11.15	40.00	-28.85	QP
3	66.034	23.89	11.21	23.68	0.56	11.98	40.00	-28.02	QP
4	140.835	21.63	11.74	23.64	1.13	10.86	43.50	-32.64	QP
5	165.487	21.97	12.24	23.63	1.26	11.84	43.50	-31.66	QP
6	403.250	23.19	14.43	23.70	2.21	16.13	46.00	-29.87	QP

802.11b

Highest Channel

Horizontal



Item	Freq.	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1	43.202	22.64	13.10	23.70	0.31	12.35	40.00	-27.65	QP
2	50.942	21.96	12.59	23.69	0.43	11.29	40.00	-28.71	QP
3	71.581	22.92	10.01	23.68	0.61	9.86	40.00	-30.14	QP
4	151.597	22.96	12.30	23.64	1.17	12.79	43.50	-30.71	QP
5	165.487	22.30	12.24	23.63	1.26	12.17	43.50	-31.33	QP
6	603.539	22.71	19.56	23.81	2.74	21.20	46.00	-24.80	QP



Above 1GHz:

Test mode: 802.11b

Channel: lowest

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4824	40.71	6.40	47.11	54	-6.89	peak	Horizontal
2	7236	38.14	10.76	48.90	54	-5.10	peak	Horizontal
3	9648	38.52	14.37	52.89	54	-1.11	peak	Horizontal
4	4824	39.59	6.40	45.99	54	-8.01	peak	Vertical
5	7236	35.99	10.76	46.75	54	-7.25	peak	Vertical
6	9648	37.28	14.37	51.65	54	-2.35	peak	Vertical

Test mode: 802.11b

Channel: Middle

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4874	39.82	6.92	46.74	54	-7.26	peak	Horizontal
2	7311	39.63	11.08	50.71	54	-3.29	peak	Horizontal
3	9748	38.06	14.36	52.42	54	-1.58	peak	Horizontal
4	4874	39.28	6.92	46.20	54	-7.80	peak	Vertical
5	7311	40.45	11.08	51.53	54	-2.47	peak	Vertical
6	9748	38.11	14.36	52.47	54	-1.53	peak	Vertical

Test mode: 802.11b

Channel: Highest

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4924	40.04	7.31	47.35	54	-6.65	peak	Horizontal
2	7386	40.31	11.41	51.72	54	-2.28	peak	Horizontal
3	9848	36.72	14.38	51.10	54	-2.90	peak	Horizontal
4	4924	40.37	7.31	47.68	54	-6.32	peak	Vertical
5	7386	40.83	11.41	52.24	54	-1.76	peak	Vertical
6	9848	36.72	14.38	51.10	54	-2.90	peak	Vertical

Test mode: 802.11g

Channel: lowest

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4824	41.19	6.40	47.59	54	-6.41	peak	Horizontal
2	7236	37.30	10.76	48.06	54	-5.94	peak	Horizontal
3	9648	38.33	14.37	52.70	54	-1.30	peak	Horizontal
4	4824	41.24	6.40	47.64	54	-6.36	peak	Vertical
5	7236	37.38	10.76	48.14	54	-5.86	peak	Vertical
6	9648	37.79	14.37	52.16	54	-1.84	peak	Vertical

Test mode: 802.11g

Channel: Middle

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4874	38.35	6.92	45.27	54	-8.73	peak	Horizontal
2	7311	38.85	11.08	49.93	54	-4.07	peak	Horizontal
3	9748	37.90	14.36	52.26	54	-1.74	peak	Horizontal
4	4874	40.07	6.92	46.99	54	-7.01	peak	Vertical
5	7311	40.46	11.08	51.54	54	-2.46	peak	Vertical
6	9748	38.33	14.36	52.69	54	-1.31	peak	Vertical

Test mode: 802.11g

Channel: Highest

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4924	39.91	7.31	47.22	54	-6.78	peak	Horizontal
2	7386	39.78	11.41	51.19	54	-2.81	peak	Horizontal
3	9848	36.78	14.38	51.16	54	-2.84	peak	Horizontal
4	4924	40.81	7.31	48.12	54	-5.88	peak	Vertical
5	7386	41.34	11.41	52.75	54	-1.25	peak	Vertical
6	9848	37.25	14.38	51.63	54	-2.37	peak	Vertical

Test mode: 802.11n20

Channel: lowest

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4824	40.64	6.4	47.04	54	-6.96	peak	Horizontal
2	7236	36.74	10.76	47.50	54	-6.50	peak	Horizontal
3	9648	38.60	14.37	52.97	54	-1.03	peak	Horizontal
4	4824	41.16	6.40	47.56	54	-6.44	peak	Vertical
5	7236	38.79	10.76	49.55	54	-4.45	peak	Vertical
6	9648	38.25	14.37	52.62	54	-1.38	peak	Vertical

Test mode: 802.11n20

Channel: Middle

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4874	39.19	6.92	46.11	54	-7.89	peak	Horizontal
2	7311	39.73	11.08	50.81	54	-3.19	peak	Horizontal
3	9748	39.08	14.36	53.44	54	-0.56	peak	Horizontal
4	4874	41.36	6.92	48.28	54	-5.72	peak	Vertical
5	7311	39.66	11.08	50.74	54	-3.26	peak	Vertical
6	9748	38.00	14.36	52.36	54	-1.64	peak	Vertical

Test mode: 802.11n20

Channel: Highest

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4924	40.08	7.31	47.39	54	-6.61	peak	Horizontal
2	7386	39.59	11.41	51.00	54	-3.00	peak	Horizontal
3	9848	36.19	14.38	50.57	54	-3.43	peak	Horizontal
4	4924	40.83	7.31	48.14	54	-5.86	peak	Vertical
5	7386	41.32	11.41	52.73	54	-1.27	peak	Vertical
6	9848	36.80	14.38	51.18	54	-2.82	peak	Vertical

Test mode: 802.11n40

Channel: lowest

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4844	40.82	6.60	47.42	54	-6.58	peak	Horizontal
2	7266	40.01	10.89	50.90	54	-3.10	peak	Horizontal
3	9688	37.18	14.35	51.53	54	-2.47	peak	Horizontal
4	4822	40.76	6.37	47.13	54	-6.87	peak	Vertical
5	7266	40.28	10.89	51.17	54	-2.83	peak	Vertical
6	9688	36.27	14.35	50.62	54	-3.38	peak	Vertical

Test mode: 802.11n40

Channel: Middle

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4874	39.39	6.92	46.31	54	-7.69	peak	Horizontal
2	7311	40.04	11.08	51.12	54	-2.88	peak	Horizontal
3	9748	38.93	14.36	53.29	54	-0.71	peak	Horizontal
4	4874	39.30	6.92	46.22	54	-7.78	peak	Vertical
5	7311	41.16	11.08	52.24	54	-1.76	peak	Vertical
6	9748	38.44	14.36	52.80	54	-1.20	peak	Vertical

Test mode: 802.11n40

Channel: Highest

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4904	39.67	7.22	46.89	54	-7.11	peak	Horizontal
2	7356	38.88	11.28	50.16	54	-3.84	peak	Horizontal
3	9808	36.75	14.37	51.12	54	-2.88	peak	Horizontal
4	4904	40.37	7.22	47.59	54	-6.41	peak	Vertical
5	7356	39.40	11.28	50.68	54	-3.32	peak	Vertical
6	9808	37.01	14.37	51.38	54	-2.62	peak	Vertical



- Remark: 1. Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.
 2. No any other emissions level which are attenuated less than 20dB below the limit. According to 15.31(o), the amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part. Hence there no other emissions have been reported.
 3. If the Peak value below the AV Limit, the AV test doesn't perform for this submission.

7.8.2 Radiated Band edge

Test Mode: 802.11b

Channel: lowest



MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2390	44.73	-3.89	40.84	54	-13.16	Peak	Horizontal
2	2411.04	94.81	-3.93	90.88	54	36.88	Peak	Horizontal
1	2390	46.12	-3.89	42.23	54	-11.77	Peak	Vertical
2	2413.8	96.92	-3.93	92.99	54	38.99	Peak	Vertical



Test Mode: 802.11b

Channel: Highest

MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2460.46	98.62	-3.99	94.63	54	40.63	Peak	Horizontal
2	2483.5	48.74	-4.01	44.73	54	-9.27	Peak	Horizontal
3	2500	54.67	-4.03	50.64	54	-3.36	Peak	Horizontal
1	2463.32	98.79	-3.98	94.81	54	40.81	Peak	Vertical
2	2483.5	48.49	-4.01	44.48	54	-9.52	Peak	Vertical
3	2500	55.78	-4.03	51.75	54	-2.25	Peak	Vertical







Test Mode: 802.11g

Channel: lowest



MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2390	51.14	-3.89	47.25	54	-6.75	Peak	Horizontal
2	2413.44	90.53	-3.93	86.60	54	32.60	Peak	Horizontal
1	2390	52.64	-3.89	48.75	54	-5.25	Peak	Vertical
2	2412.84	91.64	-3.93	87.71	54	33.71	Peak	Vertical



Test Mode: 802.11g

Channel: Highest



MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2462.99	93.94	-3.99	89.95	74	15.95	Peak	Horizontal
2	2483.5	58.43	-4.01	54.42	74	-19.58	Peak	Horizontal
3	2500	52.54	-4.03	48.51	74	-25.49	Peak	Horizontal
1	2462.88	49.12	-3.99	45.13	54	-8.87	Average	Horizontal
2	2483.5	33.48	-4.01	29.47	54	-24.53	Average	Horizontal
3	2500	31.08	-4.03	27.05	54	-26.95	Average	Horizontal



Test Mode: 802.11g

Channel: Highest



MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2463.43	94.38	-3.98	90.40	74	16.40	Peak	Vertical
2	2483.5	59.41	-4.01	55.40	74	-18.60	Peak	Vertical
2	2500	52.17	-4.03	48.14	74	-25.86	Peak	Vertical
1	2469.15	45.88	-3.99	41.89	54	-12.11	Average	Vertical
2	2483.5	32.62	-4.01	28.61	54	-25.39	Average	Vertical
3	2500	30.40	-4.03	26.37	54	-27.63	Average	Vertical



Test Mode: 802.11n20

Channel: lowest


MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2390	56.84	-3.89	52.95	54	-1.05	Peak	Horizontal
2	2418.84	96.73	-3.93	92.8	54	38.80	Peak	Horizontal
1	2390	59.06	-3.89	55.17	74	-18.83	Peak	Vertical
2	2412.72	96.61	-3.93	92.68	74	18.68	Peak	Vertical



Test Mode: 802.11n20

Channel: lowest



MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2390	31.84	-3.89	27.95	54	-26.05	Average	Vertical
2	2410.56	46.39	-3.93	42.46	54	-11.54	Average	Vertical



Test Mode: 802.11n20

Channel: Highest



MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2464.86	98.24	-4.00	94.24	74	20.24	Peak	Horizontal
2	2483.5	65.11	-4.01	61.10	74	-12.90	Peak	Horizontal
3	2500	60.38	-4.03	56.35	74	-17.65	Peak	Horizontal
1	2463.43	48.63	-3.98	44.65	54	-9.35	Average	Horizontal
2	2483.5	34.21	-4.01	30.20	54	-23.80	Average	Horizontal
3	2500	31.23	-4.03	27.20	54	-26.80	Average	Horizontal



Test Mode: 802.11n20

Channel: Highest



MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2463.87	96.64	-3.99	92.65	74	18.65	Peak	Vertical
2	2483.5	63.18	-4.01	59.17	74	-14.83	Peak	Vertical
3	2500	56.62	-4.03	52.59	74	-21.41	Peak	Vertical
1	2463.32	47.22	-3.98	43.24	54	-10.76	Average	Vertical
2	2483.5	34.24	-4.01	30.23	54	-23.77	Average	Vertical
3	2500	30.71	-4.03	26.68	54	-27.32	Average	Vertical



Test Mode: 802.11n40

Channel: lowest



MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2390	63.11	-3.89	59.22	74	-14.78	Peak	Horizontal
2	2423.825	93.46	-3.94	89.52	74	15.52	Peak	Horizontal
1	2390	32.18	-3.89	28.29	54	-25.71	Average	Horizontal
2	2439.34	45.24	-3.96	41.28	54	-12.72	Average	Horizontal



Test Mode: 802.11n40

Channel: lowest



MK.	Frequency (MHz)	Reading (dBUV/m)	Corrected factor(dB)	Result (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	Detector	Polarization
1	2390	64.25	-3.89	60.36	74	-13.64	Peak	Vertical
2	2437.89	91.45	-3.96	87.49	74	13.49	Peak	Vertical
1	2390	34.55	-3.89	30.66	54	-23.34	Average	Vertical
2	2439.34	44.01	-3.96	40.05	54	-13.95	Average	Vertical



Test Mode: 802.11n40

Channel: Highest



MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2461.25	95.68	-3.98	91.70	74	17.7	Peak	Horizontal
2	2483.5	70.93	-4.01	66.92	74	-7.08	Peak	Horizontal
3	2500	61.06	-4.03	57.03	74	-16.97	Peak	Horizontal
1	2465.375	45.04	-3.99	41.05	54	-12.95	Average	Horizontal
2	2483.5	34.15	-4.01	30.14	54	-23.86	Average	Horizontal
3	2500	32.78	-4.03	28.75	54	-25.25	Average	Horizontal



Test Mode: 802.11n40

Channel: Highest

MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2464.875	97.59	-4.00	93.59	74	19.59	Peak	Vertical
2	2483.5	73.21	-4.01	69.20	74	-4.80	Peak	Vertical
3	2500	63.80	-4.03	59.77	74	-14.23	Peak	Vertical
1	2469.125	44.44	-3.99	40.45	54	-13.55	Average	Vertical
2	2483.5	35.17	-4.01	31.16	54	-22.84	Average	Vertical
3	2500	34.22	-4.03	30.19	54	-23.81	Average	Vertical



- Remark: 1. Test Level = Receiver Reading + Antenna Factor + Cable Loss- Preamplifier Factor
 2. No any other emission which falls in restricted bands can be detected and be reported.
 3. If the Peak value below the AV Limit, the AV test doesn't perform for this submission.

All frequencies within the "Restricted bands" have been evaluated to compliance. Section 15.205 Restricted bands of operation.

Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

1. FCC Part 15, Subpart C Section 15.205 Restricted bands of operation.


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.5 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	
13.36 - 13.41			

2. RSS-Gen section 7.2.2 Restricted bands of operation

MHz	MHz	GHz
0.090-0.110	240-285	9.0-9.2
2.1735-2.1905	322-335.4	9.3-9.5
3.020-3.026	399.9-410	10.6-12.7
4.125-4.128	608-614	13.25-13.4
4.17725-4.17775	960-1427	14.47-14.5
4.20725-4.20775	1435-1626.5	15.35-16.2
5.677-5.683	1645.5-1646.5	17.7-21.4
6.215-6.218	1660-1710	22.01-23.12
6.26775-6.26825	1718.8-1722.2	23.6-24.0
6.31175-6.31225	2200-2300	31.2-31.8
8.291-8.294	2310-2390	36.43-36.5
8.362-8.366	2655-2900	Above 38.6
8.37625-8.38675	3260-3267	
8.41425-8.41475	3332-3339	
12.29-12.293	3345.8-3358	
12.51975-12.52025	3500-4400	
12.57675-12.57725	4500-5150	
13.36-13.41	5350-5460	
16.42-16.423	7250-7750	
16.69475-16.69525	8025-8500	
16.80425-16.80475		
25.5-25.67		
37.5-38.25		
73-74.6		
74.8-75.2		
108-138		
156.52475-156.52525		
156.7-156.9		

7.9 99% Occupied Bandwidth

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: Span = approximately 2 to 3 times the 20dB bandwidth, centred on the hopping channel;
3. Set the spectrum analyzer: RBW \geq 1% of the 20dB bandwidth (set 1MHz). VBW \geq RBW. Sweep = auto; Detector Function = Peak. Trace = Max Hold.
4. Mark the peak frequency and -20dB points.

Test Result:


Pass

Test Date:


Test Mode	Channel (MHz)	Bandwidth (MHz)
802.11b	Lowest (2412)	12.39
	Middle (2437)	12.39
	Highest (2462)	12.39
802.11g	Lowest (2412)	16.74
	Middle (2437)	16.74
	Highest (2462)	16.74
802.11n20	Lowest (2412)	17.79
	Middle (2437)	17.79
	Highest (2462)	17.76
802.11n40	Lowest (2422)	36.24
	Middle (2437)	36.32
	Highest (2452)	36.40

Test plot as follows:


Test Mode:	802.11b	Channel:	lowest
-------------------	----------------	-----------------	---------------




Test Mode:	802.11b	Channel:	Middle
-------------------	----------------	-----------------	---------------




Test Mode:	802.11b	Channel:	Highest
-------------------	----------------	-----------------	----------------




Test Mode:	802.11g	Channel:	lowest
-------------------	----------------	-----------------	---------------




Test Mode:	802.11g	Channel:	Middle
-------------------	----------------	-----------------	---------------




Test Mode:	802.11g	Channel:	Highest
-------------------	----------------	-----------------	----------------



Test Mode:	802.11n20	Channel:	lowest
-------------------	------------------	-----------------	---------------




Test Mode:	802.11n20	Channel:	Middle
-------------------	------------------	-----------------	---------------






Test Mode:	802.11n20	Channel:	Highest
-------------------	------------------	-----------------	----------------



Test Mode:	802.11n40	Channel:	lowest
-------------------	------------------	-----------------	---------------



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only




Test Mode:	802.11n40	Channel:	Middle
-------------------	------------------	-----------------	---------------



Ref 20 dBm *Att 30 dB *RBW 1 MHz *VBW 3 MHz SWT 5 ms
Marker 1 [T1] 2.93 dBm 2.434600000 GHz

1 PK
MAXH




Test Mode:	802.11n40	Channel:	Highest
-------------------	------------------	-----------------	----------------



Ref 20 dBm *Att 30 dB *RBW 1 MHz *VBW 3 MHz SWT 5 ms
Marker 1 [T1] 3.30 dBm 2.448560000 GHz

1 PK
MAXH



8 Test Setup Photographs

Refer to the < HS6 _Test Setup photos-FCC>.

9 EUT Constructional Details

Refer to the < HS6 _External Photos-FCC > & < HS6_Internal Photos-FCC>.

--End of the Report--