





ISO/IEC17025Accredited Lab.

Report No: FCC 0806102 File reference No: 2008-06-24

Applicant: WANLIDA GROUP CO.,LTD.

Product: Notebook

Model No: PC-88002

Trademark: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247& Part 15 Subpart B

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4, Part 15 Subpart B &FCC Part 15 Subpart C, Paragraph 15.247 regulations for the

evaluation of electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: Jun 24,2008

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District, Shenzhen,CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 0806102 Page 2 of 78

Date: 2008-06-24



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAL-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC-Registration No.: IC5205A-01

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-01.

Page 3 of 78

Report No: 0806102 Date: 2008-06-24



Test Report Conclusion Content

1.0	General Details	3
1.1	Test Lab Details	3
1.2	Applicant Details	3
1.3	Description of EUT	3
1.4	Submitted Sample	3
1.5	Test Duration.	4
1.6	Test Uncertainty	4
1.7	Test By	4
2.0	List of Measurement Equipment.	4
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test.	14
6.1	Test Method and Test Procedure.	14
6.2	Configuration of the EUT	14
6.3	EUT Operation Condition.	14
6.4	Radiated Emission Limit	15
7.0	6dB Bandwidth Measurement	40
8.0	Maximum Peak Output Power	54
9.0	Power Spectral Density Measurement.	56
10.0	Out of Band Measurement.	64
11.0	Antenna Requirement	69
12.0	Maximum Permissible Exposure	70
13.0	FCC ID Label.	72
14.0	Photo of Test Setup and EUT View	73

Date: 2008-06-24



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Wanlida Group Co., Ltd.

Address: No.618, Jiahe Road, Xiamen, China 361006

Telephone: +86-596-7653680-8516 Fax: +86-596-7662886

1.3 Description of EUT

Product: Notebook

Manufacturer: Wanlida Group Co., Ltd.

Brand Name: N/A

Model Number: PC-88002 Additional Model Name PC-88005

Additional Trade Name N/A

Rating: Input: DC 12V; 24W

Power Supply: Model: MPA-630, Input: 100-240V~, 1A, 50/60Hz; Output: DC12V, 2A

Type of Modulation DBPSK、DQPSK、CCK、OFDM

Frequency range 2412-2462MHz

Number of Channel 11

Air Data Rate 54, 48, 36, 24, 18, 12, 9, 6Mbps at 802.11g mode; 11, 5.5, 2, 1Mbps

at 802.11b mode

Frequency Selection By software

1.4 Submitted Sample

1 Sample

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 5 of 78

Report No: 0806102 Date: 2008-06-24



1.5 Test Duration

2008-06-12 to 2008-06-22

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty = 4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

2.0	.0 Test Equipments							
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date			
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2007-12-05	2008-12-04			
Absorbing Clamp	ROHDE&SCHWARZ	MDS-21	100126	2007-12-05	2008-12-04			
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2007-12-05	2008-12-04			
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2007-12-05	2008-12-04			
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2007-12-05	2008-12-04			
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2007-03-30	2008-03-29			
4-WIRE ISN	ROHDE&SCHWARZ	ENY 41	830663/044	2008-02-18	2009-02-17			
GG ENY22 Double 2-Wire ISN	ROHDE&SCHWARZ	ENY22	83066/016	2008-02-18	2009-02-17			
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2008-02-18	2009-02-17			
System Controller	CT	SC100	-	2008-02-18	2009-02-17			
Printer	EPSON	РНОТО ЕХЗ	CFNH234850	2008-02-18	2009-02-17			
FM-AM Signal Generator	JUNG.JIN	SG-150M	389911177	2008-02-18	2009-02-17			
Color TV Pattern Generator	PHILIPS	PM5418	LO621747	2008-02-18	2009-02-17			

The report refers only to the sample tested and does not apply to the bulk.

Page 6 of 78

Report No: 0806102 Date: 2008-06-24

	,		<i>5</i> /		
Computer	IBM	8434	1S8434KCE99BLX LO*	-	-
Oscillator	KENWOOD	AG-203D	3070002	2008-02-18	2009-02-17
Power meter	Anritsu	ML2487A	6K00003613	2008-02-18	2008-02-17
Power sensor	Anritsu	MA2491A	32263	2008-02-8	2008-02-17
Spectrum Analyzer	HAMEG	HM5012	-	-	-
Power Supply	LW	APS1502	-	-	-
5K VA AC Power Source	California Instruments	5001iX	56060	2008-02-18	2009-02-17
CDN	EM TEST	CDN M2/M3	-	2008-02-18	2009-02-17
Attenuation	EM TEST	ATT6/75	-	2008-02-18	2009-02-17
Resistance	EM TEST	R100	-	2008-02-18	2009-02-17
Electromagnetic Injection Clamp	LITTHI	EM101	35708	2008-02-18	2009-02-17
Signal Generator	ROHDE&SCHWARZ	SMT03	100029	2008-02-18	2009-02-17
Power Amplifier	AR	150W1000	300999	2008-02-18	2009-02-17
Field probe	Holaday	HI-6005	105152	2008-02-18	2009-02-17
Bilog Antenna	Chase	CBL6111C	2576	2008-02-18	2009-02-17
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2008-02-18	2009-02-17
3m OATS			N/A	2008-02-18	2009-02-17
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2007-08-16	2008-08-15
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2007-07-03	2008-07-02

Page 7 of 78

Report No: 0806102 Date: 2008-06-24



3.0 Technical Details

3.1 Summary of test results

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107 & 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(c)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies


3.2 Test Standards

FCC Part 15 Subpart & Subpart C, Paragraph 15.247


4.0 EUT Modification

No modification by Shenzhen Timeway Technology Consulting Co., Ltd

5.



5.1




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 -2003.

Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

Two channels are provided to the EUT

Channel	Channel Frequency (MHz)		Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Page 9 of 78

Report No: 0806102 Date: 2008-06-24



A. EUT

Device	Manufacturer	Model	FCC ID
Notebook	Wanlida Group Co., Ltd.	PC-88002	SMFPC-88002

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
N/A				

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107

Frequ	ency	Class A Lim	its (dB μ V)	Class B Limits (dB µ V)		
(MF	łz)	Quasi-peak Level Average Level		Quasi-peak Level	Average Level	
0.15 ~	0.50	79.0	66.0	66.0~56.0*	56.0~46.0*	
0.50 ~	5.00	73.0	60.0	56.0	46.0	
5.00 ~	30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Note: the worse cases was selected to conducted the test


A Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Read USB,SD card and software, Running EMC test software and Ping

wireless network

Results: Pass

Please refer to following diagram for individual



Date: 17.JUN.2008 12:54:26

Fraguanay	Reading(dB µ V)				Limi	t
Frequency (MHz)	Line	}	Neutral		(dB µ V)	
(MHZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.414	29.54	29.21			57.60	47.60

The report refers only to the sample tested and does not apply to the bulk.




EUT set Condition: Read USB,SD card and software, Running EMC test software and Ping

wireless network

Results: Pass

Please refer to following diagram for individual



Date: 17.JUN.2008 12:52:31

Fraguanay	Reading(dB μ V)				Limi	t
Frequency (MHz)	Live		Neutr	(dB µ	V)	
(MHZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.414			30.00	29.56	57.60	47.60
1.584			21.32	18.76	56.00	46.00


The report refers only to the sample tested and does not apply to the bulk.

C Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Running notebook test program and Ping network

Results: Pass

Please refer to following diagram for individual



Date: 17.JUN.2008 12:45:17

Enganomary		Reading(dB \(\mu \)			Limit		
Frequency (MHz)	Line	Line		Neutral		$(dB \mu V)$	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average	
0.310	34.54	29.21			60.00	50.00	
1.288	33.87	27.98			56.00	46.00	
1.656	33.65	24.55			56.00	46.00	
1.948	36.20	24.43			56.00	46.00	


The report refers only to the sample tested and does not apply to the bulk.



EUT set Condition: Running notebook test program and Ping network

Results: Pass

Please refer to following diagram for individual



Date: 17.JUN.2008 12:48:19

Frequency		Reading(dB µ V)			Limit	
	Live	ve Neutral		(dB µ V)		
(MHz)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.242			36.10	30.43	62.00	52.00
1.184			34.43	27.90	56.00	46.00
1.672			35.32	24.76	56.00	46.00
1.948			36.43	24.43	56.00	46.00

The report refers only to the sample tested and does not apply to the bulk.

Report No: 0806102 Page 14 of 78

Date: 2008-06-24



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization : Vertical polarization and Horizontal polarization.

Block diagram of Test setup Distance = 3m Computer Pre -Amplifier EUT Turn-table Receiver

- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No: 0806102 Page 15 of 78

Date: 2008-06-24



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT

Report No: 0806102 Page 16 of 78

Date: 2008-06-24



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Read USB,SD card and software, Running EMC test software and Ping

wireless network


Results: Pass

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
117.300	35.58	Н	43.50
124.575	37.65	Н	43.50
134.275	35.92	Н	43.50
236.125	36.86	Н	46.00
907.850	40.97	Н	46.00
54.250	34.70	V	40.00
114.875	37.58	V	43.50
124.575	37.51	V	43.50
168.225	35.94	V	43.50



Test Figure:

Radiated Emission Measurement



Radiated Emission Measurement



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 0806102 Page 18 of 78

Date: 2008-06-24

EUT set Condition: Running notebook test program and Ping network


Results: Pass

Frequency (MHz)	Level@3m (dB \mu V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
122.150	36.81	Н	43.50
236.125	35.99	Н	46.00
493.712	40.51	Н	46.00
827.719	40.58	Н	46.00
54.250	34.12	V	40.00
117.300	37.99	V	43.50
192.475	35.65	V	43.50
515.000	40.57	V	46.00



Test Figure:

Radiated Emission Measurement



Radiated Emission Measurement



Note:. Emission level $(dB\mu V/m)$ =Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading $(dB\mu V)$.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 0806102 Page 20 of 78

Date: 2008-06-24

Operation Mode: Transmitting & Receiving under CH01 at 6Mbps

	0 0		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2412.00	85.2(PK) /78.6 (AV)	V	Fundamental Frequency
2412.00	80.2(PK) /76.8 (AV)	Н	Tundamental Trequency
4824.00		H/V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6Mbps
- 4. Test results are for the worst case condition

Operation Mode: Transmitting & Receiving under CH06 at 6Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB μ V/m)
2437.00	78.2 (PK) /74.2 (AV)	Н	Fundamental Frequency
2437.00	84.4 (PK) /75.3 (AV)	V	Fundamental Frequency
4874.00	-	H/V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00	1	H/V	74(Peak)/ 54(AV)
12185	1	H/V	74(Peak)/ 54(AV)
14622	1	H/V	74(Peak)/ 54(AV)
17059	1	H/V	74(Peak)/ 54(AV)
19496	1	H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6Mbps
- 4. Test results are for the worst case condition

The report refers only to the sample tested and does not apply to the bulk.

Report No: 0806102 Page 21 of 78

Operation Mode: Transmitting & Receiving under CH11 at 6Mbps

	operation in our remainment of recording and of course				
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)		
2462.00	83.7 (PK) /76.2 (AV)	V	Fundamental Fraguency		
2462.00	76.9 (PK) /70.5 (AV)	Н	Fundamental Frequency		
4824		H/V	74(Peak)/ 54(AV)		
7368		H/V	74(Peak)/ 54(AV)		
9848		H/V	74(Peak)/ 54(AV)		
12310		H/V	74(Peak)/ 54(AV)		
14772		H/V	74(Peak)/ 54(AV)		
17234		H/V	74(Peak)/ 54(AV)		
19696		H/V	74(Peak)/ 54(AV)		
22158		H/V	74(Peak)/ 54(AV)		
24650		H/V	74(Peak)/ 54(AV)		

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 6Mbps


Date: 2008-06-24

4. Test results are for the worst case condition



Please refer to the following test plots for details

CH01 at 6Mbps: Vertical




Page 23 of 78

Report No: 0806102 Date: 2008-06-24



CH01 at 6Mbps: Horizontal




Page 24 of 78

Report No: 0806102 Date: 2008-06-24



CH06 at 6Mbps: Vertical




Page 25 of 78

Report No: 0806102 Date: 2008-06-24



CH06 at 6Mbps: Horizontal




Page 26 of 78

Report No: 0806102 Date: 2008-06-24



CH11 at 6Mbps: Vertical




Page 27 of 78

Report No: 0806102 Date: 2008-06-24




CH11at 6Mbps: Horizontal





18-25G CH11 6M Horizontal




Page 29 of 78

Report No: 0806102 Date: 2008-06-24



18-25G CH11 6M Vertical



Report No: 0806102 Page 30 of 78

Operation Mode: Transmitting & Receiving under CH01 at 11Mbps					
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)		
2412.00	83.0 (PK)/ 76.1(AV)	V	Fundamental Frequency		
2412.00	80.7 (PK)/74.8 (AV)	Н	Tundamental Frequency		
4824.00	-	H/V	74(Peak)/ 54(AV)		
7236.00	-	H/V	74(Peak)/ 54(AV)		
9648.00	1	H/V	74(Peak)/ 54(AV)		
12060	1	H/V	74(Peak)/ 54(AV)		
14472		H/V	74(Peak)/ 54(AV)		
16684		H/V	74(Peak)/ 54(AV)		
19296		H/V	74(Peak)/ 54(AV)		
21708		H/V	74(Peak)/ 54(AV)		
24120		H/V	74(Peak)/ 54(AV)		

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Date: 2008-06-24

4. Test results are for the worst case condition

Operation Mode: Transmitting & Receiving under CH06 at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2437.00	82.8(PK)/ 75.4AV)	V	Fundamental Fraguency
2437.00	78.7(PK)/73.6 (AV)	Н	Fundamental Frequency
4874.00	1	H/V	74(Peak)/ 54(AV)
7311.00	1	H/V	74(Peak)/ 54(AV)
9748.00	-	H/V	74(Peak)/ 54(AV)
12185	1	H/V	74(Peak)/ 54(AV)
14622	1	H/V	74(Peak)/ 54(AV)
17059	1	H/V	74(Peak)/ 54(AV)
19496	1	H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps
- 4. test results are for the worst case condition

The report refers only to the sample tested and does not apply to the bulk.

Report No: 0806102 Page 31 of 78

Operation Mode: Transmitting & Receiving under CHII at ITM bps				
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)	
2462.00	82.6 (PK) /73.6(AV)	V	Fundamental Frequency	
2462.00	76.5 (PK) /70.8 (AV)	Н	Fundamental Frequency	
4924		H/V	74(Peak)/ 54(AV)	
7368		H/V	74(Peak)/ 54(AV)	
9848		H/V	74(Peak)/ 54(AV)	
12310		H/V	74(Peak)/ 54(AV)	
14772		H/V	74(Peak)/ 54(AV)	
17234		H/V	74(Peak)/ 54(AV)	
19696		H/V	74(Peak)/ 54(AV)	
22158		H/V	74(Peak)/ 54(AV)	
24650		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at 11Mbps


Date: 2008-06-24

4. Test results are for the worst case condition



Please refer to the following test plots for details

CH01 at 11Mbps: Vertical




Page 33 of 78

Report No: 0806102 Date: 2008-06-24



CH01 at 11Mbps: Horizontal




Page 34 of 78

Report No: 0806102 Date: 2008-06-24



CH06 at 11Mbps: Vertical




Page 35 of 78

Report No: 0806102 Date: 2008-06-24



CH06 at 11Mbps: Horizontal




Page 36 of 78

Report No: 0806102 Date: 2008-06-24



CH11 at 11Mbps: Vertical




Page 37 of 78

Report No: 0806102 Date: 2008-06-24



CH11 at 11Mbps: Horizontal




Page 38 of 78

Report No: 0806102 Date: 2008-06-24



18-25G CH11 11M Horizontal




Page 39 of 78

Report No: 0806102 Date: 2008-06-24




18-25G CH11 11M Vertical





7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500KHz

7.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator.

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 100 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

7.4 Test Result

EUT		Notebook		Model		PC-88002		
Mode		802.11b			Input Voltage		120V~	
Temperat	ure	24 deg. C,			Humidity		56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		undwidth Hz)		num Limit MHz)	Pass/ Fail
1		2412	1 11		.10		0.5	Pass
6		2437	1 11		.10	0.5		Pass
11		2462	1 11		.10	0.5		Pass


Page 41 of 78

Report No: 0806102 Date: 2008-06-24




Test Figure:

1. Condition: 802.11b at 11Mbps of CH01




Date: 17.JUN.2008 16:03:47

2. Condition: 802.11b at 11Mbps of CH06



Date: 17.JUN.2008 16:07:43


3. 802.11b at 11Mbps of CH11



Date: 17.JUN.2008 16:11:45




4. 802.11b at 1Mbps of CH01



Date: 17.JUN.2008 16:16:03



5. 802.11b at 1Mbps of CH06




Date: 17.JUN.2008 15:38:05

Report No: 0806102 Page 46 of 78

Date: 2008-06-24



6. 802.11b at 1Mbps of CH11



Date: 17.JUN.2008 15:43:03

Report No: 0806102 Page 47 of 78

Date: 2008-06-24

EUT N		otebook		Model		PC-88002		
Mode		8	302.11g		Input Vo	oltage	120V~	
Temperat	ure	24 deg. C,			Humidity		56% RH	
Channel		nel Frequency (MHz)	Data Transfer Rate (Mbps)		undwidth Hz)		num Limit MHz)	Pass/ Fail
1		2412	6 54		.55		0.5	Pass
6		2437	6 54		.59		0.5	Pass
11		2462	6 54		.63		0.5	Pass


Page 48 of 78

Report No: 0806102 Date: 2008-06-24



Test Plots:

1. 802.11g at 6Mbps of CH01




Date: 17.JUN.2008 15:58:54

Report No: 0806102 Page 49 of 78

Date: 2008-06-24



2. 802.11g at 6Mbps of CH06




Date: 17.JUN.2008 15:56:56

Report No: 0806102 Page 50 of 78

Date: 2008-06-24



3. 802.11g at 6Mbps of CH11




Date: 17.JUN.2008 15:54:34

Report No: 0806102 Page 51 of 78

Date: 2008-06-24



4. 802.11g at 54Mbps of CH01




Date: 17.JUN.2008 16:18:58

Report No: 0806102 Page 52 of 78

Date: 2008-06-24



5. 802.11g at 54Mbps of CH06




Date: 17.JUN.2008 16:22:28

Report No: 0806102 Page 53 of 78

Date: 2008-06-24



6. 802.11g at 54Mbps of CH11



Date: 17.JUN.2008 16:24:48


Report No: 0806102 Page 54 of 78

Date: 2008-06-24



8. Maximum Peak Output Power

8.1 Test Setup



8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Page 55 of 78

Report No: 0806102 Date: 2008-06-24



8.4Test Results

EUT		Noteb	ook Mo		odel P		PC-88002	
Mode	Mode 802.1		Input Input		Input Voltage		20V~	
Temperat	Temperature 24 deg. C,		g. C,	Humidity		50	5% RH	
Channel	Ch	annel Frequency (MHz)	Peak Power Output (dBm)		Peak P Lin (dB	nit	Pass/ Fail	
1		2412	13.74		30)	Pass	
6		2437	13.43		30)	Pass	
11		2462	13.22		30)	Pass	

Note: 1. At finial test to get the worst-case emission at 6Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator


EUT		Notebook		Model		PC-88002	
Mode	Mode 802.11		Input Input		Input Voltage		20V~
Temperati	ature 24 deg. C, Humidity		Humidity 56% RH		umidity 5		
Channel	Cha	annel Frequency (MHz)	y Peak Power Output (dBm)		Peak Power Limit (dBm)		Pass/ Fail
1		2412	13.22		30)	Pass
6		2437	13.12		30)	Pass
11		2462	12.73		30)	Pass


Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

Report No: 0806102 Page 56 of 78





9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3KHz RBW and 10kHz VBW, set sweep time=100s

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

Page 57 of 78

Report No: 0806102 Date: 2008-06-24



9.4Test Result


EUT		Noteb	ook Mo		odel P		PC-88002	
Mode	Mode 802.1		1g	Input Voltage		t Voltage 12		
Temperati	Temperature 24 deg. C,		g. C,	Humidity		56	5% RH	
Channel	Ch	annel Frequency (MHz)	Level in 3kHz BV		Maximum Limit (dBm)		Pass/ Fail	
1		2412	-22.83		8		Pass	
6		2437	-23.01		8		Pass	
11		2462	-23.31		8		Pass	


Note: For 802.11g mode at finial test to get the worst-case emission at 6Mbps for CH11, CH06 and CH01

EUT		Noteb	ook Mo		odel	PC	C-88002		
Mode	Mode 802.1		1g	Input Voltage		1	20V~		
Temperati	ure	24 deg	C, Humidity 56		eg. C, Humidity		24 deg. C,		5% RH
Channel	Cha	annel Frequency (MHz)		nal RF Power el in 3kHz BW (dBm)		m Limit m)	Pass/ Fail		
1		2412	-17.33		8		Pass		
6		2437	-17.64		8		Pass		
11		2462	-17.73	8			Pass		

Note: For 802.11g mode at finial test to get the worst-case emission at 54Mbps for CH11, CH06 and CH01

Report No: 0806102 Date: 2008-06-24





Date: 27.JUN.2008 12:30:52

Page 59 of 78


Span 300 kHz

Report No: 0806102 Date: 2008-06-24



2. 802.11g at 6Mbps at CH06





30 kHz/

27.JUN.2008 12:32:51 Date:

Center 2.437 GHz


Page 60 of 78

Report No: 0806102 Date: 2008-06-24



3. 802.11g at 6Mbps of CH11





27.JUN.2008 12:35:21 Date:

Page 61 of 78


Span 300 kHz

Report No: 0806102 Date: 2008-06-24



4. 802.11b at 11Mbps of CH01





30 kHz/

Date: 27.JUN.2008 12:42:33

Center 2.412 GHz

-90


Page 62 of 78

Span 300 kHz

Report No: 0806102 Date: 2008-06-24



5. 802.11b at 11Mbps of CH06



30 kHz/

Date: 27.JUN.2008 12:40:22

Center 2.437 GHz

80

-90

Page 63 of 78


Span 300 kHz

Report No: 0806102 Date: 2008-06-24



6. 802.11b at 11Mbps of CH11





30 kHz/

27.JUN.2008 12:38:01 Date:

Center 2.462 GHz


Report No: 0806102 Page 64 of 78

Date: 2008-06-24



10 Out of Band Measurement

10.1 Test Setup



10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of the amplitude of the spurious emissions with respect to the intentional signals. The relative amplitude, in dBc, was applied to the average and peak filed strength of the intentional signal made on the OATS to calculate the field strength of the unintentional signals.

The spectrum plots (Peak RBW=VBW=1MHz; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

10.4Test Result

Report No: 0806102 Date: 2008-06-24




For 802.11b mode

CH01 at 11Mbps

10.4 Out of Band Test Result

Product:	Notel	oook	Test Mode:	CH1
Mode	Keeping Tr	ansmitting	Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pas	Pass		PK
The Max. FS in	PK (dBμV/m)	41.9(V)/38.2(H)	Limit	$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)	35.6(V)/32.2(H)	Limit	54(dBµV/m)

Test Figure:



Date: 17.JUN.2008 19:15:57

Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 66 of 78

Report No: 0806102 Date: 2008-06-24




CH11 at 11Mbps

10.4 Out of Band Test Result

Product:	Notel	ook	Test Mode:	CH11
Mode	Keeping Tr	ansmitting	Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBµV/m)	40.3(V)/39.2(H)	T ' ',	$74(dB\mu V/m)$
Restrict Band	$AV(dB\mu V/m)$	34.1(V)/33.6(H)	Limit	$54(dB\mu V/m)$

Test Figure:



Date: 17.JUN.2008 19:20:48

Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 0806102 Date: 2008-06-24




For 802.11g mode

CH01 at 6Mbps

10.4 Out of Band Test Result

Product:	Notel	oook	Test Mode:	CH1
Mode	Keeping Tr	ansmitting	Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pas	SS	Detector	PK
The Max. FS in	PK ($dB\mu V/m$)	55.3(V)/53.2(H)	Limit	$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)	42.8(V)/41.2(H)	Limit	54(dBµV/m)

Test Figure:



Date: 27.JUN.2008 15:26:40

Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 68 of 78

Report No: 0806102 Date: 2008-06-24




CH11 at 6Mbps

10.4 Out of Band Test Result

Product:	Notel	ook	Test Mode:	CH11
Mode	Keeping Tra	ansmitting	Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBµV/m)	50.2(H)/47.5(V)	T ' '/	$74(dB\mu V/m)$
Restrict Band	$AV(dB\mu V/m)$	37.3(H)/36.8(V)	Limit	$54(dB\mu V/m)$

Test Figure:



Date: 17.JUN.2008 19:21:45

Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 0806102 Page 69 of 78

Date: 2008-06-24



11.0 Antenna Requirement 11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi

are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

There are two antennas used in the device. An RF cable connected the IPX connector with the antenna board. The maximum Gain of both antennas is 1.50dBi.

Report No: 0806102 Page 70 of 78

Date: 2008-06-24



12.0 Maximum Permissible Exposure

Applicable Standard

According to §1.1307(b)(5), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline. This is a Portable device.

According to §1.1310 and §2.1093 RF exposure is calculated.

Measurement Result

This is a laptop and the conducted output power is 13.74dBm (23.659mW), which is lower than low threshold 60/fGHz mW (60/2.462GHz = 24.37 mW), and the antenna is 1.5dBi which is less than 6dBi.

The SAR measurement is not necessary.

Page 71 of 78

Report No: 0806102 Date: 2008-06-24



13.0 FCC ID Label

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Report No: 0806102 Date: 2008-06-24




14.0 Photo of testing

14.1 Conducted test View--



14.2 Emission Radiated test View--



14.3 Photo for the EUT

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Report No: 0806102 Date: 2008-06-24







14.4 Photo for the EUT

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 74 of 78

Report No: 0806102 Date: 2008-06-24







The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Report No: 0806102 Date: 2008-06-24







The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 76 of 78

Report No: 0806102 Date: 2008-06-24








The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report

Report No: 0806102 Date: 2008-06-24





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 78 of 78

Report No: 0806102 Date: 2008-06-24







End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to