



Product Service

RF - TEST REPORT

Report Number : **68/850.9.011.01** Date of Issue: 27 March 2009

Model : **PC-88012N**

Product Type : Notebook Computer

Applicant : Wanlida Group Co., Ltd.

Address : No. 618 Jiahe Road, Wanlida Industry Zone,
Xiamen Fujian, China 361006

Production Facility : Wanlida Group Co., Ltd.

Address : Wanlida Industry Zone, Nanjing, Fujian, China 363601

Test Result : **Positive** **Negative**

Total pages including
Appendices : 45

Jiangsu TÜV Product Service Ltd. – Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

Jiangsu TÜV Product Service Ltd. – Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. Jiangsu TÜV Product Service Ltd. – Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from Jiangsu TÜV Product Service Ltd. – Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval



1 Table of Contents

| | | |
|-----|--|----|
| 1 | Table of Contents..... | 2 |
| 2 | Details about the Test Laboratory..... | 3 |
| 3 | Description of the Equipment Under Test..... | 4 |
| 4 | Summary of Test Standards..... | 5 |
| 5 | Summary of Test Results..... | 6 |
| 6 | General Remarks..... | 7 |
| 7 | Technical Requirements..... | 8 |
| 7.1 | Conducted Emission AC Power Port..... | 8 |
| 7.2 | Conducted Peak Power..... | 12 |
| 7.3 | Band edge compliance of RF emission..... | 14 |
| 7.4 | Spurious RF Conducted emission..... | 22 |
| 7.5 | Spurious radiated emissions..... | 27 |
| 7.6 | 6dB bandwidth..... | 33 |
| 7.7 | Power spectral density..... | 39 |
| 8 | System Measurement Uncertainty..... | 45 |



Product Service

2 Details about the Test Laboratory

Details about the Test Laboratory

Company name: Jiangsu TÜV Product Service Ltd. – Shenzhen Branch
6th Floor, H Hall,
Century Craftwork Culture Square,
No. 4001, Fuqiang Road,
Futian District 518048,
Shenzhen, P.R.C.

Telephone: 86 755 8828 6998
Fax: 86 755 8828 5299

Company name: China Shenzhen Academy of Metrology and Quality Inspection,
Metrology and Quality Inspection building,
Central Section of LongZhu Road,
Nan Shan,
Shenzhen,

Telephone: 86 755 2694 1599
Fax: 86 755 2694 1545



3 Description of the Equipment Under Test

Description of the Equipment Under Test

| | |
|----------------------------|---|
| Product: | Notebook Computer |
| Model no.: | PC-88012N |
| Serial number: | NIL |
| Options and accessories: | NIL |
| Rating: | DC 12V 3A, 36W AC Adaptor: Model: MPA-12030 Input: 100-240V ~ 50/60Hz 0.65A MAX Output: 12V DC 3A |
| Antenna: | One integral antenna inside enclosure of EUT, NOT accessible by end user Antenna gain: 1.5dBi |
| RF Transmission Frequency: | 2412-2462MHz |
| Description of the EUT: | NIL |

Auxiliary Equipment and Cable Used during Test:

| DESCRIPTION | MANUFACTURER | MODEL NO.(SHIELD) | S/N(LENGTH) |
|-----------------|--------------|-------------------|-------------|
| LCD monitor | Lenovo | 9227-AE1 | V1TDB38 |
| Keyboard | Lenovo | SK-8825 (L) | 02553778 |
| Mouse | Lenovo | MO28UOL | 4418011108 |
| Headphone | Ouyun | OH601 | ---- |
| USB flash drive | Kingston | Data Traveller | ---- |
| SD card | Kingston | SD4/4GBFE | ---- |
| VGA cable | Lenovo | Shield | 140cm |
| AC Power cable | Lenovo | Unshield | 180cm |



Product Service

4 Summary of Test Standards

| Test Standards | |
|-----------------------|--|
| FCC Part 15 Subpart C | PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators |

5 Summary of Test Results

| Technical Requirements | | | | |
|--|-------|-------------------------------------|--------------------------|--------------------------|
| FCC Part 15 Subpart C | | | | |
| Test Condition | Pages | Test Result | | |
| | | Pass | Fail | N/A |
| 15.207 Conducted Emission AC Power Port | 8 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 15.247 (b) (1) Conducted peak output power | 12 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 15.247(d) Band edge compliance of RF emissions | 14 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 15.247(d) Spurious RF conducted emissions | 22 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 15.247(d) 15.209 Spurious radiated emissions | 27 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 15.247(a)(2) 6dB bandwidth | 33 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 15.247(e) Power spectral density | 39 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |



6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: SMFPC88012N filing to comply with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment Under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: 7 Jan 2009

Testing Start Date: 10 Feb 2009

Testing End Date: 10 March 2009

- TÜV SÜD CHINA, SHENZHEN BRANCH -

Reviewed by:

Prepared by:

Paul Yu
EMC Project Manager

Tammy Chen
EMC Assistant Project Manager

7 Technical Requirement

7.1 Conducted Emission

Test Method

- 1 The EUT was placed on a table, which is 0.8m above ground plane
- 2 The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
- 3 Maximum procedure was performed to ensure EUT compliance
- 4 A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions from both sides of AC line

Limit


| Frequency MHz | QP Limit dB μ V | AV Limit dB μ V |
|------------------|------------------------|------------------------|
| 0.150-0.500 | 66-56* | 56-46* |
| 0.500-5 | 56 | 46 |
| 5-30 | 60 | 50 |

Decreasing linearly with logarithm of the frequency

Conducted Emission

Conducted Disturbance

EUT: M/N:PC-88012N
 Op Cond: WIFI
 Test Spec: L
 Comment: AC 120V/60Hz



| Frequency MHz | Cable Loss dB | Reading dBµV | QP Test result dBµV | QP Limit dBµV | Margin dB |
|------------------|------------------|-----------------|------------------------|------------------|--------------|
| 0.168 | 9.8 | 31.3 | 41.1 | 65.1 | 24 |
| 0.201 | 9.8 | 32.5 | 42.3 | 63.6 | 21.3 |
| 0.335 | 9.8 | 22.1 | 31.9 | 59.3 | 27.4 |
| 0.441 | 9.8 | 19.4 | 29.2 | 57.0 | 27.8 |
| 0.553 | 9.9 | 24.2 | 34.1 | 56 | 21.9 |
| 0.879 | 9.9 | 22.3 | 32.2 | 56 | 23.8 |


| Frequency MHz | Cable Loss dB | Reading dBµV | AV Test result dBµV | AV Limit dBµV | Margin dB |
|------------------|------------------|-----------------|------------------------|------------------|--------------|
| 0.168 | 9.8 | 20.1 | 29.9 | 55.1 | 25.2 |
| 0.201 | 9.8 | 14.3 | 24.1 | 53.6 | 29.5 |
| 0.335 | 9.8 | 16.3 | 26.1 | 49.3 | 23.2 |
| 0.441 | 9.8 | 9.7 | 19.5 | 47 | 27.5 |
| 0.553 | 9.9 | 17.2 | 27.1 | 46 | 18.9 |
| 0.879 | 9.9 | 15.6 | 25.5 | 46 | 20.5 |

Remark: Test Result= Reading + Cable Loss

Conducted Emission

Conducted Disturbance

EUT: M/N:PC-88012N
 Op Cond: WIFI
 Test Spec: N
 Comment: AC 120V/60Hz



| Frequency MHz | Cable Loss dB | Reading dBµV | QP Test result dBµV | QP Limit dBµV | Margin dB |
|------------------|------------------|-----------------|------------------------|------------------|--------------|
| 0.161 | 9.8 | 30.6 | 40.4 | 65.4 | 25 |
| 0.196 | 9.8 | 33.5 | 43.3 | 63.8 | 20.5 |
| 0.354 | 9.8 | 22.5 | 32.3 | 58.9 | 26.6 |
| 0.416 | 9.8 | 20.5 | 30.3 | 57.5 | 27.2 |
| 0.587 | 9.9 | 25.5 | 35.4 | 56 | 20.6 |
| 0.881 | 9.9 | 23.2 | 33.1 | 56 | 22.9 |

| Frequency MHz | Cable Loss dB | Reading dBµV | AV Test result dBµV | AV Limit dBµV | Margin dB |
|------------------|------------------|-----------------|------------------------|------------------|--------------|
| 0.161 | 9.8 | 20.5 | 30.3 | 55.4 | 25.1 |
| 0.196 | 9.8 | 15.7 | 25.5 | 53.8 | 28.3 |
| 0.354 | 9.8 | 14.9 | 24.7 | 48.9 | 24.2 |
| 0.416 | 9.8 | 13.9 | 23.7 | 47.5 | 23.8 |
| 0.587 | 9.9 | 14.9 | 24.8 | 46 | 21.2 |
| 0.881 | 9.9 | 14.2 | 24.1 | 46 | 21.9 |

Remark: Test Result= Reading + Cable Loss



Test Equipment List

| DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL DUE DATE |
|-------------------|-----------------|-----------|------------|--------------|
| EMI Test Receiver | Rohde & Schwarz | ESCS30 | 100003 | Dec 23 2009 |
| AMN | Rohde & Schwarz | ESH3-Z5 | 100229 | Dec 23 2009 |
| AMN | Rohde & Schwarz | ENV216 | 100042 | Dec 23 2009 |

7.2 Conducted peak output power

Test Method

The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.

Limits for conducted peak output power measurements

| Frequency Range MHz | Limit W | Limit dBm |
|------------------------|------------|--------------|
| 2400-2483 | ≤1 | ≤30 |

Conducted peak output power

DSSS mode QPSK modulation 11Mbps data rate Test Result

| Frequency MHz | Conducted Peak Output Power dBm | Result |
|------------------|---------------------------------------|--------|
| CH1 2412MHz | 15.73 | Pass |
| CH2 2442MHz | 16.31 | Pass |
| CH3 2462MHz | 16.31 | Pass |

OFDM mode BPSK modulation 6Mbps data rate Test Result

| Frequency MHz | Conducted Peak Output Power dBm | Result |
|------------------|---------------------------------------|--------|
| CH1 2412MHz | 14.85 | Pass |
| CH2 2442MHz | 15.13 | Pass |
| CH3 2462MHz | 15.12 | Pass |



Product Service

Test Equipment

| DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL DUE DATE |
|-------------------|-----------------|-----------|------------|--------------|
| EMI Test Receiver | Rohde & Schwarz | ESPI3 | 100244 | Dec 23 2009 |

7.3 Band edge compliance of RF emissions

Test Method

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW and VBW to 1MHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength.

The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW and VBW to 100kHz, to measure the conducted peak band edge.

Limits

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

| Frequency MHz | Limit Average dBuV/m | Limit Peak dBuV/m |
|-------------------------|-------------------------|----------------------|
| Below 2390 Above 2483.5 | 54 | 74 |




Band edge compliance of RF emissions

DSSS mode QPSK modulation 11Mbps data rate Test Result

Maximum Carrier Field strength

| Frequency MHz | Cable Loss dB | Antenna Factor dB/m | Reading dBuV | Emission Level dBuV/m | Polarization | Limit dBuV/m | Detector | Result |
|------------------|---------------------|---------------------------|-----------------|-----------------------------|--------------|-----------------|----------|--------|
| 2412.000 | 5.6 | 28.5 | 58.6 | 92.7 | Horizontal | --- | PK | --- |
| 2412.000 | 5.6 | 28.5 | 51.1 | 85.2 | Horizontal | --- | AV | --- |
| 2462.000 | 5.6 | 28.5 | 60.3 | 94.4 | Horizontal | --- | PK | --- |
| 2462.000 | 5.6 | 28.5 | 53.5 | 87.6 | Horizontal | --- | AV | --- |


Lower Edge PK plot



Date: 17.FEB.2009 02:55:44

Max carrier field strength PK 92.7dBuV/m, AV 85.2dBuV/m
 At 2.390GHz, the deviation of PK plot is 51.36dB
 The field strength at 2.390GHz PK 41.34dBuV/m
 Which fulfill the requirement of PK 74dBuV/m, AV 54dBuV/m.
 PK plot shows compliance with the AV limit, AV plot is omitted.

Upper Edge PK plot



Date: 17.FEB.2009 02:58:03

Max carrier field strength PK 94.4dBuV/m, AV 87.6dBuV/m
 At 2.4835GHz, the deviation of PK plot is 56.41dB
 The field strength at 2.4835GHz PK 40.55dBuV/m
 Which fulfill the requirement of PK 74dBuV/m, AV 54dBuV/m.
 PK plot shows compliance with the AV limit, AV plot is omitted.



Band edge compliance of RF emissions

OFDM mode BPSK modulation 6Mbps data rate Test Result


Maximum Carrier Field strength Carrier Field strength

| Frequency MHz | Cable Loss dB | Antenna Factor dB/m | Reading dBuV | Emission Level dBuV/m | Polarization | Limit dBuV/m | Detector | Result |
|------------------|---------------------|---------------------------|-----------------|-----------------------------|--------------|-----------------|----------|--------|
| 2412.000 | 5.6 | 28.5 | 57.4 | 91.5 | Horizontal | --- | PK | --- |
| 2412.000 | 5.6 | 28.5 | 49.3 | 83.4 | Horizontal | --- | AV | --- |
| 2462.000 | 5.6 | 28.5 | 60.0 | 94.1 | Horizontal | --- | PK | --- |
| 2462.000 | 5.6 | 28.5 | 51.5 | 85.6 | Horizontal | --- | AV | --- |

Lower Edge PK Plot



Ref 127 dBµV Att 30 dB RBW 100 kHz Marker 2 [T1]
 VBW 100 kHz 66.38 dBµV
 SWT 5 ms 2.390000000 GHz




Date: 17.FEB.2009 02:52:35

Max carrier field strength PK 91.5dBuV/m, AV 83.4dBuV/m
 At 2.390GHz, the deviation of PK plot is 40.66dB
 The field strength at 2.390GHz PK 50.84dBuV/m
 Which fulfill the requirement of PK 74dBuV/m, AV 54dBuV/m.
 PK plot shows compliance with the AV limit, AV plot is omitted.

Upper Edge PK Plot



Ref 127 dBuV *Att 30 dB SWT 5 ms
 *RBW 100 kHz Marker 1 [T1] 107.59 dBuV
 *VBW 100 kHz 2.459500000 GHz



Date: 17.FEB.2009 02:58:57

Max carrier field strength PK 94.1dBuV/m, AV 85.6dBuV/m
 At 2.4835GHz, the deviation of PK plot is 40.34dB
 The field strength at 2.4835GHz PK 53.76dBuV/m
 Which fulfill the requirement of PK 74dBuV/m, AV 54dBuV/m.
 PK plot shows compliance with the AV limit, AV plot is omitted.



Product Service

Test Equipment List

| DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL DUE DATE |
|-------------------|-----------------|-----------|------------|--------------|
| EMI Test Receiver | Rohde & Schwarz | ESPI3 | 100244 | Dec 23 2009 |

7.4 Spurious RF conducted emissions

Test Method

The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.


Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The resolution bandwidth(RBW) and the video bandwidth (VBW) of the spectrum analyzer were respectively set to 100kHz and 100kHz.


Limit

| Frequency Range MHz | Limit (dBc) |
|------------------------|-------------|
| 1000-25000 | -20 |

Spurious RF conducted emissions DSSS mode QPSK modulation 11Mbps data rate Test Result 2412MHz




2442MHz



Spurious RF conducted emissions

2462MHz

| | | | | | | |
|--|----------------|-------------------|-----|---------|--------|------------|
| | Ref Lvl | Marker 1 [T1] | RBW | 100 kHz | RF Att | 30 dB |
| | 117 dB μ V | 111.48 dB μ V | VBW | 100 kHz | | |
| | | 2.38188377 GHz | SWT | 6.4 s | Unit | dB μ V |




Date: 17.FEB.2009 15:23:29

OFDM mode BPSK modulation 6Mbps data rate Test Result

2412MHz

| | | | | | | |
|--|----------------|-------------------|-----|---------|--------|------------|
| | Ref Lvl | Marker 1 [T1] | RBW | 100 kHz | RF Att | 30 dB |
| | 117 dB μ V | 106.96 dB μ V | VBW | 100 kHz | | |
| | | 2.38188377 GHz | SWT | 6.4 s | Unit | dB μ V |




Date: 17.FEB.2009 14:34:12

Spurious RF conducted emissions

2442MHz


| | | | | | | |
|--|----------------|-------------------|-----|---------|--------|------------|
| | Ref Lvl | Marker 1 [T1] | RBW | 100 kHz | RF Att | 30 dB |
| | 117 dB μ V | 106.81 dB μ V | VBW | 100 kHz | | |
| | | 2.38188377 GHz | SWT | 6.4 s | Unit | dB μ V |



Date: 17.FEB.2009 15:21:09

2462MHz

| | | | | | | |
|--|----------------|-------------------|-----|---------|--------|------------|
| | Ref Lvl | Marker 1 [T1] | RBW | 100 kHz | RF Att | 30 dB |
| | 117 dB μ V | 108.10 dB μ V | VBW | 100 kHz | | |
| | | 2.43192385 GHz | SWT | 6.4 s | Unit | dB μ V |



Date: 17.FEB.2009 15:22:49



Product Service

Test Equipment List

| DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL DUE DATE |
|-------------------|-----------------|-----------|------------|--------------|
| EMI Test Receiver | Rohde & Schwarz | ES126 | 838786/013 | Dec 23 2009 |

7.5 Spurious radiated emissions

Test Method

- 1 The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2 The turntable shall be rotated for 360 degrees to determine the position of maximum emission level
- 3 EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4 Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5 Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

Limit

| Frequency MHz | Field Strength uV/m | Field Strength dB μ V/m | Detector |
|------------------|------------------------|--------------------------------|----------|
| 30-88 | 100 | 40 | QP |
| 88-216 | 150 | 43.5 | QP |
| 216-960 | 200 | 46 | QP |
| 960-1000 | 500 | 54 | QP |
| Above 1000 | 500 | 54 | AV |
| Above 1000 | 5000 | 74 | PK |

Radiated Emission

DSSS mode QPSK modulation 11Mbps data rate CH1 2412MHz Test Result

| Frequency MHz | Cable Loss dB | Antenna Factor dB/m | Reading dBuV | Emission Level dBuV/m | Polarization | Limit dBuV/m | Detector | Result |
|------------------|---------------------|---------------------------|-----------------|-----------------------------|--------------|-----------------|----------|--------|
| 31.343 | 0.9 | 18.8 | 13.0 | 32.7 | Horizontal | 40 | QP | Pass |
| 98.331 | 1.6 | 11.9 | 24.3 | 37.8 | Horizontal | 43.5 | QP | Pass |
| 31.793 | 0.9 | 18.8 | 13.5 | 33.2 | Vertical | 40 | QP | Pass |
| 180.934 | 2.2 | 9.8 | 26.5 | 38.5 | Vertical | 43.5 | QP | Pass |
| 1300.009 | 4.4 | 28.5 | 14.1 | 48.1 | Horizontal | 74 | PK | Pass |
| 1300.009 | 4.4 | 28.5 | 13.2 | 47.2 | Horizontal | 54 | AV | Pass |
| 2133.376 | 5.3 | 28.5 | 13.3 | 47.1 | Horizontal | 74 | PK | Pass |
| 2133.376 | 5.3 | 28.5 | 12.7 | 46.5 | Horizontal | 54 | AV | Pass |
| 4824.884 | 4.2 | 33.3 | 11.7 | 48.8 | Horizontal | 74 | PK | Pass |
| 4824.884 | 4.2 | 33.3 | 10.1 | 47.2 | Horizontal | 54 | AV | Pass |
| 7236.541 | 4.2 | 36.4 | 8.2 | 48.4 | Horizontal | 74 | PK | Pass |
| 7236.541 | 5.2 | 36.4 | 7.3 | 47.5 | Horizontal | 54 | AV | Pass |
| 9648.562 | 5.2 | 37.5 | 6.5 | 47.8 | Horizontal | 74 | PK | Pass |
| 9648.562 | 6.0 | 37.5 | 5.6 | 46.9 | Horizontal | 54 | AV | Pass |
| 12060.514 | 6.0 | 38.4 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 12060.514 | 7.0 | 38.4 | ---- | ---- | Horizontal | 54 | AV | Pass |
| 14472.542 | 7.0 | 42.6 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 14472.542 | 7.6 | 42.6 | ---- | ---- | Horizontal | 54 | AV | Pass |

DSSS mode QPSK modulation 11Mbps data rate CH7 2442MHz Test Result

| Frequency MHz | Cable Loss dB | Antenna Factor dB/m | Reading dBuV | Emission Level dBuV/m | Polarization | Limit dBuV/m | Detector | Result |
|------------------|---------------------|---------------------------|-----------------|-----------------------------|--------------|-----------------|----------|--------|
| 1300.009 | 4.4 | 25.1 | 9.4 | 38.9 | Horizontal | 74 | PK | Pass |
| 1300.009 | 4.4 | 25.1 | 1.6 | 31.1 | Horizontal | 54 | AV | Pass |
| 2133.376 | 5.3 | 28.5 | 12.5 | 46.3 | Horizontal | 74 | PK | Pass |
| 2133.376 | 5.3 | 28.5 | 4.0 | 37.8 | Horizontal | 54 | AV | Pass |
| 4884.433 | 4.3 | 33.3 | 12.1 | 49.2 | Horizontal | 74 | PK | Pass |
| 4884.433 | 4.3 | 33.3 | 10.0 | 47.1 | Horizontal | 54 | AV | Pass |
| 7326.512 | 5.2 | 36.4 | 8.6 | 48.8 | Horizontal | 74 | PK | Pass |
| 7326.512 | 5.2 | 36.4 | 6.2 | 46.4 | Horizontal | 54 | AV | Pass |
| 9768.438 | 6.0 | 37.5 | 5.0 | 46.3 | Horizontal | 74 | PK | Pass |
| 9768.438 | 6.0 | 37.5 | 3.2 | 44.5 | Horizontal | 54 | AV | Pass |
| 12210.322 | 7.0 | 38.4 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 12210.322 | 7.0 | 38.4 | ---- | ---- | Horizontal | 54 | AV | Pass |
| 14652.279 | 7.6 | 41.1 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 14652.279 | 7.6 | 41.1 | ---- | ---- | Horizontal | 54 | AV | Pass |

**Radiated Emission**

DSSS mode QPSK modulation 11Mbps data rate CH11 2462MHz Test Result

| Frequency MHz | Cable Loss dB | Antenna Factor dB/m | Reading dBuV | Emission Level dBuV/m | Polarization | Limit dBuV/m | Detector | Result |
|------------------|---------------------|---------------------------|-----------------|-----------------------------|--------------|-----------------|----------|--------|
| 1300.009 | 4.4 | 25.1 | 9.6 | 39.1 | Horizontal | 74 | PK | Pass |
| 1300.009 | 4.4 | 25.1 | 2.7 | 32.2 | Horizontal | 54 | AV | Pass |
| 2133.376 | 5.3 | 28.5 | 12.5 | 46.3 | Horizontal | 74 | PK | Pass |
| 2133.376 | 5.3 | 28.5 | 4.4 | 38.2 | Horizontal | 54 | AV | Pass |
| 4924.723 | 4.3 | 33.3 | 15.1 | 52.2 | Horizontal | 74 | PK | Pass |
| 4924.723 | 4.3 | 33.3 | 10.6 | 47.7 | Horizontal | 54 | AV | Pass |
| 7386.564 | 5.2 | 36.4 | 9.2 | 49.4 | Horizontal | 74 | PK | Pass |
| 7386.564 | 5.2 | 36.4 | 7.9 | 48.1 | Horizontal | 54 | AV | Pass |
| 9848.331 | 6.0 | 37.5 | 7.5 | 48.8 | Horizontal | 74 | PK | Pass |
| 9848.331 | 6.0 | 37.5 | 0.8 | 42.1 | Horizontal | 54 | AV | Pass |
| 12310.651 | 6.9 | 38.4 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 12310.651 | 6.9 | 38.4 | ---- | ---- | Horizontal | 54 | AV | Pass |
| 14772.289 | 7.6 | 41.1 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 14772.289 | 7.6 | 41.1 | ---- | ---- | Horizontal | 54 | AV | Pass |

Remark:

- (1) Emission Level= Cable Loss(include amplifier factor) + Antenna Factor + Reading
- (2) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.

Radiated Emission

OFDM mode BPSK modulation 6Mbps data rate CH1 2412MHz Test Result

| Frequency MHz | Cable Loss dB | Antenna Factor dB/m | Reading dBuV | Emission Level dBuV/m | Polarization | Limit dB μ V/m | Detector | Result |
|------------------|---------------------|---------------------------|-----------------|-----------------------------|--------------|-----------------------|----------|--------|
| 146.633 | 2.1 | 11.3 | 24.8 | 38.2 | Vertical | 43.5 | QP | Pass |
| 220.441 | 2.6 | 10.6 | 5.0 | 18.1 | Vertical | 46 | QP | Pass |
| 200.032 | 2.4 | 10.3 | 24.6 | 37.3 | Horizontal | 46 | QP | Pass |
| 280.150 | 2.8 | 13.4 | 4.4 | 20.6 | Horizontal | 46 | QP | Pass |
| 2324.501 | 5.5 | 28.5 | 14.1 | 48.1 | Horizontal | 74 | PK | Pass |
| 2324.501 | 5.5 | 28.5 | 13.2 | 47.2 | Horizontal | 54 | AV | Pass |
| 2133.452 | 5.3 | 28.5 | 13.3 | 47.1 | Horizontal | 74 | PK | Pass |
| 2133.452 | 5.3 | 28.5 | 12.7 | 46.5 | Horizontal | 54 | AV | Pass |
| 4824.552 | 4.2 | 33.3 | 11.7 | 48.8 | Horizontal | 74 | PK | Pass |
| 4824.552 | 4.2 | 33.3 | 10.1 | 47.2 | Horizontal | 54 | AV | Pass |
| 7236.220 | 5.2 | 36.4 | 8.2 | 48.4 | Horizontal | 74 | PK | Pass |
| 7236.220 | 5.2 | 36.4 | 7.3 | 47.5 | Horizontal | 54 | AV | Pass |
| 9648.407 | 6.0 | 37.5 | 2.5 | 43.8 | Horizontal | 74 | PK | Pass |
| 9648.407 | 6.0 | 37.5 | -5.5 | 35.8 | Horizontal | 54 | AV | Pass |
| 12060.377 | 7.0 | 38.4 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 12060.377 | 7.0 | 38.4 | ---- | ---- | Horizontal | 54 | AV | Pass |
| 14472.262 | 7.6 | 42.6 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 14472.262 | 7.6 | 42.6 | ---- | ---- | Horizontal | 54 | AV | Pass |

OFDM mode BPSK modulation 6Mbps data rate CH7 2442MHz Test Result

| Frequency MHz | Cable Loss dB | Antenna Factor dB/m | Reading dBuV | Emission Level dBuV/m | Polarization | Limit dB μ V/m | Detector | Result |
|------------------|---------------------|---------------------------|-----------------|-----------------------------|--------------|-----------------------|----------|--------|
| 1300.009 | 4.4 | 25.1 | 9.1 | 38.6 | Horizontal | 74 | PK | Pass |
| 1300.009 | 4.4 | 25.1 | 2.6 | 32.1 | Horizontal | 54 | AV | Pass |
| 2133.376 | 5.3 | 28.5 | 11.1 | 44.9 | Horizontal | 74 | PK | Pass |
| 2133.376 | 5.3 | 28.5 | 1.9 | 35.7 | Horizontal | 54 | AV | Pass |
| 4884.448 | 4.3 | 33.3 | 14.0 | 51.1 | Horizontal | 74 | PK | Pass |
| 4884.448 | 4.3 | 33.3 | 7.1 | 44.2 | Horizontal | 54 | AV | Pass |
| 7326.312 | 5.2 | 36.4 | 8.3 | 48.5 | Horizontal | 74 | PK | Pass |
| 7326.312 | 5.2 | 36.4 | 7.1 | 47.3 | Horizontal | 54 | AV | Pass |
| 9768.304 | 6.0 | 37.5 | 6.4 | 47.7 | Horizontal | 74 | PK | Pass |
| 9768.304 | 6.0 | 37.5 | 5.1 | 46.4 | Horizontal | 54 | AV | Pass |
| 12210.276 | 7.0 | 38.4 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 12210.276 | 7.0 | 38.4 | ---- | ---- | Horizontal | 54 | AV | Pass |
| 14652.257 | 7.6 | 41.1 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 14652.257 | 7.6 | 41.1 | ---- | ---- | Horizontal | 54 | AV | Pass |

Radiated Emission

OFDM mode BPSK modulation 6Mbps data rate CH11 2462MHz Test Result

| Frequency MHz | Cable Loss dB | Antenna Factor dB/m | Reading dBuV | Emission Level dBuV/m | Polarization | Limit dB μ V/m | Detector | Result |
|------------------|---------------------|---------------------------|-----------------|-----------------------------|--------------|-----------------------|----------|--------|
| 1300.009 | 4.4 | 25.1 | 10.2 | 39.7 | Horizontal | 74 | PK | Pass |
| 1300.009 | 4.4 | 25.1 | 1.8 | 28.5 | Horizontal | 54 | AV | Pass |
| 2133.376 | 5.3 | 28.5 | 11.4 | 45.2 | Horizontal | 74 | PK | Pass |
| 2133.376 | 5.3 | 28.5 | 2.5 | 36.3 | Horizontal | 54 | AV | Pass |
| 4924.333 | 4.3 | 33.3 | 11.1 | 48.2 | Horizontal | 74 | PK | Pass |
| 4924.333 | 4.3 | 33.3 | 8.9 | 46.0 | Horizontal | 54 | AV | Pass |
| 7386.187 | 5.2 | 36.4 | 8.3 | 48.5 | Horizontal | 74 | PK | Pass |
| 7386.187 | 5.2 | 36.4 | 5.5 | 45.7 | Horizontal | 54 | AV | Pass |
| 9848.543 | 6.0 | 37.5 | 5.7 | 47.0 | Horizontal | 74 | PK | Pass |
| 9848.543 | 6.0 | 37.5 | 4.4 | 45.7 | Horizontal | 54 | AV | Pass |
| 12310.789 | 6.9 | 38.4 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 12310.789 | 6.9 | 38.4 | ---- | ---- | Horizontal | 54 | AV | Pass |
| 14772.116 | 7.6 | 41.1 | ---- | ---- | Horizontal | 74 | PK | Pass |
| 14772.116 | 7.6 | 41.1 | ---- | ---- | Horizontal | 54 | AV | Pass |

Remark:

- (1) Emission Level= Cable Loss(include amplifier factor) + Antenna Factor + Reading
- (2) Data of measurement within this frequency range shown “-” in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.



Test Equipment List

| DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL DUE DATE |
|-------------------|-----------------|-----------|------------|--------------|
| EMI Test Receiver | Rohde & Schwarz | ES126 | 838786/013 | Dec 23 2009 |
| Bilog Antenna | Chase | CBL6112B | 2591 | Dec 23 2009 |
| Signal Generator | Rohde & Schwarz | SMR20 | 100047 | Dec 23 2009 |
| Antenna | Schwarzbeck | VUBA9117 | 115 | Dec 23 2009 |
| Horn Antenna | Rohde & Schwarz | HF906 | 100013 | Dec 23 2009 |

7.6 6 dB bandwidth

Test Method

- 1 Place the EUT on the table and set it in the transmitting mode.
- 2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3 Mark the peak frequency and -6dB (upper and lower) frequency.

Limit


Limit [kHz]

≥ 500


6 dB bandwidth

DSSS mode QPSK modulation 11Mbps data rate Test Result

| Frequency MHz | Bandwidth kHz | Limit kHz | Result |
|------------------|------------------|--------------|--------|
| 2412 | 12200 | ≥ 500 | Pass |
| 2442 | 12200 | ≥ 500 | Pass |
| 2462 | 11800 | ≥ 500 | Pass |




Date: 17.FEB.2009 02:39:24



Date: 17.FEB.2009 02:38:43

6 dB bandwidth




Date: 17.FEB.2009 02:37:57


6 dB bandwidth

OFDM mode BPSK modulation 6Mbps data rate Test Result

| Frequency MHz | Bandwidth kHz | Limit kHz | Result |
|------------------|------------------|--------------|--------|
| 2412 | 16600 | ≥ 500 | Pass |
| 2442 | 16600 | ≥ 500 | Pass |
| 2462 | 16600 | ≥ 500 | Pass |




Date: 17.FEB.2009 02:33:53



Date: 17.FEB.2009 02:35:09

6 dB bandwidth



Date: 17.FEB.2009 02:35:09



Product Service

Test Equipment

| DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL DUE DATE |
|-------------------|-----------------|-----------|------------|--------------|
| EMI Test Receiver | Rohde & Schwarz | ESPI3 | 100244 | Dec 23 2009 |



7.7 Power spectral density

Test Method

- 1 Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 2 Set the spectrum analyzer as RBW = 3 kHz, VBW = 10 kHz, Span = 300kHz, Sweep = 100 s
- 3 Record the max reading.

Limit


Limit
dBm / 3 kHz

8

Power spectral density


DSSS mode QPSK modulation 11Mbps data rate Test Result

| Frequency MHz | P dBm | Result |
|------------------|----------|--------|
| 2412 | -10.90 | Pass |
| 2442 | -11.01 | Pass |
| 2462 | -11.03 | Pass |




Date: 17.FEB.2009 02:48:56

Power spectral density



Date: 17.FEB.2009 02:48:02




Date: 17.FEB.2009 02:47:11

Power spectral density


OFDM mode BPSK modulation 6Mbps data rate Test Result

| Frequency MHz | P dBm | Result |
|------------------|----------|--------|
| 2412 | -6.73 | Pass |
| 2442 | -6.38 | Pass |
| 2462 | -17.42 | Pass |




Date: 17.FEB.2009 02:43:17

Power spectral density



Date: 17.FEB.2009 02:44:42



Date: 17.FEB.2009 02:46:02



Product Service

Test Equipment

| DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL DUE DATE |
|-------------------|-----------------|-----------|------------|--------------|
| EMI Test Receiver | Rohde & Schwarz | ESPI3 | 100244 | Dec 23 2009 |



8 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty

| Items | | Extended Uncertainty |
|-------|----------------------------------|--------------------------|
| RE | Field strength (dB μ V/m) | U=4.6dB; k=2(30MHz-1GHz) |
| CE | Disturbance Voltage (dB μ V) | U=3.3dB; k=2 |