

FCC PART 15.247
TEST REPORT

For

SVAT Electronics

4080 Montrose Road, Niagara Falls, ON L2H 1J9 Canada

FCC ID: SMH-32104

Report Type: Original Report	Product Type: Digital Video Baby Monitor
Test Engineer: Ares Liu	<i>Ares Liu</i>
Report Number: R1DG111209004-00	
Report Date: 2012-02-28	
Reviewed By: Merry Zhao EMC Engineer	<i>Merry Zhao</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....3

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)3

 OBJECTIVE3

 RELATED SUBMITTAL(S)/GRANT(S).....3

 TEST METHODOLOGY3

 TEST FACILITY3

SYSTEM TEST CONFIGURATION.....3

 DESCRIPTION OF TEST CONFIGURATION3

 EQUIPMENT MODIFICATIONS3

 EXTERNAL I/O CABLE3

 BLOCK DIAGRAM OF TEST SETUP3

SUMMARY OF TEST RESULTS3

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....3

 APPLICABLE STANDARD3

FCC §15.203 – ANTENNA REQUIREMENT3

 APPLICABLE STANDARD3

 ANTENNA CONNECTOR CONSTRUCTION3

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS3

 APPLICABLE STANDARD3

 MEASUREMENT UNCERTAINTY3

 EUT SETUP3

 EMI TEST RECEIVER SETUP.....3

 TEST PROCEDURE3

 TEST EQUIPMENT LIST AND DETAILS.....3

 TEST RESULTS SUMMARY3

 TEST DATA3

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....3

 APPLICABLE STANDARD3

 MEASUREMENT UNCERTAINTY3

 EUT SETUP3

 EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP3

 TEST PROCEDURE3

 CORRECTED AMPLITUDE & MARGIN CALCULATION3

 TEST EQUIPMENT LIST AND DETAILS.....3

 TEST RESULTS SUMMARY3

 TEST DATA3

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST3

 APPLICABLE STANDARD3

 TEST PROCEDURE3

 TEST EQUIPMENT LIST AND DETAILS.....3

 TEST DATA3

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH TESTING3

 APPLICABLE STANDARD3

 TEST PROCEDURE3

TEST EQUIPMENT LIST AND DETAILS.....3
TEST DATA3

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST3
APPLICABLE STANDARD3
TEST PROCEDURE3
TEST EQUIPMENT LIST AND DETAILS.....3
TEST DATA3

FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME).....3
APPLICABLE STANDARD3
TEST PROCEDURE3
TEST EQUIPMENT LIST AND DETAILS.....3
TEST DATA3

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT3
APPLICABLE STANDARD3
TEST PROCEDURE3
TEST EQUIPMENT LIST AND DETAILS.....3
TEST DATA3

FCC §15.247(d) - BAND EDGES TESTING3
APPLICABLE STANDARD3
TEST PROCEDURE3
TEST EQUIPMENT LIST AND DETAILS.....3
TEST DATA3

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *SVAT Electronics*'s product, model number: 32104 (FCC ID: SMH-32104) (the "EUT") in this report was a camera unit of *Digital Video Baby Monitor*, which was measured approximately: 10.2 cm (L) x 6.3 cm (W) x 7 cm (H), rated input voltage: DC 5V from adapter.

Adapter information: SWITCHING ADAPTOR

Model: S04-003-0050-00600

Input: AC 100-240 V, 50/60Hz, 0.1A max

Output: DC 5.0V, 600mA

** All measurement and test data in this report was gathered from production sample serial number: 1112095 (Assigned by BACL, Shenzhen). The EUT was received on 2011-12-09.*

Objective

This report is prepared on behalf of *SVAT Electronics* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 FHSS submission of monitor unit with FCC ID: SMH-32109.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in typical fashion (as normally used by a typical user).


Equipment Modifications

No modification was made to the EUT tested.

External I/O Cable

Cable Description	Length(m)	From/Port	To
Unshielded Detachable DC Power Cable	2	Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to FCC 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz;
 * = Plane-wave equivalent power density;

MPE Calculation

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²);
 P = power input to the antenna (in appropriate units, e.g., mW);
 G = power gain of the antenna in the direction of interest relative to an isotropic radiator
 R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
	(dBi)	(numeric)	(dBm)	(mW)			
2468	0	1.0	12.41	17.42	20	0.003467	1.0

Result: The device meets FCC MPE limit at 20 cm distance.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a half monopole antenna connect to RF board, which in accordance to section 15.203, the maximum gain is 0 dBi; please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard


FCC §15.207

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is 2.4 dB (k=2, 95% level of confidence).

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<i>Frequency Range</i>	<i>IF B/W</i>
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2011-03-03	2012-03-02
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-03-09	2012-03-08

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

11.59 dB at 0.340 MHz in the Neutral conducted mode

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100.0 kPa

The testing was performed by Ares Liu on 2012-01-05.


Test Mode: Charging & Transmitting

AC 120 V, 60 Hz, Line:



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.340	36.77	0.02	60.57	23.80	QP
0.485	31.27	0.01	56.43	25.16	QP
1.480	27.68	0.01	56.00	28.32	QP
0.485	17.85	0.01	46.43	28.58	Ave.
2.760	26.25	0.02	56.00	29.75	QP
0.340	20.67	0.02	50.57	29.90	Ave.
1.045	24.63	0.01	56.00	31.37	QP
1.475	14.39	0.01	46.00	31.61	Ave.
5.230	18.23	0.03	50.00	31.77	Ave.
2.745	14.10	0.02	46.00	31.90	Ave.
5.225	27.02	0.03	60.00	32.98	QP
1.045	12.15	0.01	46.00	33.85	Ave.

AC 120V, 60 Hz, Neutral:



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.340	38.98	0.02	50.57	11.59	Ave.
0.630	32.33	0.01	46.00	13.67	Ave.
1.025	31.03	0.01	46.00	14.97	Ave.
1.480	30.62	0.01	46.00	15.38	Ave.
2.710	29.68	0.02	46.00	16.32	Ave.
0.340	43.18	0.02	60.57	17.39	QP
4.400	26.95	0.03	46.00	19.05	Ave.
0.635	36.64	0.01	56.00	19.36	QP
1.035	35.66	0.01	56.00	20.34	QP
1.475	35.20	0.01	56.00	20.80	QP
2.710	34.19	0.02	56.00	21.81	QP
4.400	31.87	0.03	56.00	24.13	QP

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB. (k=2, 95% level of confidence).

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>	<i>Detector</i>
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave

Test Procedure

During the radiated emission test, the adapter was connected to the outlet of the floor.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2011-08-02	2012-08-02
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
Mini-Circuits	Amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-08
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

1.24 dB at 7404 MHz in the **Horizontal** polarization in high channel (2468MHz)

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

* *The testing was performed by Ares Liu on 2012-01-05.*

Test mode: Transmitting

30MHz - 25 GHz

Frequency (MHz)	Receiver Reading (dBµV)	Detector (PK/QP/Ave)	Polar (H/V)	Antenna Loss (dB)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBµV/m)	FCC Part 15.247/205/209		
								Limit (dBµV/m)	Margin (dB)	Comment
Low Channel (2404 MHz)										
2404	69.29	PK	H	29.1	3.9	0	102.29	N/A		Fund.
2404	49.06	Ave.	H	29.1	3.9	0	82.06	N/A		Fund.
2404	76.25	PK	V	29.1	3.9	0	109.25	N/A		Fund.
2404	56.15	Ave.	V	29.1	3.9	0	89.15	N/A		Fund.
7212	33.09	PK	H	37.7	7.6	7	71.39	74	2.61*	harmonic
7212	33.06	PK	V	37.7	7.6	7	71.36	74	2.64*	harmonic
7212	12.99	Ave.	H	37.7	7.6	7	51.29	54	2.71*	harmonic
7212	12.03	Ave.	V	37.7	7.6	7	50.33	54	3.67*	harmonic
4808	18.96	Ave.	H	32.1	5.8	7.4	49.46	54	4.54	harmonic
4808	38.17	PK	V	32.1	5.8	7.4	68.67	74	5.33	harmonic
2389.8	35.53	PK	H	29.1	3.9	0	68.53	74	5.47	spurious
4808	17.56	Ave.	V	32.1	5.8	7.4	48.06	54	5.94	harmonic
2389.2	15.02	Ave.	V	29.1	3.9	0	48.02	54	5.98	spurious
2389.2	34.21	PK	V	29.1	3.9	0	67.21	74	6.79	spurious
2389.8	14.2	Ave.	H	29.1	3.9	0	47.2	54	6.80	spurious
4808	36.18	PK	H	32.1	5.8	7.4	66.68	74	7.32	harmonic
111.42	41.14	QP	V	13.04	1.39	21.31	34.26	43.5	9.24	spurious
75.14	40.39	QP	H	8.48	1.38	21.39	28.86	40	11.14	spurious
111.02	38.06	QP	H	13.04	1.39	21.31	31.18	43.5	12.32	spurious
75.59	39.01	QP	V	8.48	1.38	21.39	27.48	40	12.52	spurious
976.26	25.92	QP	V	26.89	3.69	21.39	35.11	54	18.89	spurious
976.26	24.57	QP	H	26.89	3.69	21.39	33.76	54	20.24	spurious
Middle Channel (2436 MHz)										
2436	68.99	PK	H	29.8	3.9	0	102.69	N/A		Fund.
2436	49.55	Ave.	H	29.8	3.9	0	83.25	N/A		Fund.
2436	76.55	PK	V	29.8	3.9	0	110.25	N/A		Fund.
2436	56.52	Ave.	V	29.8	3.9	0	90.22	N/A		Fund.
7308	33.68	PK	V	37.9	7.6	7.2	71.98	74	2.02*	harmonic
4872	21.1	Ave.	H	32.2	5.8	7.3	51.8	54	2.20*	harmonic
4872	21.06	Ave.	V	32.2	5.8	7.3	51.76	54	2.24*	harmonic
7308	12.56	Ave.	H	37.9	7.6	7.2	50.86	54	3.14*	harmonic
7308	32.25	PK	H	37.9	7.6	7.2	70.55	74	3.45*	harmonic
7308	12.01	Ave.	V	37.9	7.6	7.2	50.31	54	3.69*	harmonic
4872	38.39	PK	V	32.2	5.8	7.3	69.09	74	4.91	harmonic
102.25	42.9	QP	V	13.04	1.39	21.31	36.02	43.5	7.48	spurious
4872	34.84	PK	H	32.2	5.8	7.3	65.54	74	8.46	harmonic
102.25	41.13	QP	H	13.04	1.39	21.31	34.25	43.5	9.25	spurious
75.48	41.27	QP	H	8.48	1.38	21.39	29.74	40	10.26	spurious

75.98	39.97	QP	V	8.48	1.38	21.39	28.44	40	11.56	spurious
976.99	26.06	QP	V	26.89	3.69	21.39	35.25	54	18.75	spurious
976.89	21.06	QP	H	26.89	3.69	21.39	30.25	54	23.75	spurious
High Channel (2468 MHz)										
2468	69.09	PK	H	29.7	3.9	0	102.69	N/A		Fund.
2468	49.65	Ave.	H	29.7	3.9	0	83.25	N/A		Fund.
2468	76.65	PK	V	29.7	3.9	0	110.25	N/A		Fund.
2468	56.62	Ave.	V	29.7	3.9	0	90.22	N/A		Fund.
7404	33.96	PK	H	38.5	7.6	7.3	72.76	74	1.24*	harmonic
7404	33.35	PK	V	38.5	7.6	7.3	72.15	74	1.85*	harmonic
4936	20.04	Ave.	H	32.5	5.8	7.2	51.14	54	2.86*	harmonic
2484	37.44	PK	H	29.7	3.9	0	71.04	74	2.96*	spurious
7404	12	Ave.	V	38.5	7.6	7.3	50.8	54	3.20*	harmonic
7404	11.96	Ave.	H	38.5	7.6	7.3	50.76	54	3.24*	harmonic
2484	16.54	Ave.	H	29.7	3.9	0	50.14	54	3.86*	spurious
4936	39.01	PK	V	32.5	5.8	7.2	70.11	74	3.89*	harmonic
2483.9	16.05	Ave.	V	29.7	3.9	0	49.65	54	4.35*	spurious
4936	16.96	Ave.	V	32.5	5.8	7.2	48.06	54	5.94	harmonic
2483.9	34.11	PK	V	29.7	3.9	0	67.71	74	6.29	spurious
110.26	42.66	QP	V	13.04	1.39	21.31	35.78	43.5	7.72	spurious
4936	34.77	PK	H	32.5	5.8	7.2	65.87	74	8.13	harmonic
75.98	42.53	QP	V	8.48	1.38	21.39	31	40	9.00	spurious
75.99	41.78	QP	H	8.48	1.38	21.39	30.25	40	9.75	spurious
110.25	39.47	QP	H	13.04	1.39	21.31	32.59	43.5	10.91	spurious
976.99	27.06	QP	V	26.89	3.69	21.39	36.25	54	17.75	spurious
976.89	24.5	QP	H	26.89	3.69	21.39	33.69	54	20.31	spurious

*Within measurement uncertainty!

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 100 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another truece
3. Measure the channel separation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

* *The testing was performed by Ares Liu on 2012-01-04.*


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
Low	2404	2.008	1.45	Pass
Adjacent	2406			
Middle	2436	2.000	1.45	Pass
Adjacent	2438			
High	2468	2.000	1.45	Pass
Adjacent	2466			

Low Channel




Date: 4.JAN.2012 23:08:14

Middle Channel



Date: 4.JAN.2012 23:09:19

High Channel



Date: 4.JAN.2012 23:10:52

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

* The testing was performed by Ares Liu on 2012-01-04.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2404	2.12
Middle	2436	2.16
High	2468	2.18

Low Channel




Date: 4.JAN.2012 22:24:35

Middle Channel



Date: 4.JAN.2012 22:34:00

High Channel



Date: 4.JAN.2012 22:37:44

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

The testing was performed by Ares Liu on 2012-01-04.


Test Result: Compliance.

Please refer to following table and plots

Test Mode: Transmitting

Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
2400-2483.5	33	≥15

Number of Hopping Channels



Date: 4.JAN.2012 23:06:35

FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell time = Pulse time*hop rate/number of hopping channels*13.2S

Hop rate=1000/S

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

* *The testing was performed by Ares Liu on 2012-01-04.*

Test Result: Compliance.


Please refer to following table and plots

Test Mode: Transmitting

Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
Low	0.128	0.0512	0.4	Pass
Middle	0.130	0.0520	0.4	Pass
High	0.130	0.0520	0.4	Pass


Note: refer to specification files, the 1s hopping 1000, So
 Dwell time = (Pulse time/1000)*(1000/33)*33*0.4S

Low Channel




Date: 4.JAN.2012 23:12:03

Middle Channel



Date: 4.JAN.2012 23:12:40

High Channel



Date: 4.JAN.2012 23:13:25


FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

* The testing was performed by Ares Liu on 2012-01-04.


Test Result: Compliance.

Please refer to following table and plots

Test Mode: Transmitting


Channel	Frequency (MHz)	Conducted Output Power		Limit (mW)
		(dBm)	(mW)	
Low	2404	10.43	11.04	125
Middle	2436	11.16	13.06	125
High	2468	12.41	17.42	125

Low Channel




Date: 4.JAN.2012 22:25:57

Middle Channel



Date: 4.JAN.2012 22:35:01

High Channel



Date: 4.JAN.2012 22:35:52

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1 MHz, VBW=3 MHz.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100 kPa

*The testing was performed by Ares Liu on 2012-01-04.


Test Result: Compliance

Please refer to the following table and plots.

Test Mode: Transmitting


Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)
2383.4	-43.94	20
2505.2	-44.53	20

Band Edge: Left Side



Date: 4.JAN.2012 22:31:56

Band Edge: Right Side



Date: 4.JAN.2012 22:40:08

***** END OF REPORT *****