

RF exposure Estimation for WPTT

1. Introduction

Product:	PC ECG
Model no.:	SE-1515
Brand Name	EDAN
FCC ID:	SMQDX12REEDAN
Options and accessories:	Signal Simulator
Rating:	3.0Vdc supplied by 2*AA Batteries
RF Transmission Frequency:	2402-2480MHz
No. of Operated Channel:	79
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Duty Cycle:	Max 77.2%
Antenna Type:	Integral Antenna
Antenna Gain:	2.0dBi
Description of the EUT:	EUT is an electrocardiogram with Bluetooth function which operated at 2.4GHz.

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v06, no SAR required if power is lower than the following threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison

- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

3. Calculation method

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Conducted Power + tune up tolerance = 1.29mW

Distance = 5 mm

f = 2.402GHz

$[1.29/5] \cdot \text{SQRT}(2.402) = 0.40$

$0.40 \leq 3.0$

Therefore, excluded from SAR testing.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch


Reviewed by:



John Zhi/ Section Manager

Date: 2017-03-14

Prepared By:



Alan Xiong/ Project Engineer

Date: 2017-03-14