

<b>Prüfbericht-Nr.:</b> <i>Test report no.:</i>	CN23XQCR (FCC-MPE) 001	<b>Auftrags-Nr.:</b> <i>Order no.:</i>	238545871	Seite 1 von 10 Page 1 of 10
<b>Kunden-Referenz-Nr.:</b> <i>Client reference no.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date:</i>	2022-07-21	
<b>Auftraggeber:</b> <i>Client:</i>	Eve Systems LLC 100 Pine St., Suite 1250, San Francisco CA 94111 USA			
<b>Prüfgegenstand:</b> <i>Test item:</i>	Eve Play			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type no.:</i>	20EBR8701			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	FCC Certification			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	IEEE Std C95.1 47 CFR §2.1091 47 CFR §1.1310 KDB 447498 D04			
<b>Wareneingangsdatum:</b> <i>Date of sample receipt:</i>	2022-11-15			
<b>Prüfmuster-Nr.:</b> <i>Test sample no.:</i>	A003372584-003 A003372584-004			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	2023-02-23 - 2023-03-09			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	EMC/RF Taipei Testing Site			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	Taipei Testing Laboratories			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass			
<b>überprüft von:</b> <i>compiled by:</i>	 Ryan Chen	<b>genehmigt von:</b> <i>authorized by:</i>	 Brenda Chen	
<b>Datum:</b> <i>Date:</i>	2023-03-31	<b>Ausstellungsdatum:</b> <i>Issue date:</i>	2023-03-31	
<b>Stellung / Position:</b>	Senior Project Manager	<b>Stellung / Position:</b>	Senior Project Manager	
<b>Sonstiges / Other:</b>				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend N/A = nicht anwendbar	4 = ausreichend N/T = nicht getestet
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory N/A = not applicable	4 = sufficient N/T = not tested
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

## Contents

<b>HISTORY OF THIS TEST REPORT .....</b>	<b>3</b>
<b>1 GENERAL REMARKS .....</b>	<b>4</b>
<b>1.1 COMPLEMENTARY MATERIALS.....</b>	<b>4</b>
<b>1.2 DECISION RULE OF CONFORMITY .....</b>	<b>4</b>
<b>2 TEST SITES .....</b>	<b>5</b>
<b>2.1 TEST FACILITIES .....</b>	<b>5</b>
<b>2.2 TEST FACILITY.....</b>	<b>5</b>
<b>3 GENERAL PRODUCT INFORMATION.....</b>	<b>6</b>
<b>3.1 PRODUCT FUNCTION AND INTENDED USE .....</b>	<b>6</b>
<b>3.2 RATINGS AND SYSTEM DETAILS.....</b>	<b>6</b>
<b>4 MAXIMUM PERMISSIBLE EXPOSURE EVALUATION.....</b>	<b>7</b>
<b>4.1 INTRODUCTION .....</b>	<b>7</b>
<b>4.2 REFERENCE LEVELS .....</b>	<b>7</b>
<b>4.3 CLASSIFICATION OF THE ASSESSMENT METHODS.....</b>	<b>9</b>
<b>5 TEST RESULTS .....</b>	<b>10</b>
<b>5.1 MPE-BASED EXEMPTION.....</b>	<b>10</b>

### APPENDIX EP - PHOTOGRAPHS OF EUT

**Prüfbericht - Nr.:**      **CN23XQCR (FCC-MPE) 001**  
*Test Report No.*

**Seite 3 von 10**  
*Page 3 of 10*

### HISTORY OF THIS TEST REPORT

Report No.	Description	Date Issued
CN23XQCR (FCC-MPE) 001	Original Release	2023-03-31

# 1 General Remarks

## 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:  
**Appendix EP - Photographs of EUT**

## 1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

## 2 Test Sites

### 2.1 Test Facilities

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.  
Taipei City 105  
Taiwan (R.O.C.)

### 2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,  
New Taipei City 244  
Taiwan (R.O.C.)

### 3 General Product Information

#### 3.1 Product Function and Intended Use

The EUT is Eve Play. It contains WLAN compatible module enabling the user to communicate data through a Wireless interface.

For details refer to the User Guide, Data Sheet and Circuit Diagram.

#### 3.2 Ratings and System Details

##### Basic Information of EUT

Item	EUT Information
Kind of Equipment/Test Item	Eve Play
Type Identification	20EBR8701
FCC ID	SNE-EAP-001

##### Technical Specification of EUT

Item	EUT Information
Operating Frequency	WLAN 2.4GHz: 2412 MHz ~ 2462 MHz WLAN 5GHz: Band 1: 5180 MHz ~ 5240 MHz Band 2: 5260 MHz ~ 5320 MHz Band 3: 5500 MHz ~ 5700 MHz Band 4: 5745 MHz ~ 5825 MHz
Modulation	DSSS (DBPSK, DQPSK, CCK) OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Operation Voltage	Input: 100-240Vac, 50/60Hz, 0.3A max Output: 5.0Vdc, 2.0A Tested at 120Vac
Antenna Type	PCB Antenna
Antenna Gain	WLAN 2.4GHz: 3.8 dBi WLAN 5GHz: 6.3 dBi (Band 1), 6.5 dBi (Band 2), 6.4 dBi (Band 3), 6.4 dBi (Band 4)

## 4 Maximum Permissible Exposure Evaluation

### 4.1 Introduction

This Standard specifies requirements for, and provides guidance on, assessing compliance with the exposure limits of radiofrequency (RF) safety standards such as IEEE Std C95.1. This includes methodologies for making an assessment (by measurement or computation) of human exposure to ambient RF fields and induced body currents in the frequency range of 0 kHz to 300 GHz.

This Standard may also be used as a guide for making low-level environmental exposure assessments in areas around RF sources listed above, as well as other sources such as Wi-Fi devices.

### 4.2 Reference Levels

Where appropriate, the reference levels are derived from the basic restrictions by mathematical modelling and by extrapolation from the results of laboratory investigations at specific frequencies. They are given for the condition of maximum coupling of the field to the exposed individual, thereby providing maximum protection.

According to FCC 1.1310, the criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

The FCC MPE limits from 47 CFR §1.1310 are shown in the table below

Frequency Range [MHz]	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm <sup>2</sup> ]	Average Time [minutes]
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30 – 300	61.4	0.163	1.0	6
300 – 1500			f/300	6
1500 – 100000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f <sup>2</sup>	30
30 – 300	27.5	0.073	0.2	30
300 – 1500			f/1500	30
1500 – 100000			1.0	30

NOTE –

- (1)  $f$  is the frequency in MHz.
- (2) Provided that basic restrictions are met and adverse indirect effects can be excluded, field strength values can be exceeded. For the specific case of occupational exposures at frequencies up to 100 kHz, the derived electric fields can be increased by a factor of 2 under conditions in which adverse indirect effects from contact with electrically charged conductors can be excluded.
- (3) For frequencies between 100 kHz and 10 GHz, the quantities Seq, E2 and H2 are averages over any 6 minutes.
- (4) For frequencies exceeding 10 GHz, Seq, the quantities E2 and H2 are averages over any  $68/f$  1.05 minutes ( $f$  in GHz).



### 4.3 Classification of the Assessment Methods

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

#### MPE Calculation Method according to KDB 447498 D04 Interim General RF Exposure Guidance v01

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 of § 1.1307(b)(1)(i)(C) to support an exemption from further evaluation from 300 kHz through 100 GHz.

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

**TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES  
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION**

RF Source Frequency			Minimum Distance			Threshold ERP
$f_L$ MHz		$f_H$ MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	1,920 R <sup>2</sup>
1.34	–	30	35.6 m	–	1.6 m	3,450 R <sup>2</sup> /f <sup>2</sup>
30	–	300	1.6 m	–	159 mm	3.83 R <sup>2</sup>
300	–	1,500	159 mm	–	31.8 mm	0.0128 R <sup>2</sup> f
1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R <sup>2</sup>

Subscripts L and H are low and high;  $\lambda$  is wavelength.  
 From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

## 5 Test Results

### 5.1 MPE-based Exemption

The Calculated at a distance of 20 cm are shown as below:

Frequency (MHz)	Average Output Power (dBm)	Average Output Power (mW)	Antenna Gain (dBi)	ERP (mW)	ERP Limit (mW)	Pass / Fail
2412	22.56	180.30	3.8	263.63	768	Pass
5180	17.39	54.83	6.3	142.56	768	Pass

#### Conclusion

The device complies with the FCC exposure requirements since the maximum transmitter power density is below the FCC limit.