

Radio Frequency Exposure Report

On Behalf of

Graupner CO.,Ltd

FCC ID: SNL-16005700
Product Description: 2.4GHz Radio Control Receiver
Test Model No.: GR-8
Supplementary Model: GR-8L

Prepared for: Graupner CO.,Ltd
8th F,202 Dong,Chunui Techno-Park2,18, Bucheon-ro 198beon-gil,Wonmi-gu,, Bucheon-si,Kyungki-do, South Korea

Prepared by: Bontek Compliance Testing Laboratory Ltd
1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China
Tel: 86-755-86337020
Fax: 86-755-86337028


Report No.: BCT14ER206E-1
Issue Date: June 10, 2014
Test Date: May21~ June 10, 2014

Tested by:



Jiankuai.Li

Reviewed by:



Owen Yang

Approved by:



Kendy Wang

TABLE OF CONTENTS

| | |
|--|----------|
| 1 - GENERAL INFORMATION | 3 |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3 |
| 1.2 OBJECTIVE | 3 |
| 1.3 GENERAL DESCRIPTION OF TEST | 4 |
| 1.4 HUMAN EXPOSURE ASSESSMENT RESULTS | 4 |

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

| | |
|--------------------------|---|
| Applicant: | Graupner CO.,Ltd |
| Address of Applicant: | 8 th F,202 Dong,Chunui Techno-Park2,18, Bucheon-ro 198beon-gil,Wonmi-gu,, Bucheon-si,Kyungki-do, South Korea |
| Manufacturer 1: | SJ Technology(Shenzhen)Co.,Ltd |
| Address of manufacturer: | F6, 1 Bldg, A Area, Yintianxifa Industrial Area, Xixiang Town, Baoan District Shenzhen, Guangdong Province, China |
| Manufacturer 2: | Graupner CO.,Ltd |
| Address of Manufacturer: | 8 th F,202 Dong,Chunui Techno-Park2,18, Bucheon-ro 198beon-gil,Wonmi-gu,, Bucheon-si,Kyungki-do, South Korea |

General Description of E.U.T

| Items | Description |
|----------------------|---|
| EUT Description: | 2.4GHz Radio Control Receiver |
| Test Model No.: | GR-8 |
| Trade Name: | HoTT |
| Supplementary Model: | GR-8L |
| Frequency Band: | 2403.920~2472.056MHz |
| Number of Channels: | 35 |
| Type of Modulation: | FHSS |
| Antenna Gain: | 1.5dBi |
| Antenna Type: | Integral Antenna |
| Rated Voltage: | Input: DC 3.6V~8.4V Approx70mA |
| Adapter description: | Model: N/A Input: N/A Output: N/A |

Remark: * The test data gathered are from the production sample provided by the manufacturer.
* Supplementary models have the same circuit, only the appearance different

1.2 Objective

The objective of the following report is used to demonstrate that EUT operated in a manner that ensures the public is not exposed to radio frequency energy levels in excess of the relative provisions of FCC 47CFR Part 1.1307

1.3 General Description of Test

| Items | Description |
|--|--|
| EUT Frequency band | <input checked="" type="checkbox"/> FHSS: 2.400GHz ~ 2.483GHz <input type="checkbox"/> WLAN: 2.400GHz ~ 2.483GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others: _____ |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____ |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²) <input type="checkbox"/> Others: _____ |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas: <ul style="list-style-type: none"> <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | 18.02dBm (0.0634W) |
| Antenna gain (Max) | 1.5dBi (Numeric gain:1.41) |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |
| <p>Note:</p> <p>1. The maximum output power is 18.02dBm (0.06634W) at 2403.092MHz (with 1.41 numeric antenna gain.)</p> <p>2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.</p> | |

1.4 Human Exposure Assessment Results

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field Strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = 100 * d \text{ (m)}$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = distance in cm
 P = Power in mW
 G = Numeric antenna gain
 S = Power Density in mW / cm²

| EUT parameter (data from the separate report) | |
|--|---|
| Given $E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$ | Where G: numerical gain of transmitting antenna; TP: Transmitted power in watt; d: distance from the transmitting antenna in meter |
| Max average output power in Watt (TP) | 18.02dBm (0.0634W) |
| Antenna gain (G) | 1.5dBi (Numeric gain: 1.41) |
| Exposure classification | S=1mW/cm ² |
| Minimum distance in meter (d) (from transmitting structure to the human body) | 20cm (0.2m) |
| Yields $S = \frac{30 \times P \times G}{3770d^2}, \quad P=0.0634W, G=1.41, d=0.2$ $S=0.0178mW/cm^2$ Or $d = \sqrt{\frac{30 \times P \times G}{3770S}}, \quad S=1, P=0.0634W, G=1.32$ $d=0.0267m$ | |
| Conclusion: S=0.0178mW/cm ² is significant lower than the General Population Exposure Power Density Limit 1mW/cm ² or except the distance when human body proximity to the antenna is less than 2.67cm then will reach the General Population Exposure Power Density Limit (For mobile or fixed location transmitters, the maximum power density is 1.0 mW / cm ² even if the calculation indicates that the power density would be larger.) | |