

FCC Part 15C Measurement and Test Report

For

GRAUPNER CO., LTD.

202Dong 8th F,18, Bucheon-ro 198beon-gil, Wonmi-gu, Bucheon-si, Gyeonggi-do, South Korea

FCC ID: SNL-16008700

FCC Rule(s):	<u>FCC Part 15.247</u>
Product Description:	<u>2.4GHz receiver</u>
Tested Model:	<u>FALCON 12 PLUS</u>
Report No.:	<u>STR19018083I</u>
Sample Receipt Date:	<u>2018-11-22</u>
Tested Date:	<u>2018-11-23 to 2019-03-04</u>
Issued Date:	<u>2019-03-04</u>
Tested By:	<u>Jason Su / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	

Shenzhen SEM Test Technology Co. Ltd
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, 518101, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Jason Su
Silin chen
Jandyso

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....4

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4

1.2 TEST STANDARDS.....5

1.3 TEST METHODOLOGY5

1.4 TEST FACILITY5

1.5 EUT SETUP AND TEST MODE.....6

1.6 MEASUREMENT UNCERTAINTY6

1.7 TEST EQUIPMENT LIST AND DETAILS6

2. SUMMARY OF TEST RESULTS8

3. RF EXPOSURE9

3.1 STANDARD APPLICABLE.....9

3.2 TEST RESULT.....9

4. ANTENNA REQUIREMENT10

4.1 STANDARD APPLICABLE.....10

4.2 EVALUATION INFORMATION10

5. FREQUENCY HOPPING SYSTEM REQUIREMENTS11

5.1 STANDARD APPLICABLE.....11

5.2 FREQUENCY HOPPING SYSTEM.....11

5.3 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE11

6. QUANTITY OF HOPPING CHANNELS AND CHANNEL SEPARATION13

6.1 STANDARD APPLICABLE.....13

6.2 TEST PROCEDURE.....13

6.3 ENVIRONMENTAL CONDITIONS13

6.4 SUMMARY OF TEST RESULTS/PLOTS14

7. DWELL TIME OF HOPPING CHANNEL.....18

7.1 STANDARD APPLICABLE.....18

7.2 TEST PROCEDURE.....18

7.3 ENVIRONMENTAL CONDITIONS18

7.4 SUMMARY OF TEST RESULTS/PLOTS19

8. 20DB BANDWIDTH24

8.1 STANDARD APPLICABLE.....24

8.2 TEST PROCEDURE.....24

8.3 ENVIRONMENTAL CONDITIONS25

8.4 SUMMARY OF TEST RESULTS/PLOTS25

9. RF OUTPUT POWER30

9.1 STANDARD APPLICABLE.....30

9.2 TEST PROCEDURE.....30

9.3 ENVIRONMENTAL CONDITIONS30

9.4 SUMMARY OF TEST RESULTS/PLOTS30

10. FIELD STRENGTH OF SPURIOUS EMISSIONS36

10.1 STANDARD APPLICABLE.....36

10.2 TEST PROCEDURE.....36

10.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....37

10.4 ENVIRONMENTAL CONDITIONS37

10.5 SUMMARY OF TEST RESULTS/PLOTS38

11. OUT OF BAND EMISSIONS.....53

11.1 STANDARD APPLICABLE.....53

11.2 TEST PROCEDURE.....53

11.3 ENVIRONMENTAL CONDITIONS54

11.4 SUMMARY OF TEST RESULTS/PLOTS55

12. CONDUCTED EMISSIONS71

12.1 TEST PROCEDURE.....71



12.2 BASIC TEST SETUP BLOCK DIAGRAM.....71
12.3 ENVIRONMENTAL CONDITIONS71
12.4 TEST RECEIVER SETUP72
12.5 SUMMARY OF TEST RESULTS/PLOTS72

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information	
Applicant:	GRAUPNER CO., LTD.
Address of applicant:	202Dong 8th F,18, Bucheon-ro 198beon-gil, Wonmi-gu, Bucheon-si, Gyeonggi-do, South Korea
Manufacturer:	GRAUPNER CO., LTD.
Address of manufacturer:	202Dong 8th F,18, Bucheon-ro 198beon-gil, Wonmi-gu, Bucheon-si, Gyeonggi-do, South Korea

General Description of EUT	
Product Name:	2.4GHz receiver
Trade Name:	HoTT
Model No.:	FALCON 12 PLUS
Adding Model(s):	N/A
Rated Voltage:	DC 3.7 V from battery
Power Adapter Model:	N/A
<p><i>Note: 1. The test data is gathered from a production sample provided by the manufacturer.</i></p> <p><i>2. Both models are the same as HW/SW. The difference is the presence or absence of connector and shrinked. And they are for different customer.</i></p> <p><i>3. We have pre-tested all models, and choose FALCON 12 PLUS as main test model.</i></p> <p><i>4. When there is no signal yet (when there is no pairing), choose Ant1/Ant2 in 10ms period. After successful pairing, only receive antennas with better reception. Also, only one antenna is used in actual use.</i></p>	

Technical Characteristics of EUT	
Frequency Range:	2404~ 2479 MHz
RF Output Power:	11.81dBm (Conducted)
Data Rate:	N/A
Modulation:	FHSS: MSK
Quantity of Channels:	75
Channel Separation:	1MHz
Type of Antenna:	λ /4 Monopole Antenna
Antenna Gain:	Antenna 1: 1.5dBi Antenna 2: 1.5dBi

1.2 Test Standards

The following report is prepared on behalf of the **GRAUPNER CO.,LTD.** in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co. Ltd Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co. Ltd has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2404.056MHz
TM2	Middle Channel	2440.561MHz
TM3	High Channel	2479.095MHz
TM4	Hopping	2404.056-2479.095MHz

Accessories Equipment List and Details			
Description	Manufacturer	Model No.	Serial Number
Laptop	Lenovo	E42-80	/
Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
Signal Cable	0.4	Unshielded	Without Core
EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
USB Cable	0.6	Unshielded	Without Core

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21

SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2018-05-22	2019-05-21
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2018-05-22	2019-05-21
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2018-05-22	2019-05-21
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2018-05-22	2019-05-21
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2018-05-22	2019-05-21
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2018-05-22	2019-05-21

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	N/A
§ 15.209(a)	Radiated Spurious Emissions	Compliant
§ 15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§ 15.247(a)(1)	Channel Separation	Compliant
§ 15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Compliant
§ 15.247(a)	20dB Bandwidth	Compliant
§ 15.247(b)(1)	RF Power Output	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant
§ 15.247(a)(1)	Frequency Hopping Sequence	Compliant
§ 15.247(g), (h)	Frequency Hopping System	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

The device has two fixed antennas that use glue, which cannot be replaced by non-professionals. The antenna used in this product complies with the standard.

5. Frequency Hopping System Requirements

5.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

5.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

5.3 EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below:

Number	Channel	Frequency	Number	Channel	Frequency
[0]	51	2455.772	[35]	43	2447.660
[1]	63	2467.940	[36]	67	2471.997
[2]	1	2405.070	[37]	13	2417.239
[3]	20	2424.337	[38]	17	2421.295
[4]	36	2440.562	[39]	31	2435.491
[5]	46	2450.702	[40]	47	2451.716
[6]	64	2468.955	[41]	60	2464.898
[7]	12	2416.225	[42]	9	2413.182
[8]	23	2427.379	[43]	22	2426.365
[9]	39	2443.604	[44]	33	2437.519
[10]	53	2457.800	[45]	45	2449.688
[11]	56	2460.842	[46]	69	2474.025
[12]	7	2411.154	[47]	6	2410.140
[13]	25	2429.407	[48]	19	2423.323
[14]	34	2438.533	[49]	32	2436.505
[15]	55	2459.828	[50]	48	2452.730
[16]	61	2465.912	[51]	58	2462.870
[17]	10	2414.197	[52]	3	2407.098
[18]	18	2422.309	[53]	27	2431.435
[19]	41	2445.632	[54]	28	2432.449
[20]	49	2453.744	[55]	50	2454.758
[21]	59	2463.884	[56]	57	2461.856
[22]	4	2408.112	[57]	11	2415.210
[23]	15	2419.267	[58]	26	2430.421
[24]	40	2444.618	[59]	30	2434.477
[25]	54	2458.814	[60]	52	2456.786
[26]	66	2470.983	[61]	62	2466.927
[27]	8	2412.169	[62]	0	2404.056
[28]	21	2425.351	[63]	16	2420.281
[29]	38	2442.590	[64]	29	2433.463
[30]	44	2448.674	[65]	42	2446.646
[31]	65	2469.969	[66]	68	2473.011
[32]	2	2406.084	[67]	5	2409.126
[33]	14	2418.253	[68]	24	2428.393
[34]	37	2441.575	[69]	35	2439.547

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6. Quantity of Hopping Channels and Channel Separation

6.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

6.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.3, the number of hopping frequencies test method as follows.

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

According to ANSI C63.10-2013 section 7.8.2, the EUT shall have its hopping function enabled, the Carrier frequency separation test method as follows:


- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.


6.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Channel Spacing (Middle CH)




Channel Spacing (High CH)




Antenna 2:


No. of Channel = 75




Channel Spacing (Low CH)



Channel Spacing (Middle CH)



Channel Spacing (High CH)



7. Dwell Time of Hopping Channel

7.1 Standard Applicable

According to 15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

7.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.4, the dwell time of a hopping channel test method as follows.

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\text{(Number of hops in the period specified in the requirements)} = \text{(number of hops on spectrum analyzer)} \times \text{(period specified in the requirements / analyzer sweep time)}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation. The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

7.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots

The dwell time within a period in data mode is independent from the packet type (packet length).

Test data is corrected with the worse case.

The test period: $T = 0.4 \text{ Second} * 75 \text{ Channel} = 30\text{s}$

Dwell time = time slot length * (Hopping rate / Number of hopping channels) * Period

Antenna 1

Modulation	Test Channel MHz	Packet	Time Slot Length	Dwell Time	Limit
			ms	ms	ms
MSK	2404	N/A	1.94	77.60	400
	2441	N/A	1.94	77.60	400
	2479	N/A	1.94	77.60	400

Antenna 2

Modulation	Test Channel MHz	Packet	Time Slot Length	Dwell Time	Limit
			ms	ms	ms
MSK	2404	N/A	1.94	77.60	400
	2441	N/A	1.94	77.60	400
	2479	N/A	1.94	77.60	400

A period time = $0.4 \text{ (s)} * 75 = 30 \text{ (s)}$

CH Low:

$N=40$, Time slot = 1.94 (ms)

Dwell time = $N * T = 40 * 1.94 = 77.60 \text{ (ms)}$

CH Mid:

$N=40$, Time slot = 1.94 (ms)

Dwell time = $N * T = 40 * 1.94 = 77.60 \text{ (ms)}$

CH High:

$N=40$, Time slot = 1.94 (ms)


Dwell time = $N * T = 40 * 1.94 = 77.60 \text{ (ms)}$

Please refer to the test plots as below:


Antenna 1:

Time slot (Low, Middle, High Channels)


Low Channel:



Middle Channel:




High Channel:




Antenna 2:

Time slot (Low, Middle, High Channels)


Low Channel:



Middle Channel:



High Channel:



8. 20dB Bandwidth

8.1 Standard Applicable

According to 15.247(a) and 15.215(c), 20dB bandwidth is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.2 Test Procedure

According to ANSI C63.10-2013 section 6.9.2, the 20dB bandwidth test method as follows.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

8.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

8.4 Summary of Test Results/Plots

Antenna 1


Test Mode	Test Channel MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Result
MSK	2404	408.717	374.1263	Pass
	2441	411.069	405.0028	Pass
	2479	401.207	372.8203	Pass

Antenna 2


Test Mode	Test Channel MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Result
MSK	2404	469.477	387.1970	Pass
	2441	333.971	410.8020	Pass
	2479	331.118	364.6854	Pass

Antenna 1


Low Channel:



Middle Channel:




High Channel:




Antenna 2


Low Channel:



Middle Channel:



High Channel:



9. RF Output Power

9.1 Standard Applicable

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

9.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.5, the output power test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW \geq RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

9.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

Antenna 1

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2404.056	11.81	15.20	125
Middle Channel	2438.533	11.30	13.50	125
High Channel	2474.025	10.89	12.30	125


Antenna 2

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2404.056	11.64	14.6	125
Middle Channel	2438.533	11.33	13.6	125
High Channel	2474.025	10.90	12.3	125


Note: the antenna gain of 1.5dBi less than 6dBi maximum permission antenna gain value based on 0.125 watt peak output power limit.

Antenna 1


Channel Low:



Channel Middle:




Channel High:




Antenna 2


Channel Low:



Channel Middle:



Channel High:



10. Field Strength of Spurious Emissions

10.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


10.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

10.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

10.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:


*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.
All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in
this report.*

Antenna 1

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: 2.4GHz receiver
 Tested Model: FALCON 12 PLUS
 Operating Condition: Transmitting Low Channel (2404MHz)
 Comment: DC 5V from USB

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	45.0583	27.45	-11.93	15.52	40.00	-24.48	peak
2	106.0126	27.02	-13.48	13.54	43.50	-29.96	peak
3	306.7537	25.92	-8.26	17.66	46.00	-28.34	peak
4	972.3374	26.48	1.94	28.42	54.00	-25.58	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	41.7130	27.02	-12.32	14.70	40.00	-25.30	peak
2	105.6415	26.03	-13.44	12.59	43.50	-30.91	peak
3	294.1137	26.17	-8.23	17.94	46.00	-28.06	peak
4	709.1823	26.86	-1.83	25.03	46.00	-20.97	peak

Operating Condition: Transmitting Middle Channel (2441MHz)


Comment: DC 5V from USB

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	40.1347	26.70	-12.64	14.06	40.00	-25.94	peak
2	100.9340	26.86	-13.73	13.13	43.50	-30.37	peak
3	239.9874	24.59	-9.98	14.61	46.00	-31.39	peak
4	833.3171	26.96	-0.28	26.68	46.00	-19.32	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	42.8998	27.27	-12.16	15.11	40.00	-24.89	peak
2	96.4362	27.23	-14.23	13.00	43.50	-30.50	peak
3	362.9845	26.75	-7.23	19.52	46.00	-26.48	peak
4	854.0247	28.33	-0.10	28.23	46.00	-17.77	peak

7

Operating Condition: Transmitting High Channel (2479MHz)


Comment: DC 5V from USB

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.8637	27.84	-14.83	13.01	40.00	-26.99	peak
2	52.3913	26.91	-11.64	15.27	40.00	-24.73	peak
3	128.5630	26.72	-16.80	9.92	43.50	-33.58	peak
4	912.8620	26.57	1.37	27.94	46.00	-18.06	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	43.0505	25.96	-12.14	13.82	40.00	-26.18	peak
2	98.4866	26.29	-13.98	12.31	43.50	-31.19	peak
3	234.1684	25.70	-10.78	14.92	46.00	-31.08	peak
4	900.1474	26.54	0.86	27.40	46.00	-18.60	peak

Antenna 2

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: 2.4GHz receiver
 Tested Model: FALCON 12 PLUS
 Operating Condition: Transmitting Low Channel (2404MHz)
 Comment: DC 5V from USB

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	49.5328	27.95	-11.61	16.34	40.00	-23.66	peak
2	99.5281	26.95	-13.86	13.09	43.50	-30.41	peak
3	294.1137	27.90	-8.23	19.67	46.00	-26.33	peak
4	968.9338	27.21	1.86	29.07	54.00	-24.93	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	37.8121	26.88	-13.27	13.61	40.00	-26.39	peak
2	105.6415	26.03	-13.44	12.59	43.50	-30.91	peak
3	261.0583	26.12	-9.27	16.85	46.00	-29.15	peak
4	839.1818	26.58	-0.33	26.25	46.00	-19.75	peak

Operating Condition: Transmitting Middle Channel (2441MHz)


Comment: DC 5V from USB

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	33.6803	27.69	-14.82	12.87	40.00	-27.13	peak
2	90.8554	26.73	-13.57	13.16	43.50	-30.34	peak
3	282.9852	26.54	-8.84	17.70	46.00	-28.30	peak
4	665.8035	27.51	-2.59	24.92	46.00	-21.08	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	40.8446	26.21	-12.50	13.71	40.00	-26.29	peak
2	101.6443	26.43	-13.66	12.77	43.50	-30.73	peak
3	300.3673	26.10	-8.15	17.95	46.00	-28.05	peak
4	827.4934	29.94	-0.29	29.65	46.00	-16.35	peak

Operating Condition: Transmitting High Channel (2479MHz)


Comment: DC 5V from USB

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	44.9006	27.84	-11.95	15.89	40.00	-24.11	peak
2	99.8777	27.04	-13.81	13.23	43.50	-30.27	peak
3	338.4001	28.00	-7.36	20.64	46.00	-25.36	peak
4	842.1296	28.08	-0.32	27.76	46.00	-18.24	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	38.2120	26.20	-13.14	13.06	40.00	-26.94	peak
2	97.1148	27.31	-14.15	13.16	43.50	-30.34	peak
3	272.2776	25.47	-9.04	16.43	46.00	-29.57	peak
4	896.9965	26.36	0.78	27.14	46.00	-18.86	peak

Spurious Emissions Above 1GHz~26.5GHz

Antenna 1

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2404MHz							
4808	59.64	-3.59	56.05	74	-17.95	H	PK
4808	38.68	-3.59	35.09	54	-18.91	H	AV
7212	58.78	-0.52	58.26	74	-15.74	H	PK
7212	38.16	-0.52	37.64	54	-16.36	H	AV
4808	59.05	-3.59	55.46	74	-18.54	V	PK
4808	38.88	-3.59	35.29	54	-18.71	V	AV
7212	59	-0.52	58.48	74	-15.52	V	PK
7212	39.15	-0.52	38.63	54	-15.37	V	AV
Middle Channel-2441MHz							
4877	59.15	-3.49	55.66	74	-18.34	H	PK
4877	39.32	-3.49	35.83	54	-18.17	H	AV
7316	60.34	-0.47	59.87	74	-14.13	H	PK
7316	39.31	-0.47	38.84	54	-15.16	H	AV
4877	61.36	-3.49	57.87	74	-16.13	V	PK
4877	40.9	-3.49	37.41	54	-16.59	V	AV
7316	59.3	-0.47	58.83	74	-15.17	V	PK
7316	39.97	-0.47	39.5	54	-14.5	V	AV
High Channel-2479MHz							
4948	58.41	-3.41	55	74	-19	H	PK
4948	40.05	-3.41	36.64	54	-17.36	H	AV
7422	61.73	-0.42	61.31	74	-12.69	H	PK
7422	39.98	-0.42	39.56	54	-14.44	H	AV
4948	60.98	-3.41	57.57	74	-16.43	V	PK
4948	39.82	-3.41	36.41	54	-17.59	V	AV
7422	59.03	-0.42	58.61	74	-15.39	V	PK
7422	41.61	-0.42	41.19	54	-12.81	V	AV

Antenna 2

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2404MHz							
4808	58.55	-3.87	54.68	74	-19.32	H	PK
4808	42.12	-3.87	38.25	54	-15.75	H	AV
7212	55.02	1.14	56.16	74	-17.84	H	PK
7212	40.27	1.19	41.46	54	-12.54	H	AV
4808	58.43	-3.86	54.57	74	-19.43	V	PK
4808	43.06	-3.86	39.2	54	-14.8	V	AV
7212	54.43	1.1	55.53	74	-18.47	V	PK
7212	39.61	1.1	40.71	54	-13.29	V	AV
Middle Channel-2441MHz							
4877	61.95	-3.74	58.21	74	-15.79	H	PK
4877	42.41	-3.74	38.67	54	-15.33	H	AV
7316	54.18	1.47	55.65	74	-18.35	H	PK
7316	39.56	1.47	41.03	54	-12.97	H	AV
4877	60.6	-3.74	56.86	74	-17.14	V	PK
4877	42.59	-3.74	38.85	54	-15.15	V	AV
7316	52.12	1.47	53.59	74	-20.41	V	PK
7316	40.99	1.47	42.46	54	-11.54	V	AV
High Channel-2479MHz							
4948	58.7	-3.59	55.11	74	-18.89	H	PK
4948	43.9	-3.59	40.31	54	-13.69	H	AV
7422	55.68	1.79	57.47	74	-16.53	H	PK
7422	38.08	1.79	39.87	54	-14.13	H	AV
4948	61.33	-3.59	57.74	74	-16.26	V	PK
4948	43.93	-3.59	40.34	54	-13.66	V	AV
7422	53.62	1.79	55.41	74	-18.59	V	PK
7422	40.83	1.79	42.62	54	-11.38	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

11. Out of Band Emissions

11.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

11.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.6, the Band-edge measurements for RF conducted emissions test method as follows.

- a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e) (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).
- b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
- c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3.
- d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6, and orient the EUT and measurement antenna positions to produce the highest emission level.
- e) Perform the test as follows:
 - 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
 - 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
 - 3) Attenuation: Auto (at least 10 dB preferred).
 - 4) Sweep time: Coupled.
 - 5) Resolution bandwidth: 100 kHz.
 - 6) Video bandwidth: 300 kHz.
 - 7) Detector: Peak.
 - 8) Trace: Max hold.
- f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.
- g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak

function to move the marker to the peak of the in-band emission.

h) Repeat step c) through step e) for every applicable modulation.

i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).

j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Restricted-band band-edge test method please refers to ANSI C63.10-2013 section 6.10.5. The emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated band-edge measurements.

According to ANSI C63.10-2013 section 7.8.8, Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers.

Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span 30 MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector. The band 30 MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

11.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar


11.4 Summary of Test Results/Plots

Antenna 1


Bandedge (Radiated)

Lowest Bandedge

Horizontal (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	52.62	-7.78	44.84	74.00	-29.16	peak
2	2390.000	54.55	-7.32	47.23	74.00	-26.77	peak
3	2403.880	111.16	-7.23	103.93	74.00	29.93	peak




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.57	-7.78	33.79	54.00	-20.21	AVG
2	2390.000	44.72	-7.32	37.40	54.00	-16.60	AVG
3	2403.982	110.80	-7.23	103.57	54.00	49.57	AVG

Highest Bandedge
Horizontal (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2478.962	106.96	-6.79	100.17	74.00	26.17	peak
2	2483.500	68.63	-6.77	61.86	74.00	-12.14	peak
3	2500.000	51.13	-6.67	44.46	74.00	-29.54	peak



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.022	106.70	-6.79	99.91	54.00	45.91	AVG
2	2483.500	58.40	-6.77	51.63	54.00	-2.37	AVG
3	2500.000	40.38	-6.67	33.71	54.00	-20.29	AVG


Antenna 2

Bandedge (Radiated)


Lowest Bandedge

Horizontal (Worst case)

107.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	53.03	-7.78	45.25	74.00	-28.75	peak
2	2390.000	54.43	-7.32	47.11	74.00	-26.89	peak
3	2403.880	111.14	-7.23	103.91	74.00	29.91	peak




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.59	-7.78	33.81	54.00	-20.19	AVG
2	2390.000	44.79	-7.32	37.47	54.00	-16.53	AVG
3	2403.982	110.80	-7.23	103.57	54.00	49.57	AVG

Highest Bandedge
Horizontal (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2478.932	106.97	-6.79	100.18	74.00	26.18	peak
2	2483.500	68.12	-6.77	61.35	74.00	-12.65	peak
3	2500.000	51.52	-6.67	44.85	74.00	-29.15	peak





No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.022	106.67	-6.79	99.88	54.00	45.88	AVG
2	2483.500	58.39	-6.77	51.62	54.00	-2.38	AVG
3	2500.000	40.39	-6.67	33.72	54.00	-20.28	AVG



Antenna 1

Conducted Spurious Emission Test Data 30MHz-26.5GHz



Low Channel:




Middle Channel:




High Channel:



Hopping Conducted Test Result
Low Channel





High Channel





Antenna 2

Conducted Spurious Emission Test Data 30MHz-26.5GHz



Low Channel:




Middle Channel:




High Channel:



Hopping Conducted Test Result
Low Channel



High Channel




12. Conducted Emissions

12.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

12.2 Basic Test Setup Block Diagram



12.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

12.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

12.5 Summary of Test Results/Plots

Not applicable. Because the device is powered by battery.

***** END OF REPORT *****