

## 1.1. Test Result of RF Exposure Evaluation

- . Product: Wireless Mobile Router
- . Test Item: RF Exposure Evaluation Data
- . Test site: OATSI-SD
- . Test Mode: Normal Operation

### 1.1.1. Antenna Gain

The maximum Gain is 1.0 dBi.

### 1.1.2. EUT Operation condition

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 1.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Modulation Standard: IEEE 802.11b

Test Date: Oct. 24, 2004

Temperature: 24

Humidity: 63%

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density (S) (mW/cm <sup>2</sup> ) |
|---------|-------------------------|-------------------------------|---|
| 01      | 2412                    | 13.77                         | 0.0060                                  |
| 06      | 2437                    | 13.22                         | 0.0053                                  |
| 11      | 2462                    | 13.73                         | 0.0047                                  |

Modulation Standard: IEEE 802.11g

Test Date: Oct. 24, 2004

Temperature: 24

Humidity: 63%

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density (S) (mW/cm <sup>2</sup> ) |
|---------|-------------------------|-------------------------------|---|
| 01      | 2412                    | 13.09                         | 0.0051                                  |
| 06      | 2437                    | 12.73                         | 0.0047                                  |
| 11      | 2462                    | 12.19                         | 0.0041                                  |

The MPE is calculated as  $0.0060 \text{ mW/cm}^2 < \text{limit } 1 \text{ mW/cm}^2$ . So, RF exposure limit warning or SAR test are not required.