

YX023-PCS Directional Signal Antenna Installation

The YX023-CEL is a high gain, directional panel antenna for use with zBoost Consumer and Custom Install products to provide maximum signal strength when aimed in the direction of best signal. If you know the direction of your provider's tower, point the flat face in that direction. Note: the closest tower may NOT be used by your provider. Some helpful hints are included if you are unsure where your tower is located.



Note: Once the Base Unit is connected and plugged in, verify that the indicator light stays green. If the indicator light is red, you may need to reorient the antenna or increase the distance between the Base Unit and Signal Antenna. See the Troubleshooting section and www.zboost.com for more information.

Installation Steps:

1. When choosing the location for the Signal Antenna, remember higher points generally produce the best results. If you do not have roof access, choose the side of the building with the strongest signal. Using your wireless phone, walk around your house while noting the number of "bars" on your signal strength indicator.
2. When you have determined the location of the strongest signal, mount the antenna to a mast or pole (not provided) using the provided mounting brackets. Loosely tighten the mast, so that you can rotate it from the base.
Note: Maintain 6 ft of separation between metal and the antenna. Also, for best performance, maintain 15 ft of vertical separation between the Base Unit and the antenna.
3. Connect the provided cable to the antenna.
4. Route the coax cable indoors and connect to the Base Unit using the Cell Phone Signal Booster installation instructions.

Antenna Aiming:

To maximize performance, take special care in aiming the antenna in the direction of the best signal from your wireless service provider.

Note on using cell phone bars to measure signal: While the number of signal bars is a good indicator of signal strength, it is not always accurate. The ability to make and complete calls is the most important gauge of signal.

1. Place your cell phone on a non-metal surface 6-8 feet from Base Unit Antenna.
2. Connect power to the zBoost Base Unit and wait 30 seconds. Note the number of signal bars displayed on your cell phone.
3. Record the number of signal bars (or range) _____ (A) on your cell phone. Leave the phone in the same place for the following steps.
4. Rotate the antenna mast 90 degrees and then record the phone signal bars _____ (B).
5. Continue to rotate the antenna mast another 90 degrees in the same direction and record the phone signal bars (or range) _____ (C).

6. Again, rotate the antenna mast another 90 degrees in the same direction and again record the phone signal bars (or range)_____ (D).
7. Look for the highest reading above. Set the antenna to that position.
8. If you desire further optimization, look for the two highest readings above and move the antenna between these two points to find the highest signal bars reading.
9. Once you have determined the highest reading position tighten the mounting bracket hardware to antenna mast.

You have now completed the zBoost Directional Signal Antenna Installation.

YX023-PCS Specifications:

Frequency Range	1850-1990 MHz
Gain	13 dBi
VSWR	<1.5
Impedance	75 ohms
Polarization	vertical
Dimension	9.75"W x 9.75"W x 2.25"D
Weight	1.55 lbs
Connector	Type F-female

For additional information and troubleshooting:

- Consult your zBoost Signal Booster installation guide for more complete troubleshooting information
- Visit www.zBoost.com
- Email support@zBoost.com
- Call zBoost customer service at 1(800) 871-1612.