

RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-22O-RWD-047

Reception No. : 2210003337

Applicant : ROBOTIS

Address : 37, Magokjungang 5-ro 1-gil, Gangseo-gu, Seoul, South Korea

Manufacturer : ROBOTIS

Address : 37, Magokjungang 5-ro 1-gil, Gangseo-gu, Seoul, South Korea

Type of Equipment : Controller

FCC ID. : SOD-RB-88

Model Name : RB-88

Multiple Model Name : RB-86

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : October 21, 2022

Date of issue : October 28, 2022

SUMMARY

The equipment complies with the regulation; *FCC 47 CFR Part 1, 1.1310*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.


This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.



Tested by
Joon-Woo, Kim / Assistant Manager
ONETECH Corp.



Reviewed by
Tae-Ho, Kim / General Manager
ONETECH Corp.



Approved by
Ki-Hong, Nam / General Manager
ONETECH Corp.

CONTENTS**PAGE**

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE	6
4.1 APPLICABLE STANDARD	6
4.2 EUT DESCRIPTION.....	6
4.3 CALCULATED RF EXPOSURE.....	7

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-22O-RWD-047	October 28, 2022	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : ROBOTIS
 Address : 37, Magokjungang 5-ro 1-gil, Gangseo-gu, Seoul, South Korea
 Contact Person : Eunsung Lee / Research Engineer
 Telephone No. : +82-70-8671-2600
 FCC ID : SOD-RB-88
 Model Name : RB-88
 Brand Name : -
 Serial Number : N/A
 Date : October 28, 2022

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Controller
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The ROBOTIS, Model RB-88 (referred to as the EUT in this report) is a Controller. The product specification described herein was obtained from product data sheet or user’s manual.

Device Type	Controller
Temperature Range	-5 °C ~ +70 °C
Operating Frequency	2 402 MHz ~ 2 480 MHz
RF Output Power	-0.22 dBm
Number of Channel	40 Channel
Modulation Type	DSSS Modulation(GFSK)
Antenna Type	PCB Antenna
Antenna Gain	-2.23 dBi
Electrical Rating	DC 4.50 V
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	16 MHz

2.2 Alternative type(s)/model(s); also covered by this test report.

-. The following lists consist of the added model and their differences.

Model Name	Differences	Tested
RB-88	Basic Model	<input checked="" type="checkbox"/>
RB-86	The model is identical to basic model except for the model name only.	<input type="checkbox"/>

Note: 1. Applicant consigns only basic model to test. Therefore this test report just guarantees the units, which have been tested.

2. The Applicant/manufacturer is responsible for the compliance of all variants.

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guideline.

This is a Portable device with its physical nature to be used nearby, the distance between radiating structure and human is less than 20 cm.

As per KDB 447498 D01, The 1-g and 10-g SAR test exclusion thesholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are detrmined by:

$$[(\text{Max. Power of channel, including tune-up tolerance, mW})/(\text{Mim. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}]$$

< 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

F(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison.

4.2 EUT Description

Kind of EUT	Controller
Device Category	<input checked="" type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

4.3 Calculated RF Exposure

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is

$$[(\text{Max. Power of channel, including tune-up tolerance, mW})/(\text{Min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] < 3$$

$$= (1.20/5) \times \sqrt{2.402} = 0.372$$

Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
2 402	-0.22 ± 0.5	0.28	1.20	5	0.372

Conclusion:

SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.