

North 710, Yihua Building, Shennan Road, Futian District,

Shenzhen, P. R. China

Telephone: +86-755-29413628,

Fax: +86-755-22639141

FCC ID: SOVA101B2 IC ID: 5511A-A101B2

Report No.: FCCIC11-RTE040602

Page: 1 of 58

TEST REPORT

Application No.: FCC&IC11-RTE031802RF

Applicant: ARCHOS S.A.

Address of Applicant: 12 Rue Ampere ZI 91430 Igny, France

FCC ID: SOVA101B2 **IC ID**: 5511A-A101B2

Fundamental Carrier

Frequency: 2.412GHz to 2.462GHz

Equipment Under Test (EUT):

EUT Name: A10HT Home Tablet

Item No.: A101B2

Serial No.: Not supplied by client

Standards: FCC PART 15 Subpart C: 2008

RSS-210 Issue 8 2010 RSS-Gen Issue 3 2010

Date of Receipt: 18 March, 2011

Date of Test: 20 March, 2011 to 31 March, 2011

Date of Issue: 06 April, 2011

Test Result : PASS*

Authorized Signature:

Kavin Yu Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of EBO Technology Approvals or testing done by EBO Technology Approvals in connection with, distribution or use of the product described in this report must be approved by EBO Technology Approvals in writing. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: FCCIC11-RTE040602

Page: 2 of 58

1 Test Summary

Test Requirement Standard Pa		Standard Paragraph	Result	
	FCC PART 15:2008	Section 15.207	PASS	
Conducted Emissions	RSS-Gen:2010	Section 7.2.2		
	FCC PART 15:2008	Section 15.205/15.209		
Radiated Emissions	RSS-210:2010 RSS-Gen:2010	A 8.5 Secion 7.2.3	PASS	
Maximum Peak Output	FCC PART 15:2008	Section 15.247 (b)	PASS	
Power	RSS-210:2010	A 8.4(2)	PASS	
	FCC PART 15:2008	Section 15.247 (a2)	DACC	
6dB Occupied Bandwidth	RSS-210:2010	A 8.2(a)	PASS	
99% Occupied Bandwidth	RSS-Gen:2010	Section 4.6 PAS		
Band Edges and Conducted	FCC PART 15:2008	Section 15.247(d)	PASS	
Spurious Emissions	RSS-210:2010	A 8.5		
Power Spectral Density	FCC PART 15:2008	Section 15.247 (e)	PASS	
Measurement	RSS-210:2010	A 8.2(b)	PASS	
Antenna requirement	FCC PART 15:2008	Section 15.247 (b)	PASS	
RF Exposure Compliance Requirement	FCC PART 15:2008	15.247(b)(4)& 1) c) D01 Mobile Portable RF Exposure v04	PASS	
Requirement	RSS-102:2010	Section 2.5.1		

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 3 of 58

2 Contents

1 TEST SUMMARY 2 CONTENTS	3 5
2 CONTENTS	5
3 GENERAL INFORMATION	
3.1 CLIENT INFORMATION	
3.3 TEST SUPPORTING SYSTEM DETAILS	
3.4 TEST LOCATION	
3.5 TEST FACILITY	
3.6 Measurement Uncertainty	
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
4 EQUIPMENT USED DURING TEST	8
5 TEST RESULTS	Q
5.1 Conducted Emissions	
5.1.1 Test Setup	
5.1.2 Test Procesure	
5.1.3 Measurement Data	
5.2 RADIATED EMISSIONS	
5.2.1 Test Setup	14
5.2.2 Test Prosesure	
5.2.3 Measurement Data	
5.3 MAXIMUN PEAK OUTPUT POWER	
5.3.1 Test Setup	
5.3.2 Test Procedure	
5.4 6DB Occupied Bandwidth	
5.4.1 Test Setup	
5.4.2 Test Procedure	
5.4.3 Measurement Data	33
5.5 99% Occupied Bandwidth	
5.5.1 Test Setup	
5.5.2 Test Procedure	
5.5.3 Measurement Data	
5.6 BAND EDGES AND CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	
5.6.2 Test Procedure	
5.6.3 Measurement Data	
5.7 POWER SPECTRAL DENSITY MEASUREMENT	
5.7.1 Test Setup	
FCC ID: SOVA101B2	
IC ID: 5511A-A101B2	



Report No.: FCCIC11-RTE040602

Page: 4 of 58

5.	7.2	Test Procedure	51
		Measurement Data	
_	_	ENNA REQUIREMENT	
		EXPOSURE COMPLIANCE	

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 5 of 58

3 General Information

3.1 Client Information

Applicant: ARCHOS S.A.

Address of Applicant: 12 Rue Ampere ZI 91430 Igny, France

Factory: Shenzhen Shenchuang Electronics Co.,Ltd

Address of Factory: 7th floor, West Tower, Hengfanglaobing Industrial Park, Xingye

Road, Xixiang Town, Bao'an District, Shenzhen

3.2 General Description of E.U.T.

Equipment Under Test: Wireless Data Transmission (WiFi)

Trade Name: ARNOVA

Type Designation: A10HT Home tablet

Model Number: A101B2

Standards: IEEE802.11b/g

Type of modulation(802.11b): DSSS(DBPSK,DQPSK,CCK)

Type of modulation(802.11g): OFDM (BPSK,QPSK,16QAM,64QAM)

Max Data Rate: 11Mbps(802.11b),54Mbps(802.11g)

Conducted Power: 12.36dBm(802.11b), 12.29dBm(802.11g)

Number of Channels: 11

Operation Frequency: 2412 ~2462MHz

Antenna Designation: Internal Antenna soldering on the PCB

Antenna Gain: 0dBi

AC Adapter

Model:KSAS0100500200D5

Power Supply: Input:AC 100-240V 50/60Hz 0.4A

Output:DC 5.0V 2.0A

Date of Test: March 20, 2011 to March 31, 2011

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 6 of 58

Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		

Note:

Regards to the frequency band over 10MHz, the lowest, middle and highest frequency of channel were selected to perform the test, and then shown on this report.

So the there channel as follow:

Lowest channel: 2412MHz Middle channel: 2437MHz Highest channel: 2462 MHz

3.3 Test Supporting System Details

Equipment Name	Model No.	Manufacturer	FCC Status
Notebook Computer	nc4000	HP	DOC
Monitor	TFT1780PS	AOV	DOC
Keyboard	JME7053	Lenovo	DOC
Mouse	N/A	Lenovo	DOC

3.4 Test Location

All tests were sub-contracted to:

ATC Lab Co., Ltd (Guangdong, China).

205#, Yingfeng Building, Ronggu Rd, Foshan, Guangdong, China (528305)

Phone:0757-23612690 Fax:0757-23612537

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 7 of 58

3.5 Test Facility

FCC-Registration No.: 415467

ATC Lab Co., Ltd (Guangdong, China) EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 415467. Listing date October 10, 2008.

IC-Registration No.: 7949A

The 3m Alternate Test Site of ATC Lab Co., Ltd (Guangdong, China) has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7949A on March. 25th, 2011.

3.6 Measurement Uncertainty

of +/- 3×10⁻⁹ for 6dB and 99% Bandwidth Measurement

of +/- 0.8 dB for Peak Output Power Measurement

of +/- 0.8 dB for Band Edge RF Conducted Measurement

of +/- 0.8 dB for Spurious RF Conducted Emission Measurement

of +/- 0.8 dB for Power Density

of +/- 4.5 dB for Radiated Emissions

of +/- 2.3 dB for Conducted Emissions

3.7 Other Information Requested by the Customer

None

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 8 of 58

4 Equipment Used during Test

Conducted Em	Conducted Emission					
No.	Test Equipment	Manufacturer	Mo del No.	Serial No.	Cal. Due Date	
GAL-EMC002	Shielding Room	ETS	N/A	N/A	2011-05-18	
GAL-EMC003	Receiver	SCHAFFNER	SMR4503	11725	2011-07-08	
GAL-EMC005	Line impedance stabilization network	EMCO	4825/2	1161	2011-07-08	
GAL-EMC098	Line impedance stabilization network	EMCO	3810/2	2516	2011-07-08	
RF in Chambe	1				,	
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Due Date	
GAL-EMC001	Semi-anechoic Chamber	ETS	N/A	N/A	2011-05-25	
GAL-EMC003	Receiver	SCHAFFNER	SMR4503	11725	2011-07-08	
GAL-EMC007	Double-ridged Wave guide horn	ETS	3115	6587	2011-08-02	
GAL-EMC008	Microwave system amplifier (0.5G-26.5G)	Agilent	83017A	MY39500438	2011-07-08	
GAL-EMC017	Biconilog Antenna	ETS	3142C	00042672	2011-09-26	
GAL-EMC055	Band-pass Filter	Micro-Tronic	BRM50702	S/N-030	2011-11-09	
GAL-EMC056	Spectrum Analyzer 9KHz-30GHz	R&S	FSP30	100755	2011-11-02	
GAL-EMC075	Double-ridged Wave guide horn	ETS	3160	00052486	2011-08-02	
RF Conducted						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Due Date	
GAL-EMC056	Spectrum Analyzer 9KHz-30GHz	R&S	FSP30	100755	2011-11-02	
GAL-EMC099	ATC-Lab	N/A	N/A	N/A	2011-11-02	

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 9 of 58

5 Test Results

5.1 Conducted Emissions

Test Requirement: FCC Part15 B Section 15.207

RSS-Gen Section 7.2.2

Test Method: ANSI C63.4:2003 Frequency Range: 150KHz to 30MHz

Class/Severity: Class B

Detector: Peak for pre-scan (9 kHz resolution bandwidth)

Test Mode: WIFI mode (Notebook Active with the EUT under WIFI mode)

Test Voltage: 120Vac,60Hz
Test Date: 20 March, 2011

Temperature: 22° C Humidity: 42%

Limit: a) Except as shown in paragraphs (b) and (c) of this section, for an

intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu\text{H}/50$ ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit

applies at the boundary between the frequency ranges

Frequency of Emission (MHz)	Conducted Limit (dBuV)		
	Quasi-peak	Average	
0.15-0.5	66 to 56 *	56 to 46 *	
0.5-5	56	46	
5-30	60	50	

^{*} Decreases with the logarithm of the frequency.


FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 10 of 58

5.1.1 Test Setup



5.1.2Test Procesure

The Device was connected to the artifical main network via AC adapter and connect with Notebook computer(refer to section 3.3 for details), And test the EUT with actived in WIFI transmit mode.

5.1.3Measurement Data

Measure the maximised peak emissions from the EUT for both the Live and Neutral Lines. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Frequency	Line	Measured	QP Limit	Measured	AV Limit	Over Limit	Over Limit
(MHz)	Lille	QP (dBuV)	(dBuV)	AV (dBuV)	(dBuV)	QP	AV
0.1750	L	44.90	64.65	24.70	54.65	-19.75	-29.95
0.2550	L	44.80	61.55	26.40	51.55	-16.75	-25.15
0.3350	L	38.60	59.30	22.90	49.30	-20.70	-26.40
0.5100	L	33.60	56.00	24.70	46.00	-22.40	-21.30
13.4900	L	39.10	60.00	27.10	50.00	-20.90	-22.90
14.0200	L	38.80	60.00	26.80	50.00	-21.20	-23.20
0.1850	Ν	50.30	64.19	30.00	54.19	-13.89	-24.19
0.3600	N	37.90	58.71	23.40	48.71	-20.81	-25.31
0.5450	N	38.90	56.00	26.10	46.00	-17.10	-19.90
1.8200	Ν	34.50	56.00	19.50	46.00	-21.50	-26.50
8.3500	N	31.10	60.00	20.70	50.00	-28.90	-29.30
13.3450	N	37.00	60.00	25.50	50.00	-23.00	-24.50

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Live Line


Shenzhen EBO Technology Co., Ltd.

Report No.: FCCIC11-RTE040602

Page: 11 of 58

Title	Œ L
EUT / Ser.No.	A101B2
Condition	120Vae,60Hz
Frequency Range(s)	Range 1
Start Frequency	150 kHz
Stop Frequency	80 MHz
Step Frequency	5 kHz
Attenuestes	As den

Attenuate Detector CISPR IF Bandwidth 9 KHz (Pre) Measure Time (Pre) 10 ms Detector (Final) QP. IF Bandwidth 9 MHz (Final) Measure Time (Final) Sub Ranges (Final)



FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 12 of 58

Nuetral Line

I file		Œ	N	
EUT / Ser.No.		A101	B2	
Condition		120V	ac,60	Hz
Frequency Range	H(8)			Range 1
Start Frequency				150 kHz
Stop Frequency				80 MHz
Step Frequency				5 M-12
Attenuator				Auto
Detector	(Pre)			AV CISPR
IF Bandwidth	(Pre)			9 MHz
Measure Time	(Pre)			10 ms
Detector	(Final)			QP
IF Bandwidth	(Final)			9 kHz
Measure Time	(Final)			1 s
Sub Ranges	(Final)			20



FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 13 of 58

5.2 Radiated Emissions

Test Requirement: FCC Part15 C Section 15.247,15.209 and 15.205

RSS-210 A 8.5 and RSS-Gen Section 7.2.3

Test Method: ANSI C63.4:2003 Frequency Range: 30MHz to 25GHz

Receiver Setup: QP Detector (RBW=120 kHz,VBW=300kHz) for 30 to 1000 MHz RE testing

Peak Detector(RBW=1MHz,VBW=3MHz) for 1 to 25 GHz RE Peak value testing

Peak Detector(RBW=1MHz, VBW=10Hz) for 1 to 25 GHz RE AV value testing

Test Mode: WIFI transmit mode

Test Voltage: 120Vac,60Hz

Test Date: 20 March, 2011 to 23 March. 2010

Temperature: $20 \,^{\circ}\text{C} \sim 24 \,^{\circ}\text{C}$ Humidity: $40\% \sim 48\%$

Limit: The field strength of radiated emissions from unintentional radiators at a distance

of 3 meters shall not exceed the following values:

Test Procedure: Prescan on three orthogonal axes with the EUT and show the worst case

measured results in the report.

Frequency of Emission	Field Strength		
(MHz)	(microvolts/meter)	dB (μV/m)	
30 - 88	100	40(QP)	
88 - 216	150	43.5(QP)	
216 - 960	200	46(QP)	
960-1000	500	54(QP)	
Above 1000	500	54(AV)	
		74(PK)	

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 14 of 58

5.2.1 Test Setup




Figure 1: 30MHz to 1GHz radiated emissions test setup




Figure 2: Above 1GHz radiated emissions test setup

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 15 of 58

5.2.2Test Prosesure

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until all frequency measured were complete.

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 16 of 58

5.2.3Measurement Data

Radiated Emission below 1GHz

Set the WIFI model, pre-scan all channels of the WIFI with transmitting, and found out the 802.11b transmitting mode, channel 01which it is the worst case.

Frequency	Antenna	Reading	Ant./CL/	Measured	QP Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
32.240	Н	12.38	17.67	30.05	40.00	-9.95	Pass
288.570	Н	19.27	14.52	33.79	46.00	-12.21	Pass
354.700	Н	13.67	15.00	28.67	46.00	-17.33	Pass
442.540	Н	14.56	16.20	30.76	46.00	-15.24	Pass
766.260	Н	9.82	22.32	32.14	46.00	-13.86	Pass
916.800	Н	-0.21	24.30	24.09	46.00	-21.91	Pass
35.680	V	15.00	18.70	33.70	40.00	-6.30	Pass
143.790	V	11.41	9.02	20.43	43.50	-23.07	Pass
356.220	V	13.64	15.00	28.64	46.00	-17.36	Pass
440.180	V	22.53	16.17	38.70	46.00	-7.30	Pass
550.760	V	12.00	20.46	32.46	46.00	-13.54	Pass
768.080	V	8.23	22.32	30.55	46.00	-15.45	Pass

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 17 of 58

Radiated Emission Above 1GHz

Pre-scan all kind of data rate in WIFI with transmitting, and found the worse case which it is 11Mbps of 802.11b mode ,54Mbps of 802.11g mode with transmitting.

Transmitting mode (802.11b lowest channel=2412MHz)

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1028.000	Н	52.67	-5.10	47.57	74.00	-26.43	Pass
4794.000	Н	45.76	6.10	51.86	74.00	-22.14	Pass
7236.000	Н	42.03	11.80	53.83	74.00	-20.17	Pass
-	-	-	ı	-	1	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
1030.000	V	54.86	-5.10	49.76	74.00	-24.24	Pass
4791.000	V	44.82	6.10	50.92	74.00	-23.08	Pass
7236.000	V	41.64	11.80	53.44	74.00	-20.56	Pass
-	-	-	-	-	-	-	-
-		-		-	-	-	-
-	-	-	-	-	-	-	-

Average Measurement

vorage meas						1	1
Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1028.000	Н	33.76	-5.10	28.66	54.00	-25.34	Pass
4796.000	Η	29.14	6.10	35.24	54.00	-18.76	Pass
7236.000	Н	29.00	11.80	40.80	54.00	-13.20	Pass
-	-	-	1	-	ı	-	-
-	ı	-	ı	-	ı	-	-
-	-	-	1	-	1	-	-
1030.000	V	34.62	-5.10	29.52	54.00	-24.48	Pass
4971.000	V	29.10	6.10	35.20	54.00	-18.80	Pass
7236.000	V	28.88	11.80	40.68	54.00	-13.32	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	_	-

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 18 of 58

Transmitting mode (802.11b middle channel=2437MHz)

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
, ,	,	,	(dB)	(dBuV/m)	,	, ,	
1448.000	Н	48.10	-4.80	43.30	74.00	-30.70	Pass
4876.000	Н	42.68	6.10	48.78	74.00	-25.22	Pass
7311.000	Н	40.23	11.92	52.15	74.00	-21.85	Pass
-	-	-	ı	-	ı	-	-
-	-	-	-	-	1	-	-
-	-	-	-	-	-	-	-
1034.000	V	49.76	-5.10	44.66	74.00	-29.34	Pass
4876.000	V	42.16	6.10	48.26	74.00	-25.74	Pass
7311.000	V	40.35	11.92	52.27	74.00	-21.73	Pass
-	-	-	-	-		-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Average Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
, ,	,	,	(dB)	(dBuV/m)	,	, ,	
1448.000	Н	32.20	-4.80	27.40	54.00	-26.60	Pass
4874.000	Н	29.29	6.10	35.39	54.00	-18.61	Pass
7311.000	Н	28.12	11.92	40.04	54.00	-13.96	Pass
-	-	-	1	-	-	-	-
-	ı	-	•	-	-	-	-
-	-	-	-	-	-	-	-
1034.000	V	34.03	-5.10	28.93	54.00	-25.07	Pass
4874.000	V	29.47	6.10	35.57	54.00	-18.43	Pass
7311.000	V	29.13	11.92	41.05	54.00	-12.95	Pass
-	1	-	ı	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	_	_

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 19 of 58

Transmitting mode (802.11b highest channel=2462MHz)

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1502.000	Н	49.82	-4.80	45.02	74.00	-28.98	Pass
4910.000	Н	42.35	6.10	48.45	74.00	-25.55	Pass
7384.000	Н	41.13	12.10	53.23	74.00	-20.77	Pass
_	-	-	ı	-	ı	-	-
-	-	-	-	-	-	-	-
-	ı	1	ı	-	ı	-	-
1502.000	V	50.28	-4.80	45.48	74.00	-28.52	Pass
4910.000	V	44.37	6.10	50.47	74.00	-23.53	Pass
7392.000	V	40.26	12.10	52.36	74.00	-21.64	Pass
_	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Average Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
, ,	,	,	(dB)	(dBuV/m)	,	, ,	
1502.000	Н	31.75	-4.80	26.95	54.00	-27.05	Pass
4910.000	Н	29.24	6.10	35.34	54.00	-18.66	Pass
7386.000	Н	29.13	12.10	41.23	54.00	-12.77	Pass
-	-	-	1	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
1268.000	V	32.37	-4.90	27.47	54.00	-26.53	Pass
4910.000	V	29.05	6.10	35.15	54.00	-18.85	Pass
7386.000	V	28.78	12.10	40.88	54.00	-13.12	Pass
-	-	-	ı	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-		-	-	-	_

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 20 of 58

Transmitting mode (802.11g lowest channel=2412MHz)

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1544.000	Н	50.23	- 4.80	45.43	74.00	-28.57	Pass
4808.000	Н	44.68	6.10	50.78	74.00	-23.22	Pass
7256.000	Н	40.26	11.80	52.06	74.00	-21.94	Pass
-	-	-	-	-	-	-	-
-	-	-	•	-	-	-	-
-	-	-	-	-	-	-	-
1544.000	V	51.37	-4.80	46.57	74.00	-27.43	Pass
4808.000	V	43.59	6.10	49.69	74.00	-24.31	Pass
7236.000	V	40.12	11.80	51.92	74.00	-22.08	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Average Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)		Pass /Fail
			(dB)	(dBuV/m)			
1544.000	Н	30.11	-4.80	25.31	54.00	-28.69	Pass
4808.000	Н	28.62	6.10	34.72	54.00	-19.28	Pass
7256.000	Н	29.14	11.80	40.94	54.00	-13.06	Pass
-	-	-	-	-	-	-	-
-	-	-	ı	-	-	-	-
-	-	-	-	-	-	-	-
1544.000	V	31.43	- 4.80	26.63	54.00	-27.37	Pass
4808.000	V	29.47	6.10	35.57	54.00	-18.43	Pass
7236.000	V	29.12	11.80	40.92	54.00	-13.08	Pass
-	-	-	ı	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	_

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 21 of 58

Transmitting mode (802.11g middle channel=2437MHz)

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1148.000	Н	50.31	4.90	45.41	74.00	-28.59	Pass
4876.000	Н	43.56	6.10	49.66	74.00	-24.34	Pass
7324.000	Н	42.28	11.92	54.20	74.00	-19.80	Pass
-	-	-	-	-	-	-	-
-	1	-	ı	-	-	-	-
-	-	-	1	-	-	-	-
1170.000	V	51.47	-4.90	46.57	74.00	-27.43	Pass
4876.000	V	78.00	6.10	84.10	74.00	10.10	Pass
7460.000	V	41.35	11.92	53.27	74.00	-20.73	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Average Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)		Pass /Fail
			(dB)	(dBuV/m)			
1148.000	Н	32.04	-4.90	27.14	54.00	-26.86	Pass
4910.000	Н	28.54	6.10	34.64	54.00	-19.36	Pass
7426.000	Н	28.17	11.92	40.09	54.00	-13.91	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
1170.000	V	32.53	-4.90	27.63	54.00	-26.37	Pass
4876.000	V	28.76	6.10	34.86	54.00	-19.14	Pass
7426.000	V	28.43	11.92	40.35	54.00	-13.65	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-		-	-	-	-

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 22 of 58

Transmitting mode (802.11g highest channel=2462MHz)

Peak Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	PEAK Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1098.000	Н	50.74	-5.00	45.74	74.00	-28.26	Pass
4910.000	Н	43.25	6.10	49.35	74.00	-24.65	Pass
7426.000	Н	41.62	12.10	53.72	74.00	-20.28	Pass
-	-	-	1	-	-	-	-
-	1	-	1	-	1	-	-
-	1	-	1	-	1	-	-
1034.000	V	52.37	-5.10	47.27	74.00	-26.73	Pass
4910.000	V	45.29	6.10	51.39	74.00	-22.61	Pass
7386.000	V	41.00	12.10	53.10	74.00	-20.90	Pass
-	-	-	ı	-	ı	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Average Measurement

Frequency	Antenna	Reading	Ant./CL/	Measured	AV Limit	Over	
(MHz)	Polarity	(dBuV/m)	Amp.CF	Level	(dBuV/m)	Limit(dB)	Pass /Fail
			(dB)	(dBuV/m)			
1068.000	Н	33.85	-5.10	28.75	54.00	-25.25	Pass
4910.000	Н	29.46	6.10	35.56	54.00	-18.44	Pass
7426.000	Н	29.01	12.10	41.11	54.00	-12.89	Pass
-	-	-	-	-	-	-	-
-	-	-	•	-	-	-	-
-	-	-	-	-	-	-	-
1158.000	V	32.73	-4.90	27.83	54.00	-26.17	Pass
4910.000	V	29.12	6.10	35.22	54.00	-18.78	Pass
7386.000	V	28.79	12.10	40.89	54.00	-13.11	Pass
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 23 of 58


Band Edge and Restriced band (Radiated measurement)

Set the WIFI mode, pre-scan all channels of the WIFI, and found the 802.11g mode which it is worse case. Transmitting with 802.11g mode (Lowest channel=2412MHz)

Peak Measurement in Horizontal polarization



Average Measurement in Horizontal polarization




FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 24 of 58

Peak Measurement in Vertical polarization



Average Measurement in Vertical polarization




FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 25 of 58

Transmitting with 801.11g mode (Highest channel=2462MHz) Peak Measurement in Horizontal polarization



Average Measurement in Horizontal polarization




FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 26 of 58

Peak Measurement in Vertical polarization



Average Measurement in Vertical polarization



FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 27 of 58

Remark 1:

No any other emissions level which are attenuated less than 20dB below the limit According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part. Hence there no other emissions have been reported.

Remark 2:

- 1). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 2). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.
- 3) Pre-Scan has been conducted to determine the worst-case mode from all possible Combinations between available modulations, data rates and antenna ports, and found the EUT worse case mode: 802.11b (11MHz), 802.11g (54MHz).
- 4) For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the 4th harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 4th harmonic.

Remark 3: Section 15.205 Restricted bands of operation.

MHz	MHz	MHz	GHz	
0.090 - 0.110	0.090 - 0.110 16.42 - 16.423		4.5 - 5.15	
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46	
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75	
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5	
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2	
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5	
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7	
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4	
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5	
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2	
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4	
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12	
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0	
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8	
12.51975 - 12.52025	12.51975 - 12.52025 167.72 - 173.2		36.43 - 36.5	
12.57675 - 12.57725	12.57675 - 12.57725 240 - 285		(²)	
13.36 - 13.41	322 - 335.4			

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions,or comply with 15.209 limits.

FCC ID: SOVA101B2 IC ID: 5511A-A101B2

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ebotek.cn and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.ebotek.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: FCCIC11-RTE040602

Page: 28 of 58

5.3 Maximun Peak Output Power

Test Requirement: FCC 15.247(b)

RSS-210 A 8.4(2)

Test Method: ANSI C63.4:2003 and KDB558074.

Method of Measurement: The EUT was setup to ANSI C63.4, 2003, tested to DTS test

procedure of Oct 2002 KDB558074 for compliance to FCC 47CFR

15.247 requirements.

Select test data rate: 11Mbps(802.11b) & 54Mbps(802.11g)

Detector: RBW=1 MHz, VBW=3 MHz (Peak detector)

Test Mode: WIFI transmitting mode

Test Voltage: Pretest the EUT with voltage $120 \pm 15\%$ Vac,60Hz;and found out at


120Vac,60Hz is the worst case.

Test Date: 24 March, 2011

Temperature: 22° C Humidity: 43%

Limit: The Limit of Maximum Peak Output Power Measurement is 30dBm.

5.3.1Test Setup



5.3.2Test Procedure

Pre-Scan has been conducted to determine the worst-case mode from all possible Combinations between available modulations, data rates (802.11b 1/2/5.5/11Mbps and 802.11g 6/9/12/18/24/36/48/54Mbps).

Following channel(s) was (were) selected for the final test as listed below.

802.11b 11Mbps and 802.11g 54Mbps

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 29 of 58

5.3.3Measurement Data

For EUT communicating with 802.11b Mode

٠.	of Eot communicating with coz. I ib wode					
	Chanel	Peak Output	Cable Loss	Power	Limit	Over Limit
	Frequency	Power(dBm)	(dB)	level(dBm)	(dBm)	(dB)
	(GHz)					
	2.412	11.00	0.5	11.50	30.00	-18.50
	2.437	11.07	0.5	11.57	30.00	-18.43
	2.462	11.30	0.5	11.80	30.00	-18.20

For EUT communicating with 802.11g Mode

٠.	of EGT confinitioning with CCE. Fig McCC					
I	Chanel	Peak Output	Cable Loss	Power	Limit	Over Limit
	Frequency	Power(dBm)	(dB)	level(dBm)	(dBm)	(dB)
	(GHz)					, ,
ŀ						
L	2.412	10.86	0.5	11.36	30.00	-18.64
I	2.437	11.03	0.5	11.53	30.00	-18.47
Ī	2.462	11.28	0.5	11.78	30.00	-18.22

Test result: The unit does meet the requirements.

Test result plot as follows:


FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 30 of 58

The EUT communicating with 802.11b Mode



FCC ID: SOVA101B2 IC ID: 5511A-A101B2

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ebotek.cn and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.ebotek.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


Power

11.30 dBm



Report No.: FCCIC11-RTE040602

Page: 31 of 58



FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 32 of 58

5.4 6dB Occupied Bandwidth

Test Requirement: FCC 15.247(b)

RSS-210 A 8.2(a)

Test Method: ANSI C63.4:2003 and KDB558074.

Method of Measurement: The transmitter output was connected to the spectrum analyzer through

an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer. The 6 dB bandwidth isdefined as the total spectrum the power of which is higher than peak power minus 6 dB. Analyzer andthe attached plot were taken. The EUT was setup to ANSI C63.4, 2003, tested to DTS test procedure Oct 2002 KDB558074 for

compliance with FCC 47CFR 15.247 requirements.

Select test data rate: 11Mbps(802.11b) & 54Mbps(802.11g)

Detector: RBW=100kHz,VBW=300 kHz (Peak detector)


Test Mode: WIFI transmitting mode

Test Voltage: 120Vac,60Hz
Test Date: 24 March, 2011

Temperature: 22° C Humidity: 42%

Limit: The minimum 6 dB bandwidth shall be at least 500 kHz.

5.4.1 Test Setup



5.4.2Test Procedure

Pre-Scan has been conducted to determine the worst-case mode from all possible Combinations between available modulations, data rates (802.11b 1/2/5.5/11Mbps and 802.11g 6/9/12/18/24/36/48/54Mbps). Following channel(s) was (were) selected for the final test as listed below.

802.11b 11Mbps and 802.11g 54Mbps

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 33 of 58

5.4.3 Measurement Data

For EUT communicating with 802.11b Mode

r or Eet reclimationaling with cez. The wede						
Chanel Frequency (GHz)	6 dB Bandwidth (MHz)	Minimun Limit (MHz)	Pass/Fail			
2.412	10.74	0.5	Pass			
2.437	10.20	0.5	Pass			
2.462	9.36	0.5	Pass			

For EUT communicating with 802.11g Mode

	Free Ferning Mare 602: 11g Mede					
Chanel Frequency (GHz)	6 dB Bandwidth (MHz)	I I IMIT				
2.412	16.38	0.5	Pass			
2.437	16.08	0.5	Pass			
2.462	16.08	0.5	Pass			

Test result: The unit does meet the requirements.

Test result plot as follows:

FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Span 30 MHz

Report No.: FCCIC11-RTE040602


Page: 34 of 58

The EUT communicating with 802.11b Mode



Middle channel=2437MHz

enter 2.412 GHz




FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 35 of 58




FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 36 of 58

The EUT communicating with 802.11g Mode Lowest channel=2412MHz



Middle channel=2437MHz




FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 37 of 58

Highest channel=2462MHz





Report No.: FCCIC11-RTE040602

Page: 38 of 58

5.5 99% Occupied Bandwidth

Test Requirement: RSS-Gen Section 4.6.1

Test Method: ANSI C63.4:2003

Select test data rate: 11Mbps(802.11b) & 54Mbps(802.11g)


Detector: RBW=100kHz,VBW=300 kHz (Peak detector)

Test Mode: WIFI transmitting mode

Test Voltage: 120Vac,60Hz
Test Date: 24 March, 2011

Temperature: 22° C Humidity: 42% Limit: N/A

5.5.1 Test Setup



5.5.2Test Procedure

Pre-Scan has been conducted to determine the worst-case mode from all possible Combinations between available modulations, data rates (802.11b 1/2/5.5/11Mbps and 802.11g 6/9/12/18/24/36/48/54Mbps). Following channel(s) was (were) selected for the final test as listed below.

802.11b 11Mbps and 802.11g 54Mbps

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 39 of 58

5.5.3 Measurement Data

Chanel Frequency	99% Occupy Bandwidth(MHz)			
(GHz)	802.11b	802.11g		
2.412	14.40	16.44		
2.437	14.46	16.44		
2.462	14.22	16.38		

Test result: The unit does meet the requirements.


Test result plot as follows:




Report No.: FCCIC11-RTE040602

Page: 40 of 58

The EUT communicating with 802.11b Mode



Middle channel=2437MHz




FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 41 of 58

Highest channel=2462MHz




FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 42 of 58

The EUT communicating with 802.11g Mode



Middle channel=2437MHz




FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 43 of 58





FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 44 of 58

5.6 Band Edges and Conducted Spurious Emissions Measurement

Test Requirement: FCC Part15 C Section 15.247(d)

RSS-210 A 8.5

Test Method: ANSI C63.4; FCC Part15 C Section 15.247:

KDB Publication No. 558074 for DTS 11Mbps(802.11b) & 54Mbps(802.11g)

Select test data rate: 11Mbps(802.11b) & 54Mbps(802.11g)

Detector: RBW=100kHz,VBW=300 KHz (Peak detector)

Test Mode: WIFI transmitting mode

Test Voltage: 120Vac,60Hz
Test Date: 31 March, 2011

Temperature: 21°C Humidity: 41%

Limit: In any 100 kHz bandwidth outside the frequency band in which the

spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains

the highest level of the desired power, based on either an RF

conducted or a radiated measurement.

5.6.1 Test Setup



5.6.2Test Procedure

Pre-Scan has been conducted to determine the worst-case mode from all possible Combinations between available modulations, data rates (802.11b 1/2/5.5/11Mbps and 802.11g 6/9/12/18/24/36/48/54Mbps). Following channel(s) was (were) selected for the final test as listed below.

802.11b 11Mbps and 802.11g 54Mbps

5.6.3 Measurement Data

Test result: The unit does meet the requirements.

Test result plot as follows:


FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 45 of 58

Transmitting mode in lowest channel=2412MHz (802.11b)






FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 46 of 58

Transmitting mode in middle channel=2437MHz (802.11b)







Report No.: FCCIC11-RTE040602

Page: 47 of 58

Transmitting mode in highest channel=2462MHz (802.11b)






FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 48 of 58

Transmitting mode in lowest channel=2412MHz (802.11g)






FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 49 of 58

Transmitting mode in middle channel=2437MHz (802.11g)




FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 50 of 58

Transmitting mode in highest channel=2462MHz (802.11g)



FCC ID: SOVA101B2 IC ID: 5511A-A101B2

Center 12.515 GHz

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ebotek.cn and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.ebotek.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Span 24.97 GHz



Report No.: FCCIC11-RTE040602

Page: 51 of 58

5.7 Power Spectral Density Measurement

Test Requirement: FCC Part15 C Section 15.247(d)

RSS-210 A 8.2(b)

Test Method: ANSI C63.4; FCC Part15 C Section 15.247:

KDB Publication No. 558074 for DTS

Select test data rate: 11Mbps(802.11b) & 54Mbps(802.11g)

Detector: RBW=3KHz,VBW=10 KHz (Peak detector)

Test Mode: WIFI transmitting mode

Test Voltage: 120Vac,60Hz
Test Date: 31 March, 2011


Temperature: 21° C Humidity: 42°

Limit: the peak power spectral density conducted from the intentional radiator to

the antenna shall not be greater than 8 dBm in any 3 kHz band during

any time interval of continuous transmission

5.7.1 Test Setup



5.7.2Test Procedure

Pre-Scan has been conducted to determine the worst-case mode from all possible Combinations between available modulations, data rates (802.11b 1/2/5.5/11Mbps and 802.11g 6/9/12/18/24/36/48/54Mbps). Following channel(s) was (were) selected for the final test as listed below.

802.11b 11Mbps and 802.11g 54Mbps

FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 52 of 58

5.7.3 Measurement Data

For EUT communicating with 802.11b Mode

Г.	of EOT confinding with 802.11b wode								
	Chanel	Power	Cable Loss	Power	Limit	Over Limit			
	Frequency	Spectral	(dB)	Spectral	(dBm)	(dB)			
	(GHz)	Density		Density level		·			
	, ,	(dBm)		(dBm)					
		,		, ,					
	2.412	-17.68	0.5	-17.18	8.00	-25.18			
	2.437	-18.12	0.5	-17.62	8.00	-25.62			
	2.462	-17.87	0.5	-17.37	8.00	-25.37			

For EUT communicating with 802.11g Mode

Chanel	Power	Cable Loss	Power	Limit	Over Limit
Frequency	Spectral	(dB)	Spectral	(dBm)	(dB)
(GHz)	Density		Density level		
	(dBm)		(dBm)		
2.412	-22.56	0.5	-22.06	8.00	-30.06
2.437	-23.26	0.5	-22.76	8.00	-30.76
2.462	-24.06	0.5	-23.56	8.00	-31.56

Test result: The unit does meet the requirements.


Test result plot as follows:




Report No.: FCCIC11-RTE040602

Page: 53 of 58

The EUT communicating with 802.11b Mode Lowest channel=2412MHz



Middle channel=2437MHz




FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 54 of 58

Highest channel=2462MHz




FCC ID: SOVA101B2 IC ID: 5511A-A101B2




Report No.: FCCIC11-RTE040602

Page: 55 of 58

The EUT communicating with 802.11g Mode



Middle channel=2437MHz




FCC ID: SOVA101B2 IC ID: 5511A-A101B2



Report No.: FCCIC11-RTE040602

Page: 56 of 58

Highest channel=2462MHz





Report No.: FCCIC11-RTE040602

Page: 57 of 58

5.8 Antenna Requirement

EUT Antenna

Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is soldering on the PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



Report No.: FCCIC11-RTE040602

Page: 58 of 58

5.9 RF Exposure Compliance

Standard requirement

15.247(b)(4) requirement:

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section. if transmitting antennas of directional gain greater than 6 dBi are used. the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1). (b)(2). and (b)(3) of this section. as appropriate. by the amount in dB that the directional gain of the antenna exceeds 6 dBi. RSS-102 Section 2.5.1 requirement:

above 2.2 GHz and up to 3 GHz inclusively, and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 20 mW for general public use and 100 mW for controlled use;

EUT RF Exposure

The Max Conducted Peak Output Power is **11.80dBm(15.14mW)** in the Highest channel (2.462GHz); The best case gain of the antenna is 0dBi.

calculate the EIRP test result:

EIRP= 15.14mW ①

SAR requirement:

S=60 / f(GHz) = 60/2.462 = 24.37 mW ② ;

① < 20mW < ②.

So the SAR report is not required.