

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Archos 70CHT

MODEL No.: A70CHT

FCC ID: SOVA70CHT

REPORT NO: ES110210004F

ISSUE DATE: February 18, 2011

Prepared for

**ARCHOS SA
12Rue Ampere ZI 91430 Igny, France**

Prepared by

SHENZHEN EMTEK CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China
TEL: 86-755-26954280
FAX: 86-755-26954282**

VERIFICATION OF COMPLIANCE

Applicant:	ARCHOS SA 12Rue Ampere ZI 91430 Igny, France
Manufacturer:	ARCHOS SA 12Rue Ampere ZI 91430 Igny, France
Product Description:	Archos 70CHT
Brand Name:	N/A
Model Number:	A70CHT
Serial Number:	N/A
File Number:	ES110210004F
Date of Test:	February 11, 2011 to February 17, 2011


We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : February 11, 2011 to February 17, 2011

Prepared by :



(Engineer)

Reviewer :



(Quality Manager)

Approve & Authorized Signer :



(Manager)

Table of Contents

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION	5
1.2 RELATED SUBMITTAL(S) / GRANT(S).....	5
1.3 TEST METHODOLOGY	5
1.4 SPECIAL ACCESSORIES.....	6
1.5 EQUIPMENT MODIFICATIONS	6
1.6 TEST FACILITY	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION.....	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE.....	7
2.4 CONFIGURATION OF TESTED SYSTEM.....	7
3. DESCRIPTION OF TEST MODES	9
4. SUMMARY OF TEST RESULTS	10
5. CONDUCTED EMISSIONS TEST	11
5.1 MEASUREMENT PROCEDURE:	11
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	11
5.3 MEASUREMENT EQUIPMENT USED:	11
5.4 CONDUCTED EMISSION LIMIT	11
5.5 MEASUREMENT RESULT:	12
5.6 CONDUCTED MEASUREMENT PHOTOS:.....	13
6. RADIATED EMISSION TEST	14
6.1 MEASUREMENT PROCEDURE	14
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
6.3 MEASUREMENT EQUIPMENT USED:	15
6.4 RADIATED EMISSION LIMIT	15
6.5 MEASUREMENT RESULT	16
6.6 RADIATED MEASUREMENT PHOTOS:	28
7. OCCUPIED BANDWIDTH TEST.....	29
7.1 MEASUREMENT PROCEDURE	29
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	29
7.3 MEASUREMENT EQUIPMENT USED:	29
7.4 MEASUREMENT RESULTS:	29
8. MAXIMUM PEAK OUTPUT POWER TEST	34
8.1 MEASUREMENT PROCEDURE	34
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	34

8.3	MEASUREMENT EQUIPMENT USED:	34
8.4	PEAK POWER OUTPUT LIMIT	34
8.5	MEASUREMENT RESULTS:	34
9.	BAND EDGE TEST.....	36
9.1	MEASUREMENT PROCEDURE	36
9.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	36
9.3	MEASUREMENT EQUIPMENT USED:	36
9.4	MEASUREMENT RESULTS:	36
10.	POWER DENSITY.....	40
10.1	TEST EQUIPMENT	40
10.2	MEASURING INSTRUMENTS AND SETTING	40
10.3	TEST PROCEDURES.....	40
10.4	BLOCK DIAGRAM OF TEST SETUP.....	40
10.5	LIMIT	40
10.6	TEST RESULT.....	41
11.	ANTENNA PORT EMISSION.....	45
11.1	TEST EQUIPMENT	45
11.2	MEASURING INSTRUMENTS AND SETTING.....	45
11.3	TEST PROCEDURES.....	45
11.4	BLOCK DIAGRAM OF TEST SETUP	45
11.5	TEST RESULT.....	45
12.	ANTENNA APPLICATION.....	52
12.1	ANTENNA REQUIREMENT	52
12.2	RESULT.....	52

1. General Information

1.1 Product Description

A major technical descriptions of EUT is described as following:

- A). Standards: IEEE802.11b/g
- B). Operation Frequency: 2400-2483.5MHz
- C). Modulation: OFDM with BPSK, QPSK, 16QAM, 64QAM(11g), BPSK, QPSK, CCK (11b)
- D). Number of Channel: 11
- E). Max Data Rate: 11Mbps(802.11b), 54Mbps(802.11g)
- F). Conducted Power: 15.42dBm(802.11b), 13.43dBm(802.11g),
- G) PCB Gain: 0dBi
- H). Antenna Type: PCB Antenna
- I). Power Supply: DC 5V with AC Adapter and DC 3.7V from Li-ion Battery
- J). Adapter: Input: AC 100-240V, 50-60Hz, 0.4A
Output: DC 5V/2A

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Note:

1. This device is a 2.4GHz Archos 70CHT included 802.11b and 802.11g 2.4GHz transceiver function.
2. Test of channel was included the lowest middle and highest frequency in highest data rate and to perform the test, then record on this report.

1.2 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: SOVA70CHT filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules. The composite system (receiver) is compliance with Subpart B is authorized under a DOC procedure.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2009). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description

EMC Lab. : Accredited by CNAS, 2010.10.29
The certificate is valid until 2013.10.28
The Laboratory has been assessed and proved to be in compliance
with CNAS/CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291

Accredited by TUV Rheinland Shenzhen 2010.5.25
The Laboratory has been assessed according to the requirements
ISO/IEC 17025

Accredited by FCC, October 28, 2010
The Certificate Registration Number is 406365.

Accredited by Industry Canada, March 05, 2010
The Certificate Registration Number is 46405-4480.

Name of Firm : SHENZHEN EMTEK CO., LTD.
Site Location : Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	Archos 70CHT	N/A	A70CHT	SOVA70CHT	N/A	EUT
2.	Laptop computer	ACER	20020	FCC DOC	EB16076441	
3.	PC	Lenovo	ThinkCentre 8701	FCC DOC	701A53L3BC108	

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The Transmitter of EUT is a Archos 70CHT and powered by host equipment. This is Digital Transmission system(DTS) and have four type of modulation DBPSK DQPSK CCK&OFDM. The data rates are 54Mbps.

The equipment enables high-speed access without wires to network assets. This adapter uses the IEEE 802.11b/g protocol to enable wireless communications between the host Archos 70CHT and Wireless router, in the same way that the Archos 70CHT would use an Ethernet adapter.

1. For lowest channel : 2412MHz (Channel 1)
2. For middle channel : 2437MHz (Channel 6)
3. For highest channel: 2462MHz (Channel 11)

EUT operating conditions:

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to typical use, The exercise sequence is listed as below:

1. Setup the EUT and simulators as shown on 2.4.
2. Turn on the power of all equipments.
3. The EUT Ping with the wireless router.
4. Repeat the above steps.

4. Summary of Test Results


FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Compliant
§15.247(b)(3)	Max Peak output Power test	Compliant
§15.247(e)	Power density	Compliant
§15.247(d)	Band edge test	Compliant
§15.207	AC Power Conducted Emission	Compliant
§15.247(d), §15.209	Radiated Emission	Compliant
§15.203	Antenna Port Emission	Compliant
§15.109	Antenna Application	Compliant

5. Conducted Emissions Test

5.1 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used:

Conducted Emission Test Site # 4					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2010	05/29/2011
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/29/2010	05/29/2011
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/29/2010	05/29/2011
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/29/2010	05/29/2011
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/29/2010	05/29/2011

5.4 Conducted Emission Limit

Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

- Note:**
1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.5 Measurement Result:

Date of Test:	February 14, 2011	Temperature:	22
Frequency Detector:	0.15~30MHz	Humidity:	50%
Test Result:	PASS	Test Mode:	WIFI Mode

Test Line	Frequency MHz	Emission Level QP dB(μV)	Emission Level AV dB(μV)	Limits QP dB(μV)	Limits AV dB(μV)	Over QP dB(μV)	Over AV dB(μV)
Neutral	0.196	52.51	39.52	63.82	53.64	-11.31	-14.12
	0.822	48.27	32.74	56	46	-7.73	-13.26
	1.312	47.67	30.06	56	46	-8.33	-15.94
	1.851	47.05	30.17	56	46	-8.95	-15.83
	2.373	46.25	29.67	56	46	-9.75	-16.33
	16.12	53.06	38.85	56	46	-2.94	-7.15
Line	0.192	51.24	40.23	64.02	54.03	-12.78	-13.8
	0.287	45.16	35.54	60.54	50.55	-15.38	-15.01
	0.792	43.34	27.34	56	46	-12.66	-18.66
	1.316	43.29	24.46	56	46	-12.71	-21.54
	1.913	42.23	24.43	56	46	-13.77	-21.57
	16.52	54.75	41.32	60	50	-5.25	-8.68

5.6 Conducted Measurement Photos:




6. Radiated Emission Test

6.1 Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



6.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Pre-Amplifier	HP	8447D	2944A07999	05/29/2010	05/29/2011
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2010	05/29/2011
Loop Antenna	ARA	PLA-1030/B	1029	05/29/2010	05/29/2011
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/29/2010	05/29/2011
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/29/2010	05/29/2011
Cable	Schwarzbeck	AK9513	ACRX1	05/29/2010	05/29/2011
Cable	Rosenberger	N/A	FP2RX2	05/29/2010	05/29/2011
Cable	Schwarzbeck	AK9513	CRPX1	05/29/2010	05/29/2011
Cable	Schwarzbeck	AK9513	CRRX2	05/29/2010	05/29/2011
Pre-Amplifier	HP	8447D	2944A07999	05/29/2010	05/29/2011

6.4 Radiated Emission Limit

FCC Class B Limit at 3m:

Frequency MHz	Distance Meter	Field Strength uV/m	Field Strength dBuV/m
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
Above 960	3	500	54.0

Note: The frequencies above 1000MHz, as measured using instrumentation with a peak detector function was corresponding to 20dB above maximum permitted average limit.

6.5 Measurement Result

Operation Mode: 802.11b TX Channel 1 Test Date : February 14, 2011
Frequency Range: 30~1000MHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
143.11	V	22.43	43.5	-21.07	PK
207.81	V	28.27	43.5	-15.23	PK
349.65	V	26.38	46	-19.62	PK
393.49	V	33.33	46	-12.67	PK
446.74	V	30.25	46	-15.75	PK
665.26	V	36.88	46	-9.12	PK
195.84	H	28.91	43.5	-14.59	PK
204.48	H	33.14	43.5	-10.36	PK
212.51	H	28.19	43.5	-15.31	PK
371.93	H	32.61	46	-13.39	PK
392.02	H	35.58	46	-10.42	PK
442.23	H	35.23	46	-10.77	PK

Note: (1) All Readings are Peak Value.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11b TX Channel 6 Test Date : February 14, 2011
Frequency Range: 30~1000MHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
143.32	V	23.11	43.5	-20.39	PK
208.21	V	27.34	43.5	-16.16	PK
349.44	V	27.12	46	-18.88	PK
392.83	V	31.43	46	-14.57	PK
442.93	V	28.39	46	-17.61	PK
665.31	V	28.42	46	-17.58	PK
191.55	H	28.35	43.5	-15.15	PK
208.19	H	33.54	43.5	-9.96	PK
212.89	H	28.77	43.5	-14.73	PK
373.04	H	32.27	46	-13.73	PK
392.42	H	34.62	46	-11.38	PK
442.86	H	32.12	46	-13.88	PK

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11b TX Channel 11 Test Date : February 14, 2011
Frequency Range: 30~1000MHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
143.87	V	22.21	43.5	-21.29	PK
207.26	V	26.32	43.5	-17.18	PK
348.16	V	26.22	46	-19.78	PK
390.93	V	28.92	46	-17.08	PK
441.91	V	25.23	46	-20.77	PK
661.08	V	26.56	46	-19.44	PK
191.22	H	28.12	43.5	-15.38	PK
207.85	H	32.41	43.5	-11.09	PK
214.77	H	30.02	43.5	-13.48	PK
371.93	H	32.92	46	-13.08	PK
390.92	H	35.49	46	-10.51	PK
441.23	H	33.13	46	-12.87	PK

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g TX Channel 1 Test Date : February 14, 2011
Frequency Range: 30~1000MHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
191.27	V	24.22	43.5	-19.28	PK
207.01	V	26.97	43.5	-16.53	PK
390.56	V	28.08	46	-17.92	PK
441.96	V	26.85	46	-19.15	PK
598.82	V	26.57	46	-19.43	PK
661.61	V	27.22	46	-18.78	PK
168.28	H	30.31	43.5	-13.19	PK
207.09	H	29.47	43.5	-14.03	PK
371.77	H	32.61	43.5	-10.89	PK
390.95	H	35.39	46	-10.61	PK
415.88	H	33.98	46	-12.02	PK
441.65	H	32.14	46	-13.86	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g TX Channel 6 Test Date : February 14, 2011
Frequency Range: 30~1000MHz Temperature : 28
Test Result: PASS Humidity : 65%
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
191.31	V	23.12	43.5	-20.38	PK
207.27	V	27.45	43.5	-16.05	PK
391.14	V	28.93	46	-17.07	PK
441.56	V	27.54	46	-18.46	PK
598.83	V	25.91	46	-20.09	PK
661.44	V	26.67	46	-19.33	PK
169.28	H	29.02	43.5	-14.48	PK
208.26	H	29.27	43.5	-14.23	PK
372.88	H	32.41	43.5	-11.09	PK
390.72	H	35.34	46	-10.66	PK
415.14	H	32.55	46	-13.45	PK
440.19	H	33.35	46	-12.65	PK

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g TX Channel 11 Test Date : February 14, 2011
Frequency Range: 30~1000MHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
190.16	V	24.12	43.5	-19.38	PK
208.32	V	27.27	43.5	-16.23	PK
391.11	V	29.19	46	-16.81	PK
440.27	V	27.49	46	-18.51	PK
598.91	V	26.31	46	-19.69	PK
662.04	V	27.24	46	-18.76	PK
169.28	H	30.66	43.5	-12.84	PK
209.92	H	30.82	43.5	-12.68	PK
372.66	H	32.55	43.5	-10.95	PK
390.82	H	35.37	46	-10.63	PK
415.92	H	33.88	46	-12.12	PK
441.62	H	33.68	46	-12.32	PK

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11b TX Channel 1 Test Date : February 14, 2011
Frequency Range: Above 1GHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
5192.09	V	57.02	48.88	74	54	-16.98	-5.12
9514.23	V	57.12	46.45	74	54	-16.88	-7.55
9834.64	V	56.02	46.34	74	54	-17.98	-7.66
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5213.48	H	58.39	48.55	74	54	-15.61	-5.45
9887.92	H	54.39	45.51	74	54	-19.61	-8.49
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11b TX (Channel 6) Test Date : February 14, 2011
Frequency Range: Above 1GHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
9863.39	V	56.44	45.16	74	54	-17.56	-8.84
10911.23	V	53.52	43.02	74	54	-20.48	-10.98
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5189.11	H	57.17	48.62	74	54	-16.83	-5.38
5558.78	H	57.27	48.49	74	54	-16.73	-5.51
9657.66	H	53.16	45.65	74	54	-20.84	-8.35
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11b TX (Channel 11) Test Date : February 14, 2011
Frequency Range: Above 1GHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
5230.36	V	60.66	49.11	74	54	-13.34	-4.89
7269.46	V	57.54	47.23	74	54	-16.46	-6.77
8692.89	V	56.57	47.62	74	54	-17.43	-6.38
9942.68	V	53.96	44.71	74	54	-20.04	-9.29
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
7826.36	H	57.31	46.67	74	54	-16.69	-7.33
10019.21	H	57.02	44.92	74	54	-16.98	-9.08
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11g TX Channel 1 Test Date : February 14, 2011
Frequency Range: Above 1GHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
5225.13	V	58.28	48.34	74	54	-15.72	-5.66
9855.65	V	55.45	44.38	74	54	-18.55	-9.62
10794.67	V	55.93	43.22	74	54	-18.07	-10.78
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5172.33	H	59.14	49.31	74	54	-14.86	-4.69
7167.43	H	54.15	47.54	74	54	-19.85	-6.46
9964.54	H	53.24	44.46	74	54	-20.76	-9.54
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11g TX (Channel 6) Test Date : February 14, 2011
Frequency Range: Above 1GHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
5230.04	V	56.21	48.27	74	54	-17.79	-5.73
9855.55	V	56.65	47.13	74	54	-17.35	-6.87
10797.8	V	52.65	44.23	74	54	-21.35	-9.77
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
5168.16	H	59.11	48.39	74	54	-14.89	-5.61
7168.33	H	57.23	47.35	74	54	-16.77	-6.65
9966.87	H	54.27	43.25	74	54	-19.73	-10.75
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Operation Mode: 802.11g TX (Channel 11) Test Date : February 14, 2011
Frequency Range: Above 1GHz Temperature : 28
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
9801.42	V	52.12	41.24	74	54	-21.88	-12.76
10852.23	V	54.43	41.76	74	54	-19.57	-12.24
11702.22	V	56.45	42.67	74	54	-17.55	-11.33
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
7703.44	H	49.13	39.33	74	54	-24.87	-14.67
9781.64	H	52.34	41.36	74	54	-21.66	-12.64
11266.27	H	51.97	41.74	74	54	-22.03	-12.26
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

6.6 Radiated Measurement Photos:




7. Occupied Bandwidth Test

7.1 Measurement Procedure

The EUT was operating in IEEE 802.11b/g mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used:

Same as 4.3 Radiated Emission Measurement.


7.4 Measurement Results:

7.4.1 6 Bandwidth Test Data Chart:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	February 14, 2011
Test By:	Andy	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Operation Mode:	802.11b		


Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	9.75	>500
6	2437	9.37	>500
11	2462	9.25	>500







Spectrum Detector: PK Test Date : February 14, 2011
Test By: Andy Temperature : 28
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11 g

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	15.75	>500
6	2437	15.88	>500
11	2462	15.63	>500






8. Maximum Peak Output Power Test

8.1 Measurement Procedure

- The Transmitter output (antenna port) was connected to the power meter.
- Turn on the EUT and power meter and then record the peak power value.
- Repeat above procedures on all channels needed to be tested.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	Boonton	4232A	29001	05/29/2010	05/29/2011
Power sensor	Boonton	51011-EMC	31184	05/29/2010	05/29/2011

8.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

8.5 Measurement Results:

Spectrum Detector: PK Test Date : February 14, 2011
Test By: Andy Temperature : 28
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11b

Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Average Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	15.42	11.57	1W(30dBm)	PASS
6	2437.00	15.35	11.51	1W(30dBm)	PASS
11	2462.00	15.28	11.46	1W(30dBm)	PASS

Spectrum Detector: PK Test Date : February 14, 2011
Test By: Andy Temperature : 28
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11g


Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Average Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	13.33	10.00	1W(30dBm)	PASS
6	2437.00	13.43	10.07	1W(30dBm)	PASS
11	2462.00	13.35	10.01	1W(30dBm)	PASS

9. Band Edge Test

9.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used:

Same as 4.3 Radiated Emission Measurement.

9.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector: PK Test Date : February 14, 2011
Test By: Andy Temperature : 28
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11b

1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission Read Value(dBm)	Result of Band Edge(dBc)	Band Edge Limit(dBc)
<2400	-8.68	-54.93	46.25	>20dBc
>2483.5	-7.39	-67.12	59.73	>20dBc

2. Radiated Emission Test

Frequency (MHz)	Antenna Polarization (H/V)	Emission (dBuV/m)		Band Edge Limit (dBuV/m)	
		PK	AV	PK	AV
<2400	H	55.76	44.75	74.00	54.00
>2483.5	H	54.23	41.04	74.00	54.00






Spectrum Detector:	PK	Test Date :	February 14, 2011
Test By:	Andy	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Operation Mode: 802.11g			

1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission Read Value(dBm)	Result of Band Edge(dBc)	Band Edge Limit(dBc)
<2400	-22.55	-56.25	33.7	>20dBc
>2483.5	-21.57	-68.66	47.09	>20dBc

2. Radiated emission test

Frequency (MHz)	Antenna Polarization (H/V)	Emission (dBuV/m)		Band Edge Limit (dBuV/m)	
		PK	AV	PK	AV
<2400	H	53.15	42.36	74.00	54.00
>2483.5	H	52.65	42.64	74.00	54.00



10. Power Density

10.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	HP	8594E	88156318	05/29/2010	05/29/2011

10.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	300kHz
RB	3kHz
VB	30kHz
Detector	Peak
Trace	Max hold
Sweep Time	100s

10.3 Test Procedures

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz, Set Detector to Peak, Trace to Max Hold.
- Mark the frequency with maximum peak power as the center of the display of the spectrum.
- Set the span to 300kHz and the sweep time to 100s and record the maximum peak value.

10.4 Block Diagram of Test Setup




10.5 Limit

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

10.6 Test Result

Spectrum Detector:	PK	Test Date :	February 14, 2011
Test By:	Andy	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Operation Mode: 802.11 b			


Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2411.00	-15.25	<8dBm	PASS
2437.00	-13.34	<8dBm	PASS
2461.00	-13.79	<8dBm	PASS







Spectrum Detector: PK Test Date : February 14, 2011
Test By: Andy Temperature : 28
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11 g

Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2410.00	-25.18	<8dBm	PASS
2431.00	-23.86	<8dBm	PASS
2456.00	-23.14	<8dBm	PASS





11. Antenna Port Emission

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/29/2010	05/29/2011

11.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

11.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, mid, and hi channels, The limit was determined by attenuation 20dB of the RF peak power output.


11.4 Block Diagram of Test setup




11.5 Test Result

PASS.



802.11b Low Channel 1



802.11b Mid Channel 6





802.11b Hi Channel 11





802.11g Low Channel 1



802.11g Mid Channel 6



802.11b Hi Channel 11



12. Antenna Application

12.1 Antenna Requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203.

12.2 Result

The EUT'S antenna is Chip antenna on PCB. The antenna's gain is 0dBi and meets the requirement.