



## RF Exposure Evaluation

### Requirements:

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a portable device.

### Measurement Records:

802.11b mode			
Antenna Gain (dBi)	Antenna Gain (numeric)	Conducted Power (dBm)	Conducted Power (mW)
2.0	1.585	7.650	5.821
2.0	1.585	7.460	5.572
2.0	1.585	7.400	5.495

802.11g mode			
Antenna Gain (dBi)	Antenna Gain (numeric)	Conducted Power (dBm)	Conducted Power (mW)
2.0	1.585	6.430	4.395
2.0	1.585	6.430	4.395
2.0	1.585	6.380	4.345

802.11n(H20) mode			
Antenna Gain (dBi)	Antenna Gain (numeric)	Conducted Power (dBm)	Conducted Power (mW)
2.0	1.585	6.900	4.898
2.0	1.585	6.440	4.406
2.0	1.585	6.360	4.325

802.11n(H40) mode			
Antenna Gain (dBi)	Antenna Gain (numeric)	Conducted Power (dBm)	Conducted Power (mW)
2.0	1.585	6.260	4.227
2.0	1.585	6.270	4.236
2.0	1.585	6.410	4.375

The EUT works on the 2.4G ISM band, according to KDB 447498 D01 General RF Exposure Guidance v05, the SAR Test Exclusion Power Thresholds is 10mW. The max power of this device is 5.821mW < 10mW, so The SAR evaluation is not required.