

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	
Date / Time:	12/08/2006 8:39:04 AM	DUT Battery Model/No:	
Filename:	temp.txt	Probe Serial Number:	L0016
Ambient Temperature:	22.8°C	Liquid Simulant:	1900
Device Under Test:	Toshiba	Relative Permittivity:	52.75
Relative Humidity:	30%	Conductivity:	1.55
Phantom S/No:	HeadBox1.csv	Liquid Temperature:	22.0°C
Phantom Rotation:	0°	Max SAR X-axis Location:	-20.00 mm
DUT Position:	front 1.5 cm	Max SAR Y-axis Location:	1.00 mm
Antenna Configuration:	integral	Max E Field:	3.98 V/m
Test Frequency:	1880MHz	SAR 1g:	0.136 W/kg
Air Factors:	488 / 373 / 340	SAR 10g:	0.062 W/kg
Conversion Factors:	.630 / .630 / .630	SAR Start:	0.003 W/kg
Type of Modulation:		SAR End:	0.003 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	3.42 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	12/07/2006
Input Power Level:	max 2 timeslots	Extrapolation:	poly4

