

Appendix A: FCC Part 1.1307, 1.1310, 2.1091, 2.1093; IC RSS-Gen: RF Exposure

According to KDB 447498 D01 General RF Exposure Guidance v05 4.3.1. Standalone SAR test exclusion considerations, unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before the calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

EUT RF Exposure

The max conducted output power is 38.9 mW at 903.185 MHz

The gain of the antenna is 1 numeric

Worst-case duty cycle of transmission is 0.0167%

Therefore source-base time averaged power is $38.9 \text{ mW} \times 0.00167 = 0.006 \text{ mW}$

EIRP = $0.006 \text{ mW} \times 1 = 0.006 \text{ mW}$ (rounding to the nearest mW = 1 mW)

General RF Exposure = $(1 \text{ mW} / 5 \text{ mm}) \times \sqrt{0.903 \text{ GHz}} = 0.2$

Therefore, SAR testing is not required since the result is below the ≤ 3.0 1-g SAR limit.