



# FCC RF Test Report

**APPLICANT** : iMozen Group INC.  
**EQUIPMENT** : Handheld mobile computer  
**BRAND NAME** : iMozen Group INC.  
**MODEL NAME** : TC605AN  
**FCC ID** : SPYTC605AN  
**STANDARD** : 47 CFR Part 2, 96  
**CLASSIFICATION** : Citizens Band End User Devices (CBE)  
**EQUIPMENT TYPE** : End User Equipment  
**TEST DATE(S)** : Nov. 19, 2023 ~ Dec. 18, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



**Sportun International Inc. (Kunshan)**  
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Maximum EIRP Power and Emission Designator .....	6
1.5 Testing Site.....	7
1.6 Test Software .....	7
1.7 Applied Standards .....	7
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>8</b>
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System .....	9
2.3 Support Unit used in test configuration .....	9
2.4 Measurement Results Explanation Example .....	9
2.5 Frequency List of Low/Middle/High Channels.....	10
<b>3 Conducted Test Items.....</b>	<b>11</b>
3.1 Measuring Instruments.....	11
3.2 Test Setup .....	11
3.3 Conducted Output Power .....	12
3.4 Peak-to-Average Ratio .....	13
3.5 EIRP .....	14
3.6 Occupied Bandwidth .....	15
3.7 Conducted Band Edge .....	16
3.8 Conducted Spurious Emission .....	17
3.9 Frequency Stability.....	18
<b>4 Radiated Test Items .....</b>	<b>19</b>
4.1 Measuring Instruments.....	19
4.2 Test Setup .....	19
4.3 Test Result of Radiated Test.....	20
4.4 Radiated Spurious Emission .....	21
<b>5 List of Measuring Equipment.....</b>	<b>22</b>
<b>6 Measurement Uncertainty .....</b>	<b>23</b>

### Appendix A. Test Results of Conducted Test

### Appendix B. Test Results of Radiated Test

### Appendix C. Test Setup Photographs



## History of this test report



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.3	§2.1046	Conducted Output Power	Reporting only	-
3.4	§96.41	Peak-to-Average Ratio	Not Applicable	Not applicable for End User Devices
3.5	§96.41	Maximum E.I.R.P	Pass	-
		Maximum Power Spectral Density	Not Applicable	Not applicable for End User Devices
3.6	§2.1049 §96.41	Occupied Bandwidth	Reporting only	-
3.7	§2.1051 §96.41	Conducted Band Edge Measurement Adjacent Channel Leakage Ratio	Pass	-
3.8	§2.1051 §96.41	Conducted Spurious Emission	Pass	
3.9	§2.1055	Frequency Stability for Temperature & Voltage	Pass	-
4.4	§2.1051 §96.41	Radiated Spurious Emission	Pass	Under limit 6.19 dB at 7236.000 MHz

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



## 1 General Description

### 1.1 Applicant

iMozen Group INC.

6 F., No. 288, Sec. 6, Civic Blvd., Xinyi Dist., Taipei City 110417, Taiwan (R.O.C.)

### 1.2 Manufacturer

iMozen Group INC.

6 F., No. 288, Sec. 6, Civic Blvd., Xinyi Dist., Taipei City 110417, Taiwan (R.O.C.)

### 1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Handheld mobile computer
Brand Name	iMozen Group INC.
Model Name	TC605AN
FCC ID	SPYTC605AN
Tx Frequency	LTE Band 42 : 3550 MHz ~ 3600 MHz LTE Band 43 : 3600 MHz ~ 3700 MHz LTE Band 48: 3550 MHz ~ 3700 MHz
Rx Frequency	LTE Band 42 : 3550 MHz ~ 3600 MHz LTE Band 43 : 3600 MHz ~ 3700 MHz LTE Band 48: 3550 MHz ~ 3700 MHz
Bandwidth	5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 42: 23.34 dBm LTE Band 43: 23.45 dBm LTE Band 48: 23.49 dBm
Antenna Gain	LTE Band 42: -2.23 dBi LTE Band 43: -2.23 dBi LTE Band 48: -2.23 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM
IMEI Code	Conducted: 352149450707620 Radiation: 352149450708743/352149450708750 for Sample 1 352149450712141/352149450712158 for Sample 2
HW Version	V4
SW Version	ST6919A_20231220121856
EUT Stage	Identical Prototype

#### Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are three configs of samples, the differences could be referred to the TC605A\_Operational Description of Product Equality Declaration which is exhibit separately. According to the difference, sample 1 full test and the sample 2 verify the worst case RSE for the difference, sample 3 no need additional test.
3. LTE Band 48 overlaps the entire frequency range of LTE Band 42/43, the test results of LTE Band 48 also cover LTE Band 42/43.



## 1.4 Maximum EIRP Power and Emission Designator

LTE Band 42		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	3552.5~3597.5	0.1250	4M52G7D	0.0995	4M48W7D
10	3555.0~3595.0	0.1259	9M07G7D	0.0995	9M05W7D
15	3557.5~3592.5	0.1271	13M6G7D	0.0995	13M5W7D
20	3560.0~3590.0	0.1291	17M9G7D	0.1028	18M0W7D
LTE Band 43		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	3602.5~3697.5	0.1312	4M52G7D	0.1045	4M48W7D
10	3605.0~3695.0	0.1300	9M07G7D	0.1040	9M05W7D
15	3607.5~3692.5	0.1297	13M6G7D	0.1042	13M5W7D
20	3610.0~3690.0	0.1324	17M9G7D	0.1057	18M0W7D
LTE Band 48		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	3552.5~3697.5	0.1297	4M52G7D	0.1038	4M48W7D
10	3555.0~3695.0	0.1300	9M07G7D	0.1042	9M05W7D
15	3557.5~3692.5	0.1306	13M6G7D	0.1030	13M5W7D
20	3560.0~3690.0	0.1337	17M9G7D	0.1069	18M0W7D

Note:

1. LTE Band 48 overlaps the entire frequency range of LTE Band 42/43 under Part 96 rule. Therefore, the test results provided in this report covers Band 48 as well as Band 42/43.
2. All modulations have been tested, only the worst test results of PSK & QAM are shown in the report.



## 1.5 Testing Site

Sportun International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sportun International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
<b>Test Site No.</b>	<b>Sportun Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	03CH04-KS TH01-KS	CN1257	314309

## 1.6 Test Software

Item	Site	Manufacture	Name	Version
1.	TH01-KS	SPORTON	FCC LTE_Ver2.0 Auto_china_210503	2.0
2.	03CH04-KS	AUDIX	E3	210616

## 1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ 47 CFR Part 2, 96
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 940660 D01 Part 96 CBRS v03
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test


### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

Test Items	Band	Bandwidth (MHz)						Modulation					RB #		Test Channel			
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H	
Max. Output Power	42	-	-	v	v	v	v	v	v	v	v	v	v		v	v	v	
	43	-	-	v	v	v	v	v	v	v	v	v	v		v	v	v	
	48	-	-	v	v	v	v	v	v	v	v	v	v		v	v	v	
Adjacent Channel Leakage Ratio	48	-	-	v	v	v	v	v	v	v	v	v	v		v	v	v	
26dB and 99% Bandwidth	48	-	-	v	v	v	v	v	v	v					v			
Conducted Band Edge	48	-	-	v	v	v	v	v	v	v	v	v	v		v	v	v	
Conducted Spurious Emission	48	-	-	v	v	v	v	v					v		v	v	v	
E.I.R.P.	42	-	-	v	v	v	v	v	v	v	v	v	v		v	v	v	
	43	-	-	v	v	v	v	v	v	v	v	v	v		v	v	v	
	48	-	-	v	v	v	v	v	v	v	v	v	v		v	v	v	
Frequency Stability	48	-	-		v			v					v				v	
Radiated Spurious Emission	48	Worst Case													v			
Note		<ol style="list-style-type: none"><li>The mark "v" means that this configuration is chosen for testing</li><li>The mark "-" means that this bandwidth is not supported.</li><li>The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.</li><li>LTE Band 48 overlaps the entire frequency range of LTE Band 42/43 under Part 96 rule. Therefore, the test results provided in this report covers Band 48 as well as Band 42/43</li></ol>																

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820/8821	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 6.3 dB.

Example :

*Offset(dB) = RF cable loss(dB).*

= 6.3 (dB)



## 2.5 Frequency List of Low/Middle/High Channels

LTE Band 48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	55340	55990	56640
	Frequency	3560.0	3625.0	3690.0
15	Channel	55315	55990	56665
	Frequency	3557.5	3625.0	3692.5
10	Channel	55290	55990	56690
	Frequency	3555.0	3625.0	3695.0
5	Channel	55265	55990	56715
	Frequency	3552.5	3625.0	3697.5

LTE Band 42 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	43190	43340	43490
	Frequency	3560	3575	3590
15	Channel	43165	43340	43515
	Frequency	3557.5	3575	3592.5
10	Channel	43140	43340	43540
	Frequency	3555	3575	3595
5	Channel	43115	43340	43565
	Frequency	3552.5	3575	3597.5

LTE Band 43 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	43690	44090	44490
	Frequency	3610	3650	3690
15	Channel	43665	44090	44515
	Frequency	3607.5	3650	3692.5
10	Channel	43640	44090	44540
	Frequency	3605	3650	3695
5	Channel	43615	44090	44565
	Frequency	3602.5	3650	3697.5


### 3 Conducted Test Items

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power / ACLR



##### 3.2.2 26dB & 99% Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



##### 3.2.4 Test Result of Conducted Test

Please refer to Appendix A.



### 3.3 Conducted Output Power

#### 3.3.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

#### 3.3.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



## 3.4 Peak-to-Average Ratio

### 3.4.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio



## 3.5 EIRP

### 3.5.1 Description of the EIRP Measurement

EIRP limits for CBRS equipment as below table:

Device		Maximum EIRP (dBm/10 MHz)	Maximum PSD (dBm/MHz)
Applied	End User Device	23	n/a
<input type="checkbox"/>	Category A CBSD	30	20
<input type="checkbox"/>	Category B CBSD	47	37

**Remark:** The worst case EIRP shown in this section is found with LTE operating only using 1RB. As such, the EIRP/10MHz and full channel EIRP values will be identical since 1RB is fully contained within all available channel bandwidths for LTE Band 48 (i.e. 5, 10, 15, 20MHz)

### 3.5.2 Test Procedures for EIRP

1. Establishing a communications link with the call box (Base station) to measure the Maximum conducted power, the parameters were set to force the EUT transmitting at maximum output power level. Use the average power measurement function to measure total channel power of each channel bandwidth (per ANSI C63.26-2015 Section 5.2.1)
2. Determining ERP and/or EIRP from conducted RF output power measurements (Per ANSI C63.26-2015 Section 5.2.5.5)

$$\text{EIRP} = P_T + G_T - L_C, \text{ERP} = \text{EIRP} - 2.15, \text{where}$$

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB



## 3.6 Occupied Bandwidth

### 3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.6.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## 3.7 Conducted Band Edge

### 3.7.1 Description of Conducted Band Edge Measurement

#### Part 96.41 (e) (1) (ii)

For End User Devices the emission limits outside the fundamental are as follows:

Within 0 MHz to B MHz above and below the assigned channel  $\leq -13$  dBm/MHz

Greater than B MHz above and below the assigned channel  $\leq -25$  dBm/MHz

where B is the bandwidth in megahertz of the assigned channel or multiple contiguous channels of the End User Device.

Notwithstanding the emission limits in this paragraph, the Adjacent Channel Leakage Ratio for End User Devices shall be at least 30 dB.

#### Part 96.41 (e) (2)

For CBSDs and End User Devices, the conducted power of emissions below 3540 MHz or above 3710 MHz shall not exceed  $-25$  dBm/MHz, and the conducted power of emissions below 3530 MHz or above 3720 MHz shall not exceed  $-40$  dBm/MHz

### 3.7.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW  $\geq 1\%$  EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used
5. Offset has included the duty factor for LTE Band 48. Duty factor  $=10 \log (1/x)$ , where x is the measured duty cycle.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.



## 3.8 Conducted Spurious Emission

### 3.8.1 Description of Conducted Spurious Emission Measurement

96.41 (e)(2)

The conducted power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.

### 3.8.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is -40dBm/MHz.



## 3.9 Frequency Stability

### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

### 3.9.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.9.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at  $25\pm5^{\circ}\text{C}$  and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup


#### 4.2.1 For radiated test below 30MHz



#### 4.2.2 For radiated test from 30MHz to 1GHz



#### 4.2.3 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



## 4.4 Radiated Spurious Emission

### 4.4.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI C63.26-2015.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least -40dBm / MHz.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.4.2 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.  
EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain  
ERP (dBm) = EIRP - 2.15
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.  
The limit line is -40dBm/MHz



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Nov. 19, 2023~Nov. 27, 2023	Oct. 10, 2024	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Nov. 19, 2023~Nov. 27, 2023	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 06, 2023	Nov. 19, 2023~Nov. 27, 2023	Jul. 05, 2024	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471079	10Hz-44G,MAX 30dB	Oct. 10, 2023	Dec. 18, 2023	Oct. 09, 2024	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 11 2023	Dec. 18, 2023	Sep. 10, 2024	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Apr. 09, 2023	Dec. 18, 2023	Apr. 08, 2024	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1284	1GHz~18GHz	Oct. 10, 2023	Dec. 18, 2023	Oct. 09, 2024	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 08, 2023	Dec. 18, 2023	Jan. 07, 2024	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380827	9KHz-1GHz	Jul. 06, 2023	Dec. 18, 2023	Jul. 05, 2024	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 05, 2023	Dec. 18, 2023	Jan. 04, 2024	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz-18Ghz	Oct. 10, 2023	Dec. 18, 2023	Oct. 09, 2024	Radiation (03CH04-KS)
Amplifier	Agilent	8449B	3008A02370	1Ghz-18Ghz	Oct. 10, 2023	Dec. 18, 2023	Oct. 09, 2024	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Dec. 18, 2023	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Dec. 18, 2023	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Dec. 18, 2023	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required



## 6 Measurement Uncertainty

### Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Conducted Power Density	±0.88 dB
Peak to Average Ratio	±0.46 dB
Frequency Stability	±0.4 Hz

### Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{c(y)}$ )	3.82dB
--	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{c(y)}$ )	3.56dB
--	--------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{c(y)}$ )	3.54dB
--	--------

----- THE END -----



## Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%

### Conducted Output Power(Average power) and EIRP

#### LTE Band 42:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				43190	43340	43490			
Frequency (MHz)				3560	3575	3590	L	M	H
20	QPSK	1	0	23.19	23.34	23.14	0.1247	0.1291	0.1233
20	QPSK	1	99	23.21	23.27	23.09	0.1253	0.1271	0.1219
20	QPSK	100	0	22.26	22.30	22.15	0.1007	0.1016	0.0982
20	16QAM	1	0	22.24	22.35	22.19	0.1002	0.1028	0.0991
20	64QAM	1	0	21.27	21.32	21.12	0.0802	0.0811	0.0774
20	256QAM	1	0	18.23	18.25	18.15	0.0398	0.0400	0.0391
Channel				43165	43340	43515	EIRP(W)		
Frequency (MHz)				3557.5	3575	3592.5	L	M	H
15	QPSK	1	0	23.13	23.27	23.08	0.1230	0.1271	0.1216
15	16QAM	1	0	22.11	22.21	22.15	0.0973	0.0995	0.0982
Channel				43140	43340	43540	EIRP(W)		
Frequency (MHz)				3555	3575	3595	L	M	H
10	QPSK	1	0	23.06	23.23	23.03	0.1211	0.1259	0.1202
10	16QAM	1	0	22.10	22.21	22.05	0.0971	0.0995	0.0959
Channel				43115	43340	43565	EIRP(W)		
Frequency (MHz)				3552.5	3575	3597.5	L	M	H
5	QPSK	1	0	23.09	23.20	23.10	0.1219	0.1250	0.1222
5	16QAM	1	0	22.14	22.21	22.04	0.0979	0.0995	0.0957






## LTE Band 43:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
							L	M	H
20	QPSK	1	0	23.24	23.45	23.34	0.1262	0.1324	0.1291
20	QPSK	1	99	23.11	23.20	23.32	0.1225	0.1250	0.1285
20	QPSK	100	0	22.37	22.51	22.43	0.1033	0.1067	0.1047
20	16QAM	1	0	22.47	22.40	22.24	0.1057	0.1040	0.1002
20	64QAM	1	0	21.33	21.39	21.38	0.0813	0.0824	0.0822
20	256QAM	1	0	18.11	18.14	18.26	0.0387	0.0390	0.0401
Channel				43690	44090	44490	EIRP(W)		
Frequency (MHz)				3610	3650	3690	L	M	H
15	QPSK	1	0	23.12	23.36	23.29	0.1227	0.1297	0.1276
15	16QAM	1	0	22.41	22.30	22.18	0.1042	0.1016	0.0989
Channel				43665	44090	44515	EIRP(W)		
Frequency (MHz)				3607.5	3650	3692.5	L	M	H
10	QPSK	1	0	23.16	23.37	23.20	0.1239	0.1300	0.1250
10	16QAM	1	0	22.40	22.33	22.11	0.1040	0.1023	0.0973
Channel				43640	44090	44540	EIRP(W)		
Frequency (MHz)				3605	3650	3695	L	M	H
5	QPSK	1	0	23.13	23.41	23.20	0.1230	0.1312	0.1250
5	16QAM	1	0	22.42	22.37	22.11	0.1045	0.1033	0.0973



## LTE Band 48:

BW [MHz]	Modulation	RB Size	RB Offset	Power	Power	Power	EIRP(W)		
				Low Ch. / Freq.	Middle Ch. / Freq.	High Ch. / Freq.			
		Channel		55340	55990	56640			
		Frequency (MHz)		3560	3625	3690	L	M	H
20	QPSK	1	0	23.30	23.49	23.39	0.1279	0.1337	0.1306
20	QPSK	1	99	23.26	23.29	23.25	0.1268	0.1276	0.1265
20	QPSK	100	0	22.40	22.59	22.34	0.1040	0.1086	0.1026
20	16QAM	1	0	22.52	22.48	22.47	0.1069	0.1059	0.1057
20	64QAM	1	0	21.41	21.46	21.35	0.0828	0.0838	0.0817
20	256QAM	1	0	18.24	18.18	18.35	0.0399	0.0394	0.0409
		Channel		55315	55990	56665	EIRP(W)		
		Frequency (MHz)		3557.5	3625	3692.5	L	M	H
15	QPSK	1	0	23.18	23.39	23.27	0.1245	0.1306	0.1271
15	16QAM	1	0	22.36	22.33	22.32	0.1030	0.1023	0.1021
		Channel		55290	55990	56690	EIRP(W)		
		Frequency (MHz)		3555	3625	3695	L	M	H
10	QPSK	1	0	23.15	23.37	23.27	0.1236	0.1300	0.1271
10	16QAM	1	0	22.41	22.38	22.36	0.1042	0.1035	0.1030
		Channel		55265	55990	56715	EIRP(W)		
		Frequency (MHz)		3552.5	3625	3697.5	L	M	H
5	QPSK	1	0	23.19	23.36	23.25	0.1247	0.1297	0.1265
5	16QAM	1	0	22.39	22.34	22.33	0.1038	0.1026	0.1023

**ACLR**
**LTE Band 48 / 5MHz**
**QPSK**
**Lowest Channel / 1RB0**
**Lowest Channel / 1RBmax**

**Lowest Channel / Full RB**





## LTE Band 48 / 5MHz


## QPSK


## Middle Channel / 1RB0



## Middle Channel / 1RBmax




## Middle Channel / Full RB





**LTE Band 48 / 5MHz**
**16QAM**
**Lowest Channel / 1RB0**
**Lowest Channel / 1RBmax**

**Lowest Channel / Full RB**








## LTE Band 48 / 5MHz


## 16QAM




## Highest Channel / 1RB0


## Highest Channel / 1RBmax



## Highest Channel / Full RB



**LTE Band 48 / 5MHz**
**64QAM**
**Lowest Channel / 1RB0**
**Lowest Channel / 1RBmax**

**Lowest Channel / Full RB**








## LTE Band 48 / 5MHz


## 64QAM

## Highest Channel / 1RB0

## Highest Channel / 1RBmax



## Highest Channel / Full RB







## LTE Band 48 / 5MHz


## 256QAM


## Lowest Channel / 1RB0




## Lowest Channel / 1RBmax



## Lowest Channel / Full RB





**LTE Band 48 / 5MHz**
**256QAM**
**Highest Channel / 1RB0**
**Highest Channel / 1RBmax**

**Highest Channel / Full RB**






## LTE Band 48 / 10MHz


## QPSK

## Lowest Channel / 1RB0

## Lowest Channel / 1RBmax



## Lowest Channel / Full RB







## LTE Band 48 / 10MHz


## QPSK

## Middle Channel / 1RB0

## Middle Channel / 1RBmax



## Middle Channel / Full RB







## LTE Band 48 / 10MHz


QPSK

## Highest Channel / 1RB0

## Highest Channel / 1RBmax



## Highest Channel / Full RB







## LTE Band 48 / 10MHz


## 16QAM




## Lowest Channel / 1RB0

## Lowest Channel / 1RBmax



## Lowest Channel / Full RB



**LTE Band 48 / 10MHz**
**16QAM**
**Middle Channel / 1RB0**
**Middle Channel / 1RBmax**

**Middle Channel / Full RB**






## LTE Band 48 / 10MHz


## 16QAM


## Highest Channel / 1RB0

## Highest Channel / 1RBmax



## Highest Channel / Full RB









## LTE Band 48 / 10MHz


## 64QAM




## Middle Channel / 1RB0

## Middle Channel / 1RBmax



## Middle Channel / Full RB



**LTE Band 48 / 10MHz**
**64QAM**
**Highest Channel / 1RB0**
**Highest Channel / 1RBmax**

**Highest Channel / Full RB**






## LTE Band 48 / 10MHz


## 256QAM

## Lowest Channel / 1RB0

## Lowest Channel / 1RBmax



## Lowest Channel / Full RB







## LTE Band 48 / 10MHz


## 256QAM

## Middle Channel / 1RB0

## Middle Channel / 1RBmax



## Middle Channel / Full RB







## LTE Band 48 / 10MHz


## 256QAM

## Highest Channel / 1RB0

## Highest Channel / 1RBmax



## Highest Channel / Full RB







## LTE Band 48 / 15MHz


## QPSK




## Lowest Channel / 1RB0




## Lowest Channel / 1RBmax






## Lowest Channel / Full RB



**LTE Band 48 / 15MHz**
**QPSK**
**Middle Channel / 1RB0**
**Middle Channel / 1RBmax**

**Middle Channel / Full RB**


**LTE Band 48 / 15MHz**
**QPSK**
**Highest Channel / 1RB0**
**Highest Channel / 1RBmax**

**Highest Channel / Full RB**


**LTE Band 48 / 15MHz**
**16QAM**
**Lowest Channel / 1RB0**
**Lowest Channel / 1RBmax**

**Lowest Channel / Full RB**






## LTE Band 48 / 15MHz


## 16QAM

## Middle Channel / 1RB0

## Middle Channel / 1RBmax



## Middle Channel / Full RB







## LTE Band 48 / 15MHz

## 16QAM

## Highest Channel / 1RB0

## Highest Channel / 1RBmax



## Highest Channel / Full RB

