

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

DECLARATION OF COMPLIANCE		SAR RF EXPOSURE EVALUATION		FCC
Test Lab Information	Name	CELLTECH LABS INC.		
	Address	21-364 Lougheed Road, Kelowna, B.C. V1X 7R8 Canada		
Test Lab Accreditation(s)	A2LA	ISO/IEC 17025:2005 (A2LA Test Lab Certificate No. 2470.01)		
Applicant Information	Name	COVIDENCE A/S		
	Address	Strandvejen 2A 8410 Roende, Denmark		
Application Type(s)	FCC	TCB Certification		
Standard(s) Applied	FCC	47 CFR §2.1093		
Procedure(s) Applied	FCC	OET Bulletin 65, Supplement C	FCC	KDB 447498 D01v05
	IEEE	Standard 1528-2003		
Device RF Exposure Category	FCC	General Population		
Device Identifier(s)	FCC ID:	SQ7-OTX-64		
Device Model	Model	Oculus; m/n: 11002720; 64GB memory		
Additional Models	FCC ID: SQ7-OTX-8, m/n: 1102820, 8GB memory FCC ID: SQ7-OTX-16, m/n: 1102620, 16GB memory FCC ID: SQ7-OTX-32, m/n: 1102320, 32GB memory <i>All models are electrically and mechanically identical, differing only in available memory.</i>			
Test Sample Serial No.	C1009813			
Date of Sample Receipt	May 1, 2013	Date(s) of Evaluations	May 7, 2013	
Test Sample Hardware Revision No.	XANDRA_V3C	Test Sample Firmware Rev. No.	1.17	
Device-Under-Test Description (DUT)	VHF Audio Transmitter			
VHF Transmit Frequency Range(s)	150 - 174 MHz (VHF Band)			
Manuf. Rated Output Power	+23 dBm (+1 / -0.5 dB)			
Measured RF Output Power	250 mW	24.0 dBm	Conducted	150.0 MHz
Battery Type Tested	2x AAA Energizer L92 lithium			
Antenna Type Tested	MCX Wire (external detachable)			445 mm
Accessory Tested	10 x 10 mm Camera			
Max. SAR Level(s) Evaluated	Body-worn	0.151 W/kg	1g	General Population
FCC Spatial Peak SAR Limit	Head/Body	1.6 W/kg	1g	
Celltech Labs Inc. declares under its sole responsibility that this wireless portable device has demonstrated compliance with the Specific Absorption Rate (SAR) RF exposure requirements specified in FCC 47 CFR §2.1093 for the Occupational environment. The device was tested in accordance with the measurement procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01) and IEEE Standard 1528-2003. All measurements were performed in accordance with the SAR system manufacturer recommendations.				
I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.				
The results and statements contained in this report pertain only to the device(s) evaluated.				
This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc.				
Test Report Approved By		Mike Meaker	Engineering Technologist	Celltech Labs Inc.

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 1 of 32

 Celltech Testing and Engineering Services Lab	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

TABLE OF CONTENTS	
1.0 INTRODUCTION	4
2.0 SAR MEASUREMENT SYSTEM	4
3.0 NO. OF TEST CHANNELS (N_c)	4
4.0 RF CONDUCTED OUTPUT POWER MEASUREMENT	5
5.0 ACCESSORY LISTING	5
6.0 FLUID DIELECTRIC PARAMETERS	6
7.0 SAR MEASUREMENT SUMMARY	7
8.0 SAR SCALING (MANUFACTURER TUNE-UP TOLERANCE)	7
9.0 DETAILS OF SAR EVALUATION	8
10.0 SAR EVALUATION PROCEDURES	8
11.0 SYSTEM VERIFICATION	9
12.0 SIMULATED EQUIVALENT TISSUES	10
13.0 SAR LIMITS	10
14.0 ROBOT SYSTEM SPECIFICATIONS	11
15.0 PROBE SPECIFICATION (ET3DV6)	12
16.0 BARSKI PLANAR PHANTOM	12
17.0 DEVICE HOLDER	12
18.0 TEST EQUIPMENT LIST	13
19.0 REFERENCES	14
APPENDIX A - SAR MEASUREMENT PLOTS	15
APPENDIX B - SYSTEM PERFORMANCE CHECK PLOT	19
APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS	22
APPENDIX D - SAR TEST SETUP & DUT PHOTOGRAPHS	24
APPENDIX E - DIPOLE CALIBRATION	30
APPENDIX F - PROBE CALIBRATION	31
APPENDIX G - BARSKI PHANTOM CERTIFICATE OF CONFORMITY	32

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 2 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

REVISION HISTORY			
REVISION NO.	DESCRIPTION	IMPLEMENTED BY	RELEASE DATE
1.0	1st Release	Mike Meaker	May 8, 2013

TEST REPORT SIGN-OFF			
DEVICE TESTED BY	REPORT PREPARED BY	QA REVIEW BY	REPORT APPROVED BY
Mike Meaker	Mike Meaker	Glen Westwell	Mike Meaker

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 3 of 32

 Testing and Engineering Services Lab	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

1.0 INTRODUCTION

This measurement report demonstrates that the Covidence A/S model: Oculus VHF audio transmitter complies with the SAR (Specific Absorption Rate) RF exposure requirements specified in FCC 47 CFR §2.1093 (see reference [1]) for the General Population Exposure environment. The measurement procedures described in FCC KDB 865664 (see reference [5]), FCC OET Bulletin 65, Supplement C 01-01 (see reference [2]) and IEEE Standard 1528-2003 (see reference [3]) were employed. A description of the device, operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used and the various provisions of the rules are included within this test report.

2.0 SAR MEASUREMENT SYSTEM

Celltech Labs Inc. SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 measurement system is comprised of the measurement server, robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and various planar phantoms for Head and/or body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot utilizes a controller with built in VME-bus computer.

3.0 NO. OF TEST CHANNELS (N_c)

Device Frequency Range	Band	N_c	Test Frequencies (MHz)
150 - 174 MHz	VHF	4	150.0, 161.3, 167.6, 173.4
Note: The number of test channels (N_c) was calculated in accordance with the procedures specified in FCC KDB 447498 (see reference [4]).			

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 4 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

4.0 RF CONDUCTED OUTPUT POWER MEASUREMENT

Band	Frequency (MHz)	Mode	Power Setting	Measured Power Level		Method
				dBm	Watts	
VHF	150.0	CW	n/a	24.0	0.250	Average Conducted
VHF	158.0	CW	n/a	23.7	0.237	Average Conducted
VHF	166.0	CW	n/a	23.6	0.230	Average Conducted
VHF	174.0	CW	n/a	23.4	0.219	Average Conducted
Notes						
1. The test channels were selected in accordance with the procedures specified in FCC KDB 447498 (see reference [4]).						
2. The RF conducted output power levels of the DUT were measured by Celltech prior to the SAR evaluations using a Gigatronics 8652A Universal Power Meter at the antenna connector of the radio in accordance with FCC 47 CFR §2.1046 (see reference [9]).						
3. The conducted power measured was less than the manufacturer's rated maximum so the SAR results were scaled accordingly (Refer to section 8.0)						

5.0 ACCESSORY LISTING

Accessory ID # for Test Report	ACCESSORY CATEGORY: ANTENNA		
	Part Number	Description	SAR Evaluation
1	N/A	Straight Detachable MCX Wire Antenna	Yes
2	N/A	Right Angle Detachable MCX Wire Antenna	No*
Accessory ID # for Test Report	ACCESSORY CATEGORY: BATTERY		
	Part Number	Description	SAR Evaluation
a	N/A	2x AAA Energizer L92 lithium batteries	Yes
Accessory ID # for Test Report	ACCESSORY CATEGORY: BODY-WORN		
	Part Number	Description	SAR Evaluation
1	N/A	Belt (Does not contain metal)	No
Accessory ID # for Test Report	ACCESSORY CATEGORY: AUDIO		
	Part Number	Description	SAR Evaluation
a	N/A	10 x 10 mm Camera	Yes

*The 2 Antenna's are identical except for the RF connector which is available straight or right angle. This does not change the body-worn configuration, therefore only the straight antenna was tested.

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 5 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

6.0 FLUID DIELECTRIC PARAMETERS

FLUID DIELECTRIC PARAMETERS						
Date: 05/06/2013		Frequency: 150 MHz			Tissue: Body	
Freq	Test e	Test s	Target e	Target s	Deviation Permittivity	Deviation Conductivity
0.050	98.71	0.75	61.9	0.8	59.47%	-6.25%
0.060	95.2	0.74	61.9	0.8	53.80%	-7.50%
0.070	82.83	0.74	61.9	0.8	33.81%	-7.50%
0.080	75.55	0.77	61.9	0.8	22.05%	-3.75%
0.090	74.96	0.78	61.9	0.8	21.10%	-2.50%
0.100	76.6	0.75	61.9	0.8	23.75%	-6.25%
0.110	64.88	0.77	61.9	0.8	4.81%	-3.75%
0.120	61.65	0.79	61.9	0.8	-0.40%	-1.25%
0.130	65.08	0.77	61.9	0.8	5.14%	-3.75%
0.140	63	0.81	61.9	0.8	1.78%	1.25%
0.150	64.56	0.82	61.9	0.8	4.30%	2.50%
0.160	61.26	0.82	61.9	0.8	-1.03%	2.50%
0.170	60.34	0.83	61.9	0.8	-2.52%	3.75%
0.180	59.48	0.84	61.9	0.8	-3.91%	5.00%
0.190	61.79	0.83	61.9	0.8	-0.18%	3.75%
0.200	60.12	0.83	61.9	0.8	-2.88%	3.75%
0.210	58.92	0.83	61.9	0.8	-4.81%	3.75%
0.220	60.29	0.85	61.9	0.8	-2.60%	6.25%
0.230	58.26	0.86	61.9	0.8	-5.88%	7.50%
0.240	58.12	0.88	61.9	0.8	-6.11%	10.00%
0.250	58.88	0.87	61.9	0.8	-4.88%	8.75%

Test Date	Fluid Type	Ambient Temperature	Fluid Temperature	Fluid Depth	Atmospheric Pressure	Relative Humidity	ρ (Kg/m ³)
May 6	150 Body	23.0 °C	23.3 °C	≥ 15 cm	101.4 kPa	30%	1000

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 6 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

9.0 DETAILS OF SAR EVALUATION

The DUT was compliant for localized Specific Absorption Rate based on the test provisions and conditions described below. The detailed test setup photographs are shown in Appendix D.

- SAR evaluation was performed for body-worn configuration with a separation distance of 8mm between the DUT and phantom. 8mm is the minimum separation distance provided by the 'belt' accessory. The belt accessory does not contain metal and is the only body-worn accessory provided by the manufacturer. For the wire antenna, which is flexible, a separation distance of 5mm was used. This is a conservative minimum separation distance based on the requirements of KDB 447498 (see reference [4]).
- Each evaluation was performed with a fully charged battery.
- Due to the length of the antenna 2 separate area scans were required to cover its entire length. A zoom scan evaluation was performed at the highest peak according to the procedures in the following section.
- The DUT was evaluated for SAR in an unmodulated continuous transmit operation (Continuous Wave mode at 100% duty cycle).
- The SAR drift of the DUT was measured by the DASY4 system for the duration of the SAR evaluations.
- The fluid temperature remained within $\pm 2^{\circ}\text{C}$ from the fluid dielectric parameter measurement to the completion of each SAR test.
- The dielectric parameters of the simulated tissue mixtures were measured prior to the SAR evaluations using a Dielectric Probe Kit and a Network Analyzer (see Appendix C).

10.0 SAR EVALUATION PROCEDURES

- The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated using the SAM phantom.
 - For body-worn and face-held devices a planar phantom was used.
- The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 15mm x 15mm.
An area scan was determined as follows:
 - Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.
 - A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are >2 dB from the global maximum. The remaining maxima are then used to position the cube scans.
A 1g and 10g spatial peak SAR was determined as follows:
 - Extrapolation is used to find the points between the dipole center of the probe and the surface of the phantom. This data cannot be measured, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.4 mm (see probe calibration document in Appendix F). The extrapolation was based on trivariate quadratics computed from the previously calculated 3D interpolated points nearest the phantom surface.
 - Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).
 - A zoom scan volume of 30 mm x 30 mm x 30 mm (5 x 5 x 7 points) centered at the peak SAR location determined from the area scan is used for all zoom scans for devices with a transmit frequency < 800 MHz. Zoom scans for frequencies ≥ 800 MHz are determined with a scan volume of 30 mm x 30 mm x 30 mm (7 x 7 x 7) to ensure complete capture of the peak spatial-average SAR.

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 8 of 32

	Date(s) of Evaluation May 6, 2013	Test Report Serial No. 050113SQ7-T1227-S	Test Report Revision No. Rev. 1.0	
	Test Report Issue Date May 8, 2013	Description of Test(s) Specific Absorption Rate	RF Exposure Category General Population	


Test Lab Certificate No. 2470.01

11.0 SYSTEM VERIFICATION


Prior to the SAR evaluations, system verifications were performed with a planar phantom and SPEAG 300 MHz dipole (see Appendix B) in accordance with the procedures described in FCC KDB 865664 (see reference [5]). The system was verified to meet the internally generated SAR target using 150MHz tissue-equivalent medium with a 300 MHz validation dipole transmitting at 300 MHz (see Appendix E). The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using a Dielectric Probe Kit and a Network Analyzer (see Appendix C for measured fluid dielectric parameters). A forward power of 250 mW was applied to the dipole.

SYSTEM PERFORMANCE CHECK EVALUATION

Test Date	Equiv. Tissue	SAR 1g (W/kg)			Dielectric Constant ϵ_r			Conductivity σ (mho/m)			ρ (Kg/m ³)	Amb. Temp. (°C)	Fluid Temp. (°C)	Fluid Depth (cm)	Humid. (%)	Barom. Press. (kPa)
	Freq. (MHz)	Target	Meas.	Dev.	Target	Meas.	Dev.	Target	Meas.	Dev.						
May 6	Body 150	0.653	0.656	+0.5%	61.9 $\pm 5\%$	64.6	+4.4%	0.80 $\pm 5\%$	0.82	+2.5%	1000	23.0	23.3	≥ 15	30	101.4
Notes	1.	The 150MHz SAR values have a coefficient of variation < 3%.														
	2.	The target dielectric parameters are the nominal values from the SAR system manufacturer's probe calibration (see Appendix F).														
	3.	The fluid temperature remained within $\pm 2^\circ\text{C}$ from the fluid dielectric parameter measurement to the completion of the system performance check.														
	4.	The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using a Dielectric Probe Kit and a Network Analyzer (see Appendix C).														



System Performance Check Measurement Setup (IEEE Standard 1528-2003)



SPEAG 300 MHz Validation Dipole Setup

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 9 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

12.0 SIMULATED EQUIVALENT TISSUES

The simulated equivalent tissue recipes in the table below are derived from the SAR system manufacturer's suggested recipes in the DASY4 manual (see references [6] and [7]) in accordance with the procedures and requirements specified in IEEE Standard 1528-2003 (see reference [3]). The ingredient percentage may have been adjusted minimally in order to achieve the appropriate target dielectric parameters within the specified tolerance.

INGREDIENT	Water	150 MHz Body Tissue Mixture	46.6 %
	Sugar		49.7 %
	Salt		2.6 %
	HEC		1.0 %
	Bactericide		0.1 %

13.0 SAR LIMITS

SAR RF EXPOSURE LIMITS		
FCC 47 CFR 2.1093	(General Population)	(Occupational)
Spatial Average (averaged over the whole body)	0.08 W/kg	0.4 W/kg
Spatial Peak (averaged over any 1 g of tissue)	1.6 W/kg	8.0 W/kg
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0 W/kg	20.0 W/kg
The Spatial Average value of the SAR averaged over the whole body.		
The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.		
The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.		
Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.		
Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.		

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 10 of 32

 Testing and Engineering Services Lab	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

14.0 ROBOT SYSTEM SPECIFICATIONS

<u>Specifications</u>	
Positioner	Stäubli Unimation Corp. Robot Model: RX60L
Repeatability	0.02 mm
No. of axis	6
<u>Data Acquisition Electronic (DAE) System</u>	
<u>Cell Controller</u>	
Processor	AMD Athlon XP 2400+
Clock Speed	2.0 GHz
Operating System	Windows XP Professional
<u>Data Converter</u>	
Features	Signal Amplifier, multiplexer, A/D converter, and control logic
Software	Measurement Software: DASY4, V4.7 Build 80
	Postprocessing Software: SEMCAD, V1.8 Build 171
Connecting Lines	Optical downlink for data and status info., Optical uplink for commands and clock
<u>DASY4 Measurement Server</u>	
Function	Real-time data evaluation for field measurements and surface detection
Hardware	PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM
Connections	COM1, COM2, DAE, Robot, Ethernet, Service Interface
<u>E-Field Probe</u>	
Model	ET3DV6
Serial No.	1590
Construction	Triangular core fiber optic detection system
Frequency	10 MHz to 6 GHz
Linearity	±0.2 dB (30 MHz to 3 GHz)
<u>Validation Phantom</u>	
Type	Barski Planar Phantom
Shell Material	Fiberglass
Thickness	2.0 ±0.1 mm
Volume	Approx. 70 liters

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 11 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

15.0 PROBE SPECIFICATION (ET3DV6)

Construction:	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, glycol)	
Calibration:	In air from 10 MHz to 2.5 GHz In Body simulating tissue at frequencies of 900 MHz and 1.8 GHz (accuracy $\pm 8\%$)	
Frequency:	10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)	
Directivity:	± 0.2 dB in Body tissue (rotation around probe axis) ± 0.4 dB in Body tissue (rotation normal to probe axis)	
Dynamic Range:	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB	
Surface Detect:	± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces	
Dimensions:	Overall length: 330 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm	
Application:	General dosimetry up to 3 GHz Compliance tests of mobile phone	

ET3DV6 E-Field Probe

16.0 BARSKI PLANAR PHANTOM

The Barski planar phantom is a fiberglass shell phantom with a 2.0 mm (+/-0.2mm) thick device measurement area at the center of the phantom for SAR evaluations of devices with a larger surface area than the planar section of the SAM phantom. The planar phantom is integrated in a wooden table. The planar phantom was used for the DUT SAR evaluations and the system performance check evaluations. See Appendix G for dimensions and specifications of the Barski planar phantom.	
---	---

Barski Planar Phantom

17.0 DEVICE HOLDER

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections.	
--	---

Device Holder

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 12 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

18.0 TEST EQUIPMENT LIST

TEST EQUIPMENT		ASSET NO.	SERIAL NO.	DATE CALIBRATED	CALIBRATION INTERVAL
USED	DESCRIPTION				
x	Schmid & Partner DASY4 System	-	-	-	-
x	-DASY4 Measurement Server	00158	1078	CNR	CNR
x	-Robot	00046	599396-01	CNR	CNR
x	-DAE4	00019	353	19-Apr-12	Biennial
x	-ET3DV6 E-Field Probe	00017	1590	24-Apr-13	Annual
x	-D300V3 Validation Dipole	00220	1009	17-Apr-12 / 8-Jan-13	Triennial
x	Barski Planar Phantom	00155	03-01	CNR	CNR
x	HP 85070C Dielectric Probe Kit	00033	none	CNR	CNR
x	Gigatronics 8652A Power Meter	00007	1835272	03-May-12	Biennial
x	Gigatronics 80701A Power Sensor	00014	1833542	03-May-12	Biennial
x	Gigatronics 80334A Power Sensor	-	1837001	03-May-12	Biennial
x	HP 8753ET Network Analyzer	00134	US39170292	26-Apr-12	Biennial
x	Rohde & Schwarz SMR20 Signal Generator	00006	100104	02-May-12	Biennial
x	Amplifier Research 5S1G4 Power Amplifier	00106	26235	CNR	CNR
Abbr.	CNR = Calibration Not Required				

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 13 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

19.0 REFERENCES

- [1] Federal Communications Commission - "Radiofrequency radiation exposure evaluation: portable devices"; Rule Part 47 CFR §2.1093.
- [2] Federal Communications Commission - "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- [3] IEEE Standard 1528-2003 - "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques": December 2003.
- [4] Federal Communications Commission, Office of Engineering and Technology - "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies"; KDB 447498 D01v05: October 2012.
- [5] Federal Communications Commission, Office of Engineering and Technology - "SAR Measurement Requirements for 100 MHz to 6 GHz"; KDB 865664 D01v01: October 2012
- [6] Schmid & Partner Engineering AG - DASY4 Manual V4.6, Chapter 16 Application Note, Head Tissue Recipe: Sept. 2005.
- [7] Schmid & Partner Engineering AG - DASY4 Manual V4.6, Chapter 17 Application Note, Body Tissue Recipe: Sept. 2005.
- [8] ISO/IEC 17025 - "General requirements for the competence of testing and calibration laboratories (ISO/IEC 17025:2005)."
- [9] Federal Communications Commission - "Measurements Required: RF Power Output"; Rule Part 47 CFR §2.1046.

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 14 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

APPENDIX A - SAR MEASUREMENT PLOTS

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 15 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Date Tested: 5/6/2013

Body-Worn SAR - 150.0 MHz - Transmitter and base of antenna

DUT: Oculus; Type: VHF Radio Transmitter; Serial: Not Specified

Program Notes: Ambient Temp: 23C; Fluid Temp: 23.3C; Barometric Pressure: 101.4 kPa; Humidity: 30%

Procedure Notes:

Communication System: VHF

Frequency: 150 MHz; Duty Cycle: 1:1

Medium: M150 Medium parameters used: $f = 150 \text{ MHz}$; $\sigma = 0.82 \text{ mho/m}$; $\epsilon_r = 64.6$; $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(8.65, 8.65, 8.65); Calibrated: 24/04/2013
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 19/04/2012
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

150.0MHz - Belt - Antenna 5mm/Area Scan (7x24x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.155 mW/g


150.0MHz - Belt - Antenna 5mm/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.2 V/m; Power Drift = -0.094 dB

Peak SAR (extrapolated) = 0.269 W/kg

SAR(1 g) = 0.151 mW/g; SAR(10 g) = 0.099 mW/g

Maximum value of SAR (measured) = 0.159 mW/g



Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 16 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Date Tested: 5/6/2013

Body-Worn SAR - 150.0 MHz - Tip of antenna

DUT: Oculus; Type: VHF Radio Transmitter; Serial: Not Specified

Program Notes: Ambient Temp: 23C; Fluid Temp: 23.3C; Barometric Pressure: 101.4 kPa; Humidity: 30%

Procedure Notes:

Communication System: VHF


Frequency: 150 MHz; Duty Cycle: 1:1

Medium: M150 Medium parameters used: $f = 150 \text{ MHz}$; $\sigma = 0.82 \text{ mho/m}$; $\epsilon_r = 64.6$; $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(8.65, 8.65, 8.65); Calibrated: 24/04/2013
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))
- Electronics: DAE4 Sn353; Calibrated: 19/04/2012
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

150.0MHz - Belt - Antenna 5mm 2/Area Scan (7x24x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.111 mW/g



Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 17 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Z-Axis Scan



Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 18 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

APPENDIX B - SYSTEM PERFORMANCE CHECK PLOT

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 19 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

Date Tested: 5/6/2013

System Verification - 300 MHz Dipole - 150 MHz Body Fluid

DUT: Dipole 300 MHz Body; Type: D300V3; Serial: 1009; Calibrated: 01/08/2013

Program Notes: Ambient Temp: 23C; Fluid Temp: 23.3C; Barometric Pressure: 101.4 kPa; Humidity: 30%

Procedure Notes: 300 MHz Dipole transmitting at 300 MHz using 150 MHz SAR probe calibration and 150 MHz tissue dielectric parameters

Communication System: CW

Frequency: 150 MHz; Duty Cycle: 1:1

Medium: M150 Medium parameters used: $f = 150 \text{ MHz}$; $\sigma = 0.82 \text{ mho/m}$; $\epsilon_r = 64.6$; $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(8.65, 8.65, 8.65); Calibrated: 24/04/2013
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 19/04/2012
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body d=15mm, Pin = 250mW/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.645 mW/g


Body d=15mm, Pin = 250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 29.1 V/m; Power Drift = -0.001 dB

Peak SAR (extrapolated) = 1.10 W/kg

SAR(1 g) = 0.656 mW/g; SAR(10 g) = 0.435 mW/g

Maximum value of SAR (measured) = 0.694 mW/g




Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 20 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

Z-Axis Scan



Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 21 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 22 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

150 MHz Body

Celltech Labs
Test Result for UIM Dielectric Parameter
06/May/2013
Freq Frequency(GHz)
FCC_eB FCC Limits for Body Epsilon
FCC_sB FCC Limits for Body Sigma
Test_e Epsilon of UIM
Test_s Sigma of UIM

Freq	FCC_eB	FCC_sB	Test_e	Test_s
0.0500	64.37	0.72	98.71	0.75
0.0600	64.12	0.73	95.20	0.74
0.0700	63.87	0.74	82.83	0.74
0.0800	63.63	0.74	75.55	0.77
0.0900	63.38	0.75	74.96	0.78
0.1000	63.13	0.76	76.60	0.75
0.1100	62.89	0.77	64.88	0.77
0.1200	62.64	0.78	61.65	0.79
0.1300	62.39	0.78	65.08	0.77
0.1400	62.15	0.79	63.00	0.81
0.1500	61.90	0.80	64.56	0.82
0.1600	61.65	0.81	61.26	0.82
0.1700	61.41	0.82	60.34	0.83
0.1800	61.16	0.82	59.48	0.84
0.1900	60.91	0.83	61.79	0.83
0.2000	60.67	0.84	60.12	0.83
0.2100	60.42	0.85	58.92	0.83
0.2200	60.17	0.86	60.29	0.85
0.2300	59.93	0.86	58.26	0.86
0.2400	59.68	0.87	58.12	0.88
0.2500	59.43	0.88	58.88	0.87

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 23 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01


APPENDIX D - SAR TEST SETUP & DUT PHOTOGRAPHS

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 24 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

BODY-WORN SAR TEST SETUP PHOTOGRAPHS




Body-Worn Test Setup


Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 25 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

BODY-WORN SAR TEST SETUP PHOTOGRAPHS



Device and Antenna base area scan (8mm device separation and 5mm antenna separation distance)



Antenna tip area scan (5mm antenna separation distance)

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 26 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

DUT PHOTOGRAPHS



DUT with Straight Antenna and Camera

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 27 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

DUT PHOTOGRAPHS



Front of DUT



Back of DUT



Back of DUT - Battery cover removed

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 28 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

DUT PHOTOGRAPHS



Antenna connector side of DUT

Accessory connector side of DUT



Straight and Right Angle antennas

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 29 of 32

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

APPENDIX E - DIPOLE CALIBRATION

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 30 of 32



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **Celltech**

Certificate No: **D300V3-1009_Jan13**

CALIBRATION CERTIFICATE

Object **D300V3 - SN: 1009**

Calibration procedure(s) **QA CAL-15.v7**
Calibration procedure for dipole validation kits below 700 MHz

Calibration date: **January 08, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	29-Mar-12 (No. 217-01508)	Apr-13
Power sensor E4412A	MY41498087	29-Mar-12 (No. 217-01508)	Apr-13
Reference 3 dB Attenuator	SN: S5054 (3c)	27-Mar-12 (No. 217-01531)	Apr-13
Reference 20 dB Attenuator	SN: S5086 (20b)	27-Mar-12 (No. 217-01529)	Apr-13
Type-N mismatch combination	SN: 5047.3 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe ET3DV6	SN: 1507	28-Dec-12 (No. ET3-1507_Dec12)	Dec-13
DAE4	SN: 654	18-Apr-12 (No. DAE4-654_Apr12)	Apr-13
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: January 8, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.4
Extrapolation	Advanced Extrapolation	
Phantom	ELI4 Flat Phantom	Shell thickness: 2 ± 0.2 mm
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	300 MHz $\pm$ 1 MHz	

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	58.2	0.92 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	57.6 $\pm$ 6 %	0.91 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	0.717 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	2.89 W/kg $\pm$ 18.1 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	0.483 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	1.94 W/kg $\pm$ 17.6 % (k=2)

Appendix

Antenna Parameters with Body TSL

Impedance, transformed to feed point	57.1 Ω - 5.9 j Ω
Return Loss	- 21.3 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.748 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	February 26, 2009

DASY5 Validation Report for Body TSL

Date: 08.01.2013

Test Laboratory: SPEAG, Zürich, Switzerland

DUT: Dipole 300 MHz; Type: D300V3; Serial: D300V3 - SN: 1009

Communication System: CW; Frequency: 300 MHz

Medium parameters used: $f = 300 \text{ MHz}$; $\sigma = 0.91 \text{ S/m}$; $\epsilon_r = 57.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ET3DV6 - SN1507; ConvF(7.08, 7.08, 7.08); Calibrated: 28.12.2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 18.04.2012
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1003
- DASY52 52.8.4(1052); SEMCAD X 14.6.8(7028)

Dipole Calibration for Body Tissue/ $d=15\text{mm}$, $P_{in}=250\text{mW}$ /Zoom Scan (7x7x7)/Cube 0:


Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 29.820 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.11 W/kg


SAR(1 g) = 0.717 W/kg; SAR(10 g) = 0.483 W/kg

Maximum value of SAR (measured) = 0.763 W/kg



0 dB = 0.763 W/kg = -1.17 dBW/kg

Impedance Measurement Plot for Body TSL



	<u>Date:</u> May. 2, 2013	<u>Revision No.</u> Rev. 1.0	 Test Lab Certificate No. 2470.01
	Establishment of 150MHz Body SAR Target for System Verification		

A 300MHz System Verification was performed to support the results.

300 MHZ SYSTEM VERIFICATION																
Test Date	Equiv. Tissue	SAR 1g (W/kg)			Dielectric Constant ϵ_r			Conductivity σ (mho/m)			ρ (Kg/m ³)	Amb. Temp. (°C)	Fluid Temp. (°C)	Fluid Depth (cm)	Humid. (%)	Barom. Press. (kPa)
	Freq. (MHz)	Target	Meas.	Dev.	Target	Meas.	Dev.	Target	Meas.	Dev.						
May 2	Body 300	0.717 ±10%	0.748	-4.1%	58.2 ±5%	55.7	-4.3%	0.92 ±5%	0.88	-4.3%	1000	23.0	21.5	≥ 15	30	103.3

Five System Verifications were performed with the 300 MHz dipole transmitting at 300 MHz with the Barski Planar phantom filled with 150 MHz Body tissue simulating fluid.

150 MHZ SYSTEM VERIFICATION													
Test #	Test Date	SAR 1g (W/kg)	Dielectric Constant ϵ_r			Conductivity σ (mho/m)			ρ (Kg/m ³)	Amb. Temp. (°C)	Fluid Temp. (°C)	Humid. (%)	Barom. Press. (kPa)
			Target	Meas.	Dev.	Target	Meas.	Dev.					
1	May 2	0.658	61.9 ±5%	60.5	-2.3%	0.80 ±5%	0.79	-1.3%	1000	23	21.2	30	103.3
2	May 2	0.659	61.9 ±5%	60.5	-2.3%	0.80 ±5%	0.79	-1.3%	1000	23	21.2	30	103.3
3	May 2	0.653	61.9 ±5%	64.7	+4.5%	0.80 ±5%	0.80	0%	1000	23	21.4	30	103.3
4	May 3	0.645	61.9 ±5%	62.5	+1.0%	0.80 ±5%	0.80	0%	1000	23	22.6	30	103.1
5	May 3	0.651	61.9 ±5%	62.5	+1.0%	0.80 ±5%	0.80	0%	1000	23	22.6	30	103.1

150 MHz Target Coefficient of Variation Calculation				
			calc	
Measured Values	0.658		2.304E-05	
	0.659		3.364E-05	
	0.653		4E-08	
	0.645		6.724E-05	
	0.651		4.84E-06	
Sum	3.266	Standard Deviation		0.51%
# of Values	5	Mean		0.653
		Coefficient		0.78%

Other KDB 865664 Requirements:

	300 Body	150 Body	% Diff.
Fluid Permittivity	55.7	61.9 +/- 5%	10%
Fluid Conductivity	0.88	0.80 +/- 5%	10%
Probe Cal. Factor	8.41	8.65	2.8%
1g SAR Target	0.717	0.653	8.9%

The established 1g system verification SAR target for 150MHz body is **0.653 W/kg**. All of the requirements of FCC KDB 865664 have been met.

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

APPENDIX F - PROBE CALIBRATION

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 31 of 32



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Celltech**

Certificate No: **ET3-1590_Apr13**

CALIBRATION CERTIFICATE

Object **ET3DV6 - SN:1590**

Calibration procedure(s) **QA CAL-01.v8, QA CAL-12.v7, QA CAL-23.v4, QA CAL-25.v4**
Calibration procedure for dosimetric E-field probes

Calibration date: **April 24, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	04-Apr-13 (No. 217-01733)	Apr-14
Power sensor E4412A	MY41498087	04-Apr-13 (No. 217-01733)	Apr-14
Reference 3 dB Attenuator	SN: S5054 (3c)	04-Apr-13 (No. 217-01737)	Apr-14
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-13 (No. 217-01735)	Apr-14
Reference 30 dB Attenuator	SN: S5129 (30b)	04-Apr-13 (No. 217-01738)	Apr-14
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	31-Jan-13 (No. DAE4-660_Jan13)	Jan-14
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-15
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

	Name	Function	Signature
Calibrated by:	Claudio Leubler	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
Issued: April 27, 2013			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * *frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * *ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ET3DV6

SN:1590

Manufactured: March 19, 2001
Calibrated: April 24, 2013

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ET3DV6 - SN:1590

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V/m})^2$) ^A	1.73	1.85	1.61	$\pm 10.1 \%$
DCP (mV) ^B	94.7	99.4	88.0	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	186.7	$\pm 2.7 \%$
		Y	0.0	0.0	1.0		151.0	
		Z	0.0	0.0	1.0		171.2	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ET3DV6 - SN:1590

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
450	43.5	0.87	7.53	7.53	7.53	0.21	2.23	± 13.4 %
750	41.9	0.89	7.24	7.24	7.24	0.25	3.00	± 12.0 %
835	41.5	0.90	6.84	6.84	6.84	0.26	3.00	± 12.0 %
900	41.5	0.97	6.68	6.68	6.68	0.28	3.00	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: ET3DV6 - SN:1590

Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
450	56.7	0.94	7.98	7.98	7.98	0.13	2.14	± 13.4 %
750	55.5	0.96	6.84	6.84	6.84	0.31	2.49	± 12.0 %
835	55.2	0.97	6.67	6.67	6.67	0.29	2.67	± 12.0 %
900	55.0	1.05	6.63	6.63	6.63	0.26	3.00	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f = 900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ , θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ET3DV6 - SN:1590

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	6
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	6.8 mm
Probe Tip to Sensor X Calibration Point	2.7 mm
Probe Tip to Sensor Y Calibration Point	2.7 mm
Probe Tip to Sensor Z Calibration Point	2.7 mm
Recommended Measurement Distance from Surface	4 mm

Additional Conversion Factors

for Dosimetric E-Field Probe

Type:

ET3DV6

Serial Number:

1590

Place of Assessment:

Zurich

Date of Assessment:

April 29, 2013

Probe Calibration Date:

April 24, 2013

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. Since the evaluation is coupled with measured conversion factors, it has to be recalculated yearly, i.e., following the re-calibration schedule of the probe. The uncertainty of the numerical assessment is based on the extrapolation from measured value at 450, 835 and 900 MHz.

Assessed by:



Dosimetric E-Field Probe ET3DV6 SN:1590

Conversion factor ($\pm$ standard deviation)

150 $\pm$ 50 MHz *ConvF* 9.31 $\pm$ 10%

$\epsilon_r = 52.3 \pm 5\%$
 $\sigma = 0.76 \pm 5\%$ mho/m
 (head tissue)

300 $\pm$ 50 MHz *ConvF* 8.36 $\pm$ 9%

$\epsilon_r = 45.3 \pm 5\%$
 $\sigma = 0.87 \pm 5\%$ mho/m
 (head tissue)

150 $\pm$ 50 MHz *ConvF* 8.65 $\pm$ 10%

$\epsilon_r = 61.9 \pm 5\%$
 $\sigma = 0.80 \pm 5\%$ mho/m
 (body tissue)

300 $\pm$ 50 MHz *ConvF* 8.41 $\pm$ 9%

$\epsilon_r = 58.2 \pm 5\%$
 $\sigma = 0.92 \pm 5\%$ mho/m
 (body tissue)

Important Note:

For numerically assessed probe conversion factors, parameters Alpha and Delta in the DASY software must have the following entries: Alpha = 0 and Delta = 1.

Please see also DASY Manual.

	<u>Date(s) of Evaluation</u> May 6, 2013	<u>Test Report Serial No.</u> 050113SQ7-T1227-S	<u>Test Report Revision No.</u> Rev. 1.0	
	<u>Test Report Issue Date</u> May 8, 2013	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> General Population	

Test Lab Certificate No. 2470.01

APPENDIX G - BARSKI PHANTOM CERTIFICATE OF CONFORMITY

Applicant:	Covidence A/S	FCC ID:	SQ7-OTX-64	Model:	Oculus	
DUT Type:	VHF Audio Transmitter				150-174 MHz	
2013 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 32 of 32

2378 Westlake Road
Kelowna, B.C. Canada
V1Z-2V2



Ph. # 250-769-6848
Fax # 250-769-6334
E-mail: barskiind@shaw.ca
Web: www.bcfiberglass.com

FIBERGLASS FABRICATORS

Certificate of Conformity

Item : Flat Planar Phantom Unit # 03-01
Date: June 16, 2003
Manufacturer: Barski Industries (1985 Ltd)

Test	Requirement	Details
Shape	Compliance to geometry according to drawing	Supplied CAD drawing
Material Thickness	Compliant with the requirements	2mm +/- 0.2mm in measurement area
Material Parameters	Dielectric parameters for required frequencies Based on Dow Chemical technical data	100 MHz-5 GHz Relative permittivity<5 Loss Tangent<0.05

Conformity

Based on the above information, we certify this product to be compliant to the requirements specified.

Signature: _____

A handwritten signature in black ink, appearing to read 'Daniel Chailier', is written over a horizontal line.

Daniel Chailier



Fiberglass Planar Phantom - Top View



Fiberglass Planar Phantom - Front View




Fiberglass Planar Phantom - Back View



Fiberglass Planar Phantom - Bottom View

Dimensions of Fiberglass Planar Phantom

(Manufactured by Barski Industries Ltd. - Unit# 03-01)



**Note: Measurements that aren't repeated for the opposite sides are the same as the side measured.
This drawing is not to scale.**