

## TEST REPORT

Report No.: HK10051190-1

Hallmark Cards, Inc.

Application  
For  
Certification  
(Original Grant)  
**(FCC ID: SQ9XOX1002)**  
**(IC: 5768A-XOX1002)**

Transceiver

Prepared and Checked by:

Approved by:

Signed On File

Benny Lau

Engineer

---

Chan Chi Hung, Terry

Senior Lead Engineer

Date: June 11, 2010

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

---

## INTERTEK TESTING SERVICES

---

### GENERAL INFORMATION

**Hallmark Cards, Inc.  
MODEL: XOX1002**

**FCC ID: SQ9XOX1002  
IC: 5768A-XOX1002**

Grantee:	Hallmark Cards, Inc.
Grantee Address:	2501 McGee, MD 166, Missouri, Kansas City, U. S. A.
Contact Person:	Ronald Carlson
Tel:	816 5074150
Fax:	N/A
e-mail:	rcarlson@hallmark.com
Manufacturer:	Jetta Company Limited
Manufacturer Address:	Jetta House, 19 On Kui Street, On Lok Tsuen, Fanling, N.T., Hong Kong.
Brand Name:	N/A
Model:	XOX1002
Type of EUT:	Transceiver
Description of EUT:	Wireless Snowman Band Trumpet Tom
Serial Number:	N/A
FCC ID / IC:	SQ9XOX1002 / 5768A-XOX1002
Date of Sample Submitted:	May 24, 2010
Date of Test:	May 27, 2010
Report No.:	HK10051190-1
Report Date:	June 11, 2010
Environmental Conidtions:	Temperature: +10 to 40°C Humidity: 10 to 90%

---

---

## INTERTEK TESTING SERVICES

---

---

### SUMMARY OF TEST RESULT

**Hallmark Cards, Inc.**  
**MODEL: XOX1002**

**FCC ID: SQ9XOX1002**  
**IC: 5768A-XOX1002**

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	N/A
Hopping Channel Carrier Frequencies Separation	15.247(e) / RSS-210 A8.1	N/A
20dB Bandwidth of the Hopping Channel	15.247(a) / RSS-210 A8.1	N/A
Number of Hopping Frequencies	15.247(e) / RSS-210 A8.1	N/A
Average Time of Occupancy of Hopping Frequency	15.247(e) / RSS-210 A8.1	N/A
Antenna Conducted Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
RF Exposure Compliance	15.247(i) / RSS-Gen 5.5	N/A
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 7.2.2	N/A
Transmitter Field Strength	15.227 / RSS-310 3.8	N/A
Transmitter Field Strength	15.229 / RSS-210 A2.7	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(a) / RSS-210 A1.1.1	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(e) / RSS-210 A1.1.5	N/A
Transmitter Field Strength and Bandwidth Requirement	15.239 / RSS-210 A2.8	N/A
Transmitter Field Strength and Bandwidth Requirement	15.249 / RSS-210 A2.9	Pass
Transmitter Field Strength and Bandwidth Requirement	15.235 / RSS-310 3.9	N/A
Digital Device Radiated Emissions	15.109 / ICES-003	Pass
Receiver Radiated Emissions	RSS-210 2.6	Pass

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

1.0	<b><u>General Description</u></b> .....	1
1.1	Product Description .....	1
1.2	Related Submittal(s) Grants.....	1
1.3	Test Methodology.....	1
1.4	Test Facility .....	1
2.0	<b><u>System Test Configuration</u></b> .....	2
2.1	Justification .....	2
2.2	EUT Exercising Software.....	2
2.3	Special Accessories .....	2
2.4	Equipment Modification .....	2
2.5	Measurement Uncertainty.....	2
2.6	Support Equipment List and Description .....	2
3.0	<b><u>Emission Results</u></b> .....	3
3.1	Field Strength Calculation.....	3
3.2	Radiated Emission Configuration Photograph.....	4
3.3	Radiated Emission Data .....	4
4.0	<b><u>Equipment Photographs</u></b> .....	10
5.0	<b><u>Product Labelling</u></b> .....	10
6.0	<b><u>Technical Specifications</u></b> .....	10
7.0	<b><u>Instruction Manual</u></b> .....	10
8.0	<b><u>Miscellaneous Information</u></b> .....	10
8.1	Measured Bandwidth / RF Output Signal .....	11
8.2	Discussion of Pulse Desensitization.....	11
8.3	Calculation of Average Factor.....	12
8.4	Emissions Test Procedures .....	12
9.0	<b><u>Equipment List</u></b> .....	14

---

## INTERTEK TESTING SERVICES

---

### 1.0 General Description

#### 1.1 Product Description

The Equipment Under Test (EUT) is the Wireless Snowman band Trumpet Tom operating at 2406MHz, 2438MHz and 2452MHz only. The EUT is powered by 4.5VDC (3 x 1.5V 'AAA' size batteries). It will play songs and move in time to the song. There are totally four snowman styles. When it is put together with other members of the band, they communicate wirelessly to move in time and play along with each other's songs. After powered up, the EUT will scan the ambient field strength among those three channels. Then it will select the channel with the least ambient field strength to operate.

Antenna Type : Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

The Certification procedure of transceiver for this transceiver (with FCC ID: SQ9XOX1000, SQ9XOX1001, SQ9XOX1002) are being processed as the same time of this application.

The receiver portion for this transceiver is exempted from the Part 15 technical rules per 15.101(b).

#### 1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

#### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC and IC.

---

Report No.: HK10051190-1

FCC ID: SQ9XOX1002

IC: 5768A-XOX1002

---

## INTERTEK TESTING SERVICES

---

### 2.0 System Test Configuration

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The device was powered by 3 x 1.5V AAA size batteries during test.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it receives and transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Equipment Modification

Any modifications installed previous to testing by Hallmark Cards, Inc. will be incorporated in each production model sold/leased in the United States and Canada.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

#### 2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

#### 2.6 Support Equipment List and Description

N/A.

---

## INTERTEK TESTING SERVICES

---

### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB $\mu$ V/m
- RR = RA - AG - AV in dB $\mu$ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

RA = 52.0 dB $\mu$ V/m	
AF = 7.4 dB	RR = 18.0 dB $\mu$ V
CF = 1.6 dB	LF = 9.0 dB
AG = 29.0 dB	
AV = 5.0 dB	
FS = RR + LF	
FS = 18 + 9 = 27 dB $\mu$ V/m	

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 4904 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 0.1 dB



## INTERTEK TESTING SERVICES

Company: Hallmark Cards, Inc.  
 Model: XOX1002  
 Mode: TX Mode

Date of Test: May 27, 2010

### Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

#### Channel Low

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2406.175	78.5	33	29.4	17.8	74.9	94.0	-19.1
V	4812.350	51.6	33	34.9	17.8	53.5	54.0	-0.5
V	7218.525	38.4	33	37.9	17.8	43.3	54.0	-10.7
V	9624.700	27.9	33	40.4	17.8	35.3	54.0	-18.7
V	12030.875	28.1	33	40.5	17.8	35.6	54.0	-18.4
V	14437.050	28.5	33	40.0	17.8	35.5	54.0	-18.5

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2406.175	78.5	33	29.4	92.7	114.0	-21.3
V	4812.350	51.6	33	34.9	71.3	74.0	-2.7
V	7218.525	38.4	33	37.9	61.1	74.0	-12.9
V	9624.700	27.9	33	40.4	53.1	74.0	-20.9
V	12030.875	28.1	33	40.5	53.4	74.0	-20.6
V	14437.050	28.5	33	40.0	53.3	74.0	-20.7

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

## INTERTEK TESTING SERVICES

Company: Hallmark Cards, Inc.  
 Model: XOX1002  
 Mode: TX Mode

Date of Test: May 27, 2010

### Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

#### Channel Middle

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2438.075	78.4	33	29.4	17.8	74.8	94.0	-19.2
V	4876.150	51.9	33	34.9	17.8	53.8	54.0	-0.2
V	7314.225	38.1	33	37.9	17.8	43.0	54.0	-11.0
V	9752.300	27.5	33	40.4	17.8	34.9	54.0	-19.1
V	12190.375	27.5	33	40.5	17.8	35.0	54.0	-19.0
V	14628.450	30.0	33	38.4	17.8	35.4	54.0	-18.6

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2438.075	78.4	33	29.4	92.6	114.0	-21.4
V	4876.150	51.9	33	34.9	71.6	74.0	-2.4
V	7314.225	38.1	33	37.9	60.8	74.0	-13.2
V	9752.300	27.5	33	40.4	52.7	74.0	-21.3
V	12190.375	27.5	33	40.5	52.8	74.0	-21.2
V	14628.450	30.0	33	38.4	53.2	74.0	-20.8

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

## INTERTEK TESTING SERVICES

Company: Hallmark Cards, Inc.  
 Model: XOX1002  
 Mode: TX mode

Date of Test: May 27, 2010

### Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

#### Channel High

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2452.000	78.7	33	29.4	17.8	75.1	94.0	-18.9
V	4904.000	52.0	33	34.9	17.8	53.9	54.0	-0.1
V	7356.000	38.6	33	37.9	17.8	43.5	54.0	-10.5
V	9808.000	27.7	33	40.4	17.8	35.1	54.0	-18.9
V	12260.000	27.3	33	40.5	17.8	34.8	54.0	-19.2
V	14712.000	30.4	33	38.4	17.8	35.8	54.0	-18.2

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2452.000	78.7	33	29.4	92.9	114.0	-21.1
V	4904.000	52.0	33	34.9	71.7	74.0	-2.3
V	7356.000	38.6	33	37.9	61.3	74.0	-12.7
V	9808.000	27.7	33	40.4	52.9	74.0	-21.1
V	12260.000	27.3	33	40.5	52.6	74.0	-21.4
V	14712.000	30.4	33	38.4	53.6	74.0	-20.4

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

---

---

## INTERTEK TESTING SERVICES

---

---

Applicant: Hallmark Cards, Inc.  
Model: XOX1002  
Mode: RX mode

Date of Test: May 27, 2010

### Radiated Emissions Pursuant to RSS-210 Requirement

#### Channel Low

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2380.175	42.9	33	29.4	39.3	54.0	-14.7
V	4760.350	38.9	33	34.9	40.8	54.0	-13.2
V	7140.525	36.8	33	37.9	41.7	54.0	-12.3
V	9520.700	35.4	33	40.4	42.8	54.0	-11.2
V	11900.875	36.1	33	40.5	43.6	54.0	-10.4

#### Channel Middle

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2412.075	43.2	33	29.4	39.6	54.0	-14.4
V	4824.150	38.4	33	34.9	40.3	54.0	-13.7
V	7236.225	37.0	33	37.9	41.9	54.0	-12.1
V	9648.300	35.4	33	40.4	42.8	54.0	-11.2
V	12060.375	36.1	33	40.5	43.6	54.0	-10.4

#### Channel High

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2426.000	43.0	33	29.4	39.4	54.0	-14.6
V	4852.000	38.8	33	34.9	40.7	54.0	-13.3
V	7278.000	36.7	33	37.9	41.6	54.0	-12.4
V	9704.000	34.9	33	40.4	42.3	54.0	-11.7
V	12130.000	36.2	33	40.5	43.7	54.0	-10.3

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

---

---

Report No.: HK10051190-1  
FCC ID: SQ9XOX1002  
IC: 5768A-XOX1002

---

## INTERTEK TESTING SERVICES

---

Applicant: Hallmark Cards, Inc.  
Model: XOX1002  
Mode: Sound On mode

Date of Test: May 27, 2010

### Data Table

#### Radiated Scan Pursuant to FCC 15.109: Emissions Requirement

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	32.768	39.3	16	10.0	33.3	40.0	-6.7
V	49.152	37.8	16	11.0	32.8	40.0	-7.2
V	65.536	39.6	16	9.0	32.6	40.0	-7.4
V	81.920	40.7	16	7.0	31.7	40.0	-8.3
H	98.304	36.4	16	12.0	32.4	43.5	-11.1
H	114.688	34.0	16	14.0	32.0	43.5	-11.5

---

## INTERTEK TESTING SERVICES

---

### 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 5.0 **Product Labelling**

For electronics filing, the FCC ID and IC label artwork and the label location are saved with filename: label.pdf.

### 6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States and Canada.

### 8.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and measured bandwidth, calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

---

## INTERTEK TESTING SERVICES

---

### 8.1 Measured Bandwidth

From the following plots, they show that the fundamental emissions are confined in the specified band 2400MHz to 2483.5MHz. In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2003) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower and Upper edge Frequency (MHz)	Fundamental Emission - Average (dB $\mu$ V/m)	Delta from the plot (dB)	Resultant Field Strength (dB $\mu$ V/m)	Average Limited (dB $\mu$ V/m)	Margin (dB)
2400.000	74.9	40.8	34.1	54	-19.9
2483.500	75.1	43.3	31.8	54	-22.2

Lower and Upper edge Frequency (MHz)	Fundamental Emission - Peak (dB $\mu$ V/m)	Delta from the plot (dB)	Resultant Field Strength (dB $\mu$ V/m)	Peak Limited (dB $\mu$ V/m)	Margin (dB)
2400.000	92.7	40.8	51.9	74	-22.1
2483.500	92.9	43.3	49.6	74	-24.4

### 8.2 Discussion Pulse Desensitvity

Pulse desnesitivity is not applicable for this device. The effective period (Teff) is approximately 330 $\mu$ s for a ditital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse densensitivity factor is 0dB.

---

## INTERTEK TESTING SERVICES

---

### 8.3 Calculation of Average Factor

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 100 ms

Effective period of the cycle = 12.87

DC = 0.1287

Therefore, the averaging factor is found by  $20\log 0.1287 = -17.8\text{dB}$ .

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003. A typical or an unmodulated CW signal at the operating frequency of the EUT has been supplied to the EUT for all measurements. Such a signal is supplied by a signal generator and an antenna in close proximity to the EUT. The signal level is sufficient to stabilize the local oscillator of the EUT.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



## INTERTEK TESTING SERVICES

---

### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

## INTERTEK TESTING SERVICES

---

### 9.0 Equipment List

Equipment	EMI Test Receiver	Log Periodic Antenna	Biconical Antenna
Registration No.	EW-0014	EW-0446	EW-0571
Manufacturer	ROHDESCHWARZ	EMCO	EMCO
Model No.	ESVS30	3146	3104C
Calibration Date	Jun 01, 2009	Apr 26, 2010	Nov 12, 2008
Calibration Due Date	Jun 01, 2010	Oct 26, 2011	Aug 13, 2010

Equipment	Spectrum Analyzer	Double Ridged Guide Antenna	Spectrum Analyzer
Registration No.	EW-2188	EW-0194	EW-2249
Manufacturer	AGILENTTECH	EMCO	ROHDESCHWARZ
Model No.	E4407B	3115	FSP30
Calibration Date	Dec 25, 2009	Dec 24, 2008	Jun 25, 2009
Calibration Due Date	Dec 31, 2010	Jun 24, 2010	Jun 25, 2010