



Certification Report for WLAN 6220 Access Point Unit

FCC Part 15 & Industry Canada RSS-210

Document Number: KP000923-CR-RAD-03-01
Release Date: November 24, 2004

Prepared for: MTI Co., Ltd
166-10 Karak-Dong, Songpa-ku
Seoul
Korea, 138-810

Author: Denis Lalonde
Radio Compliance Discipline Leader

C-MAC Engineering Inc.
A Solectron Company
21 Richardson Side Road,
Kanata, Ontario, K2K 2C1
<http://www.solectrontechnicalctr.com/>

© Copyright C-MAC Engineering Inc. November 24, 2004

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

C-MAC Engineering Inc. accepts no liability for the content of this document except when it is reproduced in its entirety by a method acceptable to C-MAC Engineering Inc.

Release Control Record

This document is based on CEI document template KG000347-TR-EMC-03.

Release no.	Reason for change	Date released
01	Original Release	November 24, 2004

Approvals

Function	Name	Job title	Signature
Document Release Approval	Real Perriard	Project Manager	 Nov 23, 04
Author	Denis Lalonde	Radio Compliance Discipline Leader	 Nov 23, 2004
Technical Reviewer	Jacques Rollin	EMC Advisor	 Nov 23, 04

Accreditations

C-MAC Engineering test facilities are accredited by the Standards Council of Canada (SCC) in accordance with the scope of accreditation outlined at the following web site <http://www.scc.ca/scopes/reg126-eng-s.pdf>. [1]. The SCC is a member of the APLAC [13] and ILAC [14] organizations which, through mutual recognition arrangements, provide accreditation of test facilities in the member countries.



C-MAC Engineering is ISO 9001:2000 and ISO-IEC 17025 certified and its processes are documented in the C-MAC Engineering Quality Manual [2] and Lab Operations Manual [3].

Table of Contents

RELEASE CONTROL RECORD.....	2
APPROVALS	2
ACCREDITATIONS	2
TABLE OF CONTENTS	3
LIST OF FIGURES	5
LIST OF TABLES	7
1. EXECUTIVE SUMMARY.....	9
2. COMPLIANCE SUMMARY.....	10
3. EQUIPMENT UNDER TEST (EUT)	11
3.1 PRODUCT FUNCTIONAL DESCRIPTION	11
3.2 MANUFACTURER INFORMATION.....	11
3.3 TRANSMITTER SPECIFICATIONS.....	12
3.4 SYSTEM COMPONENTS	12
3.5 EUT INTERFACES AND CABLES	12
3.6 SUPPORT EQUIPMENT	12
3.7 SYSTEM SET-UP AND TEST CONFIGURATIONS	13
3.8 SYSTEM MODIFICATIONS	13
4. GENERAL TEST CONDITIONS	14
4.1 TEST FACILITY	14
4.2 MEASUREMENT INSTRUMENTATION.....	14
5. DETAILED TEST RESULTS.....	15
5.1 RF POWER	15
5.1.1 Test Specification	15
5.1.1.1 Limits	15
5.1.2 Test Facility Information	15
5.1.3 Test Procedure	15
5.1.4 Test Results.....	16
5.1.5 Test Conclusion	16
5.1.6 Test Equipment List.....	16
5.2 6 dB BANDWIDTH.....	16
5.2.1 Test Specification	16
5.2.2 Test Facility Information	17
5.2.3 Limits.....	17
5.2.4 Test Procedure	17
5.2.5 Test Results.....	17

5.2.6	Test Conclusion	17
5.2.7	Test Equipment List.....	18
5.3	PEAK POWER SPECTRAL DENSITY.....	18
5.3.1	Test Specification	18
5.3.1.1	Limits	18
5.3.2	Test Facility Information.....	18
5.3.3	Test Procedure	18
5.3.4	Test Results.....	19
5.3.5	Test Conclusion	19
5.3.6	Test Equipment List.....	19
5.4	CONDUCTED SPURIOUS EMISSIONS	20
5.4.1	Test Specification	20
5.4.1.1	Limits	20
5.4.2	Table 5-15Test Facility Information.....	20
5.4.3	Test Procedure	20
5.4.4	Test Results.....	20
5.4.5	Test Conclusion	21
5.4.6	Test Equipment List.....	21
5.5	FIELD STRENGTH OF SPURIOUS EMISSIONS	21
5.5.1	Test Specification	21
5.5.1.1	Limits	21
5.5.2	Test Facility Information.....	23
5.5.3	Test Procedure	23
5.5.4	Test Results.....	24
5.5.5	Calculation of the Compliance Margin.....	26
5.5.6	Test Conclusion	27
5.5.7	Test Equipment List.....	27
5.6	RECEIVER SPURIOUS EMISSIONS	28
5.6.1	Test Specification	28
5.6.1.1	Limits	28
5.6.2	Test Facility Information.....	28
5.6.3	Test Procedure	29
5.6.4	Test Results.....	29
5.6.5	Calculation of the Compliance Margin.....	30
5.6.6	Test Conclusion	30
5.6.7	Test Equipment List.....	31
5.7	RF EXPOSURE	31
5.7.1	Test Specification	31
5.7.1.1	Limits	31
5.7.2	RF Exposure Evaluation.....	31
5.7.3	Evaluation Conclusion.....	32
6.	REFERENCES	33

7. APPENDICES	35
7.1 APPENDIX A: GLOSSARY	35
7.2 APPENDIX B: TEST SET-UP PHOTOGRAPHS	36
7.3 APPENDIX C: 6 dB BANDWIDTH PLOTS	37
7.4 APPENDIX D: PEAK POWER SPECTRAL DENSITY PLOTS	39
7.5 APPENDIX E: CONDUCTED SPURIOUS EMISSIONS PLOTS	45
7.6 APPENDIX F: FIELD STRENGTH OF SPURIOUS EMISSIONS PLOTS	48

List of Figures

FIGURE 3-1 PRODUCT DESCRIPTION	11
FIGURE 3-2: EUT CONFIGURATION	13
FIGURE 7-1: WLAN 6220 ACCESS POINT UNIT RADIATED EMISSIONS SET-UP	36
FIGURE 7-2: 6 dB OCCUPIED BANDWIDTH, CHANNEL 1, 11 MBPS	37
FIGURE 7-3: 6 dB OCCUPIED BANDWIDTH, CHANNEL 6, 11 MBPS	37
FIGURE 7-4: 6 dB OCCUPIED BANDWIDTH, CHANNEL 11, 11 MBPS	38
FIGURE 7-5: PSD, CHANNEL 1, 1 MBPS	39
FIGURE 7-6: PSD, CHANNEL 1, 2 MBPS	39
FIGURE 7-7: PSD, CHANNEL 1, 5.5 MBPS	40
FIGURE 7-8: PSD, CHANNEL 1, 11 MBPS	40
FIGURE 7-9: PSD, CHANNEL 6, 1 MBPS	41
FIGURE 7-10: PSD, CHANNEL 6, 2 MBPS	41
FIGURE 7-11: PSD, CHANNEL 6, 5.5 MBPS	42
FIGURE 7-12: PSD, CHANNEL 6, 11 MBPS	42
FIGURE 7-13: PSD, CHANNEL 11, 1 MBPS	43
FIGURE 7-14: PSD, CHANNEL 11, 2 MBPS	43
FIGURE 7-15: PSD, CHANNEL 11, 5.5 MBPS	44
FIGURE 7-16: PSD, CHANNEL 11, 11 MBPS	44
FIGURE 7-17: CONDUCTED SPURIOUS EMISSIONS BETWEEN 30 MHZ AND 25 GHZ, CHANNEL 1, 1 MBPS	45
FIGURE 7-18: CONDUCTED SPURIOUS EMISSIONS AT 2400 MHZ, CHANNEL 1, 1 MBPS	45
FIGURE 7-19: CONDUCTED SPURIOUS EMISSIONS BETWEEN 30 MHZ AND 25 GHZ, CHANNEL 6, 1 MBPS	46
FIGURE 7-20: CONDUCTED SPURIOUS EMISSIONS BETWEEN 30 MHZ AND 25 GHZ, CHANNEL 11, 1 MBPS	46
FIGURE 7-21: CONDUCTED SPURIOUS EMISSIONS AT 2483.5 MHZ, CHANNEL 11, 1 MBPS	47

FIGURE 7-22: FIELD STRENGTH ON CHANNEL 1 (1 MBPS), 30 MHZ TO 1 GHZ (VERTICAL POLARIZATION).....	48
FIGURE 7-23: FIELD STRENGTH ON CHANNEL 1 (1 MBPS), 30 MHZ TO 1 GHZ (HORIZONTAL POLARIZATION).....	49
FIGURE 7-24: FIELD STRENGTH ON CHANNEL 1 (1 MBPS), 1 GHZ TO 12.5 GHZ (VERTICAL POLARIZATION).....	50
FIGURE 7-25: FIELD STRENGTH ON CHANNEL 1 (1 MBPS), 1 GHZ TO 12.5 GHZ (HORIZONTAL POLARIZATION).....	51
FIGURE 7-26: FIELD STRENGTH ON CHANNEL 1 (1 MBPS), 10GHZ TO 18 GHz (VERTICAL POLARIZATION).....	52
FIGURE 7-27: FIELD STRENGTH ON CHANNEL 1 (1 MBPS), 10 GHz TO 18 GHz (HORIZONTAL POLARIZATION).....	53
FIGURE 7-28: FIELD STRENGTH ON CHANNEL 1 (1 MBPS), 18 GHz TO 26 GHz (VERTICAL POLARIZATION).....	54
FIGURE 7-29: FIELD STRENGTH ON CHANNEL 1 (1 MBPS), 18 GHz TO 26 GHz (HORIZONTAL POLARIZATION).....	55
FIGURE 7-30: FIELD STRENGTH ON CHANNEL 6 (1 MBPS), 30 MHZ TO 1 GHZ (VERTICAL POLARIZATION).....	56
FIGURE 7-31: FIELD STRENGTH ON CHANNEL 6 (1 MBPS), 30 MHZ TO 1 GHZ (HORIZONTAL POLARIZATION).....	57
FIGURE 7-32: FIELD STRENGTH ON CHANNEL 6 (1 MBPS), 1 GHZ TO 12.5 GHZ (VERTICAL POLARIZATION).....	58
FIGURE 7-33: FIELD STRENGTH ON CHANNEL 6 (1 MBPS), 1 GHZ TO 12.5 GHZ (HORIZONTAL POLARIZATION).....	59
FIGURE 7-34: FIELD STRENGTH ON CHANNEL 6 (1 MBPS), 10GHz TO 18 GHz (VERTICAL POLARIZATION).....	60
FIGURE 7-35: FIELD STRENGTH ON CHANNEL 6 (1 MBPS), 10 GHz TO 18 GHz (HORIZONTAL POLARIZATION).....	61
FIGURE 7-36: FIELD STRENGTH ON CHANNEL 11 (1 MBPS), 30 MHZ TO 1 GHZ (VERTICAL POLARIZATION).....	64
FIGURE 7-37: FIELD STRENGTH ON CHANNEL 11 (1 MBPS), 30 MHZ TO 1 GHZ (HORIZONTAL POLARIZATION).....	65
FIGURE 7-38: FIELD STRENGTH ON CHANNEL 11 (1 MBPS), 1 GHZ TO 12.5 GHZ (VERTICAL POLARIZATION).....	66
FIGURE 7-39: FIELD STRENGTH ON CHANNEL 11 (1 MBPS), 1 GHZ TO 12.5 GHZ (HORIZONTAL POLARIZATION).....	67
FIGURE 7-40: FIELD STRENGTH ON CHANNEL 11 (1 MBPS), 10GHz TO 18 GHz (VERTICAL POLARIZATION).....	68
FIGURE 7-41: FIELD STRENGTH ON CHANNEL 11 (1 MBPS), 10 GHz TO 18 GHz (HORIZONTAL POLARIZATION).....	69

FIGURE 7-42: FIELD STRENGTH ON CHANNEL 11 (1 MBPS), 18 GHZ TO 26 GHZ (VERTICAL POLARIZATION).....	70
FIGURE 7-43: FIELD STRENGTH ON CHANNEL 11 (1 MBPS), 18 GHZ TO 26 GHZ (HORIZONTAL POLARIZATION).....	71
FIGURE 7-44: FIELD STRENGTH OF RECEIVER EMISSIONS, 30 MHZ TO 1 GHZ (VERTICAL POLARIZATION).....	72
FIGURE 7-45: FIELD STRENGTH OF RECEIVER EMISSIONS, 30 MHZ TO 1 GHZ (HORIZONTAL POLARIZATION).....	73
FIGURE 7-46: FIELD STRENGTH OF RECEIVER EMISSIONS, 1 GHZ TO 12.5 GHZ (VERTICAL POLARIZATION).....	74
FIGURE 7-47: FIELD STRENGTH OF RECEIVER EMISSIONS, 1 GHZ TO 12.5 GHZ (HORIZONTAL POLARIZATION).....	75

List of Tables

TABLE 2-1: COMPLIANCE RESULTS SUMMARY.....	10
TABLE 3-1: TRANSMITTER SPECIFICATIONS.....	12
TABLE 3-2: EUT COMPONENTS	12
TABLE 3-3: SYSTEM CABLES	12
TABLE 3-4: SUPPORT EQUIPMENT	12
TABLE 5-1: RF POWER REQUIREMENTS.....	15
TABLE 5-2: RF POWER LIMIT	15
TABLE 5-3: RF POWER LEVELS	16
TABLE 5-4: TEST EQUIPMENT USED FOR RF POWER	16
TABLE 5-5: OCCUPIED BANDWIDTH.....	16
TABLE 5-6: 6 dB OCCUPIED BANDWIDTH LIMIT.....	17
TABLE 5-7: OCCUPIED BANDWIDTH VALUES	17
TABLE 5-8: TEST EQUIPMENT USED FOR 6 dB OCCUPIED BANDWIDTH	18
TABLE 5-9: EMISSION MASK REQUIREMENT.....	18
TABLE 5-10: PEAK POWER SPECTRAL DENSITY LIMITS	18
TABLE 5-11: PEAK POWER SPECTRAL DENSITY RESULTS.....	19
TABLE 5-12: TEST EQUIPMENT USED FOR PEAK POWER SPECTRAL DENSITY	19
TABLE 5-13: CONDUCTED SPURIOUS EMISSIONS REQUIREMENT	20
TABLE 5-14: CONDUCTED SPURIOUS EMISSION LIMIT	20
5.4.2 TABLE 5-15 TEST FACILITY INFORMATION.....	20
TABLE 5-16: CONDUCTED SPURIOUS EMISSIONS	21
TABLE 5-17: TEST EQUIPMENT USED FOR CONDUCTED SPURIOUS EMISSIONS	21

TABLE 5-18: EMISSION MASK REQUIREMENT	21
TABLE 5-19: FIELD STRENGTH OF SPURIOUS EMISSIONS LIMIT	22
TABLE 5-20: E-FIELD RADIATED EMISSIONS WITH AVERAGE DETECTOR TEST RESULTS #1	25
TABLE 5-21: E-FIELD RADIATED EMISSIONS WITH AVERAGE DETECTOR TEST RESULTS #2	25
TABLE 5-22: E-FIELD RADIATED EMISSIONS WITH PEAK DETECTOR TEST RESULTS #1	26
TABLE 5-23: E-FIELD RADIATED EMISSIONS WITH PEAK DETECTOR TEST RESULTS #2	26
TABLE 5-24: TEST EQUIPMENT USED FOR FIELD STRENGTH OF SPURIOUS EMISSIONS.....	27
TABLE 5-25: EMISSION MASK REQUIREMENT	28
TABLE 5-26: TABLE 5-27: FIELD STRENGTH OF RECEIVER SPURIOUS EMISSIONS LIMIT	28
TABLE 5-28: E-FIELD RADIATED EMISSIONS TEST RESULTS (30-1000 MHZ, AVERAGE DETECTION)	30
TABLE 5-29: TEST EQUIPMENT USED FOR FIELD STRENGTH OF SPURIOUS EMISSIONS.....	31
TABLE 5-30: RF EXPOSURE REQUIREMENT	31
TABLE 5-31: RF EXPOSURE LIMIT	31
TABLE 5-32: EIRP CALCULATIONS	32
TABLE 5-33: RF EXPOSURE EVALUATION	32

1. Executive Summary

This test report documents the measurements performed on the WLAN 6220 Access Point Unit as part of a Original Equipment FCC and Industry Canada application.

The FCCID and Industry Canada certification number for this equipment are the following:

- FCCID: SM4-WCAP6220APU
- IC: 5340A-6220APU

On the basis of measurements performed in October and November 2004, the WLAN 6220 Access Point Unit is verified to be compliant with FCC Part 15 and Industry Canada RSS-210 requirements. The test data included in this report apply to the product titled above manufactured by MTI Co., Ltd. A detailed summary of compliance results is found in Table 2-1.

2. Compliance Summary

This section summarizes all the measurements performed on WLAN 6220 Access Point Unit and its compliance to FCC Part 15 and Industry Canada RSS-210.

Table 2-1: Compliance Results Summary

Product Summary					
Product Name:		WLAN 6220 Access Point Unit	Project Manager:		Real Perriard
Product Code:		6220	Measurements by :		D. Lalonde
Product Status:		GA	Date:		Oct. 29 to Nov. 12, 2004
Test Cases					
Performed	Description	Specification	Test Results		Notes
			Pass	Fail	
■	RF Power	FCC Part 15.247 b) 3) RSS-210 6.2.2 o) b)	■	□	
■	6 dB Bandwidth	FCC Part 15.247 a) 2)	■	□	
■	Peak Power Spectral Density	FCC Part 15.247 d) RSS-210 6.2.2 o) b)	■	□	
■	Conducted Spurious Emissions	FCC Part 15.247 c) RSS-210 6.2.2 o) e1)	■	□	
■	Field Strength of Spurious Emissions	FCC Part 15.247 c)	■	□	
■	Receiver Spurious Emissions	RSS-210 7.3	■	□	
□	AC Mains Conducted Emissions	FCC 2.1047 RSS-210 6.6 & 7.4	□	□	The equipment does not connect to public AC Mains
■	RF Exposure	FCC 1.1310 RSS-210 14.	■	□	

3. Equipment Under Test (EUT)


3.1 Product Functional Description

The product trade name of the unit tested was "WLAN 6220 Access Point Unit".

The Wireless LAN Cable Access Point 6220 is an outdoor hardened, strand-mountable access point solution designed to extend the reach of cable operators' hybrid fiber coax network utilizing wireless technologies from existing rights of way. This solution from Nortel Networks provides cable operators a fast, low-cost alternative for delivering service to new customers by eliminating the time, permitting, and construction costs associated with extending aerial or buried drops.

Figure 3-1 shows pictures of the tested product.

Figure 3-1 Product Description



3.2 Manufacturer Information

Company Name	MTI Co., Ltd
Mailing Address	166-10 Karak-Dong, Songpa-ku, Seoul, Korea, 138-810
Product Name	WLAN 6220 Access Point Unit

3.3 Transmitter Specifications

Table 3-1 lists the specifications of the transmitter under test.

Table 3-1: Transmitter Specifications

Transmitter Specifications	Values
Tx power	12.4 dBm
Tx frequency	2400 to 2483.5 MHz
Modulation	IEEE 802.11 b
Antenna gain	Panel Antenna (NTA.2407): 14 +/- 1 dBi Bi-directional Antenna (NTA.2412): 9 dBi (peak) Omni directional Antenna (NTA.2400): 7 dBi (typical)

3.4 System Components

The system tested consists of the following units, as shown in Table 3-2.

Table 3-2: EUT Components

Component	Model	Serial Number
WLAN Access Point Unit	6220 APU	NNTMDM000002

3.5 EUT Interfaces and Cables

The system contained the following interfaces, as shown in Table 3-3:

Table 3-3: System Cables

Interface Type	EUT Connection	Description	Type	Length	Qty
Power and data	Coaxial port	RG-6	Coaxial, 75 ohms	15 m	1

3.6 Support Equipment

The support equipment used for operation and monitoring of the EUT is described in Table 3-4.


Table 3-4: Support Equipment

Description	Manufacturer	Model Number
Server	Multimedia Computer System	MC-2001
CMTS	Cisco	MAS-uBR 7223
Power Inserter	ST	CA-1000
HFC power supply	Power Max	AX-1000TV

3.7 System Set-up and Test Configurations

The system configuration used for all test cases is presented in Figure 3-2.

Figure 3-2: EUT Configuration



A photograph of the test setup used in this test report is presented in Appendix B: Test Set-up Photographs, on page 36.

3.8 System Modifications

No modifications were required to pass the requirements.

4. General Test Conditions

4.1 Test Facility

Radiated emissions testing was performed in a 3-meter Ambient Free Chamber (AFC) located at the Electronics Test Centre MPB Technologies Inc., 302 Legget Drive, Kanata, Ontario, Canada. The AFC consists of a shielded room lined with ferrite tiles and RF absorbing material.

These test facilities are approved and registered by Industry Canada and the FCC.

4.2 Measurement Instrumentation

The measurement instrumentation conforms to ANSI C63.2 [5] and CISPR 16 [6]. Calibration of the measurement instrumentation is maintained in accordance with the supplier's recommendations, or as necessary to ensure its accuracy.

5. Detailed Test Results

5.1 RF Power

5.1.1 Test Specification

The system was tested to the requirements listed in Table 5-1:

Table 5-1: RF Power Requirements

Requirement	Part / Section
FCC	15.247 b) 3)
RSS-210	6.2.2 o) b)

5.1.1.1 Limits

The system was tested to the rated power of the EUT, listed in Table 5-2. In the case where transmitting antennas of directional gain greater than 6 dBi were used, the peak output power from the intentional radiator was reduced below 1W by the amount in dB that the directional gain of the antenna exceeded 6 dBi.

Table 5-2: RF Power Limit

Antenna	Power Reduction Because of Antenna Directional Gain	Power Limit
Panel Antenna (NTA.2407): 14 +/- 1 dBi	30 dBm - (15 - 6) dB	21 dBm
Bi-directional Antenna (NTA.2412): 9 dBi (peak)	30 dBm - (9 - 6) dB	27 dBm
Omni directional Antenna (NTA.2400): 7 dBi (typical)	30 dBm - (7 - 6) dB	29 dBm

The value used for the RF power limit is 21 dBm.

5.1.2 Test Facility Information

Location: Solelectron Technical Centre Lab 1

Date tested: October 29, 2004

Tested by: Denis Lalonde

5.1.3 Test Procedure

The RF output of the APU was connected to a power meter.

The RF signal was set at both extremities and in the middle of the frequency band. The power measurement was repeated for all the bit rate capabilities of the equipment.

5.1.4 Test Results

Test results are shown in Table 5-3.

Table 5-3: RF Power Levels

Channel (MHz)	RF Power at 1 Mbps (dBm)	RF Power at 2 Mbps (dBm)	RF Power at 5.5 Mbps (dBm)	RF Power at 11 Mbps (dBm)
2412 (channel 1)	12.0	11.2	10.2	9.7
2437 (channel 6)	12.2	11.4	10.4	9.9
2462 (channel 11)	12.3	11.5	10.5	10.0

5.1.5 Test Conclusion

The test results met the requirement.

5.1.6 Test Equipment List

Table 5-4: Test Equipment used for RF Power

Category	Manufacture	Model Number	Serial Number	Cal. Due
Power meter	Anritsu	M2438A	SSG012588	27 April 2005
Power sensor	Anritsu	M2424A	SSG012587	27 April 2005

The measurement instrumentation conforms to ANSI C63.2[5] and CISPR 16 [6].Calibration of the measurement instrumentation is maintained in accordance with the supplier's recommendations, or as necessary to ensure its accuracy.

5.2 6 dB Bandwidth

5.2.1 Test Specification

The system occupied bandwidth was evaluated according to the specifications listed in Table 5-5:

Table 5-5: Occupied Bandwidth

Requirement	Part / Section
FCC	15.247 a) 2)

5.2.2 Test Facility Information

Location: Solectron Technical Centre Lab 1
Date tested: October 29, 2004
Tested by: Denis Lalonde

5.2.3 Limits

The system was tested to the requirement listed in Table 5-6.

Table 5-6: 6 dB Occupied Bandwidth Limit

6 dB Occupied Bandwidth Limit
> 500 kHz

5.2.4 Test Procedure

Three occupied bandwidth measurements were performed at channel 1, 6, and 11. The bit rate used for the occupied bandwidth was 11 Mbps.

For all of these measurements, the RF port output was connected to the spectrum analyzer through a RF cable.

5.2.5 Test Results

Table 5-7 lists the occupied bandwidth calculated and measured:

Table 5-7: Occupied Bandwidth Values

Channel	Bandwidth (MHz)	Reference
1	10.5	Figure 7-2
6	10.3	Figure 7-3
11	10.2	Figure 7-4

5.2.6 Test Conclusion

The test results met the requirement.

5.2.7 Test Equipment List

Table 5-8: Test Equipment used for 6 dB Occupied Bandwidth

Category	Manufacture	Model	Description	Serial Number	Cal. Due
Spectrum analyzer	HP	8564E	40 GHz	3835A01346	28/04/2005

The measurement instrumentation conforms to ANSI C63.2[5]. Calibration of the measurement instrumentation is maintained in accordance with the supplier's recommendations, or as necessary to ensure its accuracy.

5.3 Peak Power Spectral Density

5.3.1 Test Specification

The system was tested to the limits of the requirements listed in Table 5-9:

Table 5-9: Emission Mask Requirement

Requirement	Part / Section
FCC	15.247 a) 2)

5.3.1.1 Limits

The specification levels in Table 5-10 were used.

Table 5-10: Peak Power Spectral Density Limits

Peak Power Spectral Density Limits
8 dBm in any 3 kHz

5.3.2 Test Facility Information

Location: Solelectron Technical Centre Lab 1

Date tested: October 29, 2004

Tested by: Denis Lalonde

5.3.3 Test Procedure

Peak power spectral density measurements were performed on channel 1, 6, and 11 for all 4 bit rates (1, 2, 5.5 and 11 Mbps).

For all of these measurements, the EUT RF output was connected to the spectrum analyzer through a calibrated RF cable.

5.3.4 Test Results

Table 5-11 lists the highest emissions measured:

Table 5-11: Peak Power Spectral Density Results

Channel	Bit rate (Mbps)	PSD (dBm)	Reference
1	1	-5.0	Figure 7-5
	2	-8.2	Figure 7-6
	5.5	-8.7	Figure 7-7
	11	-13.0	Figure 7-8
6	1	-6.5	Figure 7-9
	2	-10.2	Figure 7-10
	5.5	-8.3	Figure 7-11
	11	-12.2	Figure 7-12
11	1	-1.8	Figure 7-13
	2	-3.3	Figure 7-14
	5.5	-10.5	Figure 7-15
	11	-11.2	Figure 7-16

5.3.5 Test Conclusion

The test results met the requirement.

5.3.6 Test Equipment List

Table 5-12: Test Equipment used for Peak Power Spectral Density

Category	Manufacture	Model	Description	Serial Number	Cal. Due
Spectrum analyzer	HP	8564E	40 GHz	3835A01346	28/04/2005

The measurement instrumentation conforms to ANSI C63.2[5]. Calibration of the measurement instrumentation is maintained in accordance with the supplier's recommendations, or as necessary to ensure its accuracy.

5.4 Conducted Spurious Emissions

5.4.1 Test Specification

The system was tested to the limits of the requirements listed in Table 5-13:

Table 5-13: Conducted Spurious Emissions Requirement

Requirement	Part / Section
FCC 15	15.247 c)
RSS-210	6.2.2 o) e1)

5.4.1.1 Limits

The following specification levels are applicable to this test:

Table 5-14: Conducted Spurious Emission Limit

Frequency Range (MHz)	Limit (dBc)
0 to 24620	-20 dBc in any 100 kHz

5.4.2 Table 5-15 Test Facility Information

Location: Soletron Technical Centre Lab 1
Date tested: October 29, 2004
Tested by: Denis Lalonde

5.4.3 Test Procedure

Conducted spurious emissions were measured at channel 1, 6, and 11. The measurement was performed while the bit rate was set to 1 Mbps to maximize the level of transmitter harmonics.

The EUT output was connected to the spectrum analyzer through a calibrated RF cable.

5.4.4 Test Results

The test result are shown in Table 5-16.

Table 5-16: Conducted Spurious Emissions

Channel (MHz)	Results	Reference
2412 (channel 1)	-47.8 dBc at 290 MHz -37.5 dBc at 2398.08 MHz	Figure 7-17 & Figure 7-18
2437 (channel 6)	-47.0 dBc at 290 MHz	Figure 7-19
2462 (channel 11)	-49.0 dBc at 290 MHz -63.5 dBc at 2488.17MHz	Figure 7-20 & Figure 7-21

5.4.5 Test Conclusion

The test results met the requirement.

5.4.6 Test Equipment List

Table 5-17: Test Equipment used for Conducted Spurious Emissions

Category	Manufacture	Model Number	Description	Serial Number	Cal. Due
Spectrum analyzer	HP	8564E	40 GHz	3835A01346	28/04/2005

The measurement instrumentation conforms to ANSI C63.2[5] and CISPR 16 [6]. Calibration of the measurement instrumentation is maintained in accordance with the supplier's recommendations, or as necessary to ensure its accuracy.

5.5 Field Strength of Spurious Emissions

5.5.1 Test Specification

The system was tested to the limits of the following requirements:

Table 5-18: Emission Mask Requirement

Requirement	Part / Section
FCC Part 15	15.247 c)

5.5.1.1 Limits

The following specification levels are worst-case limits taken from all test specifications.

Table 5-19: Field Strength of Spurious Emissions Limit

Restricted Bands as per FCC Part 15.205	Radiated Emissions Limit at 10 m, AVG detection (dBuV/m)	Radiated Emissions Limit at 10 m, Peak detection (dBuV/m)
37.5–38.25 MHz	29.5	49.5
73–74.6 MHz	29.5	49.5
74.8–75.2 MHz	29.5	49.5
108–121.94 MHz	33.1	53.1
123–138 MHz	33.1	53.1
149.9–150.05 MHz	33.1	53.1
156.7–156.9 MHz	33.1	53.1
156.52475–156.52525 MHz	33.1	53.1
162.0125–167.17 MHz	33.1	53.1
167.72–173.2 MHz	33.1	53.1
240–285 MHz	35.6	55.6
322–335.4 MHz	35.6	55.6
399.9–410 MHz	35.6	55.6
608–614 MHz	35.6	55.6
960–1240 MHz	43.5	63.5
1300–1427 MHz	43.5	63.5
1435–1626.5 MHz	43.5	63.5
1645.5–1646.5 MHz	43.5	63.5
1660–1710 MHz	43.5	63.5
1718.8–1722.2 MHz	43.5	63.5
2200–2300 MHz	43.5	63.5
2310–2390 MHz	43.5	63.5
2483.5–2500 MHz	43.5	63.5
2655–2900 MHz	43.5	63.5
3260–3267 MHz	43.5	63.5
3332–3339 MHz	43.5	63.5
3345.8–3358 MHz	43.5	63.5
3600–4400 MHz	43.5	63.5
4.5–5.15 GHz	43.5	63.5
5.35–5.46 GHz	43.5	63.5
7.25–7.75 GHz	43.5	63.5

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Restricted Bands as per FCC Part 15.205	Radiated Emissions Limit at 10 m, AVG detection (dBuV/m)	Radiated Emissions Limit at 10 m, Peak detection (dBuV/m)
8.025–8.5 GHz	43.5	63.5
9.0–9.2 GHz	43.5	63.5
9.3–9.5 GHz	43.5	63.5
10.6–12.7 GHz	43.5	63.5
13.25–13.4 GHz	43.5	63.5
14.47–14.5 GHz	43.5	63.5
15.35–16.2 GHz	43.5	63.5
17.7–21.4 GHz	43.5	63.5
22.01–23.12 GHz	43.5	63.5
23.6–24.0 GHz	43.5	63.5

5.5.2 Test Facility Information

Location: Electronic Test Centre, MPB Technologies

Date tested: November 4 to November 9, 2004

Tested by: S. Drysdale

5.5.3 Test Procedure

The test was performed as per the relevant Test procedures: ANSI C63.4-2003 [4].

The system was tested in the following manner:

- The EUT was placed on a 80 cm high wooden table which was set on a turntable inside the AFC and it was configured as in normal operation. The cable routed up to a 2 m high wooden rack and then routed outside of the AFC where the EUTs support equipment was installed. The system was grounded in accordance with its normal installation specifications. No additional grounding connections are allowed.
- For tests between:
 - 30 MHz and 1 GHz, a broadband bilog antenna was placed at a 3 m distance;
 - 1 GHz and 2 GHz, a horn antenna, LNA, and a 1 GHz to 2 GHz band pass filter were placed at a 3 m distance.
 - 2 GHz and 3 GHz, a horn antenna, LNA (with 20 dB attenuator in front of it) were placed at a 3 m distance.
 - 3 GHz and 12.5 GHz, a horn antenna, LNA, and a 3 GHz high pass filter were placed at a 3 m distance.
 - 12.5 GHz and 26.5 GHz, a horn antenna and a LNA were placed at a 1 m distance.

- Between 30 MHz and 12.5 GHz, a pre-scan was performed to find emissions (frequencies) requiring detail measurement. The pre-scan was performed by rotating the system 360 degrees while recording all emissions (frequency and amplitude). This procedure was repeated for antenna heights of 1 to 4 meters, in steps of 1 meter, and for horizontal and vertical polarizations of the receiving antenna.
- Between 12.5 GHz 25 GHz, a pre-scan was performed to find emissions (frequencies) requiring detail measurement. The pre-scan was performed by rotating the system 360 degrees while recording all emissions (frequency and amplitude) at a antenna height of 1 meter. This procedure was repeated for horizontal and vertical polarizations of the receiving antenna. The search of emissions in this frequency range also included the manual sweeping of the test antenna around a 1 meter sphere that surrounds the EUT.
- Prescan optimization was performed based on the pre-scan data. All frequencies, having emission levels within 10 dB of the specification(s) limits, were optimized. For each such frequency, the EUT was rotated in azimuth over 360 degrees and the direction of maximum emission was noted. Antenna height was then varied from 1 to 4 meters at this azimuth to obtain maximum emissions. Then the maximum level measured was recorded.
- The frequency range investigated was 30 MHz to 26 GHz.
- Between 30 MHz and 1 GHz, a resolution bandwidth of 120 kHz was used.
- Above 1 GHz, a 1 MHz resolution bandwidth and 3 kHz video bandwidth were used.

The measurements were performed while the radio transmitted a 1 Mbps signal to maximize the level of transmitter harmonics. All test were repeated for operation on channel 1, 6, and 11.

The radiated emissions of all 3 antenna types (NTA.2407, NTA.2412, and NTA.2400) were compared. The radiated emissions shown in the test report are the highest that were observed. They were observed while the NTA.2407 panel antenna (14 +/- 1 dBi gain) was installed

Plots of the 30 MHz to 26 GHz prescan measurements are shown in Appendix F: Field Strength of Spurious Emissions Plots (Figure 7-22 to Figure 7-45).

5.5.4 Test Results

Table 5-20 to Table 5-23 list the highest emissions measured:

Table 5-20: E-field Radiated Emissions with Average Detector Test Results #1

Parameter	Unit	Channel 1	Channel 1	Channel 1	Channel 6	Channel 6	Channel 6
Frequency	(MHz)	2390	2483.5	2709.74	2390	2483.5	2723.55
Azimuth	(deg)	19	19	336	21	21	343
Height	(cm)	106	106	119	110	110	116
Polarization		Vert.	Vert.	Vert.	Vert.	Vert.	Vert.
Meter Reading	(dB μ V)	35.6	35.3	36.6	35.5	35.4	37.4
Detector	(Pk,QP,Av)	Av	Av	Av	Av	Av	Av
Gain / Loss Factor	(dB)	-22.7	-22.1	-20.9	-22.7	-22.1	-20.9
Transducer Factor	(dB)	30.3	30.6	31.1	30.3	30.6	31.1
Level	(dB μ V/m)	43.2	43.8	46.8	43.1	43.9	47.7
Margin to FCC Part 15	(dB)	10.8	10.2	7.2	10.9	10.1	6.3

Table 5-21: E-field Radiated Emissions with Average Detector Test Results #2

Parameter	Unit	Channel 11	Channel 11
Frequency	(MHz)	2390	2483.5
Azimuth	(deg)	66	281
Height	(cm)	358	365
Polarization		Vert.	Vert.
Meter Reading	(dB μ V)	38.2	38.1
Detector	(Pk,QP,Av)	Av	Av
Gain / Loss Factor	(dB)	-22.7	-22.1
Transducer Factor	(dB)	30.3	30.6
Level	(dB μ V/m)	45.8	46.6
Margin to FCC Part 15	(dB)	8.2	7.4

Table 5-22: E-field Radiated Emissions with Peak Detector Test Results #1

Parameter	Unit	Channel 1	Channel 1	Channel 1	Channel 6	Channel 6	Channel 6
Frequency	(MHz)	2390	2483.5	2709.74	2390	2483.5	2723.55
Azimuth	(deg)	19	19	336	21	21	343
Height	(cm)	106	106	119	110	110	116
Polarization		Vert.	Vert.	Vert.	Vert.	Vert.	Vert.
Meter Reading	(dB μ V)	50.0	48.4	49.9	49.3	48.9	50.5
Detector	(Pk,QP,Av)	Pk	Pk	Pk	Pk	Pk	Pk
Gain / Loss Factor	(dB)	-22.7	-22.1	-20.9	-22.7	-22.1	-20.9
Transducer Factor	(dB)	30.3	30.6	31.1	30.3	30.6	31.1
Level	(dB μ V/m)	57.6	56.9	60.1	56.9	57.4	60.8
Margin to FCC Part 15	(dB)	16.4	17.1	13.9	17.1	16.6	13.2

Table 5-23: E-field Radiated Emissions with Peak Detector Test Results #2

Parameter	Unit	Channel 11	Channel 11
Frequency	(MHz)	2390	2483.5
Azimuth	(deg)	66	281
Height	(cm)	358	365
Polarization		Vert.	Vert.
Meter Reading	(dB μ V)	48.5	52.0
Detector	(Pk,QP,Av)	Pk	Pk
Gain / Loss Factor	(dB)	-22.7	-22.1
Transducer Factor	(dB)	30.3	30.6
Level	(dB μ V/m)	56.1	60.5
Margin to FCC Part 15	(dB)	17.9	13.5

5.5.5 Calculation of the Compliance Margin

The following illustrates the manner in which the compliance margin is calculated in the “E-field Radiated Emissions Test Results” table(s) from Section 5.5.4 above.

The rows in these tables are defined as follows:

Meter Reading (dBmV) = Voltage measured using the spectrum analyzer with quasi-peak adapter

Gain/Loss Factor (dB) =	Cumulative gain or loss of pre-amplifier and cables used in the measurement path (a negative value indicates gain)
Transducer Factor (dB) =	Antenna factor
Level (dBmV/m) =	Corrected value or field strength, i.e., the parameter of interest that is compared to the limit
Margin (dB) =	Level with respect to the appropriate limit (a positive Margin indicates that the Level is below the limit and that the measurement is a PASS)

The values in the **Level** row are calculated as follows:

$$\text{Level} = \text{Meter Reading} + \text{Gain/Loss Factor} + \text{Transducer Factor}$$

The values in the **Margin** row are calculated as follows:

$$\text{Margin} = \text{Limit} - \text{Level}$$

5.5.6 Test Conclusion

The test results met the requirement.

5.5.7 Test Equipment List

Table 5-24: Test Equipment used for Field Strength of Spurious Emissions

Description	Manufacture	Model	Asset Number	Cal. Due
Spectrum Analyzer	HP	8566B	2747A05484	23-Jul-05
Quasi-Peak Adapter	HP	85650A	2811A01123	20-Jul-05
Bilog Antenna	Antenna Research	LPB 2520A	5078	Aug-05
Ridged Horn Antenna	Electro Metrics	RGA-60	2966	23-Dec-04
LNA (10 kHz to 20 GHz)	ETC MPB		2316	19-Jul-05
20 dB attenuator	Tenuline	8343-200	291	31-Dec-04
1-2 GHz Band Pass Filter	HP	8430A	SSG012120	13-Oct-05
3 GHz High Pass Filter	Micro Circuits	H3G020G1	SSG012728	31-Aug-05
Horn Antenna (18 - 26.5 GHz)	Emco	3160-09	SSG012292	29-Dec-04
Pre-Amplifier	Narda DBS Microwave	DB95-0040R	SSG012296	29-Dec-04

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Description	Manufacture	Model	Asset Number	Cal. Due
Spectrum Analyzer- portable	HP	8564E	SSG012069	28-Apr-05

The measurement instrumentation conforms to ANSI C63.2[5] and CISPR 16 [6]. Calibration of the measurement instrumentation is maintained in accordance with the supplier's recommendations, or as necessary to ensure its accuracy.

5.6 Receiver Spurious Emissions

5.6.1 Test Specification

The system was tested to the limits of the following requirements:

Table 5-25: Emission Mask Requirement

Requirement	Part / Section
RSS-210	7.3

5.6.1.1 Limits

The following specification levels are worst-case limits taken from all test specifications.

Table 5-26: Table 5-27: Field Strength of Receiver Spurious Emissions Limit

Frequency (MHz)	RSS 210 Table 3 requirement (dBuV/m)
30 – 88	40
88 – 216	43.5
216 – 960	46
960 – 1610	54.0
1610 – 12310	60.0

5.6.2 Test Facility Information

Location: Electronic Test Centre, MPB Technologies

Date tested: November 4 to 9, 2004

Tested by: Dan Zanette

5.6.3 Test Procedure

The test was performed as per the relevant Test procedures: ANSI C63.4-2003 [4].

The system was tested in the following manner:

- The EUT was placed on a 80 cm high wooden table which was set on a turntable inside the AFC and it was configured as in normal operation. The cable routed up to a 2 m high wooden rack and then routed outside of the AFC where the EUTs support equipment was installed. The system was grounded in accordance with its normal installation specifications. No additional grounding connections were installed.
- For tests between:
 - 30 MHz and 1 GHz, a broadband bilog antenna was placed at a 3 m distance;
 - 1 GHz and 12.5 GHz, a horn antenna and a LNA were placed at a 3 m distance.
- A pre-scan was performed to find emissions (frequencies) requiring detail measurement. The pre-scan (using a peak detector) was performed by rotating the system 360 degrees while recording all emissions (frequency and amplitude). This procedure was repeated for antenna heights of 1 to 4 meters, in steps of 1 meter, and for horizontal and vertical polarizations of the receiving antenna.
- Prescan optimization was performed based on the pre-scan data. All frequencies, having emission levels within 10 dB of the specification(s) limits, were optimized. For each such frequency, the EUT was rotated in azimuth over 360 degrees and the direction of maximum emission was noted. Antenna height was then varied from 1 to 4 meters at this azimuth to obtain maximum emissions. The procedure was repeated for both horizontal and vertical polarizations of the search antenna. Then the maximum level measured was recorded.
- The frequency range investigated was 30 MHz to 12.5 GHz.
- Between 30 MHz and 1 GHz, a resolution bandwidth of 120 kHz was used.
- Above 1 GHz, a 1 MHz resolution bandwidth and 3 kHz video bandwidth were used.

The measurements were performed while the radio was setup in receive/standby mode. The panel antenna (14 dBi gain) was used because it is the antenna with the highest gain.

Plots of the 30 MHz to 12.5 GHz prescan measurements are shown in Appendix F: Field Strength of Spurious Emissions Plots (Figure 7-46 to Figure 7-49).

5.6.4 Test Results

Table 5-28 lists the highest emissions measured:

Table 5-28: E-field Radiated Emissions Test Results (30-1000 MHz, average detection)

Parameter	Unit	Emission 1	Emission 2	Emission 3
Frequency	(MHz)	873.884	929.366	929.366
Azimuth	(deg)	278	155	25
Height	(cm)	400	100	200
Polarization		Horz	Horz	Vert
Meter Reading	(dB μ V)	31.5	32.5	31.7
Detector	(Pk, QP, Av)	Pk	Pk	Pk
Gain / Loss Factor	(dB)	-23.1	-22.6	-22.6
Transducer Factor	(dB)	21.6	21.9	22.6
Level	(dB μ V/m)	30	31.7	31.7
Margin to FCC Part 15	(dB)	16.0	14.3	14.3

5.6.5 Calculation of the Compliance Margin

The following illustrates the manner in which the compliance margin is calculated in the “E-field Radiated Emissions Test Results” table(s) from Section 5.6.4 above.

The rows in these tables are defined as follows:

Meter Reading (dBmV) = Voltage measured using the spectrum analyzer with quasi-peak adapter

Gain/Loss Factor (dB) = Cumulative gain or loss of pre-amplifier and cables used in the measurement path (a negative value indicates gain)

Transducer Factor (dB) = Antenna factor

Level (dBmV/m) = Corrected value or field strength, i.e., the parameter of interest that is compared to the limit

Margin (dB) = Level with respect to the appropriate limit (a positive **Margin** indicates that the **Level** is below the limit and that the measurement is a PASS)

The values in the **Level** row are calculated as follows:

$$\text{Level} = \text{Meter Reading} + \text{Gain/Loss Factor} + \text{Transducer Factor}$$

The values in the **Margin** row are calculated as follows:

$$\text{Margin} = \text{Limit} - \text{Level}$$

5.6.6 Test Conclusion

The test results met the requirement.

5.6.7 Test Equipment List

Table 5-29: Test Equipment used for Field Strength of Spurious Emissions

Description	Manufacture	Model	Asset Number	Cal. Due
Spectrum Analyzer	HP	8566B	2747A05484	23-Jul-05
Quasi-Peak Adapter	HP	85650A	2811A01123	20-Jul-05
Bilog Antenna	Antenna Research	LPB 2520A	5078	Aug-05
Ridged Horn Antenna	Electro Metrics	RGA-60	2966	23-Dec-04
LNA (10 kHz to 20 GHz)	ETC MPB		2316	19-Jul-05

The measurement instrumentation conforms to ANSI C63.2[5] and CISPR 16 [6]. Calibration of the measurement instrumentation is maintained in accordance with the supplier's recommendations, or as necessary to ensure its accuracy.

5.7 RF Exposure

5.7.1 Test Specification

The system was tested to the limits of the following requirement:

Table 5-30: RF Exposure Requirement

Requirement	Part / Section
FCC Part 1	1.1310
RSS-210	14.

RSS-210 makes reference to the RSS-102 [17] requirements.

5.7.1.1 Limits

The specification levels are listed in Table 5-31.

Table 5-31: RF Exposure Limit

Frequency Range (MHz)	FCC and Industry Canada General Exposure Limit (mW/cm ²)
2412 to 2462	1.0

5.7.2 RF Exposure Evaluation

Table 5-31 and Table 5-32 demonstrate the results of RF exposure calculations:

Table 5-32: EIRP Calculations

Peak Power (W)	Antenna gain			EIRP (W)		
	NTA2412 antenna	NTA2407 antenna	NTA2400 antenna	NTA2412 antenna	NTA2407 antenna	NTA2400 antenna
0.0174 (12.3 dBm)	31.6 (15 dBi)	7.9 (9 dBi)	5 (7 dBi)	0.54 (27.3 dBm)	0.13 (21.3 dBm)	0.09 (19.3 dBm)

Table 5-33: RF Exposure Evaluation

Power Density at 20 cm (mW/cm ²)			FCC and Industry Canada RF Exposure limit (mW/cm ²)
NTA2412 antenna	NTA2407 antenna	NTA2400 antenna	
0.11	0.026	0.018	1

The power density was calculated using the following equation.

$$S = (P \times G) / (4 \times \pi \times R^2)$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

5.7.3 Evaluation Conclusion

The test results met the requirement.

6. References

1. Standards Council of Canada Scope of Accreditation Letter SCC 1003-15/163 dated 2002-12-16 (Scope of accreditation is effective until 2005-10-05 and includes FCC Part 15 and ICES-003). This scope of accreditation is outlined at the following web site <http://www.scc.ca/scopes/reg126-eng-s.pdf>.
2. C-MAC Engineering Inc. Quality Manual, K0000608-QD-QM-01-05, March 2003.
3. C-MAC Engineering Inc. Lab Operations Manual KG000347-QD-LAB-01-03, January 2003.
4. ANSI C63.4-2003, Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz, January 2004.
5. ANSI C63.2-1996, American National Standard for Electromagnetic Noise and Field Strength Instrumentation, 10 Hz to 40 GHz – Specifications.
6. CISPR 16-1, Specification for Radio Disturbance and Immunity Measuring Apparatus and Methods - Part 1: Radio Disturbance and Immunity Measuring Apparatus, Edition 2.0, 1999-10.
7. C-MAC Engineering Inc., EMC General Lab Test Procedure, KP000270-LP-EMC-01-04 July 2004.
8. FCC Rules for Radio Frequency Devices, Title 47 of the Code of Federal Regulations), Part 1, U.S. Federal Communications Commission.
9. FCC Rules for Radio Frequency Devices, Title 47 of the Code of Federal Regulations), Part 2, U.S. Federal Communications Commission.
10. FCC Rules for Radio Frequency Devices, Title 47 of the Code of Federal Regulations), Part 15, U.S. Federal Communications Commission.
11. RSS-210, Issue 5, “Low Power License-Exempt Radiocommunication Devices (All Frequency Bands)”, November, 2001.
12. VCCI, V-3/02.04 16th edition, April 2002. Title: AGREEMENT OF VOLUNTARY CONTROL COUNCIL FOR INTERFERENCE BY INFORMATION TECHNOLOGY EQUIPMENT
13. APLAC, Asia Pacific Laboratory Accreditation Cooperation, Website (February 10th, 2004): <http://www.aplac.org>.
14. ILAC, International Laboratory Accreditation Cooperation, Website (February 10th, 2004): <http://www.ilac.org/>
15. Industry Canada, RSS 212, Test Facilities and Test Methods for Radio Equipment, Issue 1 (Provisional), February 27, 1999.
16. NAMAS Publication NIS 81: “The Treatment of Uncertainty in EMC Measurements”, Edition 1, May 1994.

17. RSS-102, Issue 1 (Provisional), Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields, September 25, 1999.

7. Appendices


7.1 Appendix A: Glossary

Included below are definitions and abbreviations of terms used in this document.

Term	Definition
AC	Alternating Current
AFC	Ambient Free Chamber
AM	Amplitude modulation
ANSI	American National Standards Institute
AVG	Average detector
CISPR	Comité International Spécial Perturbation Radioélectrique (International Special Committee on Radio Interference)
Class A	Class A Limits for typical commercial establishments
Class B	Class B Limits for typical domestic and residential establishments
dB	Decibel
EMC	Electromagnetic Compatibility
EMI	Electromagnetic Interference
EN	European Normative
EUT	Equipment Under Test
FCC	Federal Communications Commission, USA
GND	Ground
IC	Industry Canada
PA	Broadband Power Amplifier
RBW	Resolution Bandwidth
RF	Radio-Frequency
RFI	Radio-Frequency Interference
SCC	Standards Council of Canada

7.2 Appendix B: Test Set-up Photographs

Figure 7-1: WLAN 6220 Access Point Unit radiated emissions set-up



7.3 Appendix C: 6 dB Bandwidth Plots

This appendix presents all occupied bandwidth plots for the test cases measured.

Figure 7-2: 6 dB Occupied Bandwidth, Channel 1, 11 Mbps




Figure 7-3: 6 dB Occupied Bandwidth, Channel 6, 11 Mbps





Figure 7-4: 6 dB Occupied Bandwidth, Channel 11, 11 Mbps



7.4 Appendix D: Peak Power Spectral Density plots

This appendix presents all peak power spectral density plots for the test cases measured.

Figure 7-5: PSD, Channel 1, 1 Mbps




Figure 7-6: PSD, Channel 1, 2 Mbps




Figure 7-7: PSD, Channel 1, 5.5 Mbps




Figure 7-8: PSD, Channel 1, 11 Mbps




Figure 7-9: PSD, Channel 6, 1 Mbps




Figure 7-10: PSD, Channel 6, 2 Mbps




Figure 7-11: PSD, Channel 6, 5.5 Mbps




Figure 7-12: PSD, Channel 6, 11 Mbps






Figure 7-13: PSD, Channel 11, 1 Mbps**Figure 7-14: PSD, Channel 11, 2 Mbps**

Figure 7-15: PSD, Channel 11, 5.5 Mbps





Figure 7-16: PSD, Channel 11, 11 Mbps



7.5 Appendix E: Conducted Spurious Emissions Plots

Figure 7-17: Conducted Spurious Emissions Between 30 MHz and 25 GHz, Channel 1, 1 Mbps




Figure 7-18: Conducted Spurious Emissions at 2400 MHz, Channel 1, 1 Mbps




Figure 7-19: Conducted Spurious Emissions Between 30 MHz and 25 GHz, Channel 6, 1 Mbps




Figure 7-20: Conducted Spurious Emissions Between 30 MHz and 25 GHz, Channel 11, 1 Mbps






Figure 7-21: Conducted Spurious Emissions at 2483.5 MHz, Channel 11, 1 Mbps

7.6 Appendix F: Field Strength of Spurious Emissions Plots


This appendix presents all field strength plots for the test cases measured.

Figure 7-22: Field Strength on Channel 1 (1 Mbps), 30 MHz to 1 GHz (Vertical Polarization)




Note: the 924 MHz signal is outside the restricted bands identified in FCC Part 15.205

Figure 7-23: Field Strength on Channel 1 (1 Mbps), 30 MHz to 1 GHz (Horizontal Polarization)




The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-24: Field Strength on Channel 1 (1 Mbps), 1 GHz to 12.5 GHz (Vertical Polarization)




The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.


Figure 7-25: Field Strength on Channel 1 (1 Mbps), 1 GHz to 12.5 GHz (Horizontal Polarization)

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-26: Field Strength on Channel 1 (1 Mbps), 10GHz to 18 GHz (Vertical Polarization)



The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-27: Field Strength on Channel 1 (1 Mbps), 10 GHz to 18 GHz (Horizontal Polarization)

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-28: Field Strength on Channel 1 (1 Mbps), 18 GHz to 26 GHz (Vertical Polarization)






Figure 7-29: Field Strength on Channel 1 (1 Mbps), 18 GHz to 26 GHz (Horizontal Polarization)


The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-30: Field Strength on Channel 6 (1 Mbps), 30 MHz to 1 GHz (Vertical Polarization)



Note: the 924 MHz signal is outside the restricted bands identified in FCC Part 15.205

Figure 7-31: Field Strength on Channel 6 (1 Mbps), 30 MHz to 1 GHz (Horizontal Polarization)



The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-32: Field Strength on Channel 6 (1 Mbps), 1 GHz to 12.5 GHz (Vertical Polarization)







Figure 7-33: Field Strength on Channel 6 (1 Mbps), 1 GHz to 12.5 GHz (Horizontal Polarization)

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-34: Field Strength on Channel 6 (1 Mbps), 10GHz to 18 GHz (Vertical Polarization)



The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-35: Field Strength on Channel 6 (1 Mbps), 10 GHz to 18 GHz (Horizontal Polarization)

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-36: Field Strength on Channel 6 (1 Mbps), 18GHz to 26 GHz (Vertical Polarization)







Figure 7-37: Field Strength on Channel 6 (1 Mbps), 18 GHz to 26 GHz (Horizontal Polarization)

Figure 7-38: Field Strength on Channel 11 (1 Mbps), 30 MHz to 1 GHz (Vertical Polarization)



Note: the 924 MHz signal is outside the restricted bands identified in FCC Part 15.205

Figure 7-39: Field Strength on Channel 11 (1 Mbps), 30 MHz to 1 GHz (Horizontal Polarization)

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-40: Field Strength on Channel 11 (1 Mbps), 1 GHz to 12.5 GHz (Vertical Polarization)





Figure 7-41: Field Strength on Channel 11 (1 Mbps), 1 GHz to 12.5 GHz (Horizontal Polarization)

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-42: Field Strength on Channel 11 (1 Mbps), 10GHz to 18 GHz (Vertical Polarization)





Figure 7-43: Field Strength on Channel 11 (1 Mbps), 10 GHz to 18 GHz (Horizontal Polarization)

Figure 7-44: Field Strength on Channel 11 (1 Mbps), 18 GHz to 26 GHz (Vertical Polarization)





Figure 7-45: Field Strength on Channel 11 (1 Mbps), 18 GHz to 26 GHz (Horizontal Polarization)

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

Figure 7-46: Field Strength of Receiver Emissions, 30 MHz to 1 GHz (Vertical Polarization)






Figure 7-47: Field Strength of Receiver Emissions, 30 MHz to 1 GHz (Horizontal Polarization)




Note: the emission at 829 MHz was caused by the use of a cellular telephone in the vicinity of the test equipment. That signal couldn't be maximized because it was an intermittent ambient signal.

Figure 7-48: Field Strength of Receiver Emissions, 1 GHz to 12.5 GHz (Vertical Polarization)



Note: the RSS-210 limit is 60 dB_{Up}/m from 1610 MHz to 12310 MHz

Figure 7-49: Field Strength of Receiver Emissions, 1 GHz to 12.5 GHz (Horizontal Polarization)

Note: the RSS-210 limit is 60 dBm/m from 1610 MHz to 12310 MHz

**C-MAC ENGINEERING INC.
A Solectron Company**

**Certification Report for WLAN 6220 Access Point Unit
FCC Part 15 & Industry Canada RSS-210**

© Copyright C-MAC Engineering Inc. November 24, 2004

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.

C-MAC Engineering Inc. accepts no liability for the content of this document except when it is reproduced in its entirety by a method acceptable to C-MAC Engineering Inc.

The master of this document is stored on an electronic database and is "write-protected" and may be altered only by authorized persons at C-MAC Engineering Inc.. Viewing of the master document electronically ensures access to the current issue. Any hard copies must be regarded as uncontrolled copies.