





FCC RF Exposure Report

FCC ID : SQG-MT320

Equipment : WiFi 6 + Bluetooth 5.3 Module

Model No. : Sona MT320

Brand Name : Laird Connectivity

Applicant : Laird Connectivity LLC

Address : W66N220 Commerce Court, Cedarburg, WI

53012 United States Of America

Standard : 47 CFR FCC Part 2.1091

Received Date : Sep. 25, 2023

Tested Date : Oct. 17 ~ Dec. 08, 2023

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chel // Assistant Manager

Gary Chanġ / Manager、

Report No.: FA392501 Page: 1 of 6
Report Version: Rev. 01



Table of Contents

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	
1.2	MPE EVALUATION FORMULA	4
1.3	REFERENCE GUIDANCE	4
1.4	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	4
1.5	MEASUREMENT UNCERTAINTY	4
1.6	MPE EVALUATION RESULTS	5
_	TEGT LADORATORY INFORMATION	_
2	TEST LABORATORY INFORMATION	

Report No.: FA392501 Report Version: Rev. 01



Release Record

Report No.	Version	Description	Issued Date
FA392501	Rev. 01	Initial issue	Jan. 23, 2024

Report No.: FA392501 Page: 3 of 6



1 MPE EVALUATION OF MOBILE DEVICES

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)		
300~1500	F/1500	30		
1500~100000	1.0	30		

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

1.3 REFERENCE GUIDANCE

447498 D01 General RF Exposure Guidance v06

1.4 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

1.5 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Parameters	Uncertainty			
Conducted power	±0.808 dB			

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FA392501 Page: 4 of 6



1.6 **MPE EVALUATION RESULTS**

Non-beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	*Ratio	Pass / Fail
WLAN	WLAN							
2412-2462	22.04	22.5	2.4	20	0.061	1	0.061	Pass
5180-5240	20.26	20.5	4.4	20	0.061	1	0.061	Pass
5260-5320	20.21	20.5	4.4	20	0.061	1	0.061	Pass
5500-5720	22.56	23.0	4.4	20	0.109	1	0.109	Pass
5745-5825	22.78	23.0	4.4	20	0.109	1	0.109	Pass
ВТ								
2402-2480	7.21	7.5	2.4	20	0.002	1	0.002	Pass

^{*}Ratio = Power density / Limit.

Beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	*Ratio	Pass / Fail
2412-2462	16.07	16.5	5.41	20	0.031	1	0.031	Pass
5180-5240	17.07	17.5	7.41	20	0.062	1	0.062	Pass
5260-5320	17.20	17.5	7.41	20	0.062	1	0.062	Pass
5500-5720	19.55	20.0	7.41	20	0.110	1	0.110	Pass
5745-5825	19.77	20.0	7.41	20	0.110	1	0.110	Pass

^{*}Ratio = Power density / Limit.

Remarks:

For 2412~2462MHz: Directional gain = 2.4+10* log(2/1)=5.41 dBi

For 5180~5825MHz:

Directional gain = $4.4+10* \log(2/1)=7.41 \text{ dBi}$

Report No.: FA392501 Page: 5 of 6



2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No.30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan (R.O.C.)

Kwei Shan

Tel: 886-3-271-8666
No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640 No.14-1, Lane 19, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

__END__

Report No.: FA392501 Page: 6 of 6