



Modulation	ax HE40 RU242	Test Freq. (MHz)	5310																																																												
Polarization	Vertical																																																														
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																															
Level (dBuV/m) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>7080.00</td><td>47.56</td><td>68.20</td><td>-20.64</td><td>42.87</td><td>4.69</td><td>Peak</td><td>100</td><td>41</td></tr><tr><td>2</td><td>10620.00</td><td>41.34</td><td>54.00</td><td>-12.66</td><td>33.77</td><td>7.57</td><td>Average</td><td>100</td><td>102</td></tr><tr><td>3</td><td>10620.00</td><td>54.75</td><td>74.00</td><td>-19.25</td><td>47.18</td><td>7.57</td><td>Peak</td><td>100</td><td>102</td></tr><tr><td>4</td><td>15930.00</td><td>41.77</td><td>54.00</td><td>-12.23</td><td>37.46</td><td>4.31</td><td>Average</td><td>100</td><td>212</td></tr><tr><td>5</td><td>15930.00</td><td>55.39</td><td>74.00</td><td>-18.61</td><td>51.08</td><td>4.31</td><td>Peak</td><td>100</td><td>212</td></tr></tbody></table> Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	7080.00	47.56	68.20	-20.64	42.87	4.69	Peak	100	41	2	10620.00	41.34	54.00	-12.66	33.77	7.57	Average	100	102	3	10620.00	54.75	74.00	-19.25	47.18	7.57	Peak	100	102	4	15930.00	41.77	54.00	-12.23	37.46	4.31	Average	100	212	5	15930.00	55.39	74.00	-18.61	51.08	4.31	Peak	100	212
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																						
1	7080.00	47.56	68.20	-20.64	42.87	4.69	Peak	100	41																																																						
2	10620.00	41.34	54.00	-12.66	33.77	7.57	Average	100	102																																																						
3	10620.00	54.75	74.00	-19.25	47.18	7.57	Peak	100	102																																																						
4	15930.00	41.77	54.00	-12.23	37.46	4.31	Average	100	212																																																						
5	15930.00	55.39	74.00	-18.61	51.08	4.31	Peak	100	212																																																						



Modulation	ax HE40 RU242	Test Freq. (MHz)	5510																																																												
Polarization	Horizontal																																																														
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																															
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>7346.67</td><td>37.28</td><td>54.00</td><td>-16.72</td><td>32.21</td><td>5.07</td><td>Average</td><td>100</td><td>55</td></tr><tr><td>2</td><td>7346.67</td><td>50.36</td><td>74.00</td><td>-23.64</td><td>45.29</td><td>5.07</td><td>Peak</td><td>100</td><td>55</td></tr><tr><td>3</td><td>11020.00</td><td>40.25</td><td>54.00</td><td>-13.75</td><td>32.71</td><td>7.54</td><td>Average</td><td>100</td><td>149</td></tr><tr><td>4</td><td>11020.00</td><td>55.34</td><td>74.00</td><td>-18.66</td><td>47.80</td><td>7.54</td><td>Peak</td><td>100</td><td>149</td></tr><tr><td>5</td><td>16530.00</td><td>59.14</td><td>68.20</td><td>-9.06</td><td>52.92</td><td>6.22</td><td>Peak</td><td>100</td><td>220</td></tr></tbody></table> Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	7346.67	37.28	54.00	-16.72	32.21	5.07	Average	100	55	2	7346.67	50.36	74.00	-23.64	45.29	5.07	Peak	100	55	3	11020.00	40.25	54.00	-13.75	32.71	7.54	Average	100	149	4	11020.00	55.34	74.00	-18.66	47.80	7.54	Peak	100	149	5	16530.00	59.14	68.20	-9.06	52.92	6.22	Peak	100	220
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																						
1	7346.67	37.28	54.00	-16.72	32.21	5.07	Average	100	55																																																						
2	7346.67	50.36	74.00	-23.64	45.29	5.07	Peak	100	55																																																						
3	11020.00	40.25	54.00	-13.75	32.71	7.54	Average	100	149																																																						
4	11020.00	55.34	74.00	-18.66	47.80	7.54	Peak	100	149																																																						
5	16530.00	59.14	68.20	-9.06	52.92	6.22	Peak	100	220																																																						



Modulation	ax HE40 RU242	Test Freq. (MHz)	5510																																																												
Polarization	Vertical																																																														
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																															
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>7346.67</td><td>37.14</td><td>54.00</td><td>-16.86</td><td>32.07</td><td>5.07</td><td>Average</td><td>100</td><td>35</td></tr><tr><td>2</td><td>7346.67</td><td>50.38</td><td>74.00</td><td>-23.62</td><td>45.31</td><td>5.07</td><td>Peak</td><td>100</td><td>35</td></tr><tr><td>3</td><td>11020.00</td><td>40.59</td><td>54.00</td><td>-13.41</td><td>33.05</td><td>7.54</td><td>Average</td><td>100</td><td>142</td></tr><tr><td>4</td><td>11020.00</td><td>54.03</td><td>74.00</td><td>-19.97</td><td>46.49</td><td>7.54</td><td>Peak</td><td>100</td><td>142</td></tr><tr><td>5</td><td>16530.00</td><td>59.61</td><td>68.20</td><td>-8.59</td><td>53.39</td><td>6.22</td><td>Peak</td><td>100</td><td>182</td></tr></tbody></table> Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	7346.67	37.14	54.00	-16.86	32.07	5.07	Average	100	35	2	7346.67	50.38	74.00	-23.62	45.31	5.07	Peak	100	35	3	11020.00	40.59	54.00	-13.41	33.05	7.54	Average	100	142	4	11020.00	54.03	74.00	-19.97	46.49	7.54	Peak	100	142	5	16530.00	59.61	68.20	-8.59	53.39	6.22	Peak	100	182
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																						
1	7346.67	37.14	54.00	-16.86	32.07	5.07	Average	100	35																																																						
2	7346.67	50.38	74.00	-23.62	45.31	5.07	Peak	100	35																																																						
3	11020.00	40.59	54.00	-13.41	33.05	7.54	Average	100	142																																																						
4	11020.00	54.03	74.00	-19.97	46.49	7.54	Peak	100	142																																																						
5	16530.00	59.61	68.20	-8.59	53.39	6.22	Peak	100	182																																																						



Modulation	ax HE40 RU242	Test Freq. (MHz)	5590
Polarization	Horizontal		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBUV/m)			



Modulation	ax HE40 RU242	Test Freq. (MHz)	5590																																																												
Polarization	Vertical																																																														
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																															
Level (dBuV/m) <table><thead><tr><th>Point</th><th>Freq. (MHz)</th><th>Emission level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>SA reading (dBuV)</th><th>Factor (dB/m)</th><th>Remark</th><th>ANT High (cm)</th><th>Turn Table (deg)</th></tr></thead><tbody><tr><td>1</td><td>7453.33</td><td>37.51</td><td>54.00</td><td>-16.49</td><td>32.23</td><td>5.28</td><td>Average</td><td>100</td><td>46</td></tr><tr><td>2</td><td>7453.33</td><td>50.65</td><td>74.00</td><td>-23.35</td><td>45.37</td><td>5.28</td><td>Peak</td><td>100</td><td>46</td></tr><tr><td>3</td><td>11180.00</td><td>40.69</td><td>54.00</td><td>-13.31</td><td>33.89</td><td>6.80</td><td>Average</td><td>100</td><td>133</td></tr><tr><td>4</td><td>11180.00</td><td>53.96</td><td>74.00</td><td>-20.04</td><td>47.16</td><td>6.80</td><td>Peak</td><td>100</td><td>133</td></tr><tr><td>5</td><td>16770.00</td><td>59.55</td><td>68.20</td><td>-8.65</td><td>52.24</td><td>7.31</td><td>Peak</td><td>100</td><td>172</td></tr></tbody></table>				Point	Freq. (MHz)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	SA reading (dBuV)	Factor (dB/m)	Remark	ANT High (cm)	Turn Table (deg)	1	7453.33	37.51	54.00	-16.49	32.23	5.28	Average	100	46	2	7453.33	50.65	74.00	-23.35	45.37	5.28	Peak	100	46	3	11180.00	40.69	54.00	-13.31	33.89	6.80	Average	100	133	4	11180.00	53.96	74.00	-20.04	47.16	6.80	Peak	100	133	5	16770.00	59.55	68.20	-8.65	52.24	7.31	Peak	100	172
Point	Freq. (MHz)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	SA reading (dBuV)	Factor (dB/m)	Remark	ANT High (cm)	Turn Table (deg)																																																						
1	7453.33	37.51	54.00	-16.49	32.23	5.28	Average	100	46																																																						
2	7453.33	50.65	74.00	-23.35	45.37	5.28	Peak	100	46																																																						
3	11180.00	40.69	54.00	-13.31	33.89	6.80	Average	100	133																																																						
4	11180.00	53.96	74.00	-20.04	47.16	6.80	Peak	100	133																																																						
5	16770.00	59.55	68.20	-8.65	52.24	7.31	Peak	100	172																																																						
<table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>7453.33</td><td>37.51</td><td>54.00</td><td>-16.49</td><td>32.23</td><td>5.28</td><td>Average</td><td>100</td><td>46</td></tr><tr><td>2</td><td>7453.33</td><td>50.65</td><td>74.00</td><td>-23.35</td><td>45.37</td><td>5.28</td><td>Peak</td><td>100</td><td>46</td></tr><tr><td>3</td><td>11180.00</td><td>40.69</td><td>54.00</td><td>-13.31</td><td>33.89</td><td>6.80</td><td>Average</td><td>100</td><td>133</td></tr><tr><td>4</td><td>11180.00</td><td>53.96</td><td>74.00</td><td>-20.04</td><td>47.16</td><td>6.80</td><td>Peak</td><td>100</td><td>133</td></tr><tr><td>5</td><td>16770.00</td><td>59.55</td><td>68.20</td><td>-8.65</td><td>52.24</td><td>7.31</td><td>Peak</td><td>100</td><td>172</td></tr></tbody></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	7453.33	37.51	54.00	-16.49	32.23	5.28	Average	100	46	2	7453.33	50.65	74.00	-23.35	45.37	5.28	Peak	100	46	3	11180.00	40.69	54.00	-13.31	33.89	6.80	Average	100	133	4	11180.00	53.96	74.00	-20.04	47.16	6.80	Peak	100	133	5	16770.00	59.55	68.20	-8.65	52.24	7.31	Peak	100	172
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																						
1	7453.33	37.51	54.00	-16.49	32.23	5.28	Average	100	46																																																						
2	7453.33	50.65	74.00	-23.35	45.37	5.28	Peak	100	46																																																						
3	11180.00	40.69	54.00	-13.31	33.89	6.80	Average	100	133																																																						
4	11180.00	53.96	74.00	-20.04	47.16	6.80	Peak	100	133																																																						
5	16770.00	59.55	68.20	-8.65	52.24	7.31	Peak	100	172																																																						
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																															



Modulation	ax HE40 RU242	Test Freq. (MHz)	5670																																																															
Polarization	Horizontal																																																																	
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																																		
<table><thead><tr><th>Freq.</th><th>Emission level</th><th>Limit</th><th>Margin</th><th>SA reading</th><th>Factor</th><th>Remark</th><th>ANT High</th><th>Turn Table</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>7560.00</td><td>37.42</td><td>54.00</td><td>-16.58</td><td>32.41</td><td>5.01</td><td>Average</td><td>100 55</td></tr><tr><td>2</td><td>7560.00</td><td>50.74</td><td>74.00</td><td>-23.26</td><td>45.73</td><td>5.01</td><td>Peak</td><td>100 55</td></tr><tr><td>3</td><td>11340.00</td><td>40.11</td><td>54.00</td><td>-13.89</td><td>33.06</td><td>7.05</td><td>Average</td><td>100 158</td></tr><tr><td>4</td><td>11340.00</td><td>55.03</td><td>74.00</td><td>-18.97</td><td>47.98</td><td>7.05</td><td>Peak</td><td>100 158</td></tr><tr><td>5</td><td>17010.00</td><td>60.04</td><td>68.20</td><td>-8.16</td><td>52.87</td><td>7.17</td><td>Peak</td><td>100 229</td></tr></tbody></table>				Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg	1	7560.00	37.42	54.00	-16.58	32.41	5.01	Average	100 55	2	7560.00	50.74	74.00	-23.26	45.73	5.01	Peak	100 55	3	11340.00	40.11	54.00	-13.89	33.06	7.05	Average	100 158	4	11340.00	55.03	74.00	-18.97	47.98	7.05	Peak	100 158	5	17010.00	60.04	68.20	-8.16	52.87	7.17	Peak	100 229
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg																																																										
1	7560.00	37.42	54.00	-16.58	32.41	5.01	Average	100 55																																																										
2	7560.00	50.74	74.00	-23.26	45.73	5.01	Peak	100 55																																																										
3	11340.00	40.11	54.00	-13.89	33.06	7.05	Average	100 158																																																										
4	11340.00	55.03	74.00	-18.97	47.98	7.05	Peak	100 158																																																										
5	17010.00	60.04	68.20	-8.16	52.87	7.17	Peak	100 229																																																										
<table><thead><tr><th>Freq.</th><th>Emission level</th><th>Limit</th><th>Margin</th><th>SA reading</th><th>Factor</th><th>Remark</th><th>ANT High</th><th>Turn Table</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>7560.00</td><td>37.42</td><td>54.00</td><td>-16.58</td><td>32.41</td><td>5.01</td><td>Average</td><td>100 55</td></tr><tr><td>2</td><td>7560.00</td><td>50.74</td><td>74.00</td><td>-23.26</td><td>45.73</td><td>5.01</td><td>Peak</td><td>100 55</td></tr><tr><td>3</td><td>11340.00</td><td>40.11</td><td>54.00</td><td>-13.89</td><td>33.06</td><td>7.05</td><td>Average</td><td>100 158</td></tr><tr><td>4</td><td>11340.00</td><td>55.03</td><td>74.00</td><td>-18.97</td><td>47.98</td><td>7.05</td><td>Peak</td><td>100 158</td></tr><tr><td>5</td><td>17010.00</td><td>60.04</td><td>68.20</td><td>-8.16</td><td>52.87</td><td>7.17</td><td>Peak</td><td>100 229</td></tr></tbody></table> Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).				Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg	1	7560.00	37.42	54.00	-16.58	32.41	5.01	Average	100 55	2	7560.00	50.74	74.00	-23.26	45.73	5.01	Peak	100 55	3	11340.00	40.11	54.00	-13.89	33.06	7.05	Average	100 158	4	11340.00	55.03	74.00	-18.97	47.98	7.05	Peak	100 158	5	17010.00	60.04	68.20	-8.16	52.87	7.17	Peak	100 229
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg																																																										
1	7560.00	37.42	54.00	-16.58	32.41	5.01	Average	100 55																																																										
2	7560.00	50.74	74.00	-23.26	45.73	5.01	Peak	100 55																																																										
3	11340.00	40.11	54.00	-13.89	33.06	7.05	Average	100 158																																																										
4	11340.00	55.03	74.00	-18.97	47.98	7.05	Peak	100 158																																																										
5	17010.00	60.04	68.20	-8.16	52.87	7.17	Peak	100 229																																																										



Modulation	ax HE40 RU242	Test Freq. (MHz)	5670
Polarization	Vertical		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBUV/m) </			



Modulation	ax HE40 RU242	Test Freq. (MHz)	5710
Polarization	Horizontal		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBuV/m) </			



Modulation	ax HE40 RU242	Test Freq. (MHz)	5710																																																												
Polarization	Vertical																																																														
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																															
Level (dBuV/m) UNI 1~2-PK UNI 1~2-AV <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>7613.33</td><td>37.42</td><td>54.00</td><td>-16.58</td><td>32.49</td><td>4.93</td><td>Average</td><td>100</td><td>25</td></tr><tr><td>2</td><td>7613.33</td><td>50.64</td><td>74.00</td><td>-23.36</td><td>45.71</td><td>4.93</td><td>Peak</td><td>100</td><td>25</td></tr><tr><td>3</td><td>11420.00</td><td>40.85</td><td>54.00</td><td>-13.15</td><td>33.67</td><td>7.18</td><td>Average</td><td>100</td><td>148</td></tr><tr><td>4</td><td>11420.00</td><td>54.26</td><td>74.00</td><td>-19.74</td><td>47.08</td><td>7.18</td><td>Peak</td><td>100</td><td>148</td></tr><tr><td>5</td><td>17130.00</td><td>59.45</td><td>68.20</td><td>-8.75</td><td>52.83</td><td>6.62</td><td>Peak</td><td>100</td><td>161</td></tr></tbody></table> Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	7613.33	37.42	54.00	-16.58	32.49	4.93	Average	100	25	2	7613.33	50.64	74.00	-23.36	45.71	4.93	Peak	100	25	3	11420.00	40.85	54.00	-13.15	33.67	7.18	Average	100	148	4	11420.00	54.26	74.00	-19.74	47.08	7.18	Peak	100	148	5	17130.00	59.45	68.20	-8.75	52.83	6.62	Peak	100	161
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																						
1	7613.33	37.42	54.00	-16.58	32.49	4.93	Average	100	25																																																						
2	7613.33	50.64	74.00	-23.36	45.71	4.93	Peak	100	25																																																						
3	11420.00	40.85	54.00	-13.15	33.67	7.18	Average	100	148																																																						
4	11420.00	54.26	74.00	-19.74	47.08	7.18	Peak	100	148																																																						
5	17130.00	59.45	68.20	-8.75	52.83	6.62	Peak	100	161																																																						




Modulation	ax HE40 RU242	Test Freq. (MHz)	5755
Polarization	Horizontal		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBUV/m) </			



Modulation	ax HE40 RU242	Test Freq. (MHz)	5755
Polarization	Vertical		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBUV/m)			



Modulation	ax HE40 RU242		Test Freq. (MHz)		5795																																																																
Polarization	Horizontal																																																																				
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																																					
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>7726.67</td><td>36.81</td><td>54.00</td><td>-17.19</td><td>32.12</td><td>4.69</td><td>Average</td><td>100</td><td>46</td></tr><tr><td>2</td><td>7726.67</td><td>50.21</td><td>74.00</td><td>-23.79</td><td>45.52</td><td>4.69</td><td>Peak</td><td>100</td><td>46</td></tr><tr><td>3</td><td>11590.00</td><td>41.75</td><td>54.00</td><td>-12.25</td><td>34.65</td><td>7.10</td><td>Average</td><td>100</td><td>188</td></tr><tr><td>4</td><td>11590.00</td><td>55.36</td><td>74.00</td><td>-18.64</td><td>48.26</td><td>7.10</td><td>Peak</td><td>100</td><td>188</td></tr><tr><td>5</td><td>17385.00</td><td>61.96</td><td>68.20</td><td>-6.24</td><td>54.94</td><td>7.02</td><td>Peak</td><td>110</td><td>22</td></tr></table>											Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	7726.67	36.81	54.00	-17.19	32.12	4.69	Average	100	46	2	7726.67	50.21	74.00	-23.79	45.52	4.69	Peak	100	46	3	11590.00	41.75	54.00	-12.25	34.65	7.10	Average	100	188	4	11590.00	55.36	74.00	-18.64	48.26	7.10	Peak	100	188	5	17385.00	61.96	68.20	-6.24	54.94	7.02	Peak	110	22
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																												
1	7726.67	36.81	54.00	-17.19	32.12	4.69	Average	100	46																																																												
2	7726.67	50.21	74.00	-23.79	45.52	4.69	Peak	100	46																																																												
3	11590.00	41.75	54.00	-12.25	34.65	7.10	Average	100	188																																																												
4	11590.00	55.36	74.00	-18.64	48.26	7.10	Peak	100	188																																																												
5	17385.00	61.96	68.20	-6.24	54.94	7.02	Peak	110	22																																																												
Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).																																																																					



Modulation	ax HE40 RU242	Test Freq. (MHz)	5795																																																																													
Polarization	Vertical																																																																															
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																																																
Level (dBUV/m) <table><tr><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB/m</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>7726.67</td><td>37.41</td><td>54.00</td><td>-16.59</td><td>32.72</td><td>4.69</td><td>Average</td><td>100</td><td>46</td></tr><tr><td>2</td><td>7726.67</td><td>51.03</td><td>74.00</td><td>-22.97</td><td>46.34</td><td>4.69</td><td>Peak</td><td>100</td><td>46</td></tr><tr><td>3</td><td>11590.00</td><td>44.58</td><td>54.00</td><td>-9.42</td><td>37.48</td><td>7.10</td><td>Average</td><td>154</td><td>46</td></tr><tr><td>4</td><td>11590.00</td><td>57.28</td><td>74.00</td><td>-16.72</td><td>50.18</td><td>7.10</td><td>Peak</td><td>154</td><td>46</td></tr><tr><td>5</td><td>17385.00</td><td>60.42</td><td>68.20</td><td>-7.78</td><td>53.40</td><td>7.02</td><td>Peak</td><td>100</td><td>231</td></tr></table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dB/m		High	Table					dBuV			cm	deg	1	7726.67	37.41	54.00	-16.59	32.72	4.69	Average	100	46	2	7726.67	51.03	74.00	-22.97	46.34	4.69	Peak	100	46	3	11590.00	44.58	54.00	-9.42	37.48	7.10	Average	154	46	4	11590.00	57.28	74.00	-16.72	50.18	7.10	Peak	154	46	5	17385.00	60.42	68.20	-7.78	53.40	7.02	Peak	100	231
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																								
MHz	level	dBuV/m	dB	reading	dB/m		High	Table																																																																								
				dBuV			cm	deg																																																																								
1	7726.67	37.41	54.00	-16.59	32.72	4.69	Average	100	46																																																																							
2	7726.67	51.03	74.00	-22.97	46.34	4.69	Peak	100	46																																																																							
3	11590.00	44.58	54.00	-9.42	37.48	7.10	Average	154	46																																																																							
4	11590.00	57.28	74.00	-16.72	50.18	7.10	Peak	154	46																																																																							
5	17385.00	60.42	68.20	-7.78	53.40	7.02	Peak	100	231																																																																							
Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).																																																																																



Unwanted Emissions (Above 1GHz) for ax HE80 RU484

Modulation	ax HE80 RU484	Test Freq. (MHz)	5210
Polarization	Horizontal		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBuV/m) </			



Modulation	ax HE80 RU484	Test Freq. (MHz)	5210																																																		
Polarization	Vertical																																																				
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																					
Level (dBuV/m) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>6946.67</td><td>48.22</td><td>68.20</td><td>-19.98</td><td>44.29</td><td>3.93</td><td>Peak</td><td>100</td><td>53</td></tr><tr><td>2</td><td>10420.00</td><td>54.61</td><td>68.20</td><td>-13.59</td><td>47.28</td><td>7.33</td><td>Peak</td><td>100</td><td>205</td></tr><tr><td>3</td><td>15630.00</td><td>42.36</td><td>54.00</td><td>-11.64</td><td>38.44</td><td>3.92</td><td>Average</td><td>100</td><td>124</td></tr><tr><td>4</td><td>15630.00</td><td>55.59</td><td>74.00</td><td>-18.41</td><td>51.67</td><td>3.92</td><td>Peak</td><td>100</td><td>124</td></tr></tbody></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	6946.67	48.22	68.20	-19.98	44.29	3.93	Peak	100	53	2	10420.00	54.61	68.20	-13.59	47.28	7.33	Peak	100	205	3	15630.00	42.36	54.00	-11.64	38.44	3.92	Average	100	124	4	15630.00	55.59	74.00	-18.41	51.67	3.92	Peak	100	124
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																												
1	6946.67	48.22	68.20	-19.98	44.29	3.93	Peak	100	53																																												
2	10420.00	54.61	68.20	-13.59	47.28	7.33	Peak	100	205																																												
3	15630.00	42.36	54.00	-11.64	38.44	3.92	Average	100	124																																												
4	15630.00	55.59	74.00	-18.41	51.67	3.92	Peak	100	124																																												
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																					



Modulation	ax HE80 RU484	Test Freq. (MHz)	5290
Polarization	Horizontal		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBuV/m) <			



Modulation	ax HE80 RU484	Test Freq. (MHz)	5290
Polarization	Vertical		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBuV/m) </			



Modulation	ax HE80 RU484	Test Freq. (MHz)	5530																																																												
Polarization	Horizontal																																																														
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																															
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>7373.33</td><td>37.24</td><td>54.00</td><td>-16.76</td><td>32.21</td><td>5.03</td><td>Average</td><td>100</td><td>46</td></tr><tr><td>2</td><td>7373.33</td><td>50.29</td><td>74.00</td><td>-23.71</td><td>45.26</td><td>5.03</td><td>Peak</td><td>100</td><td>46</td></tr><tr><td>3</td><td>11060.00</td><td>40.22</td><td>54.00</td><td>-13.78</td><td>32.73</td><td>7.49</td><td>Average</td><td>100</td><td>142</td></tr><tr><td>4</td><td>11060.00</td><td>55.29</td><td>74.00</td><td>-18.71</td><td>47.80</td><td>7.49</td><td>Peak</td><td>100</td><td>142</td></tr><tr><td>5</td><td>16590.00</td><td>59.02</td><td>68.20</td><td>-9.18</td><td>52.70</td><td>6.32</td><td>Peak</td><td>100</td><td>208</td></tr></tbody></table> Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	7373.33	37.24	54.00	-16.76	32.21	5.03	Average	100	46	2	7373.33	50.29	74.00	-23.71	45.26	5.03	Peak	100	46	3	11060.00	40.22	54.00	-13.78	32.73	7.49	Average	100	142	4	11060.00	55.29	74.00	-18.71	47.80	7.49	Peak	100	142	5	16590.00	59.02	68.20	-9.18	52.70	6.32	Peak	100	208
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																						
1	7373.33	37.24	54.00	-16.76	32.21	5.03	Average	100	46																																																						
2	7373.33	50.29	74.00	-23.71	45.26	5.03	Peak	100	46																																																						
3	11060.00	40.22	54.00	-13.78	32.73	7.49	Average	100	142																																																						
4	11060.00	55.29	74.00	-18.71	47.80	7.49	Peak	100	142																																																						
5	16590.00	59.02	68.20	-9.18	52.70	6.32	Peak	100	208																																																						



Modulation	ax HE80 RU484	Test Freq. (MHz)	5530																																																												
Polarization	Vertical																																																														
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																															
Level (dBUV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>7373.33</td><td>37.08</td><td>54.00</td><td>-16.92</td><td>32.05</td><td>5.03</td><td>Average</td><td>100</td><td>41</td></tr><tr><td>2</td><td>7373.33</td><td>50.26</td><td>74.00</td><td>-23.74</td><td>45.23</td><td>5.03</td><td>Peak</td><td>100</td><td>41</td></tr><tr><td>3</td><td>11060.00</td><td>40.48</td><td>54.00</td><td>-13.52</td><td>32.99</td><td>7.49</td><td>Average</td><td>100</td><td>141</td></tr><tr><td>4</td><td>11060.00</td><td>53.96</td><td>74.00</td><td>-20.04</td><td>46.47</td><td>7.49</td><td>Peak</td><td>100</td><td>141</td></tr><tr><td>5</td><td>16590.00</td><td>59.48</td><td>68.20</td><td>-8.72</td><td>53.16</td><td>6.32</td><td>Peak</td><td>100</td><td>177</td></tr></tbody></table> Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).					Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	7373.33	37.08	54.00	-16.92	32.05	5.03	Average	100	41	2	7373.33	50.26	74.00	-23.74	45.23	5.03	Peak	100	41	3	11060.00	40.48	54.00	-13.52	32.99	7.49	Average	100	141	4	11060.00	53.96	74.00	-20.04	46.47	7.49	Peak	100	141	5	16590.00	59.48	68.20	-8.72	53.16	6.32	Peak	100	177
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																						
1	7373.33	37.08	54.00	-16.92	32.05	5.03	Average	100	41																																																						
2	7373.33	50.26	74.00	-23.74	45.23	5.03	Peak	100	41																																																						
3	11060.00	40.48	54.00	-13.52	32.99	7.49	Average	100	141																																																						
4	11060.00	53.96	74.00	-20.04	46.47	7.49	Peak	100	141																																																						
5	16590.00	59.48	68.20	-8.72	53.16	6.32	Peak	100	177																																																						



Modulation	ax HE80 RU484	Test Freq. (MHz)	5610
Polarization	Horizontal		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBUV/m) <			



Modulation	ax HE80 RU484	Test Freq. (MHz)	5610
Polarization	Vertical		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBuV/m) <			



Modulation	ax HE80 RU484	Test Freq. (MHz)	5690
Polarization	Horizontal		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBuV/m)			




Modulation	ax HE80 RU484	Test Freq. (MHz)	5690
Polarization	Vertical		
Test By :Brad Wu Temperature(°C):25 Humidity(%):62			
Level (dBuV/m) <			



Modulation	ax HE80 RU484	Test Freq. (MHz)	5775																																																												
Polarization	Horizontal																																																														
Test By :Brad Wu Temperature(°C):25 Humidity(%):62																																																															
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>7700.00</td><td>36.54</td><td>54.00</td><td>-17.46</td><td>31.84</td><td>4.70</td><td>Average</td><td>100</td><td>31</td></tr><tr><td>2</td><td>7700.00</td><td>49.84</td><td>74.00</td><td>-24.16</td><td>45.14</td><td>4.70</td><td>Peak</td><td>100</td><td>31</td></tr><tr><td>3</td><td>11550.00</td><td>41.52</td><td>54.00</td><td>-12.48</td><td>34.18</td><td>7.34</td><td>Average</td><td>100</td><td>189</td></tr><tr><td>4</td><td>11550.00</td><td>55.44</td><td>74.00</td><td>-18.56</td><td>48.10</td><td>7.34</td><td>Peak</td><td>100</td><td>189</td></tr><tr><td>5</td><td>17325.00</td><td>61.95</td><td>68.20</td><td>-6.25</td><td>55.17</td><td>6.78</td><td>Peak</td><td>100</td><td>52</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	7700.00	36.54	54.00	-17.46	31.84	4.70	Average	100	31	2	7700.00	49.84	74.00	-24.16	45.14	4.70	Peak	100	31	3	11550.00	41.52	54.00	-12.48	34.18	7.34	Average	100	189	4	11550.00	55.44	74.00	-18.56	48.10	7.34	Peak	100	189	5	17325.00	61.95	68.20	-6.25	55.17	6.78	Peak	100	52
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																						
1	7700.00	36.54	54.00	-17.46	31.84	4.70	Average	100	31																																																						
2	7700.00	49.84	74.00	-24.16	45.14	4.70	Peak	100	31																																																						
3	11550.00	41.52	54.00	-12.48	34.18	7.34	Average	100	189																																																						
4	11550.00	55.44	74.00	-18.56	48.10	7.34	Peak	100	189																																																						
5	17325.00	61.95	68.20	-6.25	55.17	6.78	Peak	100	52																																																						
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																															



Modulation	ax HE80 RU484	Test Freq. (MHz)	5775						
Polarization	Vertical								
Test By :Brad Wu Temperature(°C):25 Humidity(%):62									
									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	7700.00	37.26	54.00	-16.74	32.56	4.70	Average	100	44
2	7700.00	51.19	74.00	-22.81	46.49	4.70	Peak	100	44
3	11550.00	44.39	54.00	-9.61	37.05	7.34	Average	132	41
4	11550.00	57.15	74.00	-16.85	49.81	7.34	Peak	132	41
5	17325.00	60.31	68.20	-7.89	53.53	6.78	Peak	100	198
Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).									




Modulation Mode	ax HE80 RU242	Test Freq. (MHz)	5690
Power Phase	Line		

Test by : Brad Wu

Temperature: 23°C

Humidity: 64%



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Aux dB	Remark
1	0.150	25.58	56.00	-30.42	15.67	9.63	0.08	0.20	Average
2*	0.150	43.99	66.00	-22.01	34.08	9.63	0.08	0.20	QP
3	0.162	26.90	55.34	-28.44	16.99	9.63	0.07	0.21	Average
4	0.162	43.32	65.34	-22.02	33.41	9.63	0.07	0.21	QP
5	0.204	26.27	53.45	-27.18	16.34	9.62	0.06	0.25	Average
6	0.204	39.24	63.45	-24.21	29.31	9.62	0.06	0.25	QP
7	0.400	23.69	47.86	-24.17	13.66	9.62	0.08	0.33	Average
8	0.400	32.23	57.86	-25.63	22.20	9.62	0.08	0.33	QP
9	1.065	15.37	46.00	-30.63	5.29	9.63	0.09	0.36	Average
10	1.065	20.82	56.00	-35.18	10.74	9.63	0.09	0.36	QP
11	10.397	15.90	50.00	-34.10	5.40	9.69	0.36	0.45	Average
12	10.397	20.19	60.00	-39.81	9.69	9.69	0.36	0.45	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).

2: Over Limit (dB) = Level (dBuV) - Limit Line (dBuV).




Modulation Mode	ax HE80 RU242	Test Freq. (MHz)	5690
Power Phase	Neutral		

Test by : Brad Wu

Temperature: 23°C

Humidity: 64%



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Aux dB	Remark
1	0.162	25.78	55.34	-29.56	15.95	9.63	0.07	0.13	Average
2	0.162	43.25	65.34	-22.09	33.42	9.63	0.07	0.13	QP
3	0.189	24.51	54.06	-29.55	14.66	9.63	0.06	0.16	Average
4	0.189	39.56	64.06	-24.50	29.71	9.63	0.06	0.16	QP
5*	0.396	29.38	47.95	-18.57	19.43	9.62	0.08	0.25	Average
6	0.396	36.84	57.95	-21.11	26.89	9.62	0.08	0.25	QP
7	4.622	12.42	46.00	-33.58	2.15	9.66	0.21	0.40	Average
8	4.622	19.65	56.00	-36.35	9.38	9.66	0.21	0.40	QP
9	19.224	14.08	50.00	-35.92	3.21	9.79	0.50	0.58	Average
10	19.224	19.23	60.00	-40.77	8.36	9.79	0.50	0.58	QP
11	22.063	13.83	50.00	-36.17	2.91	9.80	0.52	0.60	Average
12	22.063	17.85	60.00	-42.15	6.93	9.80	0.52	0.60	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).

2: Over Limit (dB) = Level (dBuV) - Limit Line (dBuV).




Modulation Mode	ax HE20 RU26	Test Freq. (MHz)	5720
Power Phase	Line		

Test by : Brad Wu

Temperature: 23°C

Humidity: 64%



	Freq	Level	Limit	Over	Read	Factor	Cable	Aux	Remark
	MHz	dBuV	Line	Limit	Level		loss		
			dBuV	dB	dBuV	dB	dB	dB	
1	0.159	25.57	55.52	-29.95	15.65	9.63	0.08	0.21	Average
2	0.159	42.61	65.52	-22.91	32.69	9.63	0.08	0.21	QP
3	0.165	26.94	55.21	-28.27	17.02	9.63	0.07	0.22	Average
4*	0.165	43.09	65.21	-22.12	33.17	9.63	0.07	0.22	QP
5	0.228	25.60	52.52	-26.92	15.66	9.62	0.06	0.26	Average
6	0.228	36.06	62.52	-26.46	26.12	9.62	0.06	0.26	QP
7	0.393	25.36	47.99	-22.63	15.33	9.62	0.08	0.33	Average
8	0.393	32.19	57.99	-25.80	22.16	9.62	0.08	0.33	QP
9	1.054	14.24	46.00	-31.76	4.16	9.63	0.09	0.36	Average
10	1.054	21.07	56.00	-34.93	10.99	9.63	0.09	0.36	QP
11	10.179	15.50	50.00	-34.50	5.01	9.69	0.35	0.45	Average
12	10.179	19.83	60.00	-40.17	9.34	9.69	0.35	0.45	QP

Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).

2: Over Limit (dB) = Level (dBUV) - Limit Line (dBUV).




Modulation Mode	ax HE20 RU26	Test Freq. (MHz)	5720
Power Phase	Neutral		

Test by : Brad Wu

Temperature: 23°C

Humidity: 64%



	Freq	Level	Limit	Over	Read	Factor	Cable	Aux	
	MHz	dBuV	Line	Limit	Level		loss		Remark
			dBuV	dB	dBuV	dB	dB	dB	
1	0.162	25.78	55.34	-29.56	15.95	9.63	0.07	0.13	Average
2	0.162	43.17	65.34	-22.17	33.34	9.63	0.07	0.13	QP
3	0.204	25.51	53.45	-27.94	15.65	9.63	0.06	0.17	Average
4	0.204	38.82	63.45	-24.63	28.96	9.63	0.06	0.17	QP
5*	0.402	28.16	47.81	-19.65	18.21	9.62	0.08	0.25	Average
6	0.402	36.62	57.81	-21.19	26.67	9.62	0.08	0.25	QP
7	4.598	12.50	46.00	-33.50	2.23	9.66	0.21	0.40	Average
8	4.598	19.32	56.00	-36.68	9.05	9.66	0.21	0.40	QP
9	10.342	12.07	50.00	-37.93	1.57	9.71	0.36	0.43	Average
10	10.342	16.80	60.00	-43.20	6.30	9.71	0.36	0.43	QP
11	19.224	14.32	50.00	-35.68	3.45	9.79	0.50	0.58	Average
12	19.224	20.02	60.00	-39.98	9.15	9.79	0.50	0.58	QP

Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).

2: Over Limit (dB) = Level (dBUV) - Limit Line (dBUV).