

# FCC Co-Location Test Report

**FCC ID** : SQG-SU60SOMC  
**Equipment** : 802.11ac Professional Wi-Fi + BT5.0 Module  
**Model No.** : SU60-SOMC-2G (453-00004)  
**Brand Name** : Laird Connectivity  
**Applicant** : Laird Connectivity  
**Address** : W66N220 Commerce Court, Cedarburg,  
Wisconsin 53012, USA  
**Standard** : 47 CFR FCC Part 15.247  
47 CFR FCC Part 15.407  
**Received Date** : Aug. 19, 2019  
**Tested Date** : Jan. 09 ~ Mar. 26, 2020

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Approved by:

  
\_\_\_\_\_  
Along Chen / Assistant Manager

  
\_\_\_\_\_  
Gary Chang / Manager



---

## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	The Equipment List .....	7
1.3	Test Standards .....	9
1.4	Deviation from Test Standard and Measurement Procedure.....	9
1.5	Measurement Uncertainty .....	9
<b>2</b>	<b>TEST CONFIGURATION.....</b>	<b>10</b>
2.1	Testing Condition .....	10
2.2	The Worst Test Modes and Channel Details .....	10
<b>3</b>	<b>TRANSMITTER TEST RESULTS .....</b>	<b>11</b>
3.1	Unwanted Emissions into Restricted Frequency Bands .....	11
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>61</b>

---

## Release Record

Report No.	Version	Description	Issued Date
FR8N2101-01	Rev. 01	Initial issue	Apr. 24, 2020
FR8N2101-01	Rev. 02	Updated brand name	May 25, 2020

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.247(d) 15.407(b) 15.209	Radiated Emissions	[dBuV/m at 3m]: 57.23MHz 36.55(Margin -3.45dB) - PK	Pass

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

# 1 General Description

## 1.1 Information

### 1.1.1 Specification of the Equipment under Test (EUT)

<b>Operating Frequency</b>	802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz, 5745 ~ 5825 MHz
<b>Modulation Type</b>	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
<b>BT</b>	
<b>Operating Frequency</b>	2402 MHz ~ 2480 MHz
<b>Modulation Type</b>	Bluetooth 4.2 LE: GFSK Bluetooth BR(1Mbps): GFSK Bluetooth EDR (2Mbps): $\pi/4$ -DQPSK Bluetooth EDR (3Mbps): 8-DPSK

### 1.1.2 Information of Host

<b>Brand Name</b>	Laird
<b>Product name</b>	Sentrius™ IG60 Serial, Wi-Fi, & LTE Cat 1 Gateway
<b>Model name</b>	Sentrius™ IG60-SERIAL-LTE
<b>Certified module (installed in the system)</b>	SQG-IGUPCAT1

### 1.1.3 Antenna Details of Specific platform

#### For Wi-Fi

Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)				
			2400~2483.5	5150~5250	5250~5350	5470~5725	5725~5850
LSR/001-0009	Dipole	IPEX U.FL	2	2	2	2	2

#### For LTE& WWAN

Brand / Model	Type	Connector	Gain (dBi)	Operating Band
Laird/DBA6927C1	Dipole	SMA_MALE	2.2	LTE Band 2 / PCS 1900
			2.2	LTE Band 4 / WCDMA II / WCDMA Band IV
			0.5	LTE Band 5 / GSM850 / WCDMA Band V
			0.5	LTE Band 12

**For BT**

Model	Type	Connector	Antenna Gain (dBi)
LSR/001-0009	Dipole	IPEX U.FL	2

**1.1.4 Host Accessories**

Host Accessories		
No.	Equipment	Description
1	AC adapter	Brand: FRECOM Model: F30L2-120250SPACP Power Rating: I/P: 100-240Vac, 50/60Hz, 0.8A O/P: 12Vdc, 2.5A Power Line: 1.5m non-shielded without core
2	AC adapter	Brand: FRECOM Model: F48L-120400SPAU Power Rating: I/P: 100-240Vac, 50/60Hz, 1.4A O/P: 12Vdc, 4A Power Line: 1.5m non-shielded with one core
3	DC cable	3m non-shielded, without core
4	Serial loopback adapter	Model : DB9 female Brand : Kingmate

## 1.2 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Tested Date	Jan. 09, 2020				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 17, 2019	Dec. 16, 2020
Receiver	R&S	ESR3	101658	Dec. 12, 2019	Dec. 10, 2020
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 17, 2019	Apr. 16, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Dec. 27, 2019	Dec. 26, 2020
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2019	Nov. 14, 2020
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2019	Nov. 12, 2020
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 07, 2019	Oct. 06, 2020
Preamplifier	EMC	EMC02325	980187	Aug. 14, 2019	Aug. 13, 2020
Preamplifier	Agilent	83017A	MY53270014	Aug. 07, 2019	Aug. 06, 2020
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Sep. 27, 2019	Sep. 26, 2020
RF cable-8M	EMC	EMC104-SM-SM-80 00	181107	Sep. 27, 2019	Sep. 26, 2020
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Sep. 27, 2019	Sep. 26, 2020
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Sep. 27, 2019	Sep. 26, 2020
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Sep. 27, 2019	Sep. 26, 2020
LF cable-13M	EMC	EMC8D-NM-NM-130 00	131104	Sep. 27, 2019	Sep. 26, 2020
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

<b>Test Item</b>	Radiated Emission				
<b>Test Site</b>	966 chamber 3 / (03CH03-WS)				
<b>Tested Date</b>	Feb. 24 ~ Mar. 26, 2020				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101499	Jan. 09, 2020	Jan. 08, 2021
Receiver	R&S	ESR3	101657	Feb. 14, 2020	Feb. 13, 2021
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 17, 2019	Apr. 16, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Dec. 27, 2019	Dec. 26, 2020
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2019	Nov. 14, 2020
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2019	Nov. 12, 2020
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 07, 2019	Oct. 06, 2020
Preamplifier	EMC	EMC02325	980187	Aug. 14, 2019	Aug. 13, 2020
Preamplifier	Agilent	83017A	MY53270014	Aug. 07, 2019	Aug. 06, 2020
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Sep. 27, 2019	Sep. 26, 2020
RF cable-8M	EMC	EMC104-SM-SM-80 00	181107	Sep. 27, 2019	Sep. 26, 2020
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Sep. 27, 2019	Sep. 26, 2020
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Sep. 27, 2019	Sep. 26, 2020
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Sep. 27, 2019	Sep. 26, 2020
LF cable-13M	EMC	EMC8D-NM-NM-130 00	131104	Sep. 27, 2019	Sep. 26, 2020
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					



### 1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

### 1.4 Deviation from Test Standard and Measurement Procedure

None

### 1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Radiated emission $\leq$ 1GHz	$\pm 3.96$ dB
Radiated emission $>$ 1GHz	$\pm 4.51$ dB

## 2 Test Configuration

### 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions ≤ 1GHz	03CH03-WS	23°C / 62%	Roger Lu
Radiated emission > 1GHz	03CH03-WS	22-25°C / 65-68%	Roger Lu Akun Chung

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- ISED#: 10807A
- CAB identifier: TW2732

### 2.2 The Worst Test Modes and Channel Details

Test item	Test mode
Radiated Emissions	2.4G 11g CH06 + 2G GSM850 CH251
	2.4G 11g CH06 + 2G PCS1900 CH512
	2.4G 11g CH06 + 3G WCDMA Band4 CH1513
	2.4G 11g CH06 + LTE Band 12, CH23095
	5G 11ac CH48 + 2G GSM850 CH251
	5G 11ac CH48 + 2G PCS1900 CH512
	5G 11ac CH48 + 3G WCDMA Band4 CH1513
	5G 11ac CH48 + LTE Band 12, CH23095
	BT Normal link + WWAN 2G GPRS 850 CH251
	BT Normal link + WWAN 2G GPRS 1900 CH512
	BT Normal link + WWAN 3G WCDMA Band4 CH1513
	BT Normal link + WWAN LTE Band 12 Channel 23095
	<b>NOTE:</b>
1. The selected channel is the maximum power channel of 2.4 GHz Wi-Fi / 5 GHz Wi-Fi / WWAN / BT.	
2. Two adapters (F30L2-120250SPACP and F48L-120400SPAV) had been covered during the pretest, and found that Adapter F30L2-120250SPACP was the worst case and was selected for final test.	

## 3 Transmitter Test Results

### 3.1 Unwanted Emissions into Restricted Frequency Bands

#### 3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
 Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
 Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.1.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

**Note:**


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

### 3.1.3 Test Setup


#### Radiated Emissions below 1 GHz




#### Radiated Emissions above 1 GHz



### 3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

<b>Test mode</b>	2.4G 11g CH06 + 2G GSM850 CH251								
<b>Polarization</b>	Horizontal								
									
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level	dBuV/m	dB	reading	dB		High	Table
		dBuV/m	dBuV/m	dB	dBuV			cm	deg
1	57.21	36.34	40.00	-3.66	45.31	-8.97	Peak	---	---
2	124.16	38.17	43.50	-5.33	48.85	-10.68	Peak	---	---
3	191.83	38.62	43.50	-4.88	50.11	-11.49	Peak	---	---
4	334.62	40.11	46.00	-5.89	47.25	-7.14	Peak	---	---
5	480.17	40.86	46.00	-5.14	44.29	-3.43	Peak	---	---
6	624.78	39.36	46.00	-6.64	39.50	-0.14	Peak	---	---
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)  *Factor includes antenna factor , cable loss and amplifier gain  Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).  Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.</p>									

<b>Test mode</b>	2.4G 11g CH06 + 2G GSM850 CH251
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.15	37.33	43.50	-6.17	48.02	-10.69	Peak	---	---
2	263.78	38.18	46.00	-7.82	47.82	-9.64	Peak	---	---
3	311.27	37.69	46.00	-8.31	45.61	-7.92	Peak	---	---
4	360.72	38.25	46.00	-7.75	45.01	-6.76	Peak	---	---
5	480.02	35.78	46.00	-10.22	39.21	-3.43	Peak	---	---
6	624.76	36.77	46.00	-9.23	36.91	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	2.4G 11g CH06 + 2G PCS1900 CH512
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.22	36.38	40.00	-3.62	45.35	-8.97	Peak	---	---
2	191.86	38.64	43.50	-4.86	50.13	-11.49	Peak	---	---
3	334.61	40.37	46.00	-5.63	47.51	-7.14	Peak	---	---
4	408.36	39.34	46.00	-6.66	44.76	-5.42	Peak	---	---
5	480.03	40.85	46.00	-5.15	44.28	-3.43	Peak	---	---
6	624.67	38.76	46.00	-7.24	38.90	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	2.4G 11g CH06 + 2G PCS1900 CH512
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.19	36.38	43.50	-7.12	47.06	-10.68	Peak	---	---
2	192.06	36.27	43.50	-7.23	47.77	-11.50	Peak	---	---
3	311.39	37.84	46.00	-8.16	45.75	-7.91	Peak	---	---
4	360.87	39.23	46.00	-6.77	45.99	-6.76	Peak	---	---
5	480.19	36.10	46.00	-9.90	39.53	-3.43	Peak	---	---
6	624.67	36.26	46.00	-9.74	36.40	-0.14	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.



<b>Test mode</b>	2.4G 11g CH06 + 3G WCDMA Band4 CH1513
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.22	35.79	40.00	-4.21	44.76	-8.97	Peak	---	---
2	143.59	39.26	43.50	-4.24	48.16	-8.90	Peak	---	---
3	191.84	37.96	43.50	-5.54	49.45	-11.49	Peak	---	---
4	334.62	40.48	46.00	-5.52	47.62	-7.14	Peak	---	---
5	408.36	39.55	46.00	-6.45	44.97	-5.42	Peak	---	---
6	624.67	38.67	46.00	-7.33	38.81	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	2.4G 11g CH06 + 3G WCDMA Band4 CH1513
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.17	37.35	43.50	-6.15	48.03	-10.68	Peak	---	---
2	167.64	38.38	43.50	-5.12	47.35	-8.97	Peak	---	---
3	263.79	38.07	46.00	-7.93	47.71	-9.64	Peak	---	---
4	360.74	38.64	46.00	-7.36	45.40	-6.76	Peak	---	---
5	499.58	35.17	46.00	-10.83	38.22	-3.05	Peak	---	---
6	624.67	35.59	46.00	-10.41	35.73	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	2.4G 11g CH06 + LTE Band 12, CH23095
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.22	35.54	40.00	-4.46	44.51	-8.97	Peak	---	---
2	124.08	37.16	43.50	-6.34	47.85	-10.69	Peak	---	---
3	334.61	40.53	46.00	-5.47	47.67	-7.14	Peak	---	---
4	408.36	38.94	46.00	-7.06	44.36	-5.42	Peak	---	---
5	480.12	40.07	46.00	-5.93	43.50	-3.43	Peak	---	---
6	624.68	38.69	46.00	-7.31	38.83	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	2.4G 11g CH06 + LTE Band 12, CH23095
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.11	37.35	43.50	-6.15	48.04	-10.69	Peak	---	---
2	167.76	38.40	43.50	-5.10	47.37	-8.97	Peak	---	---
3	263.77	37.64	46.00	-8.36	47.28	-9.64	Peak	---	---
4	360.74	38.86	46.00	-7.14	45.62	-6.76	Peak	---	---
5	480.12	36.70	46.00	-9.30	40.13	-3.43	Peak	---	---
6	624.58	36.19	46.00	-9.81	36.33	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	5G 11ac CH48 + 2G GSM850 CH251
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.23	35.59	40.00	-4.41	44.57	-8.98	Peak	---	---
2	124.18	37.33	43.50	-6.17	48.01	-10.68	Peak	---	---
3	192.11	38.97	43.50	-4.53	50.47	-11.50	Peak	---	---
4	311.23	41.25	46.00	-4.75	49.18	-7.93	Peak	---	---
5	334.63	40.66	46.00	-5.34	47.80	-7.14	Peak	---	---
6	624.69	38.47	46.00	-7.53	38.61	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	5G 11ac CH48 + 2G GSM850 CH251
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.15	37.52	43.50	-5.98	48.21	-10.69	Peak	---	---
2	167.78	38.26	43.50	-5.24	47.23	-8.97	Peak	---	---
3	263.59	36.71	46.00	-9.29	46.36	-9.65	Peak	---	---
4	311.43	37.99	46.00	-8.01	45.90	-7.91	Peak	---	---
5	360.68	37.74	46.00	-8.26	44.50	-6.76	Peak	---	---
6	624.55	35.76	46.00	-10.24	35.90	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	5G 11ac CH48 + 2G PCS1900 CH512
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.08	35.64	40.00	-4.36	44.59	-8.95	Peak	---	---
2	124.29	36.74	43.50	-6.76	47.41	-10.67	Peak	---	---
3	191.82	38.57	43.50	-4.93	50.06	-11.49	Peak	---	---
4	334.43	40.19	46.00	-5.81	47.33	-7.14	Peak	---	---
5	480.11	41.24	46.00	-4.76	44.67	-3.43	Peak	---	---
6	624.69	38.97	46.00	-7.03	39.11	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	5G 11ac CH48 + 2G PCS1900 CH512
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.01	37.20	43.50	-6.30	47.90	-10.70	Peak	---	---
2	167.83	37.74	43.50	-5.76	46.71	-8.97	Peak	---	---
3	311.48	37.39	46.00	-8.61	45.30	-7.91	Peak	---	---
4	360.72	38.04	46.00	-7.96	44.80	-6.76	Peak	---	---
5	480.17	36.05	46.00	-9.95	39.48	-3.43	Peak	---	---
6	624.66	36.36	46.00	-9.64	36.50	-0.14	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.



<b>Test mode</b>	5G 11ac CH48 + 3G WCDMA Band4 CH1513
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.21	35.78	40.00	-4.22	44.75	-8.97	Peak	---	---
2	124.64	37.68	43.50	-5.82	48.32	-10.64	Peak	---	---
3	334.65	40.59	46.00	-5.41	47.73	-7.14	Peak	---	---
4	360.61	41.38	46.00	-4.62	48.15	-6.77	Peak	---	---
5	480.17	40.06	46.00	-5.94	43.49	-3.43	Peak	---	---
6	624.77	38.66	46.00	-7.34	38.80	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	5G 11ac CH48 + 3G WCDMA Band4 CH1513
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.26	37.37	43.50	-6.13	48.04	-10.67	Peak	---	---
2	191.83	37.82	43.50	-5.68	49.31	-11.49	Peak	---	---
3	263.81	36.57	46.00	-9.43	46.21	-9.64	Peak	---	---
4	360.88	38.64	46.00	-7.36	45.39	-6.75	Peak	---	---
5	480.17	36.14	46.00	-9.86	39.57	-3.43	Peak	---	---
6	624.65	37.21	46.00	-8.79	37.35	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	5G 11ac CH48 + LTE Band 12, CH23095
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.22	36.28	40.00	-3.72	45.25	-8.97	Peak	---	---
2	124.26	37.71	43.50	-5.79	48.38	-10.67	Peak	---	---
3	191.85	38.96	43.50	-4.54	50.45	-11.49	Peak	---	---
4	334.42	40.68	46.00	-5.32	47.82	-7.14	Peak	---	---
5	480.13	40.35	46.00	-5.65	43.78	-3.43	Peak	---	---
6	624.66	38.84	46.00	-7.16	38.98	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	5G 11ac CH48 + LTE Band 12, CH23095
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.26	36.65	43.50	-6.85	47.32	-10.67	Peak	---	---
2	167.82	37.63	43.50	-5.87	46.60	-8.97	Peak	---	---
3	311.49	37.69	46.00	-8.31	45.60	-7.91	Peak	---	---
4	360.72	38.44	46.00	-7.56	45.20	-6.76	Peak	---	---
5	480.17	35.94	46.00	-10.06	39.37	-3.43	Peak	---	---
6	624.67	35.69	46.00	-10.31	35.83	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	BT Normal link + WWAN 2G GPRS 850 CH251
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.23	36.55	40.00	-3.45	45.53	-8.98	Peak	---	---
2	124.55	38.23	43.50	-5.27	48.87	-10.64	Peak	---	---
3	191.85	38.22	43.50	-5.28	49.71	-11.49	Peak	---	---
4	334.85	40.63	46.00	-5.37	47.76	-7.13	Peak	---	---
5	481.25	40.71	46.00	-5.29	44.13	-3.42	Peak	---	---
6	624.87	39.44	46.00	-6.56	39.58	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	BT Normal link + WWAN 2G GPRS 850 CH251
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.25	37.45	43.50	-6.05	48.13	-10.68	Peak	---	---
2	264.22	38.41	46.00	-7.59	48.02	-9.61	Peak	---	---
3	311.33	37.55	46.00	-8.45	45.47	-7.92	Peak	---	---
4	361.25	38.36	46.00	-7.64	45.10	-6.74	Peak	---	---
5	480.41	35.99	46.00	-10.01	39.42	-3.43	Peak	---	---
6	624.87	37.00	46.00	-9.00	37.14	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	BT Normal link + WWAN 2G GPRS 1900 CH512
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.33	36.44	40.00	-3.56	45.44	-9.00	Peak	---	---
2	124.58	37.98	43.50	-5.52	48.62	-10.64	Peak	---	---
3	191.47	38.41	43.50	-5.09	49.90	-11.49	Peak	---	---
4	334.25	40.69	46.00	-5.31	47.83	-7.14	Peak	---	---
5	480.23	40.71	46.00	-5.29	44.14	-3.43	Peak	---	---
6	590.44	31.95	46.00	-14.05	32.96	-1.01	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	BT Normal link + WWAN 2G GPRS 1900 CH512
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.25	36.98	43.50	-6.52	47.66	-10.68	Peak	---	---
2	264.25	38.25	46.00	-7.75	47.86	-9.61	Peak	---	---
3	311.62	37.44	46.00	-8.56	45.35	-7.91	Peak	---	---
4	359.35	37.87	46.00	-8.13	44.69	-6.82	Peak	---	---
5	590.47	31.15	46.00	-14.85	32.16	-1.01	Peak	---	---
6	623.44	36.47	46.00	-9.53	36.62	-0.15	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.



<b>Test mode</b>	BT Normal link + WWAN 3G WCDMA Band4 CH1513
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.55	36.11	40.00	-3.89	45.14	-9.03	Peak	---	---
2	124.52	37.88	43.50	-5.62	48.53	-10.65	Peak	---	---
3	191.05	37.98	43.50	-5.52	49.47	-11.49	Peak	---	---
4	334.52	40.36	46.00	-5.64	47.50	-7.14	Peak	---	---
5	480.63	40.47	46.00	-5.53	43.90	-3.43	Peak	---	---
6	685.44	32.48	46.00	-13.52	31.83	0.65	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	BT Normal link + WWAN 3G WCDMA Band4 CH1513
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.66	36.77	43.50	-6.73	47.40	-10.63	Peak	---	---
2	264.25	38.14	46.00	-7.86	47.75	-9.61	Peak	---	---
3	311.25	37.52	46.00	-8.48	45.45	-7.93	Peak	---	---
4	360.55	39.11	46.00	-6.89	45.88	-6.77	Peak	---	---
5	624.88	36.47	46.00	-9.53	36.61	-0.14	Peak	---	---
6	685.44	32.97	46.00	-13.03	32.32	0.65	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	BT Normal link + WWAN LTE Band 12 Channel 23095
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	57.44	36.41	40.00	-3.59	45.43	-9.02	Peak	---	---
2	124.88	37.98	43.50	-5.52	48.59	-10.61	Peak	---	---
3	191.85	38.44	43.50	-5.06	49.93	-11.49	Peak	---	---
4	333.88	40.63	46.00	-5.37	47.78	-7.15	Peak	---	---
5	480.32	40.74	46.00	-5.26	44.17	-3.43	Peak	---	---
6	624.87	39.44	46.00	-6.56	39.58	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Test mode</b>	BT Normal link + WWAN LTE Band 12 Channel 23095
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	124.32	36.98	43.50	-6.52	47.65	-10.67	Peak	---	---
2	262.88	38.25	46.00	-7.75	47.92	-9.67	Peak	---	---
3	310.58	37.41	46.00	-8.59	45.37	-7.96	Peak	---	---
4	361.25	38.63	46.00	-7.37	45.37	-6.74	Peak	---	---
5	481.25	35.44	46.00	-10.56	38.86	-3.42	Peak	---	---
6	624.85	36.54	46.00	-9.46	36.68	-0.14	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

<b>Test mode</b>	2.4G 11g CH06 + 2G GSM850 CH251								
<b>Polarization</b>	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	3285.80	33.51	54.00	-20.49	31.32	2.19	Average	100	60
2	3285.80	43.03	74.00	-30.97	40.84	2.19	Peak	100	60
3	4134.60	35.96	54.00	-18.04	31.56	4.40	Average	100	70
4	4134.60	44.99	74.00	-29.01	40.59	4.40	Peak	100	70
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)  *Factor includes antenna factor , cable loss and amplifier gain  Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									


<b>Test mode</b>	2.4G 11g CH06 + 2G GSM850 CH251
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3285.80	33.53	54.00	-20.47	31.34	2.19	Average	100	50
2	3285.80	42.93	74.00	-31.07	40.74	2.19	Peak	100	50
3	4134.60	35.11	54.00	-18.89	30.71	4.40	Average	100	20
4	4134.60	45.11	74.00	-28.89	40.71	4.40	Peak	100	20

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	2.4G 11g CH06 + 2G PCS1900 CH512
<b>Polarization</b>	Horizontal




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3023.80	34.35	54.00	-19.65	32.56	1.79	Average	100	91
2	3023.80	43.64	74.00	-30.36	41.85	1.79	Peak	100	91
3	4287.20	35.26	54.00	-18.74	30.32	4.94	Average	100	40
4	4287.20	45.19	74.00	-28.81	40.25	4.94	Peak	100	40

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	2.4G 11g CH06 + 2G PCS1900 CH512
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3023.80	38.33	54.00	-15.67	36.54	1.79	Average	100	155
2	3023.80	47.64	74.00	-26.36	45.85	1.79	Peak	100	155
3	4287.20	35.54	54.00	-18.46	30.60	4.94	Average	100	50
4	4287.20	45.60	74.00	-28.40	40.66	4.94	Peak	100	50

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



<b>Test mode</b>	2.4G 11g CH06 + 3G WCDMA Band4 CH1513								
<b>Polarization</b>	Horizontal								
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	3313.30	32.44	54.00	-21.56	30.31	2.13	Average	100	50
2	3313.30	42.72	74.00	-31.28	40.59	2.13	Peak	100	50
3	4189.60	34.22	54.00	-19.78	29.67	4.55	Average	100	60
4	4189.60	45.17	74.00	-28.83	40.62	4.55	Peak	100	60
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									


<b>Test mode</b>	2.4G 11g CH06 + 3G WCDMA Band4 CH1513
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3313.30	32.48	54.00	-21.52	30.35	2.13	Average	100	20
2	3313.30	42.80	74.00	-31.20	40.67	2.13	Peak	100	20
3	4189.60	34.13	54.00	-19.87	29.58	4.55	Average	100	40
4	4189.60	44.93	74.00	-29.07	40.38	4.55	Peak	100	40

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


<b>Test mode</b>	2.4G 11g CH06 + LTE Band 12, CH23095
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3144.00	32.88	54.00	-21.12	30.56	2.32	Average	100	40
2	3144.00	43.59	74.00	-30.41	41.27	2.32	Peak	100	40
3	3851.00	34.44	54.00	-19.56	30.45	3.99	Average	100	30
4	3851.00	45.67	74.00	-28.33	41.68	3.99	Peak	100	30

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	2.4G 11g CH06 + LTE Band 12, CH23095
<b>Polarization</b>	Vertical




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3144.00	32.84	54.00	-21.16	30.52	2.32	Average	100	20
2	3144.00	43.65	74.00	-30.35	41.33	2.32	Peak	100	20
3	3851.00	34.50	54.00	-19.50	30.51	3.99	Average	100	90
4	3851.00	45.53	74.00	-28.47	41.54	3.99	Peak	100	90

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	5G 11ac CH48 + 2G GSM850 CH251
<b>Polarization</b>	Horizontal




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4391.20	36.85	54.00	-17.15	31.57	5.28	Average	100	30
2	4391.20	46.85	74.00	-27.15	41.57	5.28	Peak	100	30
3	6088.80	37.84	54.00	-16.16	29.55	8.29	Average	100	30
4	6088.80	49.89	74.00	-24.11	41.60	8.29	Peak	100	30

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	5G 11ac CH48 + 2G GSM850 CH251
<b>Polarization</b>	Vertical




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4391.20	36.60	54.00	-17.40	31.32	5.28	Average	100	50
2	4391.20	46.90	74.00	-27.10	41.62	5.28	Peak	100	50
3	6088.80	37.86	54.00	-16.14	29.57	8.29	Average	100	40
4	6088.80	49.84	74.00	-24.16	41.55	8.29	Peak	100	40

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	5G 11ac CH48 + 2G PCS1900 CH512
<b>Polarization</b>	Horizontal




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3389.80	33.63	54.00	-20.37	31.48	2.15	Average	100	50
2	3389.80	43.77	74.00	-30.23	41.62	2.15	Peak	100	50
3	7090.20	42.78	54.00	-11.22	31.52	11.26	Average	100	20
4	7090.20	52.87	74.00	-21.13	41.61	11.26	Peak	100	20

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	5G 11ac CH48 + 2G PCS1900 CH512
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3389.80	33.40	54.00	-20.60	31.25	2.15	Average	100	100
2	3389.80	43.40	74.00	-30.60	41.25	2.15	Peak	100	100
3	7090.20	42.83	54.00	-11.17	31.57	11.26	Average	100	40
4	7090.20	52.83	74.00	-21.17	41.57	11.26	Peak	100	40


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).




<b>Test mode</b>	5G 11ac CH48 + 3G WCDMA Band4 CH1513
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3487.40	33.10	54.00	-20.90	30.51	2.59	Average	100	30
2	3487.40	43.97	74.00	-30.03	41.38	2.59	Peak	100	30
3	6992.60	42.19	54.00	-11.81	31.37	10.82	Average	100	60
4	6992.60	52.79	74.00	-21.21	41.97	10.82	Peak	100	60

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


<b>Test mode</b>	5G 11ac CH48 + 3G WCDMA Band4 CH1513
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3487.40	33.17	54.00	-20.83	30.58	2.59	Average	100	20
2	3487.40	43.96	74.00	-30.04	41.37	2.59	Peak	100	20
3	6992.60	41.58	54.00	-12.42	30.76	10.82	Average	100	40
4	6992.60	52.45	74.00	-21.55	41.63	10.82	Peak	100	40

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


<b>Test mode</b>	5G 11ac CH48 + LTE Band 12, CH23095
<b>Polarization</b>	Horizontal



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4533.00	36.41	54.00	-17.59	30.64	5.77	Average	100	30
2	4533.00	47.15	74.00	-26.85	41.38	5.77	Peak	100	30
3	5947.00	39.51	54.00	-14.49	31.39	8.12	Average	100	90
4	5947.00	49.66	74.00	-24.34	41.54	8.12	Peak	100	90

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	5G 11ac CH48 + LTE Band 12, CH23095
<b>Polarization</b>	Vertical




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4533.00	36.22	54.00	-17.78	30.45	5.77	Average	100	40
2	4533.00	47.29	74.00	-26.71	41.52	5.77	Peak	100	40
3	5947.00	39.47	54.00	-14.53	31.35	8.12	Average	100	100
4	5947.00	49.55	74.00	-24.45	41.43	8.12	Peak	100	100

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	BT Normal link + WWAN 2G GPRS 850 CH251
<b>Polarization</b>	Horizontal




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1592.20	35.50	54.00	-18.50	39.22	-3.72	Average	100	101
2	1592.20	48.54	74.00	-25.46	52.26	-3.72	Peak	100	101
3	3289.80	29.33	54.00	-24.67	27.16	2.17	Average	100	108
4	3289.80	41.72	54.00	-12.28	39.55	2.17	Average	100	108

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


<b>Test mode</b>	BT Normal link + WWAN 2G GPRS 850 CH251
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1592.20	35.11	54.00	-18.89	38.83	-3.72	Average	100	58
2	1592.20	48.87	74.00	-25.13	52.59	-3.72	Peak	100	58
3	3289.80	29.50	54.00	-24.50	27.33	2.17	Average	100	57
4	3289.80	41.50	74.00	-32.50	39.33	2.17	Peak	100	57

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	BT Normal link + WWAN 2G GPRS 1900 CH512
<b>Polarization</b>	Horizontal




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4291.20	32.18	54.00	-21.82	27.23	4.95	Average	100	109
2	4291.20	44.51	74.00	-29.49	39.56	4.95	Peak	100	109
3	6141.40	35.86	54.00	-18.14	27.58	8.28	Average	100	105
4	6141.40	47.89	74.00	-26.11	39.61	8.28	Peak	100	105

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	BT Normal link + WWAN 2G GPRS 1900 CH512
<b>Polarization</b>	Vertical




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4291.20	32.62	54.00	-21.38	27.67	4.95	Average	100	57
2	4291.20	44.51	74.00	-29.49	39.56	4.95	Peak	100	57
3	6141.40	36.33	54.00	-17.67	28.05	8.28	Average	100	54
4	6141.40	48.35	74.00	-25.65	40.07	8.28	Peak	100	54

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



<b>Test mode</b>	BT Normal link + WWAN 3G WCDMA Band4 CH1513								
<b>Polarization</b>	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	4196.30	31.96	54.00	-22.04	27.38	4.58	Average	100	104
2	4196.30	43.77	74.00	-30.23	39.19	4.58	Peak	100	104
3	5946.20	35.84	54.00	-18.16	27.72	8.12	Average	100	102
4	5946.20	47.76	74.00	-26.24	39.64	8.12	Peak	100	102
<p>Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)          *Factor includes antenna factor , cable loss and amplifier gain          Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).</p>									

<b>Test mode</b>	BT Normal link + WWAN 3G WCDMA Band4 CH1513
<b>Polarization</b>	Vertical




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4196.30	32.07	54.00	-21.93	27.49	4.58	Average	100	57
2	4196.30	44.10	74.00	-29.90	39.52	4.58	Peak	100	57
3	5946.20	36.09	54.00	-17.91	27.97	8.12	Average	100	55
4	5946.20	47.97	74.00	-26.03	39.85	8.12	Peak	100	55

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	BT Normal link + WWAN LTE Band 12 Channel 23095
<b>Polarization</b>	Horizontal




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1733.50	35.09	54.00	-18.91	38.57	-3.48	Average	100	101
2	1733.50	47.88	74.00	-26.12	51.36	-3.48	Peak	100	101
3	3148.50	30.40	54.00	-23.60	28.05	2.35	Average	100	104
4	3148.50	41.82	74.00	-32.18	39.47	2.35	Peak	100	104

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Test mode</b>	BT Normal link + WWAN LTE Band 12 Channel 23095
<b>Polarization</b>	Vertical



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1733.50	34.72	54.00	-19.28	38.20	-3.48	Average	100	55
2	1733.50	47.78	74.00	-26.22	51.26	-3.48	Peak	100	55
3	3148.50	30.80	54.00	-23.20	28.45	2.35	Average	100	58
4	3148.50	41.92	74.00	-32.08	39.57	2.35	Peak	100	58

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

### **Linkou**

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin  
Kou District, New Taipei City,  
Taiwan, R.O.C.

### **Kwei Shan**

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,  
Kwei Shan District, Tao Yuan City  
333, Taiwan, R.O.C.

### **Kwei Shan Site II**

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan District, Tao Yuan  
City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==