

# FCC Test Report

**FCC ID** : SQGBL5340  
**Equipment** : BT5.2 BLE module ( with passive NFC -  
13.56MHz & 802.15.4 )  
**Model No.** : BL5340  
**Brand Name** : Laird Connectivity  
**Applicant** : Laird Connectivity  
**Address** : W66N220 Commerce Court, Cedarburg,  
Wisconsin 53012, USA  
**Standard** : 47 CFR FCC Part 15.247  
**Received Date** : Jan. 27, 2021  
**Tested Date** : Feb. 05 ~ Mar. 12, 2021

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

  
\_\_\_\_\_  
Along Chen / Assistant Manager

Approved by:

  
\_\_\_\_\_  
Gary Chang / Manager



---

## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Local Support Equipment List .....	8
1.3	Test Setup Chart .....	8
1.4	The Equipment List .....	9
1.5	Test Standards .....	10
1.6	Reference Guidance .....	10
1.7	Deviation from Test Standard and Measurement Procedure.....	10
1.8	Measurement Uncertainty .....	10
<b>2</b>	<b>TEST CONFIGURATION .....</b>	<b>11</b>
2.1	Testing Facility.....	11
2.2	The Worst Test Modes and Channel Details .....	11
<b>3</b>	<b>TRANSMITTER TEST RESULTS.....</b>	<b>12</b>
3.1	Conducted Emissions.....	12
3.2	6dB and Occupied Bandwidth .....	15
3.3	RF Output Power .....	22
3.4	Power Spectral Density .....	25
3.5	Unwanted Emissions into Restricted Frequency Bands .....	32
3.6	Emissions in Non-Restricted Frequency Bands .....	76
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>81</b>

---

## Release Record

Report No.	Version	Description	Issued Date
FR112703	Rev. 01	Initial issue	May 13, 2021

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.549MHz 24.33 (Margin -21.67dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 160.95MHz 39.61 (Margin -3.89dB) - PK	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 3.21	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

### Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

# 1 General Description

## 1.1 Information

### 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Mode	Ch. Frequency (MHz)	Channel Number	Data Rate
2400~2483.5	802.15.4	2405~2480	11-26 [16]	250kbps
Note 1: 802.15.4 uses DSSS-OQPSK modulation.				

### 1.1.2 Antenna Details

Ant. No.	Brand	Model	Type	Connector	2400-2500MHz	2400-2480MHz	Remarks
					Gain (dBi)		
1	Laird	NanoBlue	PCB Dipole	IPEX MHF4	2	---	External
2	Laird	FlexPIFA	PCB Dipole	IPEX MHF4	---	2	External
3	Mag.Layers	EDA-8709-2G4C1-B27-CY	Dipole	IPEX MHF4	2	---	External
4	Laird	mFlexPIFA	PIFA	IPEX MHF4	---	2	External
5	Laird	BL5340 onboard printed PCB Trace antenna	Printed PCB	---	1.49	---	Internal
6	Laird	Laird NFC	spiral	---	---	---	External

### 1.1.3 Power Supply Type of Equipment under Test (EUT)

<b>Power Supply Type</b>	1.8 Vdc / 3.3Vdc / 5Vdc from host
--------------------------	-----------------------------------

### 1.1.4 Accessories

N/A

### 1.1.5 Channel List

Channel No.	Frequency (MHz)
11	2405
12	2410
13	2415
14	2420
15	2425
16	2430
17	2435
18	2440
19	2445
20	2450
21	2455
22	2460
23	2465
24	2470
25	2475
26	2480

### 1.1.6 Test Tool and Duty Cycle

<b>Test Tool</b>	Tera Term, V 4.74	
<b>Duty Cycle and Duty Factor</b>	<b>Duty Cycle (%)</b>	<b>Duty Factor (dB)</b>
	100	0

### 1.1.7 Power Index of Test Tool

#### *Internal antenna, Lower power*

Modulation Mode	Test Frequency (MHz)	Power Index
OQPSK	2405	-40
OQPSK	2440	-40
OQPSK	2475	-40
OQPSK	2480	-40



#### *Internal antenna, high power*

Modulation Mode	Test Frequency (MHz)	Power Index
OQPSK	2405	0
OQPSK	2440	0
OQPSK	2475	0
OQPSK	2480	-8

## 1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Notebook	DELL	Latitude 5400	DoC	---
2	50Ω terminator	---	---	---	---
3	Fixture	---	---	---	Provided by applicant.

## 1.3 Test Setup Chart





## 1.4 The Equipment List

<b>Test Item</b>	Conducted Emission				
<b>Test Site</b>	Conduction room 1 / (CO01-WS)				
<b>Tested Date</b>	Feb. 05, 2021				
<b>Instrument</b>	<b>Brand</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Receiver	R&S	ESR3	101657	Feb. 14, 2020	Feb. 13, 2021
LISN	R&S	ENV216	101579	Mar. 12, 2020	Mar. 11, 2021
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 21, 2020	Oct. 20, 2021
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

<b>Test Item</b>	Radiated Emission				
<b>Test Site</b>	966 chamber1 / (03CH01-WS)				
<b>Tested Date</b>	Mar. 03 ~ Mar. 04, 2021				
<b>Instrument</b>	<b>Brand</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101498	Dec. 04, 2020	Dec. 03, 2021
Receiver	R&S	ESR3	101658	Feb. 08, 2021	Feb. 07, 2022
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 10, 2020	Jul. 09, 2021
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 11, 2020	Dec. 10, 2021
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 06, 2020	Nov. 05, 2021
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 17, 2020	Nov. 16, 2021
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 06, 2020	Oct. 05, 2021
Preamplifier	EMC	EMC02325	980225	Jul. 03, 2020	Jul. 02, 2021
Preamplifier	Agilent	83017A	MY39501308	Sep. 26, 2020	Sep. 25, 2021
Preamplifier	EMC	EMC184045B	980192	Jul. 21, 2020	Jul. 20, 2021
RF Cable	EMC	EMC104-SM-SM-8000	181106	Oct. 06, 2020	Oct. 05, 2021
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 06, 2020	Oct. 05, 2021
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 06, 2020	Oct. 05, 2021
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 06, 2020	Oct. 05, 2021
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 06, 2020	Oct. 05, 2021
LF cable 11M	EMC	EMCCFD400-NW-N W-11000	200801	Oct. 06, 2020	Oct. 05, 2021
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

<b>Test Item</b>	RF Conducted				
<b>Test Site</b>	(TH01-WS)				
<b>Tested Date</b>	Mar. 12, 2021				
<b>Instrument</b>	<b>Brand</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101063	Apr. 30, 2020	Apr. 29, 2021
Power Meter	Anritsu	ML2495A	1241002	Nov. 04, 2020	Nov. 03, 2021
Power Sensor	Anritsu	MA2411B	1207366	Nov. 04, 2020	Nov. 03, 2021
DC POWER SOURCE	GW INSTEK	GPC-6030D	GES855395	Nov. 09, 2020	Nov. 08, 2021
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

## 1.5 Test Standards

47 CFR FCC Part 15.247  
ANSI C63.10-2013

## 1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

## 1.7 Deviation from Test Standard and Measurement Procedure

None

## 1.8 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ( $k=2$ )).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	$\pm 34.130$ Hz
Conducted power	$\pm 0.808$ dB
Power density	$\pm 0.583$ dB
Conducted emission	$\pm 2.715$ dB
AC conducted emission	$\pm 2.92$ dB
Radiated emission $\leq 1$ GHz	$\pm 3.41$ dB
Radiated emission $> 1$ GHz	$\pm 4.59$ dB

## 2 Test Configuration

### 2.1 Testing Facility

<b>Test Laboratory</b>	International Certification Corp.
<b>Test Site</b>	CO01-WS, 03CH01-WS, TH01-WS
<b>Address of Test Site</b>	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

### 2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Conducted Emissions	OQPSK	2405	250kbps	3
Radiated Emissions ≤1GHz	OQPSK	2405	250kbps	1, 2 <sup>Note4</sup>
Radiated Emissions >1GHz	OQPSK	2405 / 2440 / 2475 / 2480	250kbps	1, 2 <sup>Note4</sup>
Maximum Output Power 6dB bandwidth Power spectral density	OQPSK	2405 / 2440 / 2475 / 2480	250kbps	1, 2 <sup>Note4</sup>

**NOTE:**

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** result was found as the worst case and was shown in this report.
2. The EUT supports three DC voltage options, DC 1.8V, DC 3.3V & DC 5V. Three options were assessed and DC 3.3V was found to be the worst case and was selected for the final test.
3. Test configurations are listed as below:
  - 1) Configuration 1: Internal antenna, Lower power
  - 2) Configuration 2: Internal antenna, high power
  - 3) Configuration 3: External antenna, high power
4. The 50Ω terminators are connected to antenna port of EUT for radiated emission measurement.

## 3 Transmitter Test Results

### 3.1 Conducted Emissions

#### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.

#### 3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.


#### 3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


### External antenna, high power

#### 3.1.4 Test Result of Conducted Emissions

Modulation	OQPSK	Test Freq. (MHz)	2405																																																																																																																					
Power Phase	Line																																																																																																																							
Test by : Alex Tsai      Temperature: 20°C      Humidity: 60%																																																																																																																								
																																																																																																																								
<table border="1"> <thead> <tr> <th></th> <th>Freq MHz</th> <th>Level dBuV</th> <th>Limit Line dBuV</th> <th>Over Limit dB</th> <th>Read Level dBuV</th> <th>Factor dB</th> <th>Cable loss dB</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>0.175</td><td>26.90</td><td>54.72</td><td>-27.82</td><td>17.21</td><td>9.63</td><td>0.06</td><td>Average</td></tr> <tr><td>2</td><td>0.175</td><td>42.71</td><td>64.72</td><td>-22.01</td><td>33.02</td><td>9.63</td><td>0.06</td><td>QP</td></tr> <tr><td>3</td><td>0.209</td><td>26.26</td><td>53.23</td><td>-26.97</td><td>16.57</td><td>9.63</td><td>0.06</td><td>Average</td></tr> <tr><td>4</td><td>0.209</td><td>40.24</td><td>63.23</td><td>-22.99</td><td>30.55</td><td>9.63</td><td>0.06</td><td>QP</td></tr> <tr><td><b>5*</b></td><td><b>0.549</b></td><td><b>24.33</b></td><td><b>46.00</b></td><td><b>-21.67</b></td><td><b>14.61</b></td><td><b>9.63</b></td><td><b>0.09</b></td><td><b>Average</b></td></tr> <tr><td>6</td><td>0.549</td><td>31.24</td><td>56.00</td><td>-24.76</td><td>21.52</td><td>9.63</td><td>0.09</td><td>QP</td></tr> <tr><td>7</td><td>3.310</td><td>22.69</td><td>46.00</td><td>-23.31</td><td>12.78</td><td>9.65</td><td>0.26</td><td>Average</td></tr> <tr><td>8</td><td>3.310</td><td>28.33</td><td>56.00</td><td>-27.67</td><td>18.42</td><td>9.65</td><td>0.26</td><td>QP</td></tr> <tr><td>9</td><td>16.661</td><td>19.69</td><td>50.00</td><td>-30.31</td><td>9.35</td><td>9.71</td><td>0.63</td><td>Average</td></tr> <tr><td>10</td><td>16.661</td><td>26.62</td><td>60.00</td><td>-33.38</td><td>16.28</td><td>9.71</td><td>0.63</td><td>QP</td></tr> <tr><td>11</td><td>25.591</td><td>14.13</td><td>50.00</td><td>-35.87</td><td>3.76</td><td>9.66</td><td>0.71</td><td>Average</td></tr> <tr><td>12</td><td>25.591</td><td>18.17</td><td>60.00</td><td>-41.83</td><td>7.80</td><td>9.66</td><td>0.71</td><td>QP</td></tr> </tbody> </table>					Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Remark	1	0.175	26.90	54.72	-27.82	17.21	9.63	0.06	Average	2	0.175	42.71	64.72	-22.01	33.02	9.63	0.06	QP	3	0.209	26.26	53.23	-26.97	16.57	9.63	0.06	Average	4	0.209	40.24	63.23	-22.99	30.55	9.63	0.06	QP	<b>5*</b>	<b>0.549</b>	<b>24.33</b>	<b>46.00</b>	<b>-21.67</b>	<b>14.61</b>	<b>9.63</b>	<b>0.09</b>	<b>Average</b>	6	0.549	31.24	56.00	-24.76	21.52	9.63	0.09	QP	7	3.310	22.69	46.00	-23.31	12.78	9.65	0.26	Average	8	3.310	28.33	56.00	-27.67	18.42	9.65	0.26	QP	9	16.661	19.69	50.00	-30.31	9.35	9.71	0.63	Average	10	16.661	26.62	60.00	-33.38	16.28	9.71	0.63	QP	11	25.591	14.13	50.00	-35.87	3.76	9.66	0.71	Average	12	25.591	18.17	60.00	-41.83	7.80	9.66	0.71	QP
	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Remark																																																																																																																
1	0.175	26.90	54.72	-27.82	17.21	9.63	0.06	Average																																																																																																																
2	0.175	42.71	64.72	-22.01	33.02	9.63	0.06	QP																																																																																																																
3	0.209	26.26	53.23	-26.97	16.57	9.63	0.06	Average																																																																																																																
4	0.209	40.24	63.23	-22.99	30.55	9.63	0.06	QP																																																																																																																
<b>5*</b>	<b>0.549</b>	<b>24.33</b>	<b>46.00</b>	<b>-21.67</b>	<b>14.61</b>	<b>9.63</b>	<b>0.09</b>	<b>Average</b>																																																																																																																
6	0.549	31.24	56.00	-24.76	21.52	9.63	0.09	QP																																																																																																																
7	3.310	22.69	46.00	-23.31	12.78	9.65	0.26	Average																																																																																																																
8	3.310	28.33	56.00	-27.67	18.42	9.65	0.26	QP																																																																																																																
9	16.661	19.69	50.00	-30.31	9.35	9.71	0.63	Average																																																																																																																
10	16.661	26.62	60.00	-33.38	16.28	9.71	0.63	QP																																																																																																																
11	25.591	14.13	50.00	-35.87	3.76	9.66	0.71	Average																																																																																																																
12	25.591	18.17	60.00	-41.83	7.80	9.66	0.71	QP																																																																																																																
Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB). Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).																																																																																																																								

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2405
<b>Power Phase</b>	Neutral		

Test by : Alex Tsai      Temperature: 20°C      Humidity: 60%



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Remark
1	0.159	24.72	55.52	-30.80	15.01	9.66	0.05	Average
2	0.159	43.14	65.52	-22.38	33.43	9.66	0.05	QP
3	0.227	11.66	52.57	-40.91	1.95	9.65	0.06	Average
4	0.227	33.30	62.57	-29.27	23.59	9.65	0.06	QP
5*	0.546	24.30	46.00	-21.70	14.56	9.65	0.09	Average
6	0.546	31.17	56.00	-24.83	21.43	9.65	0.09	QP
7	3.293	22.57	46.00	-23.43	12.64	9.67	0.26	Average
8	3.293	28.12	56.00	-27.88	18.19	9.67	0.26	QP
9	16.661	17.99	50.00	-32.01	7.55	9.81	0.63	Average
10	16.661	25.63	60.00	-34.37	15.19	9.81	0.63	QP
11	25.188	16.30	50.00	-33.70	5.80	9.80	0.70	Average
12	25.188	20.82	60.00	-39.18	10.32	9.80	0.70	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).  
 Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

## 3.2 6dB and Occupied Bandwidth

### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.2.2 Test Procedures

#### 6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

#### Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

### 3.2.3 Test Setup



### 3.2.4 Test Result of 6dB and Occupied Bandwidth

Ambient Condition	24°C / 63%	Tested By	Aska Huang
-------------------	------------	-----------	------------

#### Internal antenna, Lower power

##### Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
802.15.4	1.558M	2.406M	2M41D1D	1.467M	2.37M

**Max-N dB** = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;


**Min-N dB** = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

##### Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.15.4	-	-	-	-
2405MHz	Pass	500k	1.486M	2.37M
2440MHz	Pass	500k	1.54M	2.37M
2475MHz	Pass	500k	1.467M	2.388M
2480MHz	Pass	500k	1.558M	2.406M

**Port X-N dB** = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;






802.15.4

EBW

2480MHz



6dB(Hz)	Fl-6dB(Hz)	Fh-6dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.558M	2.479221G	2.480779G	2.406M	2.47877G	2.481176G	500k	1

### Internal antenna, high power

#### Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
802.15.4	1.558M	2.37M	2M37D1D	1.522M	2.297M

**Max-N dB** = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;  
**Min-N dB** = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

#### Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.15.4	-	-	-	-
2405MHz	Pass	500k	1.558M	2.297M
2440MHz	Pass	500k	1.54M	2.315M
2475MHz	Pass	500k	1.522M	2.334M
2480MHz	Pass	500k	1.558M	2.37M

**Port X-N dB** = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

**802.15.4**


**EBW**

**2405MHz**

CF  
2.405GHz  
Span  
12.5MHz  
RBW  
100kHz  
VBW  
300kHz  
Sweep Time  
1.02ms  
Detector Type  
Peak



CF  
2.405GHz  
Span  
12.5MHz  
RBW  
30kHz  
VBW  
100kHz  
Sweep Time  
1.39ms  
Detector Type  
Sample




6dB(Hz)	Fl-6dB(Hz)	Fh-6dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.558M	2.404221G	2.405779G	2.297M	2.403842G	2.40614G	500k	1

**802.15.4**


**EBW**

**2440MHz**

CF  
2.44GHz  
Span  
12.5MHz  
RBW  
100kHz  
VBW  
300kHz  
Sweep Time  
1.02ms  
Detector Type  
Peak



CF  
2.44GHz  
Span  
12.5MHz  
RBW  
30kHz  
VBW  
100kHz  
Sweep Time  
1.39ms  
Detector Type  
Sample



6dB(Hz)	Fl-6dB(Hz)	Fh-6dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.54M	2.439221G	2.440761G	2.315M	2.438842G	2.441158G	500k	1

**802.15.4**


**EBW**

**2475MHz**

CF  
2.475GHz  
Span  
12.5MHz  
RBW  
100kHz  
VBW  
300kHz  
Sweep Time  
1.02ms  
Detector Type  
Peak



CF  
2.475GHz  
Span  
12.5MHz  
RBW  
30kHz  
VBW  
100kHz  
Sweep Time  
1.39ms  
Detector Type  
Sample




6dB(Hz)	Fl-6dB(Hz)	Fh-6dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.522M	2.474221G	2.475743G	2.334M	2.473824G	2.476158G	500k	1

802.15.4

EBW

2480MHz



6dB(Hz)	Fl-6dB(Hz)	Fh-6dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.558M	2.479221G	2.480779G	2.37M	2.478788G	2.481158G	500k	1

### 3.3 RF Output Power

#### 3.3.1 Limit of RF Output Power


Conducted power shall not exceed 1Watt.

Antenna gain  $\leq 6\text{dBi}$ , no any corresponding reduction is in output power limit.

#### 3.3.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

#### 3.3.3 Test Setup



### 3.3.4 Test Result of Maximum Output Power

Ambient Condition	24°C / 63%	Tested By	Aska Huang
-------------------	------------	-----------	------------

#### Internal antenna, Lower power

##### Summary of Peak Conducted Output Power

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.15.4	-37.03	0.0000002

##### Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.15.4	-	-	-	-	-	-	-
2405MHz	Pass	2.00	-37.26	-37.26	30.00	-35.26	36.00
2440MHz	Pass	2.00	-37.09	-37.09	30.00	-35.09	36.00
2475MHz	Pass	2.00	-37.13	-37.13	30.00	-35.13	36.00
2480MHz	Pass	2.00	-37.03	-37.03	30.00	-35.03	36.00

DG = Directional Gain; Port X = Port X output power

##### Summary of Conducted (Average) Output Power

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.15.4	-38.43	0.0000001

##### Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.15.4	-	-	-	-	-	-	-
2405MHz	Pass	2.00	-38.67	-38.67	-	-36.67	-
2440MHz	Pass	2.00	-38.49	-38.49	-	-36.49	-
2475MHz	Pass	2.00	-38.43	-38.43	-	-36.43	-
2480MHz	Pass	2.00	-38.43	-38.43	-	-36.43	-

DG = Directional Gain; Port X = Port X output power

Note : Conducted average output power is for reference only

### Internal antenna, high power

#### Summary of Peak Conducted Output Power

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.15.4	3.21	0.00209

#### Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.15.4	-	-	-	-	-	-	-
2405MHz	Pass	2.00	3.21	3.21	30.00	5.21	36.00
2440MHz	Pass	2.00	3.12	3.12	30.00	5.12	36.00
2475MHz	Pass	2.00	2.97	2.97	30.00	4.97	36.00
2480MHz	Pass	2.00	-3.42	-3.42	30.00	-1.42	36.00

DG = Directional Gain; Port X = Port X output power

#### Summary of Conducted (Average) Output Power

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.15.4	3.12	0.00205

#### Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.15.4	-	-	-	-	-	-	-
2405MHz	Pass	2.00	3.12	3.12	-	5.12	-
2440MHz	Pass	2.00	3.02	3.02	-	5.02	-
2475MHz	Pass	2.00	2.88	2.88	-	4.88	-
2480MHz	Pass	2.00	-3.98	-3.98	-	-1.98	-

DG = Directional Gain; Port X = Port X output power

Note : Conducted average output power is for reference only



## 3.4 Power Spectral Density


### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

### 3.4.2 Test Procedures

1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

### 3.4.3 Test Setup



### 3.4.4 Test Result of Power Spectral Density

<b>Ambient Condition</b>	24°C / 63%	<b>Tested By</b>	Aska Huang
--------------------------	------------	------------------	------------

#### *Internal antenna, Lower power* Summary


Mode	PD (dBm/3kHz)
2.4-2.4835GHz	-
802.15.4	-51.90


#### Result

Mode	Result	DG (dBi)	Port 1 (dBm/3kHz)	PD (dBm/3kHz)	PD Limit (dBm/3kHz)
802.15.4	-	-	-	-	-
2405MHz	Pass	2.00	-55.07	-55.07	8.00
2440MHz	Pass	2.00	-54.03	-54.03	8.00
2475MHz	Pass	2.00	-51.90	-51.90	8.00
2480MHz	Pass	2.00	-53.31	-53.31	8.00

**DG** = Directional Gain;

**PD** =Maximum power density; **Port X** = Port X power density;





### Internal antenna, high power

#### Summary


Mode	PD (dBm/3kHz)
2.4-2.4835GHz	-
802.15.4	-12.03


#### Result

Mode	Result	DG (dBi)	Port 1 (dBm/3kHz)	PD (dBm/3kHz)	PD Limit (dBm/3kHz)
802.15.4	-	-	-	-	-
2405MHz	Pass	2.00	-12.75	-12.75	8.00
2440MHz	Pass	2.00	-13.48	-13.48	8.00
2475MHz	Pass	2.00	-12.03	-12.03	8.00
2480MHz	Pass	2.00	-19.24	-19.24	8.00

**DG** = Directional Gain;

**PD** = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;





## 3.5 Unwanted Emissions into Restricted Frequency Bands

### 3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

### 3.5.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


**Note:**

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.




### 3.5.3 Test Setup


#### Radiated Emissions below 1 GHz



#### Radiated Emissions above 1 GHz




#### Transmitter Conducted Unwanted Emissions (30MHz~40GHz)




### Internal antenna, Lower power

#### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	OQPSK	Test Freq. (MHz)	2405						
Polarization	Horizontal								
Test By : Roger Lu      Temperature(°C):23      Humidity(%):68									
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (30 to 1000). A red step function represents the CLASS-B limit, starting at 40 dBuV/m from 30 MHz to 100 MHz, rising to 45 dBuV/m at 200 MHz, and rising to 50 dBuV/m at 900 MHz. Six blue vertical lines indicate emission peaks at 67.58 MHz (labeled 1), 161.18 MHz (labeled 2), 256.58 MHz (labeled 3), 480.48 MHz (labeled 4), 673.05 MHz (labeled 5), and 959.02 MHz (labeled 6).</p>									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			
1	67.58	28.41	40.00	-11.59	38.59	-10.18	Peak	---	---
2	161.18	39.45	43.50	-4.05	48.38	-8.93	Peak	---	---
3	256.58	26.87	46.00	-19.13	36.76	-9.89	Peak	---	---
4	480.48	32.59	46.00	-13.41	36.24	-3.65	Peak	---	---
5	673.05	33.54	46.00	-12.46	33.81	-0.27	Peak	---	---
6	959.02	37.64	46.00	-8.36	32.88	4.76	Peak	---	---
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).            Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.</p>									

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2405
<b>Polarization</b>	Vertical		

Test By :Roger Lu      Temperature(°C):23      Humidity(%):68



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	30.28	32.29	40.00	-7.71	41.85	-9.56	Peak	---	---
2	67.61	27.54	40.00	-12.46	37.72	-10.18	Peak	---	---
3	79.58	26.18	40.00	-13.82	39.35	-13.17	Peak	---	---
4	158.26	27.58	43.50	-15.92	36.48	-8.90	Peak	---	---
5	440.15	28.64	46.00	-17.36	33.21	-4.57	Peak	---	---
6	959.58	38.06	46.00	-7.94	33.29	4.77	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2405																																																																							
<b>Polarization</b>	Horizontal																																																																									
Test By : Roger Lu      Temperature(°C):24      Humidity(%):61																																																																										
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 25000). Two horizontal red lines represent limits: CLASS-B at approximately 75 dBuV/m and CLASS-B (AVG) at approximately 55 dBuV/m. Six vertical blue lines represent emission peaks, labeled 2, 4, 5, and 6. Peak 2 is at 3840 MHz, peak 4 at 4810 MHz, peak 5 at 12025 MHz, and peak 6 at 12025 MHz. The table below provides the numerical data for these peaks.</p>																																																																										
	<table border="1"> <thead> <tr> <th></th> <th>Freq. MHz</th> <th>Emission level dBuV/m</th> <th>Limit dBuV/m</th> <th>Margin dB</th> <th>SA reading dBuV</th> <th>Factor dB</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>3840.00</td> <td>29.51</td> <td>54.00</td> <td>-24.49</td> <td>28.65</td> <td>0.86</td> <td>Average</td> <td>100</td> <td>65</td> </tr> <tr> <td>2</td> <td>3840.00</td> <td>41.44</td> <td>74.00</td> <td>-32.56</td> <td>40.58</td> <td>0.86</td> <td>Peak</td> <td>100</td> <td>65</td> </tr> <tr> <td>3</td> <td>4810.00</td> <td>31.81</td> <td>54.00</td> <td>-22.19</td> <td>28.32</td> <td>3.49</td> <td>Average</td> <td>100</td> <td>50</td> </tr> <tr> <td>4</td> <td>4810.00</td> <td>44.17</td> <td>74.00</td> <td>-29.83</td> <td>40.68</td> <td>3.49</td> <td>Peak</td> <td>100</td> <td>50</td> </tr> <tr> <td>5</td> <td>12025.00</td> <td>44.58</td> <td>54.00</td> <td>-9.42</td> <td>30.29</td> <td>14.29</td> <td>Average</td> <td>100</td> <td>40</td> </tr> <tr> <td>6</td> <td>12025.00</td> <td>56.75</td> <td>74.00</td> <td>-17.25</td> <td>42.46</td> <td>14.29</td> <td>Peak</td> <td>100</td> <td>40</td> </tr> </tbody> </table>		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	3840.00	29.51	54.00	-24.49	28.65	0.86	Average	100	65	2	3840.00	41.44	74.00	-32.56	40.58	0.86	Peak	100	65	3	4810.00	31.81	54.00	-22.19	28.32	3.49	Average	100	50	4	4810.00	44.17	74.00	-29.83	40.68	3.49	Peak	100	50	5	12025.00	44.58	54.00	-9.42	30.29	14.29	Average	100	40	6	12025.00	56.75	74.00	-17.25	42.46	14.29	Peak	100	40			
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																	
1	3840.00	29.51	54.00	-24.49	28.65	0.86	Average	100	65																																																																	
2	3840.00	41.44	74.00	-32.56	40.58	0.86	Peak	100	65																																																																	
3	4810.00	31.81	54.00	-22.19	28.32	3.49	Average	100	50																																																																	
4	4810.00	44.17	74.00	-29.83	40.68	3.49	Peak	100	50																																																																	
5	12025.00	44.58	54.00	-9.42	30.29	14.29	Average	100	40																																																																	
6	12025.00	56.75	74.00	-17.25	42.46	14.29	Peak	100	40																																																																	
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																										


<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2405						
<b>Polarization</b>	Vertical								
Test By :Roger Lu		Temperature(°C):24	Humidity(%):61						
									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3840.00	29.35	54.00	-24.65	28.49	0.86	Average	100	192
2	3840.00	41.44	74.00	-32.56	40.58	0.86	Peak	100	192
3	4810.00	31.95	54.00	-22.05	28.46	3.49	Average	100	30
4	4810.00	45.07	74.00	-28.93	41.58	3.49	Peak	100	30
5	12025.00	44.55	54.00	-9.45	30.26	14.29	Average	100	40
6	12025.00	56.60	74.00	-17.40	42.31	14.29	Peak	100	40
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)  *Factor includes antenna factor , cable loss and amplifier gain  Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2440						
<b>Polarization</b>	Horizontal								
Test By :Roger Lu		Temperature(°C):24			Humidity(%):61				
									
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level	dBuV/m	dB	reading	dB		High	Table
		dBuV/m			dBuV			cm	deg
1	4880.00	31.81	54.00	-22.19	28.34	3.47	Average	100	20
2	4880.00	43.95	74.00	-30.05	40.48	3.47	Peak	100	20
3	7320.00	38.50	54.00	-15.50	29.48	9.02	Average	100	50
4	7320.00	51.49	74.00	-22.51	42.47	9.02	Peak	100	50
5	12200.00	44.65	54.00	-9.35	30.28	14.37	Average	100	30
6	12200.00	56.74	74.00	-17.26	42.37	14.37	Peak	100	30

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
\*Factor includes antenna factor , cable loss and amplifier gain  
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2440
<b>Polarization</b>	Vertical		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4880.00	31.92	54.00	-22.08	28.45	3.47	Average	100	50
2	4880.00	43.93	74.00	-30.07	40.46	3.47	Peak	100	50
3	7320.00	38.46	54.00	-15.54	29.44	9.02	Average	100	20
4	7320.00	51.23	74.00	-22.77	42.21	9.02	Peak	100	20
5	12200.00	44.48	54.00	-9.52	30.11	14.37	Average	100	30
6	12200.00	56.83	74.00	-17.17	42.46	14.37	Peak	100	30


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2475
<b>Polarization</b>	Horizontal		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4950.00	32.16	54.00	-21.84	28.54	3.62	Average	100	100
2	4950.00	44.29	74.00	-29.71	40.67	3.62	Peak	100	100
3	7425.00	38.28	54.00	-15.72	29.32	8.96	Average	100	30
4	7425.00	51.15	74.00	-22.85	42.19	8.96	Peak	100	30
5	12375.00	44.31	54.00	-9.69	30.19	14.12	Average	100	40
6	12375.00	56.76	74.00	-17.24	42.64	14.12	Peak	100	40

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2475
<b>Polarization</b>	Vertical		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4950.00	32.08	54.00	-21.92	28.46	3.62	Average	100	80
2	4950.00	43.99	74.00	-30.01	40.37	3.62	Peak	100	80
3	7425.00	38.30	54.00	-15.70	29.34	8.96	Average	100	20
4	7425.00	51.12	74.00	-22.88	42.16	8.96	Peak	100	20
5	12375.00	44.40	54.00	-9.60	30.28	14.12	Average	100	30
6	12375.00	56.67	74.00	-17.33	42.55	14.12	Peak	100	30


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Horizontal		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4960.00	31.99	54.00	-22.01	28.31	3.68	Average	100	50
2	4960.00	44.14	74.00	-29.86	40.46	3.68	Peak	100	50
3	7440.00	38.31	54.00	-15.69	29.33	8.98	Average	100	100
4	7440.00	51.29	74.00	-22.71	42.31	8.98	Peak	100	100
5	12400.00	44.23	54.00	-9.77	30.16	14.07	Average	100	90
6	12400.00	56.56	74.00	-17.44	42.49	14.07	Peak	100	90


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Vertical		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4960.00	31.96	54.00	-22.04	28.28	3.68	Average	100	50
2	4960.00	44.13	74.00	-29.87	40.45	3.68	Peak	100	50
3	7440.00	38.26	54.00	-15.74	29.28	8.98	Average	100	25
4	7440.00	51.15	74.00	-22.85	42.17	8.98	Peak	100	25
5	12400.00	44.25	54.00	-9.75	30.18	14.07	Average	100	40
6	12400.00	56.54	74.00	-17.46	42.47	14.07	Peak	100	40

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

**Internal antenna, high power**

**3.5.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)**

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2405
<b>Polarization</b>	Horizontal		

Test By :Roger Lu      Temperature(°C):23      Humidity(%):68



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	67.83	28.54	40.00	-11.46	38.70	-10.16	Peak	---	---
2	160.95	39.61	43.50	-3.89	48.53	-8.92	Peak	---	---
3	256.01	26.77	46.00	-19.23	36.67	-9.90	Peak	---	---
4	480.08	32.40	46.00	-13.60	36.05	-3.65	Peak	---	---
5	672.14	33.26	46.00	-12.74	33.50	-0.24	Peak	---	---
6	958.29	37.90	46.00	-8.10	33.14	4.76	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2405
<b>Polarization</b>	Vertical		

Test By :Roger Lu      Temperature(°C):23      Humidity(%):68



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	30.00	32.04	40.00	-7.96	41.52	-9.48	Peak	---	---
2	67.83	27.71	40.00	-12.29	37.87	-10.16	Peak	---	---
3	79.47	25.91	40.00	-14.09	39.05	-13.14	Peak	---	---
4	158.04	27.13	43.50	-16.37	36.06	-8.93	Peak	---	---
5	439.34	28.88	46.00	-17.12	33.46	-4.58	Peak	---	---
6	959.26	38.30	46.00	-7.70	33.54	4.76	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)


<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2405						
<b>Polarization</b>	Horizontal								
Test By : Roger Lu      Temperature(°C):24      Humidity(%):61									
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 25000). Two horizontal red lines represent CLASS-B limits: one at approximately 74 dBuV/m and another at approximately 54 dBuV/m. Six vertical blue lines represent emission peaks, labeled 1 through 6, with their corresponding data values listed in the table below.</p>									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	3840.00	29.73	54.00	-24.27	28.87	0.86	Average	100	70
2	3840.00	41.66	74.00	-32.34	40.80	0.86	Peak	100	70
3	4810.00	32.80	54.00	-21.20	29.31	3.49	Average	100	245
4	4810.00	45.14	74.00	-28.86	41.65	3.49	Peak	100	245
5	12025.00	44.44	54.00	-9.56	30.15	14.29	Average	100	60
6	12025.00	56.98	74.00	-17.02	42.69	14.29	Peak	100	60

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2405						
<b>Polarization</b>	Vertical								
Test By	:Roger Lu	Temperature(°C):24	Humidity(%):61						
									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3840.00	29.61	54.00	-24.39	28.75	0.86	Average	100	191
2	3840.00	41.51	74.00	-32.49	40.65	0.86	Peak	100	191
3	4810.00	32.84	54.00	-21.16	29.35	3.49	Average	100	248
4	4810.00	45.14	74.00	-28.86	41.65	3.49	Peak	100	248
5	12025.00	44.74	54.00	-9.26	30.45	14.29	Average	100	60
6	12025.00	56.78	74.00	-17.22	42.49	14.29	Peak	100	60
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)  *Factor includes antenna factor , cable loss and amplifier gain  Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2440
<b>Polarization</b>	Horizontal		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4880.00	32.67	54.00	-21.33	29.20	3.47	Average	100	238
2	4880.00	45.07	74.00	-28.93	41.60	3.47	Peak	100	238
3	7320.00	38.57	54.00	-15.43	29.55	9.02	Average	100	60
4	7320.00	51.21	74.00	-22.79	42.19	9.02	Peak	100	60
5	12200.00	44.52	54.00	-9.48	30.15	14.37	Average	100	30
6	12200.00	56.86	74.00	-17.14	42.49	14.37	Peak	100	30

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2440
<b>Polarization</b>	Vertical		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4880.00	32.75	54.00	-21.25	29.28	3.47	Average	100	249
2	4880.00	45.18	74.00	-28.82	41.71	3.47	Peak	100	249
3	7320.00	38.67	54.00	-15.33	29.65	9.02	Average	100	50
4	7320.00	51.33	74.00	-22.67	42.31	9.02	Peak	100	50
5	12200.00	44.76	54.00	-9.24	30.39	14.37	Average	100	40
6	12200.00	56.96	74.00	-17.04	42.59	14.37	Peak	100	40


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2475
<b>Polarization</b>	Horizontal		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4950.00	32.78	54.00	-21.22	29.16	3.62	Average	100	241
2	4950.00	45.20	74.00	-28.80	41.58	3.62	Peak	100	241
3	7425.00	38.43	54.00	-15.57	29.47	8.96	Average	100	55
4	7425.00	51.35	74.00	-22.65	42.39	8.96	Peak	100	55
5	12375.00	44.44	54.00	-9.56	30.32	14.12	Average	100	25
6	12375.00	56.88	74.00	-17.12	42.76	14.12	Peak	100	25


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2475
<b>Polarization</b>	Vertical		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4950.00	32.76	54.00	-21.24	29.14	3.62	Average	100	240
2	4950.00	45.10	74.00	-28.90	41.48	3.62	Peak	100	240
3	7425.00	38.45	54.00	-15.55	29.49	8.96	Average	100	100
4	7425.00	51.13	74.00	-22.87	42.17	8.96	Peak	100	100
5	12375.00	44.42	54.00	-9.58	30.30	14.12	Average	100	50
6	12375.00	56.99	74.00	-17.01	42.87	14.12	Peak	100	50


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Horizontal		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4960.00	32.13	54.00	-21.87	28.45	3.68	Average	100	200
2	4960.00	44.27	74.00	-29.73	40.59	3.68	Peak	100	200
3	7440.00	38.44	54.00	-15.56	29.46	8.98	Average	100	20
4	7440.00	51.43	74.00	-22.57	42.45	8.98	Peak	100	20
5	12400.00	44.30	54.00	-9.70	30.23	14.07	Average	100	40
6	12400.00	56.63	74.00	-17.37	42.56	14.07	Peak	100	40


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	OQPSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Vertical		

Test By :Roger Lu      Temperature(°C):24      Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	4960.00	32.12	54.00	-21.88	28.44	3.68	Average	100	80
2	4960.00	44.32	74.00	-29.68	40.64	3.68	Peak	100	80
3	7440.00	38.45	54.00	-15.55	29.47	8.98	Average	100	30
4	7440.00	51.29	74.00	-22.71	42.31	8.98	Peak	100	30
5	12400.00	44.41	54.00	-9.59	30.34	14.07	Average	100	60
6	12400.00	56.66	74.00	-17.34	42.59	14.07	Peak	100	60

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### Internal antenna, Lower power

### 3.5.8 Transmitter Conducted Unwanted Emissions (30MHz ~ 1GHz)

Ambient Condition	24°C / 63%	Tested By	Aska Huang
-------------------	------------	-----------	------------

#### Summary

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	GRF (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
802.15.4	Pass	30M	1G	PK	37.76M	2.00	-82.40	-82.40	4.7	-75.70	-55.20	-20.50

DG = Directional Gain;


PX=Port X; Psum=P1+..P2+..PX

#### Result

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	GRF (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
802.15.4	-	-	-	-	-	-	-	-	-	-	-	-
2480MHz	Pass	30M	1G	PK	37.76M	2.00	-82.40	-82.40	4.7	-75.70	-55.20	-20.50

DG = Directional Gain;

PX=Port X; Psum=P1+..P2+..PX



### 3.5.9 Transmitter Conducted Unwanted Emissions (1GHz ~ 3.1GHz)

<b>Ambient Condition</b>	24°C / 63%	<b>Tested By</b>	Aska Huang
--------------------------	------------	------------------	------------

#### Summary

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
802.15.4	Pass	1G	2.31G	AV	2.15395G	2.00	-72.36	-72.36	-70.36	-41.20	-29.16

DG = Directional Gain;

PX=Port X; Psum=P1+..P2+..PX

#### Result


Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
802.15.4	-	-	-	-	-	-	-	-	-	-	-
2405MHz	Pass	1G	2.31G	AV	2.15395G	2.00	-72.36	-72.36	-70.36	-41.20	-29.16
2405MHz	Pass	2.31G	2.39G	AV	2.31858G	2.00	-80.00	-80.00	-78.00	-41.20	-36.80
2405MHz	Pass	2.4835G	2.5G	AV	2.49732G	2.00	-79.69	-79.69	-77.69	-41.20	-36.49
2405MHz	Pass	2.5G	3.1G	AV	2.6887G	2.00	-78.62	-78.62	-76.62	-41.20	-35.42
2405MHz	Pass	1G	2.31G	PK	2.12791G	2.00	-59.71	-59.71	-57.71	-21.20	-36.51
2405MHz	Pass	2.31G	2.39G	PK	2.32275G	2.00	-67.95	-67.95	-65.95	-21.20	-44.75
2405MHz	Pass	2.4835G	2.5G	PK	2.48575G	2.00	-67.63	-67.63	-65.63	-21.20	-44.43
2405MHz	Pass	2.5G	3.1G	PK	2.6857G	2.00	-67.39	-67.39	-65.39	-21.20	-44.19
2440MHz	Pass	1G	2.31G	AV	2.12807G	2.00	-74.36	-74.36	-72.36	-41.20	-31.16
2440MHz	Pass	2.31G	2.39G	AV	2.34536G	2.00	-80.18	-80.18	-78.18	-41.20	-36.98
2440MHz	Pass	2.4835G	2.5G	AV	2.494G	2.00	-79.70	-79.70	-77.70	-41.20	-36.50
2440MHz	Pass	2.5G	3.1G	AV	2.6803G	2.00	-78.59	-78.59	-76.59	-41.20	-35.39
2440MHz	Pass	1G	2.31G	PK	2.12807G	2.00	-59.32	-59.32	-57.32	-21.20	-36.12
2440MHz	Pass	2.31G	2.39G	PK	2.32809G	2.00	-67.75	-67.75	-65.75	-21.20	-44.55
2440MHz	Pass	2.4835G	2.5G	PK	2.49548G	2.00	-67.55	-67.55	-65.55	-21.20	-44.35
2440MHz	Pass	2.5G	3.1G	PK	2.716G	2.00	-67.72	-67.72	-65.72	-21.20	-44.52
2475MHz	Pass	1G	2.31G	AV	2.15247G	2.00	-73.19	-73.19	-71.19	-41.20	-29.99
2475MHz	Pass	2.31G	2.39G	AV	2.34571G	2.00	-80.18	-80.18	-78.18	-41.20	-36.98
2475MHz	Pass	2.4835G	2.5G	AV	2.49703G	2.00	-79.69	-79.69	-77.69	-41.20	-36.49
2475MHz	Pass	2.5G	3.1G	AV	2.6938G	2.00	-78.65	-78.65	-76.65	-41.20	-35.45
2475MHz	Pass	1G	2.31G	PK	2.12807G	2.00	-58.82	-58.82	-56.82	-21.20	-35.62
2475MHz	Pass	2.31G	2.39G	PK	2.32577G	2.00	-67.96	-67.96	-65.96	-21.20	-44.76
2475MHz	Pass	2.4835G	2.5G	PK	2.49823G	2.00	-67.66	-67.66	-65.66	-21.20	-44.46
2475MHz	Pass	2.5G	3.1G	PK	2.8489G	2.00	-67.93	-67.93	-65.93	-21.20	-44.73

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2480MHz	Pass	1G	2.31G	AV	2.15215G	2.00	-73.63	-73.63	-71.63	-41.20	-30.43
2480MHz	Pass	2.31G	2.39G	AV	2.31417G	2.00	-79.98	-79.98	-77.98	-41.20	-36.78
2480MHz	Pass	2.4835G	2.5G	AV	2.48352G	2.00	-76.87	-76.87	-74.87	-41.20	-33.67
2480MHz	Pass	2.5G	3.1G	AV	2.6893G	2.00	-78.62	-78.62	-76.62	-41.20	-35.42
2480MHz	Pass	1G	2.31G	PK	2.12873G	2.00	-61.08	-61.08	-59.08	-21.20	-37.88
2480MHz	Pass	2.31G	2.39G	PK	2.35151G	2.00	-68.44	-68.44	-66.44	-21.20	-45.24
2480MHz	Pass	2.4835G	2.5G	PK	2.48355G	2.00	-65.79	-65.79	-63.79	-21.20	-42.59
2480MHz	Pass	2.5G	3.1G	PK	2.8339G	2.00	-67.83	-67.83	-65.83	-21.20	-44.63


**DG** = Directional Gain;

**PX**=Port X; **Psum**=P1




**802.15.4**
**CSE [PK]**
**2440MHz**

 Limit.PK  
 Port1
 
 PX=Port X  
 Psum=P1+\_PX


**802.15.4**
**CSE [AV]**
**2475MHz**

 LimitAV  
 Port1



### 3.5.10 Transmitter Conducted Unwanted Emissions (3.1GHz ~ 25GHz)

<b>Ambient Condition</b>	24°C / 63%	<b>Tested By</b>	Aska Huang
--------------------------	------------	------------------	------------

#### Summary

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
802.15.4	Pass	8G	25G	AV	20.12738G	2.00	-67.64	-67.64	-65.64	-41.20	-24.44

DG = Directional Gain;

PX=Port X; Psum=P1+..P2+..PX


#### Result




Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
802.15.4	-	-	-	-	-	-	-	-	-	-	-
2405MHz	Pass	3.1G	4G	AV	3.99303G	2.00	-77.36	-77.36	-75.36	-41.20	-34.16
2405MHz	Pass	4G	5G	AV	4.8085G	2.00	-76.83	-76.83	-74.83	-41.20	-33.63
2405MHz	Pass	4G	5G	AV	4.9345G	2.00	-76.65	-76.65	-74.65	-41.20	-33.45
2405MHz	Pass	5G	7G	AV	5.101G	2.00	-75.93	-75.93	-73.93	-41.20	-32.73
2405MHz	Pass	7G	8G	AV	7.39825G	2.00	-74.56	-74.56	-72.56	-41.20	-31.36
2405MHz	Pass	8G	25G	AV	20.12738G	2.00	-67.64	-67.64	-65.64	-41.20	-24.44
2405MHz	Pass	3.1G	4G	PK	3.96738G	2.00	-65.48	-65.48	-63.48	-21.20	-42.28
2405MHz	Pass	4G	5G	PK	4.792G	2.00	-64.90	-64.90	-62.90	-21.20	-41.70
2405MHz	Pass	4G	5G	PK	4.80825G	2.00	-66.87	-66.87	-64.87	-21.20	-43.67
2405MHz	Pass	5G	7G	PK	5.351G	2.00	-65.18	-65.18	-63.18	-21.20	-41.98
2405MHz	Pass	7G	8G	PK	7.504G	2.00	-64.19	-64.19	-62.19	-21.20	-40.99
2405MHz	Pass	8G	25G	PK	20.13588G	2.00	-57.55	-57.55	-55.55	-21.20	-34.35
2440MHz	Pass	3.1G	4G	AV	3.99955G	2.00	-77.54	-77.54	-75.54	-41.20	-34.34
2440MHz	Pass	4G	5G	AV	4.8805G	2.00	-76.85	-76.85	-74.85	-41.20	-33.65
2440MHz	Pass	4G	5G	AV	4.9385G	2.00	-76.65	-76.65	-74.65	-41.20	-33.45
2440MHz	Pass	5G	7G	AV	5.104G	2.00	-75.93	-75.93	-73.93	-41.20	-32.73
2440MHz	Pass	7G	8G	AV	7.399G	2.00	-74.55	-74.55	-72.55	-41.20	-31.35
2440MHz	Pass	8G	25G	AV	20.14066G	2.00	-67.91	-67.91	-65.91	-41.20	-24.71
2440MHz	Pass	3.1G	4G	PK	3.87265G	2.00	-66.69	-66.69	-64.69	-21.20	-43.49
2440MHz	Pass	4G	5G	PK	4.5635G	2.00	-65.05	-65.05	-63.05	-21.20	-41.85
2440MHz	Pass	4G	5G	PK	4.87875G	2.00	-66.74	-66.74	-64.74	-21.20	-43.54
2440MHz	Pass	5G	7G	PK	5.217G	2.00	-63.63	-63.63	-61.63	-21.20	-40.43
2440MHz	Pass	7G	8G	PK	7.401G	2.00	-63.73	-63.73	-61.73	-21.20	-40.53
2440MHz	Pass	8G	25G	PK	20.16988G	2.00	-58.01	-58.01	-56.01	-21.20	-34.81

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2475MHz	Pass	3.1G	4G	AV	3.98628G	2.00	-77.64	-77.64	-75.64	-41.20	-34.44
2475MHz	Pass	4G	5G	AV	4.943G	2.00	-76.66	-76.66	-74.66	-41.20	-33.46
2475MHz	Pass	4G	5G	AV	4.951G	2.00	-76.69	-76.69	-74.69	-41.20	-33.49
2475MHz	Pass	5G	7G	AV	5.104G	2.00	-75.93	-75.93	-73.93	-41.20	-32.73
2475MHz	Pass	7G	8G	AV	7.40275G	2.00	-74.55	-74.55	-72.55	-41.20	-31.35
2475MHz	Pass	8G	25G	AV	20.15234G	2.00	-67.67	-67.67	-65.67	-41.20	-24.47
2475MHz	Pass	3.1G	4G	PK	3.76105G	2.00	-65.94	-65.94	-63.94	-21.20	-42.74
2475MHz	Pass	4G	5G	PK	4.6345G	2.00	-64.25	-64.25	-62.25	-21.20	-41.05
2475MHz	Pass	4G	5G	PK	4.95125G	2.00	-66.17	-66.17	-64.17	-21.20	-42.97
2475MHz	Pass	5G	7G	PK	5.19G	2.00	-65.04	-65.04	-63.04	-21.20	-41.84
2475MHz	Pass	7G	8G	PK	7.4135G	2.00	-64.09	-64.09	-62.09	-21.20	-40.89
2475MHz	Pass	8G	25G	PK	20.22459G	2.00	-57.71	-57.71	-55.71	-21.20	-34.51
2480MHz	Pass	3.1G	4G	AV	3.97908G	2.00	-77.46	-77.46	-75.46	-41.20	-34.26
2480MHz	Pass	4G	5G	AV	4.93675G	2.00	-76.65	-76.65	-74.65	-41.20	-33.45
2480MHz	Pass	4G	5G	AV	4.96175G	2.00	-76.80	-76.80	-74.80	-41.20	-33.60
2480MHz	Pass	5G	7G	AV	5.1015G	2.00	-75.93	-75.93	-73.93	-41.20	-32.73
2480MHz	Pass	7G	8G	AV	7.39925G	2.00	-74.55	-74.55	-72.55	-41.20	-31.35
2480MHz	Pass	8G	25G	AV	20.15341G	2.00	-67.81	-67.81	-65.81	-41.20	-24.61
2480MHz	Pass	3.1G	4G	PK	3.61368G	2.00	-66.54	-66.54	-64.54	-21.20	-43.34
2480MHz	Pass	4G	5G	PK	4.93125G	2.00	-65.17	-65.17	-63.17	-21.20	-41.97
2480MHz	Pass	4G	5G	PK	4.959G	2.00	-67.03	-67.03	-65.03	-21.20	-43.83
2480MHz	Pass	5G	7G	PK	5.095G	2.00	-64.96	-64.96	-62.96	-21.20	-41.76
2480MHz	Pass	7G	8G	PK	7.3105G	2.00	-63.31	-63.31	-61.31	-21.20	-40.11
2480MHz	Pass	8G	25G	PK	20.16881G	2.00	-58.33	-58.33	-56.33	-21.20	-35.13

**DG** = Directional Gain;

**PX**=Port X; **Psum**=P1






802.15.4

2480MHz

CSE [PK]




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	Psum(dBm)	P1(dBm)
3.1G	4G	1M	PK	3.61368G	-66.54	-66.54
4G	5G	1M	PK	4.93125G	-65.17	-65.17
4G	5G	1M	PK	4.959G	-67.03	-67.03
5G	7G	1M	PK	5.095G	-64.96	-64.96
7G	8G	1M	PK	7.3105G	-63.31	-63.31
8G	25G	1M	PK	20.16881G	-58.33	-58.33

802.15.4

2480MHz

CSE [AV]



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	Psum(dBm)	P1(dBm)
3.1G	4G	1M	AV	3.97908G	-77.46	-77.46
4G	5G	1M	AV	4.93675G	-76.65	-76.65
4G	5G	1M	AV	4.96175G	-76.80	-76.80
5G	7G	1M	AV	5.1015G	-75.93	-75.93
7G	8G	1M	AV	7.39925G	-74.55	-74.55
8G	25G	1M	AV	20.15341G	-67.81	-67.81



### Internal antenna, high power

#### 3.5.11 Transmitter Conducted Unwanted Emissions (30MHz ~ 1GHz)

Ambient Condition	24°C / 63%	Tested By	Aska Huang
-------------------	------------	-----------	------------

#### Summary

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	GRF (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
802.15.4	Pass	30M	1G	PK	608.02 M	2.00	-72.88	-72.88	4.7	-66.18	-49.20	-16.98

DG = Directional Gain;


PX=Port X; Psum=P1+..P2+..PX

#### Result

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	GRF (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
802.15.4	-	-	-	-	-	-	-	-	-	-	-	-
2405MHz	Pass	30M	1G	PK	608.02 M	2.00	-72.88	-72.88	4.7	-66.18	-49.20	-16.98

DG = Directional Gain;

PX=Port X; Psum=P1+..P2+..PX



## Transmitter Conducted Unwanted Emissions (1GHz ~ 3.1GHz)

<b>Ambient Condition</b>	24°C / 63%	<b>Tested By</b>	Aska Huang
--------------------------	------------	------------------	------------

### Summary

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
802.15.4	Pass	2.4835 G	2.5G	AV	2.4835G	2.00	-45.69	-45.69	-43.69	-41.20	-2.49

DG = Directional Gain;

PX=Port X; Psum=P1+.P2+..PX




### Result


Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
802.15.4	-	-	-	-	-	-	-	-	-	-	-
2405MHz	Pass	1G	2.31G	AV	2.27725G	2.00	-64.16	-64.16	-62.16	-41.20	-20.96
2405MHz	Pass	2.31G	2.39G	AV	2.39G	2.00	-64.95	-64.95	-62.95	-41.20	-21.75
2405MHz	Pass	2.4835G	2.5G	AV	2.49323G	2.00	-67.38	-67.38	-65.38	-41.20	-24.18
2405MHz	Pass	2.5G	3.1G	AV	2.533G	2.00	-63.91	-63.91	-61.91	-41.20	-20.71
2405MHz	Pass	1G	2.31G	PK	2.14936G	2.00	-55.00	-55.00	-53.00	-21.20	-31.80
2405MHz	Pass	2.31G	2.39G	PK	2.34107G	2.00	-51.42	-51.42	-49.42	-21.20	-28.22
2405MHz	Pass	2.4835G	2.5G	PK	2.49916G	2.00	-55.22	-55.22	-53.22	-21.20	-32.02
2405MHz	Pass	2.5G	3.1G	PK	2.5333G	2.00	-54.53	-54.53	-52.53	-21.20	-31.33
2440MHz	Pass	1G	2.31G	AV	2.21617G	2.00	-64.75	-64.75	-62.75	-41.20	-21.55
2440MHz	Pass	2.31G	2.39G	AV	2.31209G	2.00	-65.32	-65.32	-63.32	-41.20	-22.12
2440MHz	Pass	2.4835G	2.5G	AV	2.4879G	2.00	-67.12	-67.12	-65.12	-41.20	-23.92
2440MHz	Pass	2.5G	3.1G	AV	2.6959G	2.00	-64.18	-64.18	-62.18	-41.20	-20.98
2440MHz	Pass	1G	2.31G	PK	2.21601G	2.00	-55.80	-55.80	-53.80	-21.20	-32.60
2440MHz	Pass	2.31G	2.39G	PK	2.37597G	2.00	-51.05	-51.05	-49.05	-21.20	-27.85
2440MHz	Pass	2.4835G	2.5G	PK	2.48776G	2.00	-54.85	-54.85	-52.85	-21.20	-31.65
2440MHz	Pass	2.5G	3.1G	PK	2.6326G	2.00	-55.14	-55.14	-53.14	-21.20	-31.94
2475MHz	Pass	1G	2.31G	AV	2.21928G	2.00	-64.67	-64.67	-62.67	-41.20	-21.47
2475MHz	Pass	2.31G	2.39G	AV	2.3471G	2.00	-64.48	-64.48	-62.48	-41.20	-21.28
2475MHz	Pass	2.4835G	2.5G	AV	2.4835G	2.00	-58.45	-58.45	-56.45	-41.20	-15.25
2475MHz	Pass	2.5G	3.1G	AV	2.6032G	2.00	-64.94	-64.94	-62.94	-41.20	-21.74
2475MHz	Pass	1G	2.31G	PK	2.21912G	2.00	-55.84	-55.84	-53.84	-21.20	-32.64
2475MHz	Pass	2.31G	2.39G	PK	2.34687G	2.00	-55.30	-55.30	-53.30	-21.20	-32.10
2475MHz	Pass	2.4835G	2.5G	PK	2.48362G	2.00	-46.30	-46.30	-44.30	-21.20	-23.10
2475MHz	Pass	2.5G	3.1G	PK	2.5396G	2.00	-54.00	-54.00	-52.00	-21.20	-30.80

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2480MHz	Pass	1G	2.31G	AV	2.12644G	2.00	-66.28	-66.28	-64.28	-41.20	-23.08
2480MHz	Pass	2.31G	2.39G	AV	2.35197G	2.00	-67.63	-67.63	-65.63	-41.20	-24.43
2480MHz	Pass	2.4835G	2.5G	AV	2.4835G	2.00	-45.69	-45.69	-43.69	-41.20	-2.49
2480MHz	Pass	2.5G	3.1G	AV	2.608G	2.00	-66.95	-66.95	-64.95	-41.20	-23.75
2480MHz	Pass	1G	2.31G	PK	2.1266G	2.00	-55.68	-55.68	-53.68	-21.20	-32.48
2480MHz	Pass	2.31G	2.39G	PK	2.36623G	2.00	-55.86	-55.86	-53.86	-21.20	-32.66
2480MHz	Pass	2.4835G	2.5G	PK	2.48352G	2.00	-36.06	-36.06	-34.06	-21.20	-12.86
2480MHz	Pass	2.5G	3.1G	PK	2.8903G	2.00	-55.72	-55.72	-53.72	-21.20	-32.52


**DG** = Directional Gain;

**PX**=Port X; **Psum**=P1




**802.15.4**
**CSE [AV]**
**2475MHz**

 LimitAV  
 Port1



### 3.5.12 Transmitter Conducted Unwanted Emissions (3.1GHz ~ 25GHz)

<b>Ambient Condition</b>	24°C / 63%	<b>Tested By</b>	Aska Huang
--------------------------	------------	------------------	------------

#### Summary

Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
802.15.4	Pass	4G	5G	AV	4.809G	2.00	-51.18	-51.18	-49.18	-41.20	-7.98

DG = Directional Gain;

PX=Port X; Psum=P1+..P2+..PX




#### Result




Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
802.15.4	-	-	-	-	-	-	-	-	-	-	-
2405MHz	Pass	3.1G	4G	AV	3.35245G	2.00	-75.87	-75.87	-73.87	-41.20	-32.67
2405MHz	Pass	4G	5G	AV	4.809G	2.00	-51.18	-51.18	-49.18	-41.20	-7.98
2405MHz	Pass	5G	7G	AV	5.413G	2.00	-75.23	-75.23	-73.23	-41.20	-32.03
2405MHz	Pass	7G	8G	AV	7.393G	2.00	-74.98	-74.98	-72.98	-41.20	-31.78
2405MHz	Pass	8G	25G	AV	20.39406G	2.00	-69.05	-69.05	-67.05	-41.20	-25.85
2405MHz	Pass	3.1G	4G	PK	3.50275G	2.00	-64.57	-64.57	-62.57	-21.20	-41.37
2405MHz	Pass	4G	5G	PK	4.80925G	2.00	-45.62	-45.62	-43.62	-21.20	-22.42
2405MHz	Pass	5G	7G	PK	5.178G	2.00	-63.58	-63.58	-61.58	-21.20	-40.38
2405MHz	Pass	7G	8G	PK	7.38075G	2.00	-63.37	-63.37	-61.37	-21.20	-40.17
2405MHz	Pass	8G	25G	PK	18.95491G	2.00	-58.51	-58.51	-56.51	-21.20	-35.31
2440MHz	Pass	3.1G	4G	AV	3.35605G	2.00	-75.87	-75.87	-73.87	-41.20	-32.67
2440MHz	Pass	4G	5G	AV	4.881G	2.00	-53.16	-53.16	-51.16	-41.20	-9.96
2440MHz	Pass	5G	7G	AV	5.133G	2.00	-75.22	-75.22	-73.22	-41.20	-32.02
2440MHz	Pass	7G	8G	AV	7.32125G	2.00	-69.57	-69.57	-67.57	-41.20	-26.37
2440MHz	Pass	8G	25G	AV	20.39778G	2.00	-69.18	-69.18	-67.18	-41.20	-25.98
2440MHz	Pass	3.1G	4G	PK	3.97885G	2.00	-64.79	-64.79	-62.79	-21.20	-41.59
2440MHz	Pass	4G	5G	PK	4.87925G	2.00	-47.17	-47.17	-45.17	-21.20	-23.97
2440MHz	Pass	5G	7G	PK	5.3635G	2.00	-63.61	-63.61	-61.61	-21.20	-40.41
2440MHz	Pass	7G	8G	PK	7.3215G	2.00	-61.58	-61.58	-59.58	-21.20	-38.38
2440MHz	Pass	8G	25G	PK	19.798G	2.00	-57.26	-57.26	-55.26	-21.20	-34.06
2475MHz	Pass	3.1G	4G	AV	3.35628G	2.00	-75.87	-75.87	-73.87	-41.20	-32.67
2475MHz	Pass	4G	5G	AV	4.951G	2.00	-55.16	-55.16	-53.16	-41.20	-11.96
2475MHz	Pass	5G	7G	AV	5.401G	2.00	-75.49	-75.49	-73.49	-41.20	-32.29
2475MHz	Pass	7G	8G	AV	7.42625G	2.00	-68.64	-68.64	-66.64	-41.20	-25.44


Mode	Result	F-Start (Hz)	F-Stop (Hz)	Type	Freq (Hz)	DG (dBi)	P1 (dBm)	Psum (dBm)	EIRP (dBm)	Limit (dBm)	Margin (dB)
2475MHz	Pass	8G	25G	AV	20.39991G	2.00	-69.01	-69.01	-67.01	-41.20	-25.81
2475MHz	Pass	3.1G	4G	PK	3.62875G	2.00	-64.34	-64.34	-62.34	-21.20	-41.14
2475MHz	Pass	4G	5G	PK	4.94925G	2.00	-49.06	-49.06	-47.06	-21.20	-25.86
2475MHz	Pass	5G	7G	PK	5.378G	2.00	-62.33	-62.33	-60.33	-21.20	-39.13
2475MHz	Pass	7G	8G	PK	7.42375G	2.00	-59.69	-59.69	-57.69	-21.20	-36.49
2475MHz	Pass	8G	25G	PK	19.73638G	2.00	-58.71	-58.71	-56.71	-21.20	-35.51
2480MHz	Pass	3.1G	4G	AV	3.34683G	2.00	-75.89	-75.89	-73.89	-41.20	-32.69
2480MHz	Pass	4G	5G	AV	4.961G	2.00	-70.14	-70.14	-68.14	-41.20	-26.94
2480MHz	Pass	5G	7G	AV	5.4015G	2.00	-75.49	-75.49	-73.49	-41.20	-32.29
2480MHz	Pass	7G	8G	AV	7.4385G	2.00	-74.73	-74.73	-72.73	-41.20	-31.53
2480MHz	Pass	8G	25G	AV	20.39513G	2.00	-69.04	-69.04	-67.04	-41.20	-25.84
2480MHz	Pass	3.1G	4G	PK	3.35403G	2.00	-64.78	-64.78	-62.78	-21.20	-41.58
2480MHz	Pass	4G	5G	PK	4.959G	2.00	-61.19	-61.19	-59.19	-21.20	-37.99
2480MHz	Pass	5G	7G	PK	5.433G	2.00	-63.20	-63.20	-61.20	-21.20	-40.00
2480MHz	Pass	7G	8G	PK	7.3025G	2.00	-63.79	-63.79	-61.79	-21.20	-40.59
2480MHz	Pass	8G	25G	PK	19.70184G	2.00	-58.35	-58.35	-56.35	-21.20	-35.15

**DG** = Directional Gain;  
**PX**=Port X; **Psum**=P1









## 3.6 Emissions in Non-Restricted Frequency Bands

### 3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

### 3.6.2 Test Procedures


#### Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

#### Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level


### 3.6.3 Test Setup




### 3.6.4 Unwanted Emissions into Non-Restricted Frequency Bands


Ambient Condition	24°C / 63%	Tested By	Aska Huang
-------------------	------------	-----------	------------

#### Internal antenna, Lower power






### Internal antenna, high power


**802.15.4**
**CSE NdB**
**2475MHz**
Port1 

 RBW (Hz)   
 VBW (Hz)   
 Detector





## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

### **Linkou**

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin  
Kou District, New Taipei City,  
Taiwan, R.O.C.

### **Kwei Shan**

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,  
Kwei Shan District, Tao Yuan City  
333, Taiwan, R.O.C.

### **Kwei Shan Site II**

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan District, Tao Yuan  
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==