

FCC RF EXPOSURE REPORT

FCC ID: SQK-FTP628WSL221A

Project No. : 1312165

Equipment : Mobile Printer
Model : FTP-628WSL221

Applicant : FUJITSU COMPONENT LIMITED
Address : 1174, Oaza Suzaka, Suzaka-shi, Nagano

382-0076 Japan

According: : FCC Guidelines for Human Exposure IEEE C95.1

Neutron Engineering Inc.

B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan. TEL: +886-2-2657-3299

FAX: +886-2-2657-3331

GENERAL CONCULUSION:

Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	mono-pole (Printed)	N/A	1.30

Maximum measured transmitter power:

Mode	Output Power (dBm)	Out Power (mW)	Limit (mW)
1 MHz	0.9600	1.2474	10
3 MHz	0.3400	1.0814	10

According to FCC KDB447498, Appendix A, SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and $\leq 50 \text{ mm}$

The transmitter power is 1.2474 mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold