

RF Exposure / SAR Statement

No. : 31AE0037-HO-05-A

Applicant : FUJITSU COMPONENT LIMITED
Type of Equipment : Bluetooth Module
Model No. : MBH7BTZ45
FCC ID : SQK-MBH7BTZ4546

FUJITSU COMPONENT LIMITED declares that Model : Bluetooth Module complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "MBH7BTZ45" has 46.77 mW of conducted Peak Output power and 20.42 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "MBH7BTZ45" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 46.77 mW (Maximum peak output power)
G = 0.44 Numerical Antenna gain; equal -3.60 dBi
r = 20.0 cm

For: MBH7BTZ45

$$S = 0.00406 \text{ mW/cm}^2$$

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401