

This is the label affixed to the top of the device on the inside of the enclosure.  
 FCC ID: SRA-ATD003160  
 and Canadian number  
 IC: 7413A-ATD003160  
 See picture below Actual size of label is first picture.

**TAILBAT | RF™**  
**CONTROL UNIT**  
 FCC ID: SRA-ATD003160 IC: 7413A-ATD003160  
*TrailerTail* by STEMCO Model: ATD003160

LED Color	Motion	LED Color		Fault Diagnostic
		(P10, 11)**	Light (Pin2)	
Green ✨	Stopped	Cyan ✨	Cyan ●	- Shorted to +12 Volts
Green ●	< 35mph	Yellow ✨	Yellow ●	- Shorted to 0 Volts
White ●	>= 35mph	Pink ✨	Pink ●	- Current Draw Too Low
Blue ●	Reverse	White ✨	-	- Latches Did Not Open
✨ = Blink		**AutoDeploy Mode = Latch		Red ✨ Pin 1 < 9V or >16V
● = Solid		Automatic Mode = Solenoid		Red ● TracBat Signal Missing

**This device complies with part 15 of the FCC Rules.**  
 Operation is subject to the following two conditions:  
 (1) This device may not cause harmful interference, and  
 (2) this device must accept any interference received,  
 including interference that may cause undesired operation.

# TAILBAT RF™ CONTROL UNIT

FCC ID: SRA-ATD003160 IC: 7413A-ATD003160  
TrailerTail by STEMCO Model: ATD003160

LED Color	Mode	LED Color (P10, 11)** Light (Pin2)		Fault Diagnostic
Green ☼	Stopped	Cyan ☼	Cyan ●	Shorted to +12 Volts
Green ●	< 35mph	Yellow ☼	Yellow ●	Shorted to 0 Volts
White ●	>= 35mph	Pink ☼	Pink ●	Current Draw Too Low
Blue ●	Reverse	White ☼	-	Latches Did Not Open
☼ - Blink		**AutoDeploy Mode - Latch	Red ☼	Pin 1 < 9V or > 16V
● - Solid		Automatic Mode - Solenoid	Red ●	TracBat Signal Missing

**This device complies with part 15 of the FCC Rules.**  
Operation is subject to the following two conditions:  
(1) This device may not cause harmful interference, and  
(2) this device must accept any interference received,  
including interference that may cause undesired operation.

# TAILBAT | RF™

## CONTROL UNIT

FCC ID: SRA-ATD003160 IC: 7413A-ATD003160  
**TrailerTail** by STEMCO Model: ATD003160

LED Color	Motion	LED Color		Fault Diagnostic
		(P10, 11)**	Light (Pin2)	
Green ☼	Stopped	Cyan ☼	Cyan ●	- Shorted to +12 Volts
Green ●	< 35mph	Yellow ☼	Yellow ●	- Shorted to 0 Volts
White ●	>= 35mph	Pink ☼	Pink ●	- Current Draw Too Low
Blue ●	Reverse	White ☼	-	- Latches Did Not Open
☼ = Blink		**AutoDeploy Mode = Latch		Red ☼ Pin 1 < 9V or > 16V
● = Solid		Automatic Mode = Solenoid		Red ● TracBat Signal Missing

**This device complies with part 15 of the FCC Rules.**

Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.