



849 NW State Road 45
 Newberry, FL 32669 USA
 Ph: 888.472.2424 or 352.472.5500
 Fax: 352.472.2030
 Email: info@timcoengr.com
 Website: www.timcoengr.com

**FCC PART 15.247 AND IC
 RSS-210 TEST REPORT
 DIGITAL SPREAD SPECTRUM**

Applicant	T&D CORPORATION
Address	817-1 SHIMADACHI MATSUMOTO 390-0852 JAPAN
FCC ID	SRD10080
IC	5558A-10080
Model Number	RTR-500DC
Product Description	HAND HELD DATA COLLECTOR
Date Sample Received	11/19/2010
Date Tested	11/29/2010
Tested By	Joe Scoglio
Approved By	Mario R. de Aranzeta
Report Number	2635AT10TestReport.doc
Test Results	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
 WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Testing Certificate # 0955-01



TABLE OF CONTENT

GENERAL REMARKS	3
GENERAL INFORMATION	4
EMC EQUIPMENT LIST.....	5
TEST PROCEDURES.....	6
RADIATION INTERFERENCE	7
POWER LINE CONDUCTED INTERFERENCE.....	10
OCCUPIED BANDWIDTH.....	13
POWER OUTPUT.....	15
SPURIOUS EMISSIONS AT ANTENNA TERMINALS	16
RADIATED SPURIOUS EMISSIONS INTO ADJACENT RESTRICTED BAND	18
POWER SPECTRAL DENSITY	20

APPLICANT: T&D CORPORATION
FCC ID: SRD10080
IC: 5558A-10080
REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, Fl 32669



Authorized Signatory Name:

Mario R. de Aranzeta
Compliance Engineer

Date: December 30, 2010

APPLICANT: T&D CORPORATION
FCC ID: SRD10080
IC: 5558A-10080
REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

GENERAL INFORMATION

DUT Specification

Applicable Standard	Part 15.247		
DUT Description	HAND HELD DATA COLLECTOR		
FCC ID	SRD10080		
IC	5558A-10080		
Model	RTR-500DC		
Operating Frequency	TX: 902-928 MHz		
DUT Power Source	<input type="checkbox"/> 110-120Vac/50- 60Hz <input checked="" type="checkbox"/> DC Power 3v <input type="checkbox"/> Battery Operated Exclusively		
Test Item	<input type="checkbox"/> Prototype	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Production
Type of Equipment	<input type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input checked="" type="checkbox"/> Portable
Test Facility	Timco Engineering Inc. located at 849 NW State Road 45 Newberry, FL 32669 USA.		
Test Conditions	Temperature: 26°C Relative humidity: 50%		
Test Exercise	The DUT was placed in continuous transmit mode of operation.		

Test Supporting Equipment

Supporting Device	Manufacturer	Model / FCC ID	Serial Number
N/A			

APPLICANT: T&D CORPORATION

FCC ID: SRD10080

IC: 5558A-10080

REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

EMC EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 3/10/10	3/10/12
AC Voltmeter	HP	400FL	2213A14499	CAL 3/23/09	3/23/11
Antenna: Dipole Kit	Electro-Metrics	TDA-30/1-4	153	CHAR 6/10/09	6/10/11
Frequency Counter	HP	5385A	3242A07460	CAL 5/26/09	5/26/11
Hygro-Thermometer	Extech	445703	0602	CAL 1/30/09	1/30/11
Modulation Analyzer	HP	8901A	3435A06868	CAL 5/26/09	5/26/11
Digital Multimeter	Fluke	FLUKE-77-3	79510405	CAL 5/18/09	5/18/11
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 11/21/09	11/21/11
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 11/22/09	11/22/11
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 11/21/09	11/21/11
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 11/24/09	11/24/11
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/10	4/25/12

APPLICANT: T&D CORPORATION

FCC ID: SRD10080

IC: 5558A-10080

REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

TEST PROCEDURES

Radiation Interference: ANSI C63.4-2003 using a spectrum analyzer, a preselector, a quasi-peak adapter, and an appropriate antenna. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz with an appropriate sweep speed and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

Formula Of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer plus the coax loss. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

Freq (MHz)	Meter Reading	+ ACF	+ CL = FS
33	20 dB μ V	+ 10.36 dB	+ 0.5 = 30.86 dB μ V/m @ 3m

Power Line Conducted Interference: The procedure used was ANSI C63.4-2003 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed. The spectrum was scanned from 0.15 to 30 MHz.

Occupied Bandwidth: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division.

Bandwidth 6.0dB: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW)=1 MHz and the video bandwidth (VBW) =3 MHz and the span set as shown on plot.

Power Output: The RF power output was measured at the antenna feed point using a peak power meter.

Antenna Conducted Emissions: The RBW=100 kHz, VBW=300 kHz and the span set to 10 MHz and the spectrum was scanned from 30 MHz to the 10th Harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

ANSI C63.4-2003 10.1 Measurement Procedures: The DUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The DUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. Emissions attenuated more than 20 dB below the permissible value are not reported.

APPLICANT: T&D CORPORATION

FCC ID: SRD10080

IC: 5558A-10080

REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

RADIATION INTERFERENCE

Rules Part No.: 15.247, 15.209

Requirements:

Frequency	Limits
Part 15.209	
9 to 490 kHz	2400/F (kHz) $\mu\text{V/m}$ @ 300 meters
490 to 1705 kHz	24000/F (kHz) $\mu\text{V/m}$ @ 30 meters
1705 kHz to 30 MHz	29.54 dB $\mu\text{V/m}$ @ 30 meters
30 – 88	40.0 dB $\mu\text{V/m}$ @ 3 meters
80 – 216	43.5 dB $\mu\text{V/m}$ @ 3 meters
216 – 960	46.0 dB $\mu\text{V/m}$ @ 3 meters
Above 960	54.0 dB $\mu\text{V/m}$ @ 3 meters
Part 15.247	
Fundamental 902 – 928 MHz	127.37 dB $\mu\text{V/m}$ @ 3 meters
Fundamental 2.4 – 2.4835 MHz	127.37 dB $\mu\text{V/m}$ @ 3 meters
Harmonics	54.0 dB $\mu\text{V/m}$ @ 3 meters

Any emissions that fall in the restricted bands (15.205) must be less than or equal to 54 dB $\mu\text{V/m}$. Spurious emissions not in a restricted band must be 20 dBc. Harmonics were checked through the 10th harmonic.

Test Data: All values are peak unless noted.
Items mark with an * designate a frequency in a restricted band.

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB μV	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Field Strength dB $\mu\text{V/m}$	Margin dB
902.9	902.90	61.1	H	1.95	23.33	86.38	41.00
902.9	902.90	75.2	V	1.95	22.67	99.82	27.56
902.9	1,805.80	18.6	H	2.74	29.96	51.30	2.7
902.9	1,805.80	20.8	V	2.74	29.96	53.50	.50
902.9	2,708.70	9.2	H	3.40	32.54	45.14	8.86
902.9	2,708.70	10.2	V	3.40	32.54	46.14	7.86
902.9	3,611.60	11.3	V	4.15	32.98	48.43	5.57
902.9	3,611.60	12.1	H	4.15	32.98	49.23	4.77
914.4	914.40	63.2	H	1.97	23.36	88.53	38.85
914.4	914.40	73.9	V	1.97	22.60	98.47	28.91
914.4	1,828.80	20.4	H	2.76	30.10	53.26	.74
914.4	1,828.80	21.0	V	2.76	30.10	53.86	.14
914.4	2,743.20	9.0	V	3.42	32.55	44.97	9.03
914.4	2,743.20	10.1	H	3.42	32.55	46.07	7.93
914.4	3,657.60	8.9	H	4.19	33.05	46.14	7.86
914.4	3,657.60	12.7	V	4.19	33.05	49.94	4.06
927.1	927.10	59.9	H	1.99	23.44	85.33	42.05

APPLICANT: T&D CORPORATION

FCC ID: SRD10080

IC: 5558A-10080

REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

TEST DATA CONTD

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBμV	Ant. Pol	Coax Loss dB	Correction Factor dB	Field Strength dBμV/m	Margin dB
927.1	927.10	71.4	V	1.99	22.67	96.06	31.32
927.1	1,854.20	16.5	H	2.78	30.27	49.55	4.45
927.1	1,854.20	19.9	V	2.78	30.27	52.95	1.05
927.1	2,781.30	9.6	V	3.45	32.56	45.61	8.39
927.1	2,781.30	9.8	H	3.45	32.56	45.81	8.19
927.1	3,708.50	7.9	V	4.24	33.13	45.27	8.73
927.1	3,708.50	10.8	H	4.24	33.13	48.17	5.83
927.1	5,562.70	5.0	V	5.17	34.79	44.96	9.04
927.1	5,562.70	5.7	H	5.17	34.79	45.66	8.34

APPLICANT: T&D CORPORATION


FCC ID: SRD10080

IC: 5558A-10080

REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

Method of Measuring Radiated Spurious Emissions

Antenna is Calibrated
and appropriate one.
Raised from 1 to 4 M.



METHOD OF MEASUREMENT: The procedure used was ANSI standard C63.4-2003 & the FCC/OET Guidance on Measurements for Spread Spectrum Systems – Public Notice DA 00-705 dated March 30th, 2000.

APPLICANT: T&D CORPORATION
FCC ID: SRD10080
IC: 5558A-10080
REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

POWER LINE CONDUCTED INTERFERENCE

Rules Part No.: Part 15.207

Requirements:

Frequency (MHz)	Quasi Peak Limits (dBμV)	Average Limits (dBμV)
0.15 – 0.5	66 – 56 *	56 – 46 *
0.5 – 5.0	56	46
5.0 – 30	60	50
* Decrease with logarithm of frequency		


Test Data: The following plots represent the emissions read for power line conducted. Both lines were observed.

POWERLINE CONDUCTED PLOT – LINE 1

NOTES:

ac line conducted line 1

FCC 15.107 Mask Class B




APPLICANT: T&D CORPORATION
 FCC ID: SRD10080
 IC: 5558A-10080
 REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

POWERLINE CONDUCTED PLOT – LINE 2

NOTES:

ac line conducted line 2

FCC 15.107 Mask Class B



APPLICANT: T&D CORPORATION
 FCC ID: SRD10080
 IC: 5558A-10080
 REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

OCCUPIED BANDWIDTH


Rules Part No.: 15.247(a)(2)

Requirements: The 6 dB bandwidth must be greater than 500 kHz.

Test Data:


Three places in the band were measured and the worst case reported.

6 dB Bandwidth



APPLICANT: T&D CORPORATION
 FCC ID: SRD10080
 IC: 5558A-10080
 REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

20 dB Bandwidth




APPLICANT: T&D CORPORATION
 FCC ID: SRD10080
 IC: 5558A-10080
 REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

POWER OUTPUT

Rules Part #: 15.247(b)

TEST SET UP:



Harmonics were checked through the 10th harmonic

Test Results:

Frequency MHz	Po dBm	Po Watts
902.9	5.97	.004
914.4	7.02	.005
927.1	6.41	.004

APPLICANT: T&D CORPORATION
 FCC ID: SRD10080
 IC: 5558A-10080
 REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Requirements: Emissions must be at least 20dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

Test Data:

Tuned Frequency	EF	dB below carrier		Tuned Frequency	EF	dB below carrier
902.9	1805.8	53.9		914.4	1828.8	53.6
	2708.7	63.1			2743.2	66.8
	3611.6	61.2			3657.6	67.9
	4514.5	82.4			4572	88
	5417.4	82.5			5486.4	86.5
	6320.3	78.1			6400.8	87.7
	7223.2	82.5			7315.2	83.5
	8126.1	84.1			8229.6	83.6
	9029	87.4			9144	88.7

Tuned Frequency	EF	dB below carrier
927.1	1854.2	55
	2781.3	76.3
	3708.4	70.2
	4635.5	84.9
	5562.6	77.8
	6489.7	79.6
	7416.8	84.3
	8343.9	83.8
	9271	87.5

15.247(c) Method of Measuring RF Conducted Spurious Emissions




RADIATED SPURIOUS EMISSIONS INTO ADJACENT RESTRICTED BAND

Requirements: Emissions that fall in the restricted bands (15.205). These emissions must be less than or equal to 500 $\mu\text{V}/\text{m}$ (54 $\text{dB}\mu\text{V}/\text{m}$).

Test Procedure: An in band field strength measurement of the fundamental Emission using the RBW and detector function required by C63.4-2000 and FCC Rules. The procedure was repeated with an average detector and a plot made. The calculated field strength in the adjacent restricted band is presented below.

Lower bandedge peak


Tuned Frequency MHz	Emission Frequency MHz	Meter Reading $\text{dB}\mu\text{V}$	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Field Strength $\text{dB}\mu\text{V}/\text{m}$	Margin dB
902.9	902.00	17.9	V	1.95	22.68	42.53	3.47



APPLICANT: T&D CORPORATION
 FCC ID: SRD10080
 IC: 5558A-10080
 REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

Upper bandedge Peak

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB μ V	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Field Strength dB μ V/m	Margin dB
927.1	928.00	17.5	V	1.99	22.68	42.17	3.83



APPLICANT: T&D CORPORATION
 FCC ID: SRD10080
 IC: 5558A-10080
 REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc

POWER SPECTRAL DENSITY


Rules Part No.: 15.247(d)

Requirements: The peak level measured must be less than +8.0 dBm.

Test Data: SEE THE FOLLOWING PLOTS

Three places in the band were measured and the worst case reported.

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBμV	Ant. Pol	Coax Loss dB	Correction Factor dB/m	Field Strength dBμV/m
902.7	902.70	16.7	V	1.95	22.67	41.32



APPLICANT: T&D CORPORATION
 FCC ID: SRD10080
 IC: 5558A-10080
 REPORT: T\T&D CORP_SRD\2635AT10\2635AT10TestReport.doc