



849 NW State Road 45
Newberry, FL 32669 USA
Ph: 888.472.2424 or 352.472.5500
Fax: 352.472.2030
Email: info@timcoengr.com
Website: www.timcoengr.com

**FCC PART 15.249 AND IC RSS-210
CLASS II PERMISSIVE
CHANGE TEST REPORT**

Applicant	T&D CORPORATION
Address	817-1 SHIMADACHI MATSUMOTO 390-0852 JAPAN
FCC ID	SRDRTR5W
IC	5558A-RTR5W
Model Number	RTR-5W
Product Description	WEB WING WL
Date Sample Received	8/4/2011
Date Tested	8/15/2011
Tested By	Joe Scoglio
Approved By	Mario R. de Aranzeta
Report Number	1741AT11TestReport.doc
Test Results	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Testing Certificate # 0955-01



TABLE OF CONTENT

GENERAL REMARKS.....	3
GENERAL INFORMATION.....	4
EMC EQUIPMENT LIST.....	5
TEST PROCEDURES.....	6
RADIATION INTERFERENCE.....	7

APPLICANT: T&D CORPORATION
FCC ID: SRDRTR5W
IC: 5558A-RTR5W
REPORT: T\T&D CORP_SRD\1741AT11\1741AT11TestReport.doc

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, Fl 32669



Authorized Signatory Name:

Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: August 15, 2011

APPLICANT: T&D CORPORATION
FCC ID: SRDRTR5W
IC: 5558A-RTR5W
REPORT: T\T&D CORP_SRD\1741AT11\1741AT11TestReport.doc

GENERAL INFORMATION

DUT Specification

Applicable Standard	Part 15.249		
DUT Description	WEB WING WL		
FCC ID	SRDRTR5W		
DUT Power Source	<input type="checkbox"/> 110-120Vac/50- 60Hz		
	<input checked="" type="checkbox"/> DC Power		
	<input type="checkbox"/> Battery Operated Exclusively		
Test Item	<input type="checkbox"/> Prototype	<input type="checkbox"/> Pre-Production	<input checked="" type="checkbox"/> Production
Type of Equipment	<input checked="" type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input type="checkbox"/> Portable
Test Facility	Timco Engineering Inc. located at 849 NW State Road 45 Newberry, FL 32669 USA.		
Test Conditions	Temperature: 26°C Relative humidity: 50%		
Test Exercise	The DUT was placed in continuous transmit mode of operation.		

Test Supporting Equipment

Supporting Device	Manufacturer	Model / FCC ID	Serial Number
N/A			

APPLICANT: T&D CORPORATION
 FCC ID: SRDRTR5W
 IC: 5558A-RTR5W
 REPORT: T\T&D CORP_SRD\1741AT11\1741AT11TestReport.doc

EMC EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 5/10/10	5/10/12
AC Voltmeter	HP	400FL	2213A14499	CAL 6/12/11	6/12/13
Antenna: Active Loop	ETS-Lindgren	6502	00062529	CAL 9/23/10	9/23/12
Antenna: Passive Loop	EMC Test Systems	EMCO 6512	9706-1211	CAL. 10/1/09	10/2/11
Frequency Counter	HP	5385A	2730A03025	CAL 8/17/11	8/17/13
Hygro-Thermometer	Extech	445703	0602	CAL 6/15/11	6/15/13
Modulation Analyzer	HP	8901A	3435A06868	CAL 7/18/11	7/18/13
Digital Multimeter	Fluke	FLUKE-77	35053830	CAL 11/18/09	11/18/11
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 11/21/09	11/21/11
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 11/22/09	11/22/11
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 11/21/09	11/21/11
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 11/24/09	11/24/11
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/10	4/25/12
Antenna	ETS	3117	41534	9/22/2010	9/22/2012
Antenna	Electro metrics	LPA-25	1122	5/04/2011	5/04/2013
Antenna	Electro metrics	BIA-25	1171	1/15/2010	1/15/2012

APPLICANT: T&D CORPORATION

FCC ID: SRDRTR5W

IC: 5558A-RTR5W

REPORT: T\T&D CORP_SRD\1741AT11\1741AT11TestReport.doc

TEST PROCEDURES

Radiation Interference: ANSI C63.4-2003 using a spectrum analyzer, a preselector, a quasi-peak adapter, and an appropriate antenna. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz with an appropriate sweep speed and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

Formula Of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

Freq (MHz)	Meter Reading	+ ACF	+ CL = FS
33	20 dBuV	+ 10.36 dB	+ 0.5 = 30.86 dBuV/m @ 3m

Power Line Conducted Interference: The procedure used was ANSI C63.4-2003 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The spectrum was scanned from 0.15 to 30 MHz.

Occupied Bandwidth: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division.

ANSI C63.4-2003 10.1 Measurement Procedures: The DUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The DUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. Emissions attenuated more than 20 dB below the permissible value are not reported.

APPLICANT: T&D CORPORATION

FCC ID: SRDRTR5W

IC: 5558A-RTR5W

REPORT: T\T&D CORP_SRD\1741AT11\1741AT11TestReport.doc

RADIATION INTERFERENCE

Rules Part No.: 15.249, 15.209

Requirements:

Frequency	Limits
Part 15.209	
9 to 490 kHz	2400/F (kHz) $\mu\text{V}/\text{m}$ @ 300 meters
490 to 1705 kHz	24000/F (kHz) $\mu\text{V}/\text{m}$ @ 30 meters
1705 kHz to 30 MHz	29.54 dB $\mu\text{V}/\text{m}$ @ 30 meters
30 – 88	40.0 dB $\mu\text{V}/\text{m}$ @ 3 meters
80 – 216	43.5 dB $\mu\text{V}/\text{m}$ @ 3 meters
216 – 960	46.0 dB $\mu\text{V}/\text{m}$ @ 3 meters
Above 960	54.0 dB $\mu\text{V}/\text{m}$ @ 3 meters
Part 15.249	
Fundamental 902 – 928 MHz	94.0 dB $\mu\text{V}/\text{m}$ @ 3 meters
Fundamental 2.4 – 2.4835 MHz	94.0 dB $\mu\text{V}/\text{m}$ @ 3 meters
Harmonics	54.0 dB $\mu\text{V}/\text{m}$ @ 3 meters

Test Data: All values are peak unless noted.
Items mark with an * designate a frequency in a restricted band.

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB μV	Ant. Pol	Coax Loss dB	Correction Factor dB	Field Strength dB $\mu\text{V}/\text{m}$	Margin dB
902.2	902.20	63.1	V	1.95	23.80	88.85	5.15
902.2	902.20	67.0	H	1.95	23.80	92.75	1.25
902.2	1,804.50	18.4	V	2.74	30.03	51.17	2.83
902.2	1,804.50	19.3	H	2.74	30.03	52.07	1.93
902.2	2,706.70	11.8	H	3.39	32.85	48.04	5.96
902.2	2,706.70	12.3	V	3.39	32.85	48.54	5.46
902.2	3,609.00	6.8	H	4.15	33.39	44.34	9.66
902.2	3,609.00	7.6	V	4.15	33.39	45.14	8.86
915.2	915.20	62.5	V	1.97	23.80	88.27	5.75
915.2	915.20	66.5	H	1.97	23.80	92.27	1.73
915.2	1,830.40	16.8	H	2.76	30.18	49.74	4.26
915.2	1,830.40	17.5	V	2.76	30.18	50.44	3.56
915.2	2,745.60	11.0	V	3.42	32.89	47.31	6.69
915.2	2,745.60	11.2	H	3.42	32.89	47.51	6.49
915.2	3,660.90	6.0	H	4.19	33.43	43.62	10.38
915.2	3,660.90	7.1	V	4.19	33.43	44.72	9.28
927.0	927.00	61.7	V	1.99	23.94	87.63	6.37
927.0	927.00	65.1	H	1.99	23.94	91.03	2.97

APPLICANT: T&D CORPORATION
 FCC ID: SRDRTR5W
 IC: 5558A-RTR5W
 REPORT: T\T&D CORP_SRD\1741AT11\1741AT11TestReport.doc

TEST DATA CONTD.

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Pol	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
927.0	1,854.10	15.2	H	2.78	30.32	48.30	5.7
927.0	1,854.10	15.3	V	2.78	30.32	48.40	5.6
927.0	2,781.10	9.1	V	3.45	32.94	45.49	8.51
927.0	2,781.10	10.4	H	3.45	32.94	46.79	7.21
927.0	3,708.20	7.5	H	4.24	33.47	45.21	8.79
927.0	3,708.20	8.3	V	4.24	33.47	46.01	7.99

APPLICANT: T&D CORPORATION


FCC ID: SRDRTR5W

IC: 5558A-RTR5W

REPORT: T\T&D CORP_SRD\1741AT11\1741AT11TestReport.doc

Method of Measuring Radiated Spurious Emissions

Antenna is Calibrated
and appropriate one.
Raised from 1 to 4 M.



METHOD OF MEASUREMENT: The procedure used was ANSI standard C63.4-2003 & the FCC/OET Guidance on Measurements for Spread Spectrum Systems – Public Notice DA 00-705 dated March 30th, 2000.

APPLICANT: T&D CORPORATION
FCC ID: SRDRTR5W
IC: 5558A-RTR5W
REPORT: T\T&D CORP_SRD\1741AT11\1741AT11TestReport.doc