REPORT No.: SZ15060079W04

FCC RF TEST REPORT

APPLICANT	:	ZTE Corporation
PRODUCT NAME	:	LTE Digital Mobile Phone Handset
MODEL NAME	:	ZTE Blade A475
TRADE NAME	:	ZTE
BRAND NAME	:	ZTE
FCC ID	:	SRQ-A475
STANDARD(S)	:	47 CFR Part 15 Subpart C
ISSUE DATE	:	2015-7-16

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555 Http://www.morlab.com Fax: 86-755-36698525 E-mail: service@morlab.cn

DIRECTORY

TEST REPORT DECLARATION 4

1. TECHNICAL INFORMATION 5

1.1 APPLICANT INFORMATION 5
1.2 EQUIPMENT UNDER TEST (EUT) DESCRIPTION 5
1.2.1 IDENTIFICATION OF ALL USED EUTS 5
1.3 TEST STANDARDS AND RESULTS 6
1.3.1 TEST ENVIRONMENT CONDITIONS 6

2. 47 CFR PART 15C REQUIREMENTS 7

2.1 ANTENNA REQUIREMENT 7
2.1.1 APPLICABLE STANDARD 7
2.1.2 RESULT: COMPLIANT 7
2.2 NUMBER OF HOPPING FREQUENCY 7
2.2.1 REQUIREMENT 7
2.2.2 TEST DESCRIPTION 7
2.2.3 TEST PROCEDURE 8
2.2.4 TEST RESULT 8
2.3 PEAK OUTPUT POWER 12
2.3.1 REQUIREMENT 12
2.3.2 TEST DESCRIPTION 12
2.3.3 TEST RESULT 12
2.4 20DB BANDWIDTH 14
2.4.1 DEFINITION 14
2.4.2 TEST DESCRIPTION 14
2.4.3 TEST PROCEDURE 14
2.4.4 TEST RESULT 14
2.5 CARRIED FREQUENCY SEPARATION 21
2.5.1 DEFINITION 21
2.5.2 TEST DESCRIPTION 21
2.5.3 TEST PROCEDURE 21
2.5.4 TEST RESULT 22
2.6 TIME OF OCCUPANCY (DWELL TIME) 24

2.6.1 REQUIREMENT 24
2.6.2 TEST DESCRIPTION 24
2.6.3 TEST PROCEDURE 24
2.6.4 TEST RESULT 25
2.7 CONDUCTED SPURIOUS EMISSIONS 36
2.7.1 REQUIREMENT 36
2.7.2 TEST DESCRIPTION 36
2.7.3 TEST PROCEDURE 36
2.7.4 TEST RESULT 37
2.8 RESTRICTED FREQUENCY BANDS 49
2.8.1 REQUIREMENT 49
2.8.2 TEST DESCRIPTION 49
2.8.3 TEST PROCEDURE 50
2.8.4 TEST RESULT 50
2.9 CONDUCTED EMISSION 58
2.9.1 REQUIREMENT 58
2.9.2 TEST DESCRIPTION 58
2.9.3 TEST RESULT 59
2.10 RADIATED EMISSION 61
2.10.1 REQUIREMENT 61
2.10.2 TEST DESCRIPTION 62
2.10.3 TEST PROCEDURE 64
2.10.4 TEST RESULT 64
2.11 RF EXPOSURE EVALUATION 74
2.11.1 REQUIREMENT 74
2.11.2 RESULT 74

ANNEX A GENERAL INFORMATION 75

Change History		
Issue	Date	Reason for change
1.0	2015-7-16	First edition

TEST REPORT DECLARATION

Applicant	ZTE Corporation
Applicant Address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China
Manufacturer	ZTE Corporation
Manufacturer Address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China
Product Name	LTE Digital Mobile Phone Handset
Model Name	ZTE Blade A475
Brand Name	ZTE
HW Version	A475_V1AMB
SW Version	A475_Z98_MX_7SSOH1I500H001
Test Standards	47 CFR Part 15 Subpart C
Test Date	2015-6-10 to 2015-7-13
Test Result	PASS

Tested by : Zou Jian

Zou Jian(Test Engineer)

Reviewed by : Qiu Xiaojun

Qiu Xiaojun(RF Manager)

Approved by : Zeng Dexin

Zeng Dexin(Chief Engineer)

1. TECHNICAL INFORMATION

Note: Provide by applicant.

1.1 Applicant Information

Company:	ZTE Corporation
Address:	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

1.2 Equipment under Test (EUT) Description

Brand Name:	ZTE
Trade Name:	ZTE
Model Name:	ZTE A475
Frequency Range:	The frequency range used is 2402MHz – 2480MHz (79 channels, at intervals of 1MHz); The frequency block is 2400MHz to 2483.5MHz.
Modulation Type:	Bluetooth: FHSS (GFSK(1Mbps), π/4-DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps))
Bluetooth Version:	2.1+EDR
Antenna Type:	PFIA Antenna
Antenna Gain:	1.5dBi

NOTE:

The EUT is a LTE Digital Mobile Phone Handset, it contains Bluetooth Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth Module is F(MHz)=2402+1*n (0<=n<=78). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 39 (2441MHz) and 78 (2480MHz).

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.2.1 Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
A01	A475_V1AMB	A475_Z98_MX_7SSOH1I500H001

1.3 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-13 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Test Date	Result
1	15.203	Antenna Requirement	N.A	**PASS**
2	15.247(a)	Number of Hopping Frequency	June 12, 2015	**PASS**
3	15.247(b)	Peak Output Power	June 12, 2015	**PASS**
4	15.247(a)	20dB Bandwidth	June 12, 2015	**PASS**
5	15.247(a)	Carrier Frequency Separation	June 12, 2015	**PASS**
6	15.247(a)	Time of Occupancy (Dwell time)	June 12, 2015	**PASS**
7	15.247(d)	Conducted Spurious Emission	June 12, 2015	**PASS**
8	15.247(d)	Restricted Frequency Bands	June 16, 2015	**PASS**
9	15.207	Conducted Emission	June 16, 2015	**PASS**
10	15.209 15.247(d)	Radiated Emission	June 16, 2015	**PASS**
11	15.247(i),1.1307& 2.1093	RF exposure evaluation	N.A	**PASS**

NOTE: The tests were performed according to the method of measurements prescribed in DA-00-705, ANSI C63.4-2009 and ANSI C63.10-2009.

1.3.1 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR PART 15C REQUIREMENTS

2.1 Antenna requirement

2.1.1 Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2 Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2 Number of Hopping Frequency

2.2.1 Requirement

According to FCC §15.247(a)(1)(iii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 15 hopping frequencies.

2.2.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW ≥ 1% of the span
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize

2.2.4 Test Result

The Bluetooth Module operates at hopping-on test mode; the frequencies number employed is counted to verify the Module's using the number of hopping frequency.

A. Test Verdict:

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Refer to Plot	Verdict
GFSK	2400 - 2483.5	79	15	Plot A	PASS
π/4-DQPSK	2400 - 2483.5	79	15	Plot B	PASS
8-DPSK	2400 - 2483.5	79	15	Plot C	PASS

B. Test Plots:


Agilent 16:43:47 12 Jun 2015
R T
Mkr1 Δ 38.95 MHz
Ref 10 dBm
Atten 20 dB
-2.8 dB
Peak
Log
10
dB/
Offst
1
dB
M1 S2
S3 FC
AA
Start 2.4 GHz
Stop 2.441 GHz
#Res BW 1 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)
Agilent 16:45:29 12 Jun 2015
R T
Mkr1 Δ 38.99 MHz
Ref 10 dBm
Atten 20 dB
2.044 dB
Peak
Log
10
dB/
Offst
1
dB
M1 S2
S3 FC
AA
Start 2.441 GHz
Stop 2.483 GHz
#Res BW 1 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)

(Plot A: GFSK)



(Plot B: π/4-DQPSK)


Agilent 16:52:04 12 Jun 2015
R T
Mkr1 Δ 39.03 MHz
Ref 10 dBm
Atten 20 dB
-2.451 dB
Peak
Log
10
dB/
Offst
1
dB
1R
M1 S2
S3 FC
AA
Start 2.4 GHz
Stop 2.441 GHz
#Res BW 1 MHz
#VBW 3 MHz
Sweep 10 ms (1001 pts)
Agilent 16:53:26 12 Jun 2015
R T
Mkr1 Δ 38.9300 MHz
Ref 10 dBm
Atten 20 dB
1.719 dB
Peak
Log
10
dB/
Offst
1
dB
1R
1
M1 S2
S3 FC
AA
Start 2.441 GHz
Stop 2.483 GHz
#Res BW 1 MHz
#VBW 3 MHz
Sweep 10 ms (1001 pts)

(Plot C: 8- DPSK)

2.3 Peak Output Power

2.3.1 Requirement

According to FCC §15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

2.3.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Power meter and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.3.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the module. The lowest, middle and highest channel were tested by power meter.

2.3.3.1 GFSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	3.064	0.002025	20.97	0.125	PASS
39	2441	0.350	0.001084			PASS
78	2480	2.309	0.001702			PASS

2.3.3.2 π/4-DQPSK Mode

B. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	2.023	0.001593	20.97	0.125	PASS
39	2441	-0.537	0.000884			PASS
78	2480	1.051	0.001274			PASS

2.3.3.3 8-DPSK Mode

C. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	2.092	0.001619	20.97	0.125	PASS
39	2441	-0.482	0.000895			PASS
78	2480	1.137	0.001299			PASS

2.4 20dB Bandwidth

2.4.1 Definition

According to FCC §15.247(a)(1), the 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth (10*log1% = 20dB) taking the total RF output power.

2.4.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.4.3 Test Procedure

Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW ≥ 1% of the 20 dB bandwidth
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

2.4.4 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to record the 20dB bandwidth of the Module.

2.4.4.1 GFSK Mode

A. Test Verdict:

The maximum 20dB bandwidth measured is 0.9627MHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
0	2402	0.964	Plot A
39	2441	1.019	Plot B
78	2480	1.027	Plot C

B. Test Plots:



(Plot A: Channel = 2402 @ GFSK)



(Plot B: Channel = 2441 @ GFSK)



(Plot C: Channel = 2480 @ GFSK)

2.4.4.2 π/4-DQPSK Mode

A. Test Verdict:

The maximum 20dB bandwidth measured is 1.284MHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
0	2402	1.317	Plot D
39	2441	1.301	Plot E
78	2480	1.304	Plot F

B. Test Plots:



(Plot D: Channel = 2402 @ π/4-DQPSK)



(Plot E: Channel = 2441 @ π/4-DQPSK)



(Plot F: Channel = 2480 @ π/4-DQPSK)

2.4.4.3 8-DPSK Mode

A. Test Verdict:

The maximum 20dB bandwidth measured is 1.294MHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
0	2402	1.313	Plot G
39	2441	1.304	Plot H
78	2480	1.296	Plot I

B. Test Plots:



(Plot G: Channel = 2402 @ 8-DPSK)



(Plot H: Channel = 2441 @ 8-DPSK)



(Plot I: Channel = 2480 @ 8-DPSK)

2.5 Carried Frequency Separation

2.5.1 Definition

According to FCC §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

2.5.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm;the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span

Video (or Average) Bandwidth (VBW) ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

2.5.4 Test Result

The Bluetooth Module operates at hopping-on test mode. For any adjacent channels (e.g. the channel 39 and 40 as showed in the Plot A), the Module does have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel (refer to section 0), whichever is greater. So, the verdict is PASSING



(Plot A: GFSK)



(Plot B: π/4-DQPSK)



(Plot C: 8-DPSK)

2.6 Time of Occupancy (Dwell time)

2.6.1 Requirement

According to FCC §15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

2.6.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.6.3 Test Procedure

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 31.6 second period (79 channel * 0.4 s) is equal to 10 * (# of pulses in 3.16 s) * pulse width.

2.6.4 Test Result

2.6.4.1 GFSK Mode

A. Test Verdict:

DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Average Time of Occupancy in 3.16 seconds (sec)	Average Time of Occupancy in 31.6 seconds (sec)	Limit (sec)	Verdict
DH1	0.35	30	0.01050	0.1050	0.4	PASS
DH3	1.60	19	0.03040	0.3040		PASS
DH5	2.85	10	0.02850	0.2850		PASS

B. Test Plots:





(Plot A: DH1 @ GFSK)





(Plot B: DH3 @ GFSK)





(Plot C: DH5 @ GFSK)

2.6.4.2 π/4-DQPSK Mode

A. Test Verdict:

DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Average Time of Occupancy in 3.16 seconds (sec)	Average Time of Occupancy in 31.6 seconds (sec)	Limit (sec)	Verdict
DH1	0.35	31	0.01085	0.1085	0.4	PASS
DH3	1.60	15	0.02400	0.2400		PASS
DH5	2.90	9	0.02610	0.2610		PASS

B. Test Plots:



(Plot D: DH1 @ π/4-DQPSK)



(Plot E: DH3 @ π/4-DQPSK)



(Plot F: DH5 @ π/4-DQPSK)

2.6.4.3 8-DPSK mode

A. Test Verdict:

DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Average Time of Occupancy in 3.16 seconds (sec)	Average Time of Occupancy in 31.6 seconds (sec)	Limit (sec)	Verdict
DH1	0.40	30	0.01200	0.1200	0.4	PASS
DH3	1.45	15	0.02175	0.2175		PASS
DH5	2.90	9	0.02610	0.2610		PASS

B. Test Plots:





(Plot G: DH1 @ 8-DPSK)





(Plot H: DH3 @ 8-DPSK)





(Plot I: DH5 @ 8-DPSK)

2.7 Conducted Spurious Emissions

2.7.1 Requirement

According to FCC §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.7.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm;the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

2.7.4 Test Result

The Bluetooth Module operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

2.7.4.1 GFSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-51.24	Plot A.1	1.988	-18.012	PASS
39	2441	-50.08	Plot B.1	-0.836	-20.836	PASS
78	2480	-50.19	Plot C.1	1.432	-18.568	PASS

B. Test Plots:

Note: the power of the Module transmitting frequency should be ignored.



(Plot A.1: Channel = 0, 30MHz to 25GHz @ GFSK Mode)



(Channel = 0, Band edge @ GFSK Mode)



(Channel = 0, Band edge with hopping on @ GFSK Mode)



(Plot B.1: Channel = 39, 30MHz to 25GHz @ GFSK Mode)



(Plot C.1: Channel = 78, 30MHz to 25GHz @ GFSK Mode)



(Channel = 78, Band edge @ GFSK Mode)



(Channel = 78, Band edge with hopping on @ GFSK Mode)

2.7.4.2 π/4-DQPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-50.75	Plot D.1	-2.642	-22.642	PASS
39	2441	-50.41	Plot E.1	-2.523	-22.523	PASS
78	2480	-50.69	Plot F.1	-2.116	-22.116	PASS

B. Test Plots:

Note: the power of the Module transmitting frequency should be ignored.



(Plot D.1: Channel = 0, 30MHz to 25GHz @π/4-DQPSK)



(Channel = 0, Band edge @π/4-DQPSK)



(Channel = 0, Band edge with hopping on @π/4-DQPSK)



(Plot E.1: Channel = 39, 30MHz to 25GHz @ π/4-DQPSK)



(Plot F.1: Channel = 78, 30MHz to 25GHz @π/4-DQPSK)



(Channel = 78, Band edge @π/4-DQPSK)



(Channel = 78, Band edge with hopping on @ π/4-DQPSK)

2.7.4.3 8-DPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-49.88	Plot G.1	-0.297	-20.297	PASS
39	2441	-51.61	Plot H.1	-4.655	-24.655	PASS
78	2480	-50.80	Plot I.1	-3.331	-23.331	PASS

B. Test Plots:

Note: the power of the Module transmitting frequency should be ignored.



(Plot G.1: Channel = 0, 30MHz to 25GHz @ 8-DPSK)



(Channel = 0, Band edge @ 8-DPSK)



(Channel = 0, Band edge with hopping on @ 8-DPSK)



(Plot H.1: Channel = 39, 30MHz to 25GHz @ 8-DPSK)



(Plot I.1: Channel = 78, 30MHz to 25GHz @ 8-DPSK)



(Plot I.1: Channel = 78, Band edge @ 8-DPSK)



(Plot I.1: Channel = 78, Band edge with hopping on @ 8-DPSK)

2.8 Restricted Frequency Bands

2.8.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.8.2 Test Description

A. Test Setup:



The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna:

Horn Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

B. Equipments List:

Please reference ANNEX A(1.4).

2.8.3 Test Procedure

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1GHz, 100 KHz for f < 1GHz
VBW = 3 MHz for peak and 10Hz for average
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize.

2.8.4 Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.
The measurement results are obtained as below:
E [dBμV/m] $=U_R + A_T + A_{Factor}$ [dB]; AT $=L_{Cable\ loss}$ [dB]$-G_{preamp}$ [dB]
AT: Total correction Factor except Antenna
UR: Receiver Reading
Gpreamp: Preamplifier Gain
AFactor: Antenna Factor at 3m
Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

2.8.4.1 GFSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
0	2384.50	PK	45.23	-33.63	32.56	44.16	74	Pass
0	2361.62	AV	32.12	-33.63	32.56	31.05	54	Pass
78	2488.51	PK	43.00	-33.18	32.5	42.32	74	Pass
78	2489.61	AV	31.49	-33.18	32.5	30.81	54	Pass

B. Test Plots:



(Plot A1:Channel = 0 PEAK @ GFSK)



(Plot A2:Channel = 0 AVERAGE @ GFSK)



(Plot B1: Channel = 78 PEAK @ GFSK)



(Plot B2: Channel = 78 AVERAGE @ GFSK)

2.8.4.2 π/4-DQPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
0	2383.46	PK	44.90	-33.63	32.56	43.83	74	Pass
0	2358.50	AV	32.03	-33.63	32.56	30.96	54	Pass
78	2488.12	PK	45.33	-33.18	32.5	44.65	74	Pass
78	2492.03	AV	31.59	-33.18	32.5	30.91	54	Pass

B. Test Plots:



(Plot C1: Channel = 0 PEAK @ π/4-DQPSK)



(Plot C2: Channel = 0 AVERAGE @ π/4-DQPSK)



(Plot D1: Channel = 78 PEAK @ π/4-DQPSK)



(Plot D2: Channel = 78 AVERAGE@ π/4-DQPSK)

2.8.4.3 8-DPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBµV/m)	Limit (dBµV/m)	Verdict
0	2383.98	PK	43.89	-33.63	32.56	42.82	74	Pass
0	2354.60	AV	32.11	-33.63	32.56	31.04	54	Pass
78	2488.73	PK	43.86	-33.18	32.5	43.18	74	Pass
78	2490.16	AV	31.51	-33.18	32.5	30.83	54	Pass

B. Test Plots:



(Plot E1: Channel = 0 PEAK @ 8-DPSK Mode)



(Plot E2: Channel = 0 AVERAGE @ 8-DPSK Mode)



(Plot F1:Channel = 78 PEAK @ 8-DPSK Mode)



(Plot F2:Channel = 78 AVERAGE @ 8-DPSK Mode)

2.9 Conducted Emission

2.9.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5- 30	60	50

NOTE:

(a) The lower limit shall apply at the band edges.

(b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.9.2 Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2009

The factors of the site are calibrated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna,

and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.9.3 Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

A. Test setup:

The EUT configuration of the emission tests is EUT + Link.

B. Test Plots:



(Plot A: L Phase)



(Plot B: N Phase)

2.10 Radiated Emission

2.10.1 Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)

2.10.2 Test Description

A. Test Setup:

1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to1GHz



3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

B. Equipments List:

Please reference ANNEX A(1.4).

2.10.3 Test Procedure

Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

2.10.4 Test Result

According to ANSI C63.4 selection 4.2.2, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

E [dBμV/m] $=U_R + A_T + A_{Factor}$ [dB]; $A_T = L_{Cable\ loss}$ [dB]$-G_{preamp}$ [dB]

A_T: Total correction Factor except Antenna

U_R: Receiver Reading

G_{preamp}: Preamplifier Gain

A_{Factor}: Antenna Factor at 3m

During the test, the total correction Factor AT and A_{Factor} were built in test software.

Note: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

2.10.4.1 GFSK Mode:

A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
32.419	24.87	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
100.150	15.29	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
223.516	15.08	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
1897.756	45.07	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS
2402.000	67.60	N.A	N.A	54.0	N.A	54.0	Horizontal	N.A
12930.175	43.53	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 0)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	35.28	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
46.933	27.91	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
216.259	17.38	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
1897.756	45.70	N.A	N.A	54.0	N.A	54.0	Vertical	PASS
2402.000	67.83	N.A	N.A	54.0	N.A	54.0	Vertical	N.A
16825.436	44.74	N.A	N.A	54.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 0)

Plot for Channel = 39



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
32.419	22.45	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
100.150	15.36	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
209.002	16.41	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
1897.756	44.08	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS
2441.000	66.01	N.A	N.A	54.0	N.A	54.0	Horizontal	N.A
9967.581	42.96	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 39)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	33.03	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
46.933	30.12	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
225.935	16.26	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
765.362	26.36	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2441.000	63.71	N.A	N.A	54.0	N.A	54.0	Vertical	N.A
9693.267	42.73	N.A	N.A	54.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 39)

Plot for Channel = 78



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	21.51	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
100.150	16.27	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
211.421	15.77	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
765.362	25.71	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2480.000	64.86	N.A	N.A	54.0	N.A	54.0	Horizontal	N.A.
16660.848	44.98	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 78)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
46.933	30.00	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
61.446	25.94	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
95.312	18.44	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
225.935	18.50	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2480.000	63.10	N.A	N.A	54.0	N.A	54.0	Vertical	N.A
16715.711	45.27	N.A	N.A	54.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 78)

2.10.4.2 π/4-DQPSK Mode:

B. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
42.095	20.36	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
100.150	14.93	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
223.516	17.94	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
1897.756	44.03	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS
2402.000	63.07	N.A	N.A	54.0	N.A	54.0	Horizontal	N.A
9693.267	43.86	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ π/4-DQPSK, channel 0)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	35.30	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
56.608	27.92	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
213.840	17.36	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
1897.756	46.56	N.A	N.A	54.0	N.A	54.0	Vertical	PASS
2402.000	62.54	N.A	N.A	54.0	N.A	54.0	Vertical	N.A
9693.267	44.44	N.A	N.A	54.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ π/4-DQPSK, channel 0)

Plot for Channel = 39



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
46.933	18.92	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
100.150	14.64	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
317.855	18.99	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
1897.756	43.21	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS
2441.000	63.07	N.A	N.A	54.0	N.A	54.0	Horizontal	N.A
16825.436	45.49	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ π/4-DQPSK, channel 39)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	32.21	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
54.190	27.48	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
211.421	18.17	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
453.317	22.85	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2441.000	64.81	N.A	N.A	54.0	N.A	54.0	Vertical	N.A
17758.105	44.75	N.A	N.A	54.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ π/4-DQPSK, channel 39)

Plot for Channel = 78



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	18.95	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
100.150	15.12	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
209.002	15.12	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
1897.756	44.74	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS
2480.000	65.71	N.A	N.A	54.0	N.A	54.0	Horizontal	N.A
16660.848	45.57	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ π/4-DQPSK, channel 78)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
46.933	32.33	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
100.150	16.56	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
221.097	16.47	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
765.362	25.27	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2480.000	63.28	N.A	N.A	54.0	N.A	54.0	Vertical	N.A
9967.581	42.88	N.A	N.A	54.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ π/4-DQPSK, channel 78)

2.10.4.3 8-DPSK Mode:

C. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
32.419	23.01	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
100.150	16.80	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
206.584	17.14	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
453.317	22.76	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2402.000	63.33	N.A	N.A	54.0	N.A	54.0	Horizontal	N.A
16770.574	44.82	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @8-DPSK, channel 0)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
34.838	35.09	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
97.731	17.38	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
223.516	18.29	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
1897.756	46.46	N.A	N.A	54.0	N.A	54.0	Vertical	PASS
2402.000	62.95	N.A	N.A	54.0	N.A	54.0	Vertical	N.A
9693.267	44.16	N.A	N.A	54.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @8-DPSK, channel 0)

Plot for Channel = 39



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
42.095	19.43	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
100.150	14.27	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
213.840	19.76	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
1897.756	43.52	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS
2441.000	63.05	N.A	N.A	54.0	N.A	54.0	Horizontal	N.A
16605.985	44.92	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @8-DPSK, channel 39)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	35.59	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
88.055	17.28	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
221.097	15.79	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
765.362	26.10	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2441.000	63.67	N.A	N.A	54.0	N.A	54.0	Vertical	N.A
16880.299	44.94	N.A	N.A	54.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @8-DPSK, channel 39)

Plot for Channel = 78



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	20.68	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
100.150	16.26	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
267.057	16.32	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
765.362	26.63	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2480.000	64.11	N.A	N.A	54.0	N.A	54.0	Horizontal	N.A
9967.581	43.37	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @8-DPSK, channel 78)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
39.676	34.94	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
56.608	28.45	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
223.516	17.08	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
765.362	26.12	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2480.000	64.65	N.A	N.A	54.0	N.A	54.0	Vertical	N.A
9693.267	42.42	N.A	N.A	54.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @8-DPSK, channel 78)

2.11 RF exposure evaluation

2.11.1 Requirement

According to § 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy lever in excess of Commission's guideline.

2.11.2 Result

Please refer to SAR report.

ANNEX A GENERAL INFORMATION

1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

1.3 Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10 2009, ANSI C63.4 2009 and CISPR Publication 22; the FCC registration number is 695796.

1.4 Test Equipments Utilized

1.4.1 Conducted Test Equipments

Conducted Test Equipment						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal. Date**	**Cal. Due**
1	System Simulator	6K00006210	MT8852B	Anritsu	2015.02.26	2016.02.25
2	Spectrum Analyzer	MY45101810	E4407B	Agilent	2015.02.26	2016.02.25
3	Power Splitter	NW521	1506A	Weinschel	2015.02.26	2016.02.25
4	Attenuator 1	(n.a.)	10dB	Resnet	2015.02.26	2016.02.25
5	Attenuator 2	(n.a.)	3dB	Resnet	2015.02.26	2016.02.25
6	EXA Signal Analzyer	MY51440152	N9010A	Agilent	2015.02.26	2016.02.25
7	RF cable	CB01	RF01	Morlab	N/A	N/A
8	Coaxial cable	CB02	RF02	Morlab	N/A	N/A
9	SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.4.2 Conducted Emission Test Equipments

Conducted Emission Test Equipments						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal. Date**	**Cal. Due**
1	Receiver	US44210471	E7405A	Agilent	2015.02.26	2016.02.25
2	LISN	812744	NSLK 8127	Schwarzbeck	2015.02.26	2016.02.25
3	Service Supplier	100448	CMU200	R&S	2015.02.26	2016.02.25
4	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2015.02.26	2016.02.25
5	Coaxial cable(BNC)	CB01	EMC01	Morlab	N/A	N/A

1.4.3 Radiated Test Equipments

Radiated Test Equipments						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal. Date**	**Cal.Due Date**
1	System Simulator	100448	CMU200	R&S	2015.02.26	2016.02.25
2	Receiver	US44210471	E7405A	Agilent	2015.02.26	2016.02.25
3	Test Antenna - Bi-Log	9163-274	9m*6m*6m	Albatross	2015.02.26	2016.02.25
4	Test Antenna - Horn	9120D-963	VULB 9163	Schwarzbeck	2015.02.26	2016.02.25
5	Test Antenna - Horn	71688	BBHA 9120D	Schwarzbeck	2015.02.26	2016.02.25
6	Test Antenna - Loop	1519-022	HL050S7	R&S	2015.02.26	2016.02.25
7	Reject Filter	(n.a.)	BRM50702	Micro-Tronics	2015.02.26	2016.02.25
8	Coaxial cable (N male)	CB02	EMC02	Morlab	N/A	N/A
9	Coaxial cable (N male)	CB03	EMC03	Morlab	N/A	N/A

1.4.4 Climate Chamber

Climate Chamber						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal.Date**	**Cal.Due Date**
1	Climate Chamber	2004012	HL4003T	Yinhe	2015.02.26	2016.02.25

1.4.5 Vibration Table

Vibration Table						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal.Date**	**Cal.Due Date**
1	Vibration Table	N/A	ACT2000-S015L	CMI-COM	2015.02.26	2016.02.25

1.4.6 Anechoic Chamber

Anechoic Chamber						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal.Date**	**Cal.Due Date**
1	Anechoic Chamber	N/A	9m*6m*6m	Albatross	2015.02.26	2016.02.25

***** END OF REPORT *****